


Item no. 00112171

High Line LED Bulb, 9W, bulb shape, E27, warm white





Design Operating Position Can be Dimmed Colour Temperature Power Consumption of an Equivalent Incandescent Lamp Nominal Service Life Optimal Ambient Temperature Socket Very Socket Sock	
Can be Dimmed Colour Temperature Power Consumption of an Equivalent Incandescent Lamp Nominal Service Life Optimal Ambient Temperature Socket Fermature Failure (min.) Diameter Dimensions Differ From Those of a Standardized Bulb 2700 K 60 W 25000 h 25000 h 40000 60 mm 40000	
Colour Temperature 2700 K Power Consumption of an Equivalent Incandescent Lamp Nominal Service Life 25000 h Optimal Ambient Temperature 25 °C Socket E 27 Number of Switching Cycles until Premature Failure (min.) 40000 Diameter 60 mm Height 120 mm Dimensions Differ From Those of a Standardized Bulb	
Power Consumption of an Equivalent Incandescent Lamp Nominal Service Life Optimal Ambient Temperature Socket F 27 Number of Switching Cycles until Premature Failure (min.) Diameter Height Dimensions Differ From Those of a Standardized Bulb	
Equivalent Incandescent Lamp Nominal Service Life Optimal Ambient Temperature Socket E 27 Number of Switching Cycles until Premature Failure (min.) Diameter Height Dimensions Differ From Those of a Standardized Bulb	
Optimal Ambient Temperature 25 °C Socket E 27 Number of Switching Cycles until Premature Failure (min.) 40000 Diameter 60 mm Height 120 mm Dimensions Differ From Those of a Standardized Bulb	
Socket E 27 Number of Switching Cycles until Premature Failure (min.) Diameter 60 mm Height 120 mm Dimensions Differ From Those of a Standardized Bulb	
Number of Switching Cycles until Premature Failure (min.) Diameter 60 mm Height 120 mm Dimensions Differ From Those of a Standardized Bulb	
Premature Failure (min.) Diameter 60 mm Height 120 mm Dimensions Differ From Those of a Standardized Bulb	
Height 120 mm Dimensions Differ From Those of a Standardized Bulb	
Dimensions Differ From Those of a Standardized Bulb	
a Standardized Bulb	
A (C 1 C A 1 E	
Energy Efficiency Class A+ (Scale from A++ to E, Value: A++)	Optimum
Lamp Current 80 mA	
Start-Up Time Until 60% of Full Light Output Has Been Reached 1 s (max.)	
Operating Voltage 230 V	
Weighted Energy Consumption 9.5 kWh/1000h	1
Nominal Power Consumption 9 W	
Mains Frequency 50 Hz	
Nominal Beam Angle Angle of Radiation	
Nominal Light Output 806 lm	
Bulb Serves as Replacement for Standard Bulbs of This Size Light Bulb	
Suitable for Accent Lighting No - Beam Angle betwee 360° (φuse)	

Errors and omissions excepted, and subject to technical changes.