

Data Sheet Fujitsu CELVIN® NAS Server Q800 Storage

Powerful 4-Drive NAS Solution

The FUJITSU CELVIN® NAS Server line is an all-in-one, high performance NAS server line. The CELVIN® NAS Server Q800 is the ideal solution for file sharing, end to end backup options and SAN (Storage Area Network) integration for SMB customers - enabling centralized data management at a reasonable price.

Business Server Feature

- Flexible usage, access and integration of the device and capacity
- Windows active directory support for centralized account information in complex organizations
- iSCSI target and initiator for simple and platform independent IP-capacity provision
- Multiple options for file management, remote access and database usage
- Outstanding file sharing possibility

Backup Management

- Complete end to end backup concept
- Powerful PC backup software and Apple Time Machine support
- Encrypted remote replication
- Quick- touch USB copy for different destination folders
- Backup to external storage device or cloud storage

Multimedia Features

- Streaming of media files via iTunes, Twonky Media
- Comprehensive download features with BitTorrent Clienet

Reliability

- Service-friendly cabinet
- 3-years spare part supply
- Country-specific warranty
- Top-up services are available















CELVIN® NAS Server Q800

Technical specifications					
	Firmware based on 3.4.x				
	Processor: Intel® Atom™ D525				
	Memory: 1 GB DDRIII RAM				
	3 GB DDRIII RAM in combination with BC HDD				
	512 MB Flash on DOM				
	FAN: 1 x quiet cooling fan (9cm)				
Hard disk capacity	Up to 4 x 2.5-inch or 3.5-inch SATA I/II/ SATA 6Gb/sHDD				
• •					
lard disk type	SATA				
equired interface	Ethernet				
LED	USB				
	Status				
	HDD 1-4				
	LAN				
	Power				
ystem controls	Power button, One-touch copy button, Alarm Buzzer (System Warning), Reset Button, Display mode button				
olor	Black				
oftware specification					
Networking	TCP/IP (IPv4 /IPv6 dual stack), multi IP setting,LACP,				
•	Port trunking /NIC teaming:				
	Balance-rr (Round-Robin), Active Backup, Balance XOR, Broadcast, IEEE 802.3ad,				
	Balance-tlb (Adaptive, Transmit Load Balancing), Balance-alb (Adaptive Load Balancing)				
	DHCP client, DHCP server				
	CIFS/SMB, AFP, NFS v3, HTTP, HTTPS, FTP,SFTP(admin), DDNS, NTP, Telnet, SSH, iSCSI, SNMP,WebDAV				
	Dual Gigabit w/ Jumbo Frame, Bonjour				
	iSCSI initiator for virtual disks (max 8 disks); stack chaining master				
	Virtual disk support for EXT3/ EXT4/ NTFS/ FAT32/ HFS+				
	Support for VMware VSphere (ESX / ESXi 4.0) via NFS and iSCSI				
	Windows Server 2008 support (Hyper-V & failover clustering)				
	iSCSI target (with multi-LUNs per target)				
	iSCSI LUN online expansion				
	LUN mapping / LUN masking				
	SCSI Primary Commands -3 (SPC-3) support / persistent reservation				
	MC/S (multiple TCP connections / session) support to reach iSCSI target				
	MPIO (multipath input output) for load balancing and failover				
	VLAN 802.1Q				
	USB WiFi-Adapter support IEEE 802.11b/g/n				
	WEP, WPA-personal (AES/TKIP), WPA2-personal (AES)				
	Connection to wireless network or Ad Hoc network				
File System Management	Network share management '(max. 512 shares)				
	Share folder level ACL support				
	Unicode support				
	!!				
	Journaling file system				
	Web File Manager				
	Google Docs support (pdf,tif/tiff,ppt,doc,xls,pptx,docx,xlsx,svg,odt)				
Disk Management	Disk usage status management; HDD S.M.A.R.T.; Bad blocks scan				
	RAID 0/1/5/5+HS/10/6, JBOD, single disk				
	Online RAID capacity expansion; online RAID-level migration				
	RAID recovery, Bitmap support				

Software specification				
User Management	User quota management			
ose menegement	Windows Active Directory support, max. 10k users			
	User account management (max. 4096users)			
	User group management (max. 512 groups)			
	Shared folders (max. 512)			
	Concurrent connections (max. 256)			
	Support batch creating users			
	User Import/ Export for Multiple CELVIN NAS Deployment			
	Subfolder Permission (File/Directory ACL)			
	Microsoft Networking (Samba) Host Access Control (Domain/IP)			
System Tools	E-mail alert (SMTP authentication); SMS alert notification			
	Disk usage alert			
	HDD standby mode			
	Automatic power on after power loss			
	Schedule power on/ off			
	System firmware upgrade			
	Wake-on-LAN			
	Smart fan setting			
	Back up, restore, reset system settings			
	Configurable management port			
	Policy-based unauthorized IP blocking			
	Secure remote login by SSH connection			
	Import SSL certificate			
	Remote login by Telnet connection			
	USB, SNMP UPS support			
	Network recycle bin			
Event Logs	Complete system logs (file level): system events management, connection logs, current connection of on-line users			
Multilingual (Online) Support	English, German, further manual languages on request			
FTP Server	FTP remote access (max. 256 concurrent connections)			
	FTP with SSL/ TLS (explicit) mode			
	FTP bandwidth control and connection control			
	Passive FTP port range control			
	FXP support			
Printer Server	USB printer network sharing (Windows / Mac)			
	Internet printing protocol, printer management, Apple Bonjour printing			
Remote Replication	Encrypted block-level remote replication (instant, scheduled backup management); synchronization mode/Rsync			
	Real-time remote replication (RTRR protocol) for real-time backup of server & client			
Web Server	Built-in editable php.ini, SQLite and MySQL			
MySQL Server	MySQL database server			
Surveillance Station	4 x IP cameras for network surveillance			
sarvemance station	IP camera finder software and configuration			
Media Server	UPnP/DLNA			
	Twonky Media			
	iTunes server			
	DLNA support for Xbox360 and PS3			
	Multimedia station features			
Download Station	BitTorrent (FTP/ HTTP scheduled download)			
	Support of TCP/ UDP tracker protocol, distributed hash table/DHT			
	Up to 500 BT download tasks			
	Download configuration / download status list			
	RSS download manager, subscription to RSS feeds, RSS download			
	Multiple URLs in one task			
 Interfaces				
USB 2.0 total	Rear side: 4x USB2.0			
eSATA	2 x (rear / SATA)			

Supported formats					
Video formats	(Madia Sarvar): wmv as	of vdr avi vvid divy fly mna m	one mis milts milt mana sats mila mily mailt maila		
video ioililats	(Media Server): wmv, asf, vdr, avi, xvid, divx, flv, mpg, mpe, mts, m2ts, m2t, mpeg, spts, m2p, m2v, mp2t, mp2p, mpg2, dvr-ms				
Subtitle formats	(Media Server): m3u, m3u8, wpl, pls				
Music formats	(Media Server): mp3, mp4, m4a, m4b, 3gp, apl, ac3, m1v, m4v, mov, aac, amr, awb, wav, pcm, lpcm, mp1, mp2, ai				
Picture formats	aiff, aifc, snd, wma, ogg, flac; Internet Radio (Media Server): vTuner, Shoutcast Media Server): jpg, jpe, jpeg, tiff, tif, gif, png, bmp				
Supported file system	EXT4 (internal/external HDD)				
Supported the system	NTFS (external HDD)				
	FAT32 (external HDD)				
	EXT3 (internal/external HDD)				
	HFS+ (externel HDD)				
Electrical values					
Power consumption	EUP mode: 0,46W WoL mode: 1,89W Sleep mode: 21W Idle: 27W Operation mode: 37 W				
Power supply input	Internal power supply 250W 50-60Hz Input: 100-240V AC				
Compliance					
Еигоре	CE				
USA/Canada	FCC Class A				
Compliance link	https://sp.ts.fujitsu.com/sites/certificates/default.aspx				
Dimensions / Weight / Environmental					
Dimensions (W x D x H)	180 x 235 x 177 mm				
Weight	Net weight: 3.65 kg, Gross weight: 4.65 kg; Package incl. System w/o HDD: 5,75 kg				
Operating ambient temperature	0 - 40°C				
Required interface	Ethernet				
Software support (Operating system)	Windows® XP				
	Windows® Server 2003				
	Windows Vista® Windows® 7				
	Windows® 7 Mac OS X				
	Mac US X Linux				
	UNIX				
Package content					
r delage content	CELVIN NAS Server Q800; Power Cord, CD, LAN cable, Key for tray lock, trays, Quick Start Guide, Service flyer				
Order information					
	S26341-F103-L241	EAN: 4051554321871	CELVIN TRAY 1 TB		
	S26341-F103-L242	EAN: 4051554321888	CELVIN TRAY 2 TB		
	S26341-F103-L800	EAN: 4049699380747	station without hard disks		
	S26341-F103-L801	EAN: 4049699478161	station without hard disks (UK/CH power plug)		
	S26341-F103-L820	EAN: 4049699380754	2 x 1TB		
	S26341-F103-L822	EAN: 4049699380785	2 x 2TB		
	S26341-F103-L840	EAN: 4049699380761	4 x 1TB		
	S26341-F103-L842	EAN: 4049699380792	4 x 2 TB		
	S26341-F103-L843	EAN: 4049699478130	4 x 2 TB (UK/CH power plug)		
	S26341-F103-L845	EAN: 4049699478062	4 x 1 TB (UK/CH power plug)		
	S26341-F103-L851	EAN: 4051554232252	4x 1 TB BC HDD		
	S26341-F103-L852	EAN: 4051554232269	4x 2 TB BC HDD		
	VFY:CQ800XX200E1	EAN: 4051554496951	4 x 1 TB		
	VFY:CQ800XX210E1	EAN: 4051554496968	4 x 2 TB		

More information

Fujitsu OPTIMIZATION Services

In addition to Fujitsu CELVIN® NAS Server Q800, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/services/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu CELVIN® NAS Server Q800, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

www.fujitsu.com/fts/accessories

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at http://www.fujitsu.com/global/about/environment/



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see www.fujitsu.com/

Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

FUJITSU Technology Solutions Website: www.fujitsu.com/fts 2012-08-20 CE-EN All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.

Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see www.fujitsu.com/terms

Copyright © Fujitsu Technology Solutions