ThinkVision T2224d 61B1JAR1EU

Product

ThinkVision T2224d

Region EMEA

Color Black

Panel In-Plane Switching

Display Size 21.5"

View Area 476.1x267.8 mm

Resolution 1920x1080

Aspect Ratio 16:9

Pixel Pitch 0.248x0.248 mm

Dot / Pixel Per Inch 102 dpi

Brightness 250 nits

Contrast Ratio 1000:1

Pixel Response Time 7 ms

Color Gamut 72%

View Angle (H / V) 178 / 178

Stand Tilt Stand

Side Bezel Width 17.6 mm

Dimensions with Stand (HxWxD) 381.4x512.9x204.9 mm

Power Comsuption (Typical / Maximum) 20W / 25W

Power Adapter Integrated

Weight (Including Stand) 6.48lb / 2.94kg Warranty 3-year

ENERGY STAR ENERGY STAR 7.0

TCO TCO 7.0

EPEAT Gold

Presets / User Settings 22 / 22

On Screen Display OSD, 8 Languages

USB Port None

Speaker None

Camera None

Multiple Input VGA, DP

Monitor Cable VGA, DP

CPU / Platform None / None

Display Ram / Storage / Card Slot None / None / None

Wireless / Ethernet / Bluetooth None / None / None

Touch Screen / Digitizer Pen / Battery None / None / None

Operating System Support Windows 7, Windows 10

Ann Date (mm/yy) 03/17

WWW.LENOVO.COM

This publication was developed for products and services offered in the United States and E.M.E.A countries. Lenovo may not offer the products, services or features discussed in this document in other countries. Lenovo may withdraw an offering at any time. Information is subject to change without notice. Consult your local representative for information on offerings available in your area.

Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors.

Lenovo provides this publication "as is" without warranty of any kind, either express or implied, including the implied warranties of merchantability or ftness for a particular purpose.

http://psref.lenovo.com

Visit psref website for the latest version of Product Specifcations Reference. © Lenovo, 2019. All rights reserved.





Lenovo ThinkVision T2224d Wide

Product Specifications Reference (PSREF)

Nomo	T2224d Wide Elet Banel Menitor	Factures
Name Bezel color	T2224d Wide Flat Panel Monitor Black	Features
Type-model	61B1JAR1US / 61B1JAT1EU	Widescreen 21.5-inch monitor
Panel	TFT-LCD, In-Plane Switching (IPS),	Supports 1920x1080 resolution
	White LED backlight	 Supports optional soundbar Supports ThinkCentre Tiny via VESA back mount
Viewable image size	21.5" (546mm) diagonal	Includes dual input connection for attachment to two
Max view area (W x H)	18.74" x 10.54" (476.1mm x 267.8mm)	systems concurrently (analog and digital)
Native resolution	1920x1080	EPEAT Gold certified
Aspect ratio Pixel pitch (mm)	16:9 0.248 x 0.248 mm	Microsoft® Windows® 7 certified
Dot/Pixel per Inch	102 dpi	Microsoft Windows 10 certified
Brightness	250 nits or cd/m ² (typical)	
Contrast ratio	1000:1 (typical)	
Pixel response time	7ms (typical); 4ms (extreme mode)	
Color gamut	72%	
Viewing angle at 10:1 CR	178° (+/- 89°) horizontal, 178° (+/- 89°) vertical	
Stand Bezel width	Tilt stand <i>Sides:</i> 0.69" (17.6mm)	
Dimensions (HxWxD)	15.02" H x 20.19" W x 8.06" D;	
	381.4mm H x 512.9mm W x 204.9mm D	
Power supply	20 watts typical,	
	25 watts maximum	
	<0.5 watts standby/suspend, universal,	
VA(a i sub t	integrated (no external brick-like power supply)	and the second
Weight Limited warranty	6.48 lb; 2.94 kg 3 year (includes backlight)	CALL COMPANY OF THE OWNER OWNER OF THE OWNER OWN
Limited warranty Available date	3 year (includes backlight) March 2017	Contraction of the Article of the Ar
Available uale		
VESA-compliant Power management	VESA DDC2B/CI ENERGY STAR® gualified	
Ergonomics	ISO 9241-307	Lawell
Emission standards	FCC Class B	
Environmental	TCO Displays 7.0, TCO Certified Edge 2.0, WEEE,	
	RoHS, EPEAT [™] Gold rating	
Preset resolutions	VGA: 640x350, 640x480, 720x400	
	SVGA: 800x600	
	XGA: 1024x768, 1152x864	
	SXGA: 1280x1024	
	WXGA: 1280x768, 1280x800, 1366x768	
	WXGA+: 1440x900 WSXGA+: 1680x1050	
	Full HD: 1920x1080	ThinkVision T2224d Wide Monitor
Presets / user settings	Standard presets: 22; user settings: 22	
Viewing adjustments	<i>Tilt:</i> 22° back, -5° forward	
Rotating screen On screen display	None On screen display with digital user controls (8 languages)	
Control features	Direct access (buttons on front) for automatic image setup, dual input and brightness	
USB hub	None	otop, dda mpat and originitoso
Multiple input	Dual input (two different PCs attach to two different connectors; one PC shows image; select via button)	
Monitor connectors	(1) VGA 15-pin D-shell, analog, blue	
o:	(2) DisplayPort, digital, black, HDCP-compliant	
Signal cables	(1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter	
Mounting features	(2) detachable, DisplayPort at each end, digital, 1.8 meter Wall or desk mounting using the Extend Arm or third-party accessories, 100mm x 100mm mount	
Security	Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)	
Ship group		1.8 meter analog signal cable, 1.8 meter DP signal cable,
Culh Broch	1.8 meter black power cord	היש הוסיטי מומוטע שעומו טמטוב, הט ווובובו עד שעומו טמטוב,
	Limited Warranty	٨
One details at bates II	•	Accessories
	port.lenovo.com/en_US/guides-and-manuals/de-	Kanainstan Miara Causa Cabla Lasta
tail.page?DocID=UM00	0201	Kensington MicroSaver Cable Lock73P2582Kensington Twin Head Cable Lock45K1620
		See details at www.lenovo.com/support/monitoraccessories
		See all monitors at www.lenovo.com/thinkvision
		Lenovo











