



Versatile Installation Projector

FEATURES

- DLP® technology with BrilliantColor™ for vibrant and rich picture quality
- 5,100 ANSI lumens of brightness, WXGA resolution, and 10,000:1 contrast ratio for clear, crisp and bright projection
- Great flexibility with 1.7x zoom centered lens and manual horizontal and vertical lens shift
- Easy image adjustment for keystone, curved screen, and individual corner corrections
- Pincushion or barrel distortions are easily corrected when projecting onto a curved screen
- HDBaseT interface for HD video and audio over standard CAT5e/6 LAN cable
- 2x 7W speakers and microphone input ensure you are clearly heard
- Integrated network monitoring and management solutions including Crestron® RoomView™, Extron, and etc.
- DICOM Simulation Mode for medical training and seminars
- Built-in 12V trigger for screen or blinds control
- MHL device compatibility for streaming of video and audio content from a compatible mobile device
- PC-Free presentation using JPG picture reader from USB thumb drive



Feature rich with extensive input options and flexible installation range

The DW3321 offers great features and performance combined with great installation flexibility. The 5,100 ANSI lumens make it bright enough for larger screens, and the wide screen WXGA native image resolution ensures that your content will be delivered with fidelity and sufficient detail for a wide range of applications. The 1,34-2,4:1 Throw Ratio makes it possible to install the projector in a wide range of distances, making installation planning easier whether you replace an older projector or making a new installation. The 1,7x zoom range and horizontal and vertical lens shift gives further flexibility when installing the projector.



DW3321 SPECIFICATIONS

Image	Display Type	Single chip DLP® Technology by Texas Instruments
	Brightness	5100
	Native Resolution	WXGA (1280 x 800)
	Max. Supported Resolution	WUXGA (1920 x 1200) @60Hz
	Native Aspect Ratio	16:10
	Contrast Ratio	10,000:1
	Keystone Correction	Vertical: +/-30° ; Horizontal: +/-25°
Optical	Throw Ratio	1.32 - 2.24:1
	Zoom Ratio	1.7x
	Lens Shift (Based on Full Image Height)	Vertical +23.7%, -12.7%; Horizontal +/-10.9%
	Image Size (Diagonal)	21" - 351"
	Projection Distance	1 - 10 m
	Projection Lens	F = 2.45 - 3.22, f = 18.8 - 32 mm
	Offset (Based on Full Image Height)	105% - 141%
Features	Features	3D Ready(DLP link, PC+Video), Direct 3D (HDMI 1.4a), 3D Mandatory Formats supported (top/bottom, right/left, frame sequential), Keypad lock, Presentation Timer, Wireless
Compatibility	Video	SDTV (480i, 576i) / EDTV (480p, 576p) / HDTV (720p, 1080i, 1080p), NTSC (M, 3.58/4.43 MHz), PAL (B,D,G,H,I,M,N) SECAM (B,D,G,K,K1,L)
Connectivity	I/O Connection Ports	VGA-In (15pin D-Sub) (x2), HDMI 1.4b (x2: HDMI/MHLx1, HDMIX1), DVI-D, Component (5 BNC) (RGBHV) , S-Video, Composite Video, Audio-In (RCA) , Audio-In (Mini-Jack) (x3), VGA-Out (15pin D-Sub), Audio-Out (RCA), Audio-Out (Mini-Jack), RJ45 (x2: LANx1, HDBaseTx1), RS-232, 3D-Sync, USB type A for Display(Frame display) and JPG reader(Photo: Jpeg / Video: Mpeg4,H.264) (yes (JPG Reader Only)), USB A (x2: WIFI Dongle or JPEG Reader), USB miniB (USB Display), USB B (Service), Microphone (Mini-Jack), Remote Jack(wire remote)
General	Dimensions (W x D x H)	445 x 331 x 162 mm
	Weight	8.4
	Power	Supply: AC 100-240V, 50/60Hz Consumption: 380W (Eco. Mode), 480W (Normal Mode), <0.5W (Standby)
	Lamp Life and Type	1,500 / 3,500 Hours (Normal / Eco. Mode), 370W/280W
	Speakers	7W x2
	Noise Level	36dB / 33dB (Normal / Eco. Mode)
	Standard Accessories	VGA Cable, User Manual (CD), Quick Start Guide, Warranty Card (by region), Remote Controller (with battery), AC Power Cord
	Optional Accessories	Spare Lamp P/N (5811119760-SVV), 3D Glasses P/N (3534257700), Remote Control P/N (5041846600), WiFi USB Dongle P/N (5040463200)
	Warranty	Standard Warranty: 3 years projector / 1 year on lamp or 1000 hours whichever comes first
	UPC Code	81309702032 1

