

## HZ45UST

Laser 1080p Ultra Short Throw Projector



- Bright Full HD 1080p laser projector 4200 ANSI Lumens
- Super-sized 100-inch images from only 30cm away from a flat surface or screen
- Enjoy live sports, TV shows and gaming in Full 1080p
- Easy to setup multiple connectivity for digital devices and great sound from integrated speakers

Super-sized 100-inch images from 30cm Experience a super-sized 100-inch image with the HZ45UST placed less than 30cm away from a flat surface\* or screen. Laser technology provides accurate, true to life colour reproduction for movies, gaming and live sports. And with high brightness and low latency it is great for playing action-packed games in any room.

An integrated speaker provides you with great sound and two HDMI inputs enables an easy setup. You can even turn it into a smart projector by connecting a HDMI dongle like the Google Chromecast<sup>TM</sup>, Amazon Fire Stick or Apple TV<sup>TM</sup> to play games, stream videos and share photos on the big screen in the comfort of your own home.

\*30cm measured from the back of the projector. Like all Ultra short projectors; to get a perfect image requires a completely flat surface. As most walls are not entirely flat, to avoid slight distortion to the top of the picture, you may need to install a screen onto your projection surface for a perfect image. If this is not possible, we suggest that for non-flat walls you might be better to use a short throw projector which can throw a 100" image from just over 1m".

## **Specifications**

Display/image
Display technology
DLP

Resolution 1080p Full HD (1920x1080)

 Brightness
 4,200 lumens

 Contrast ratio
 3,000,000:1

 Native aspect ratio
 16:10

 Aspect ratio - compatible
 4:3,16:9

 Keystone correction +/-15°

vertical

 $\begin{array}{lll} \mbox{Horizontal scan rate} & 15.3 \sim 91.1 \mbox{Khz} \\ \mbox{Vertical scan rate} & 24 \sim 85 (120 \mbox{ for 3D)Hz} \\ \end{array}$ 

Uniformity 80%

2.21m ~ 2.59m (87" ~ 102") (diagonal) Screen size Lamp info Light source type LASER life 30,000 hours Optical Throw ratio 0.25:1 Projection distance (m) 0.45m - 0.59m Zoom type Fixed Focal length (mm) 3.72 Native offset

Connectivity

Connections Inputs 2 x HDMI 1.4a 3D support, 2 x VGA (YPbPr/RGB),

1 x Composite video, 1 x Audio 3.5mm, 1 x Audio RCA L&R

Outputs 1 x VGA shared with VGA2, 1 x Audio 3.5mm, 1 x

USB-A power 2A  $\label{eq:control} \mbox{Control 1 x RS232, 1 x RJ45, 1 x 12V trigger, 1 x mini }$ 

USB service, 1 x USB-A reader/wireless

General

3D compatibility

Noise level (typical) 30dB

 PC compatibility
 FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac

 2D compatibility
 NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H//M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p,

4,43MHZ SECAM B/D/G/RXI/L, 4.25/4.4MHZ 480I/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60

3D Full 3D

Security Security bar, Kensington Lock, Password protected interface

OSD / display languages 18 languages

A rabic, Danish, Dutch, English, Finnish, French, German, Italian, Japanese, Norwegian, Polish, Portuguese, Russian, Chinese Arabic, Danish, Dutch, English, Finnish, French, German, Italian, Japanese, Norwegian, Polish, Portuguese, Russian, Chinese Arabic, Danish, Dutch, English, Finnish, French, German, Italian, Japanese, Norwegian, Polish, Portuguese, Russian, Chinese Arabic, Danish, Portuguese, Po

(simplified),Spanish,Chinese (traditional),Turkish 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m

 $\begin{array}{ll} \mbox{ Operating conditions} & 5^{\circ}\mbox{C} \sim 40^{\circ}\mbox{C}, \mbox{ Max. Humidity 85} \\ \mbox{ Remote control} & \mbox{Yes} \\ \end{array}$ 

Speaker count 1
Watts per speaker 10W
In the box AC or

the box AC power cord Remote control 2x AAA batteries Basic user manua

Networking LAN - control Yes

Power res

Power supply  $100 \sim 240 \text{V}, 50 \sim 60 \text{Hz}$ Power consumption 0.5 W

(standby)

Power consumption (min) 210W Power consumption (max) 330W

Weight and dimensions

 Net weight
 5.6kg

 Dimensions (W x D x H)
 382 x 310 x 124

mm



