

ZH550T

Brighter for longer – 30,000 hours full brightness mode



- **Bright full HD 1080p laser projector - 5500 lumens**
- **30,000 hours maintenance-free laser light source at full brightness mode**
- **Dust resistant – independently tested, IP5X certification for total reliability**
- **Versatile orientation including 360° projection**

The ZH550T professional laser projector offering 5500 lms full HD 1080p resolution. Advanced optical components, a lightweight chassis, IP5X-certified dust resistant optical engine are just some features on this affordable projector. Designed for maintenance free, continuous operation, 24 hours a day. The ZH550T is truly fit and forget. Horizontal and vertical lens shift come as standard, as does an impressive 1.6x optical zoom. The projector can be installed in any orientation without effecting performance and the HdBaseT connectivity further adds to installation flexibility by allowing users to easily send and display audio and video files with a single cable.

Specifications

Display/image	
Display technology	DLP
Resolution	1080p Full HD (1920x1080)
Brightness	5,500 lumens
Contrast ratio	300,000:1
Native aspect ratio	16:9
Aspect ratio - compatible	4:3,16:9,16:10
Keystone correction - horizontal	+/-30°
Keystone correction - vertical	+/-30°
Horizontal scan rate	15.375 ~ 91.146Khz
Vertical scan rate	24 ~ 85(120 for 3D)Hz
Uniformity	85%
Screen size	0.76m ~ 7.62m (30" ~ 300") (diagonal)
Lamp info	
Light source type	Laser
LASER life	30,000 hours
Optical	
Throw ratio	1.2:1 - 1.92:1
Projection distance (m)	1.28m - 8.5m
Zoom	1.6
Zoom type	Manual
Focal length (mm)	17.63 ~ 31.36
Lens shift	Vertical +25%, Horizontal +10%
Native offset	105%
Connectivity	
Connections	<p>Inputs 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm, 1 x Microphone, 1 x RS232, 1 x USB-A power 1.5A, 1 x USB-B service, 1 x Wired remote, 1 x RJ45, 1 x HDMI 1.4a 3D support + MHL, 1 x HDBaseT, 1 x HDMI 1.4a 3D support, 1 x 3D sync</p> <p>Outputs 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm, 1 x 12V trigger</p>
General	
Noise level (typical)	28dB
PC compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4.43MHz SECAM B/D/G/K/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
3D compatibility	Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60
3D	Full 3D
Security	Security bar,Kensington Lock,Password protected interface
OSD / display languages	18 languages: Arabic,Danish,Dutch,English,Finnish,French,German,Italian,Japanese,Nc (simplified),Spanish,Chinese (traditional),Turkish
24/7 operation	Yes
360° operation	Yes
Operating conditions	5°C ~ 40°C, Max. Humidity 90%, Max. Altitude 3000m
Remote control	Wired backlit PRO AV remote
Speaker count	2
Watts per speaker	10W
In the box	AC power cord Remote control 2x AAA batteries Basic user manual
Networking	
LAN - control	Yes
Power	
Power supply	100 ~ 240V, 50 ~ 60Hz
Power consumption (standby)	0.5W
Power consumption (min)	260W
Power consumption (max)	370W
Weight and dimensions	
Net weight	10.7kg
Dimensions (W x D x H) mm	405 x 387 x 159

