

ZH506

High brightness professional laser projector



- **Bright Full HD 1080p laser projector - 5000 ANSI Lumens**
- **30,000 hours maintenance-free laser light source at full brightness**
- **IP5X Dust protection**
- **Small lightweight chassis**

Professional life like colours the long life of laser in a smaller lighter chassis than ever before. The ZH506 is a low maintenance projector with extremely long-life laser technology offering an impressive 5000lms brightness. With 1.6 zoom, vertical lens-shift and built in 10W speakers the ZH506 is part of a range a range of products that come with the added control flexibility of Crestron. Suitable for a wide variety of applications, the ZH506 version is 16:09 native at full HD 1080p making this unit perfect for large venues, education, museums, houses of worship and anywhere a clean bright image is required.

Specifications

Display/image	
Display technology	DLP
Resolution	1080p Full HD (1920x1080)
Brightness	5,000 lumens
ANSI brightness	5,000 lumens
Contrast ratio	300,000:1
Native aspect ratio	16:9
Aspect ratio - compatible	4:3,16:9,16:10
Keystone correction - horizontal	+/-30°
Keystone correction - vertical	+/-30°
Has vertical auto keystone correction	Yes
Displayable colours (millions)	1073.4
Horizontal scan rate	15.375~91.146 KHz
Vertical scan rate	50~ 85 Hz (120Hz for 3D)Hz
Uniformity	85%
Screen size	0.72m ~ 7.62m (28.2" ~ 300") (diagonal)
Lamp info	
Light source type	Laser
LASER life	30,000 hours
Optical	
Throw ratio	1.4:1 - 2.24:1
Projection distance (m)	1m - 10m
Zoom	1.6
Zoom type	Manual
Focal length (mm)	20.913(wide)~32.626mm(tele)@ 60"
Lens shift	Vertical -103 ~ 118%, Horizontal: +/-0%
Native offset	103%
Lens shift	Yes - {{downloads_link}}
Connectivity	
Connections	Inputs 1 x HDMI 1.4a 3D support, 1 x HDMI 1.4a 3D support + MHL, 1 x VGA, 1 x Composite video, 1 x RS232, 1 x Mic 3.5mm, 1 x Audio 3.5mm, 1 x RJ45 Outputs 1 x VGA, 1 x USB-A power 1.5A, 1 x Audio 3.5mm
General	
Noise level (typical)	28dB
PC compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4.43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
3D compatibility	Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60
3D	Full 3D
Security	Security bar,Kensington Lock,Password protected interface
OSD / display languages	25 languages: Arabic,Czech,Danish,Dutch,English,Farsi,Finnish,French,German,Greek,Hungarian,Indonesian,Italian,Japanese,Norwegian,Polish,Portuguese,Romanian,(simplified),Spanish,Swedish,Chinese (traditional),Turkish,Vietnamese
24/7 operation	Yes
Operating conditions	sea level to 10,000ft (3048m)
Remote control	Backlit ProAV remote
Speaker count	2
Watts per speaker	10W
In the box	AC power cord Remote control 2x AAA batteries Basic user manual
Networking	
LAN - control	Yes
LAN - display	Yes
Power	
Power supply	100V ~ 240V ± 10%, 50-60Hz
Power consumption (standby)	<0.5W
Power consumption (min)	190W
Power consumption (max)	341W
Weight and dimensions	
Net weight	5.5kg
Dimensions (W x D x H) mm	374 x 302 x 117