

MultiSync® UN462VA

LCD 46" Video Wall Display

Datasheet



Turn every wall into an opportunity

The slim NEC MultiSync® UN462VA turns any wall into an opportunity to reliably display information like passenger information, restaurant menus, or corporate agendas. And it does so for less the price, while never sacrificing performance. These displays were made with busy spaces in mind – airports, train stations, casual dining restaurants and even mission-critical spots like control rooms – and optimised to project static and moving content. Designed with 500 cd/m² of brightness, these screens are easy to read under common light conditions. Installation and operation is a breeze. It comes equipped with powerful calibration capabilities, so the initial video wall setup requires minimal effort, while the long-term colour and brightness will maintain a striking homogeneity. The screen's frameless design forms a flat digital canvas that allows it to blend in and create one continuous image across multiple screens.

Benefits

Easy to install – it's simple to get your display up and running with its out-of-the-box calibrated picture pre-sets, managing colour settings and uniformity controlled by the SpectraView Engine — not to mention its simple, software-free calibration capabilities.

Accelerate your video wall configuration – set up your wall in no time with the display's powerful configuration capabilities, which include Auto ID/IP, Auto Tile Matrix, and Tile-/Frame Compensation. Enjoy flawless playback across your entire video wall.

Long-lasting continuous pictures – align your display with powerful calibration capabilities. Use the white copy function, colour drift correction, uniformity control, self-calibration and validation to create a continuous surface across multiple screens that gives the appearance of one, seamless wall.

Reliable image reproduction – best suited for static image reproduction with reliable accuracy in mission critical applications. Our PVA panel technology makes sure you have the best viewing experience with excellent contrast and black level.

Enhanced imaging performance – advanced settings of all relevant visual parameters allow full control of brightness, colour, gamma and uniformity via the Spectraview Engine for precise, natural images.

Future Ready with Open Modular Intelligence Expansion – upgrade the power of your display at any time by seamlessly integrating one of NEC's options for OPS Slot-in PCs, Raspberry Pi compute modules or signal interfaces for content feed and computing.

Safe and secure displays – each display is EMC class-B certified and ideally suited for critical emission environments that require safer standards than other displays do.

Product Information

| | |
|---------------|----------------------------|
| Product Name | MultiSync® UN462VA |
| Product Group | LCD 46" Video Wall Display |
| Order Code | 60004518 |

Display

| | |
|---------------------------------|---|
| Panel Technology | VA with Direct LED backlights |
| Active Screen Area (W x H) [mm] | 1,018.1 x 572.7 |
| Screen Size [inch/cm] | 46 / 117 |
| Aspect Ratio | 16:9 |
| Pixel Pitch [mm] | 0.530 |
| Brightness [cd/m²] | 500 |
| Contrast Ratio (typ.) | 3500:1 |
| Viewing Angle [°] | 178 horizontal / 178 vertical (typ. at contrast ratio 10:1) |
| Response Time (typ.) [ms] | 8 |
| Panel Refresh Rate [Hz] | 60 |
| Haze Level [%] | 25 |
| Supported Orientation | Landscape; Portrait |

Synchronisation Rate

| | |
|----------------------------|----------|
| Horizontal Frequency [kHz] | 26 - 134 |
| Vertical Frequency [Hz] | 23 - 86 |

Resolution

| | | | | |
|-----------------------------------|--------------|--------------|-------------|------------------|
| Native Resolution | 1920 x 1080 | | | |
| Supported on DisplayPort and HDMI | 3840 x 2160; | 1360 x 768; | 1080i; | 800 x 600; |
| | 1920 x 1080; | 1280 x 1024; | 1080p; | 720p (50/60 Hz); |
| | 1600 x 1200; | 1280 x 768; | 1024 x 768; | 640 x 480 |

Connectivity

| | |
|-----------------------|---|
| Input Video Analogue | 1 x VGA; Composite (RCA) |
| Input Video Digital | 1 x DVI-D (with HDCP); 1 x OPS Slot; 2 x DisplayPort (with HDCP); 2 x HDMI (with HDCP) |
| Input Audio Analogue | 2 x 3,5 mm jack |
| Input Audio Digital | 2 x DisplayPort; 2 x HDMI |
| Input Control | 1 x RS232; 2 x LAN 100Mbit; remote control wire (3,5mm jack) |
| Input Data | 1 x microSD (Media Player); 1 x USB 1.0 (Media Player); 1 x USB 2.0 (Downstream); 1 x USB 2.0 (Upstream); 2 x USB 1.0 (Compute Module, 1 x 5V/2A powered) |
| Output Video Digital | 1 x DisplayPort (loop through: DisplayPort, OPS slot-in PC); 1 x HDMI (loop through: HDMI, OPS slot-in PC, Mediaplayer) |
| Output Audio Analogue | 1 x 3,5 mm jack |
| Output Control | LAN 100Mbit |

Open Modular Intelligence

| | |
|--|--|
| OPS Slot | Slot Technology: Open pluggable specification (NEC / Intel OPS standard) |
| OPS Max. Current / Power Consumption [A / W] | 3.6 / 58 |
| Compute Module Slot | Slot Technology: Compute Module Slot (NEC proprietary standard) |

Sensors

| | |
|--------------|--|
| Human Sensor | Optional, external, 4-5m range, triggered actions programmable |
|--------------|--|

Electrical

| | |
|------------------------|--------------------------------|
| Power Consumption [W] | 290 (max.); 90 shipping |
| Power Savings Mode [W] | < 0.5; < 2 (Networked Standby) |

Environmental Conditions

| | |
|----------------------------|-----------|
| Operating Temperature [°C] | +0 to +40 |
| Operating Humidity [%] | 20 to 80 |
| Storage Humidity [%] | 10 to 90 |
| Storage Temperature [°C] | -20 to 60 |

Mechanical

| | |
|-----------------------------|-------------------------------------|
| Dimensions (W x H x D) [mm] | 1,022 x 577 x 101 |
| Weight [kg] | 21.4 |
| Bezel Width [mm] | 1.2 bottom/right; 2.3 top/left; 3.5 |
| VESA Mounting [mm] | 300 x 300 (FDMI); 4 holes; M6 |

MediaPlayer

| | |
|-------------------------|---|
| Supported Image Formats | JPG (baseline, progressive, RGB, CMYK); max. resolution 5000 x 5000; PNG (interlace, alpha channel); max. resolution 4000 x 4000 |
| Supported Video Formats | MP4 / MOV / FLV (video H.264, audio MP3, AAC); max. resolution 1080p at 30 Hz, 1080i at 60 Hz; MPG (video mpeg1/2, audio mpeg audio layer2/3, AAC-LC); MP @ ML, MP @ HL; WMV (video H.264, wmv advanced L3, wmv simple / main, audio mp3 wmv std); max. resolution 1080p at 30 Hz, 1080i at 60 Hz |
| Supported Audio Formats | MP3 (MP3); max. bit-rate 320 kBit/s; WAV (LPCM); max. 48 kHz sampling |

Available Options

| | |
|---------------------|---|
| Accessories | Calibration kit (KT-LFD-CC2); Feet (ST-322); Overframe kit (KT-46UN-OF5); Remote control kit (KT-RC2; KT-RC3); Speaker (SP-TF1); Wall mount (PD02VWM MFS 46-55 L/P; PD02VWM QR 46-55 L/P; CK02XUN MFS 46 L/P) |
| Compute Module Slot | Raspberry Pi Compute Module 1 and 3 |

Green Features

| | |
|-------------------|--|
| Energy Efficiency | Annual energy consumption: 157 kWh (based on 4 operating hours per day); Carbon savings meter; Energy efficiency class: B; Human Sensor; LED backlight |
|-------------------|--|

Additional Features

| | |
|-------------------------|---|
| Special Characteristics | Auto ID assignment; Auto tiling function; Automatic Alarm E-Mails; DICOM Simulation; Frame Comp; HTTP Server; Image flip; Intelligent Wireless Data (based on NFC); NaViSet Administrator 2; TileMatrix; USB Media Player; User input priority definition; User readable log function |
| Colour Versions | Black Front Bezel, Black Back Cabinet |
| Safety and Ergonomics | BSMI; CE; EAC; EMC Class B; FCC; PSB; RCM; REACH; RoHS; SASO; TÜV GS; TÜV S; UL/C-UL; VCCI |
| Pixel Failure Class | ISO 9241-307, Class 2 |
| Audio | Optional Speakers (15 W + 15 W) |
| Plug and Play | VESA DDC/CI |
| Shipping Content | Display; DisplayPort Cable; HDMI Cable; Power Cable |
| Warranty | 3 years warranty incl. backlight; additional services available; optional 4. + 5. year warranty extension |



CE



RCM



RoHS



TÜV GS



VCCI

This document is © 2019 NEC Display Solutions Europe GmbH.

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are excepted. 11.04.2019