


Key Features

Ultra HD Resolution | Built-in Multi-Core Media
Player with 8GB Storage | Embedded LAN, Optional
Wi-Fi, and Internet Browser | ViewBoard® Cast
Content Sharing Software | Free Bundled
vController™ Software




Product Description

The ViewSonic® CDE5510 is a 55" (54.6" viewable) 4K Ultra HD commercial display purpose-built to deliver eye-catching imagery for hotels, restaurants, retail, business, and more. With stunning 3840x2160 resolution, 350-nit high brightness, wide viewing angles, and dual 10W speakers, this display provides immersive, high-impact messaging wherever needed. An embedded Android SOC allows you to install Android apps for rich content broadcasting. In addition to HDMI, DVI, and VGA inputs to connect with various high definition devices, this display utilizes an integrated multi-core processor and 8GB of internal memory, allowing customers to playback multimedia content via USB without the need for a PC. To make life even easier, the bundled vController software offers easy maintenance and intuitive interfaces for remote management via a PC server or laptop, and its flicker-free and blue light filter technologies help provide a comfortable viewing environment.



- | | | | | |
|---|-------------------|-------------------|-----------------|------------------|
| 1. Internal Speakers | 4. Power Switch | 8. USB 2.0 Type A | 12. HDMI 2.0 x2 | 16. RS232 In/Out |
| 2. VESA® Compatible Wall Mount 400 x 400 mm | 5. Menu Controls | 9. Audio In | 13. DVI In | |
| 3. AC In | 6. SD Reader | 10. PC Audio Out | 14. IR In/Out | |
| | 7. USB 3.0 Type A | 11. VGA | 15. LAN | |



55"
DISPLAY



3840 x 2160
RESOLUTION



350 cd/m2
BRIGHTNESS

16/7

Contact Sales

- call: 888.881.8781
- email: salesinfo@viewsonic.com
- visit: viewsonic.com

Display:

Display Size (in.):	55
Viewable Area (in.):	54.6
Light Source:	DLED
Resolution:	3840 x 2160
Aspect Ratio:	16:9
Static Contrast Ratio:	4,000:1
Backlight Life (Hours):	30,000
Brightness:	350 cd/m2
Response Time (Typical GTG):	8ms
Bezel Width (mm):	Top 12.9 mm / Right 12.9 mm / Left 12.9 mm / Bottom 14.7 mm
Viewing Angles:	178° horizontal, 178° vertical
Panel Surface:	3H Anti-glare, hard-coating
Operation Rating:	16/7

Embedded Player:

CPU:	Multi-Core ARM - MSD95E1D
Memory:	2GB
Storage:	8GB eMMC
Interface:	OSD / Remote Control

Audio:

Internal Speakers:	10W (x2)
--------------------	----------

Connector:

HDMI 2.0(2), DVI-I(1), 3.5mm Audio Out(1), USB 3.0(1), USB 2.0(1), RS232(1), RS232 Out(1), Ethernet LAN (RJ45)(1), Micro SD Card Slot(1), IR in(1), IR out(1)

Power:

Voltage:	100-240 VAC +/- 10% Wide Range, 50-60Hz +/-3 Hz
Consumption (max):	190W
Consumption (typical):	145W
Stand-by:	<0.5W

Controls:

On Screen Display:	Picture, Screen, Audio, Configuration 1, Configuration 2, Advanced Option
Remote Control:	Volume, Channel, Source, Mute, Back, Input, Menu

Operating Conditions:

Temperature:	41-104° F (5 - 40° C)
Humidity (non-condensing):	20-80%

Weight (metric):

Net (kg):	17.8
Net Without Stand (kg):	16.0
Gross (kg):	22.3

Weight (imperial):

Net (lbs):	39.2
Net Without Stand (lbs):	35.2
Gross (lbs):	49.2

Dimensions (metric) (WxHxD):

Packaging (mm):	1365.0 x 864.0 x 185.0
Physical (mm):	1239.2 x 751.9 x 329.8
Physical Without Stand (mm):	1239.2 x 711.6 x 61.7

Dimensions (imperial) (WxHxD):

Packaging (in.):	53.7 x 34.0 x 7.3
Physical (in.):	48.8 x 30.0 x 13.0
Physical Without Stand (in.):	48.8 x 28.0 x 2.4

Mount:

VESA Compatible:	400 x 400 mm
------------------	--------------

General:

Warranty: Three-year limited warranty on parts, labor and backlight
Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.
PACKAGE CONTENTS: CDE5510, Remote control, CD User Manual, Quick Start Guide, Power cables, VGA cable, RS232 cable, IR sensor cable, RS232 daisy chain cable
Regulations: UL/cUL, FCC, Energy Star 7.0, UL-MX-CoC, Mexico Energy
UPC: 766907953213

Accessories:

CD-EW-55-01, CD-EW-55-02, NMP-302WX, NMP-302w, NMP580-W, NMP620-P10, NMP620-P10X, SC-A25R, STND-034, SW-071, SW-072, SW-073, SW-074, SW-090, SW-091, SW-092, SW-093, SW-094, SW-095, SW-096, VC10, VCB10, WMK-014, WMK-047-2, WMK-051, sc-a25x
--