

Key Features

Built-in Quad Core Media Player with
16GB Storage | Embedded LAN and Wi-Fi
| Internet Browser | Internal Scheduler |
Integrated USB Multimedia Player



Product Description

Physical deployment, content creation, and message delivery couldn't be easier than with the ViewSonic® CDM4300R. Featuring an internal media player this commercial display gives you everything you need for easy digital signage – right out of the box. Loaded with a powerful, high-performance processor and 16GB of storage (upgradeable to 32GB), the built-in media player ensures hours upon hours of smooth, high-definition multimedia content delivery. The CDM4300R also features built-in LAN / WiFi for easy connection to the internet for content delivery. Additional commercial features include internal scheduler, tiling for video wall application, and commercial construction delivers reliable messaging 24 hours a day, 7 days a week.

Visit Us ■ www.viewsonic.com

LCD PANEL

Panel Size:	43"
Type/Tech:	TFT LCD Module. (IPS, ELED backlight)
Display Area:	941.184(H) x 529.416(V) (42.51" diagonal)
Aspect Ratio:	16:9
Resolution:	1920x1080
Colors:	16.7M
Brightness:	450 nits (typ.)
Contrast Ratio:	1100:1 Typ.
Response Time:	12ms
Viewing Angles:	H = 178, V = 178 typ.
Backlight Life:	50,000 Hours Typ.
Surface Treatment:	Hard coating(3H), Anti- glare treatment of the front polarizer (Haze 1%(Typ.)
Orientation:	Landscape and Portrait Enabled

INPUT

HDMI:	x2
DisplayPort:	x1
DVI:	x1
Audio:	x1
RS232:	x1
IR Pass Through:	x1

OUTPUT

DisplayPort:	x1
DVI:	x1
RS232:	x1
IR Pass Through:	x1

LAN

RJ45:	x1
-------	----

USB

Type A:	x2 (Multi-media playback x 1, 5V/2A x 1)
Type B:	x1 (Up Stream)
Micro USB:	x1 (Support USB OTG)

SPEAKERS

10W (L) + 10W (R)

COMPATIBILITY

HDMI:	480i, 480p,720p,1080i,1080p
DisplayPort:	480i, 480p,720p,1080i,1080p
DVI:	480i, 480p,720p,1080i,1080p

CONTROLS

Embedded Linux OS:	Yes (4.4.4)
USB SUPPORTED FILE FORMAT:	JPG, JPEG, PNG, GIF, BMP, DAT, MPG, VOB, TS, AVI, MKV, MP4, MOV, 3GP, FLV, WEBM, ASF, MP1, MP2, MP3, WMA, AAC, M4A

POWER

Voltage:	100-240 VAC +/- 10% Wide Range, 50-60Hz +/-3 Hz
Consumption:	60W (typ)

ERGONOMICS

Wall Mount (VESA®):	400 x 400
----------------------	-----------

OPERATING CONDITIONS

Temperature (° C):	0 to 40°C (Landscape) / 0 to 35°C (Portrait)
Humidity:	20% ~ 80% non- condensing

DIMENSIONS (W X H X D)

Physical (inch / mm):	37.99 x 22.02 x 1.79 / 965.0 x 559.3 x 45.5
-----------------------	--

WEIGHT

Net (lb / kg):	23.59 / 10.7 (w/o stand)
----------------	-----------------------------

REGULATIONS

UL, FCC, Energy Star 7.0, EPEAT, Mexico Energy
--

PACKAGE CONTENTS

CDM4300R commercial display/ Remote Control with batteries / User manual CD wizard / Quick Start Guide / Power Cables / RS232 cable / 2.4mm – 2.4mm cable
