

Key Features

4K Ultra HD Resolution4K Resolution |
Broadcast Content from Android
AppsDiverse Android apps rich content |
Intel OPS Expansion Slot for
ComputingComputing expansion |
Integrated USB Multimedia PlayerUSB
playback photos, music & video |
vController™ Software: Remote Display
ManagementvController™ software:
remote display management



Product Description

The ViewSonic CDE6510 is a great value 65" 4K LED commercial display with high-reliability 16 hours per day/7 days a week operating time. The embedded Android SOC enables CDE6510 to install Android apps for rich content broadcasting while the Intel OPS PC slot supports higher computing performance with 4K DisplayPort for a wide range of user scenarios. A built-in browser offers a convenient method for displaying internet content without a PC. In addition to versatile connectivity options, including 4K DisplayPort, HDMI, VGA, USB, IR, RJ45, the display comes with a convenient USB multimedia playback function. With 3840 x 2160 resolution, 350-nit brightness with 178-degree wide viewing angles, and 2 x 10W stereo speakers, the slim-bezel CDE6510 delivers vivid images and remarkable sound for superior multimedia performance. The HDMI CEC pass-through support provides one control for multiple HDMI-connected devices while the free-bundled vController software makes remote display management easier via RSS232/RJ45 port. The display also comes equipped with Blue Light Filter technology to create a more comfortable viewing experience.

Visit Us ■ www.viewsonic.com

LCD PANEL

Panel Size:	65"
Type/ Tech:	TFT LCD Module with DLED Backlight
Display Area (mm):	1428.48 (H) x 803.52 (V)
Aspect Ratio:	16:9
Resolution:	3840x2160 @60Hz
Colors:	1.07B colors
Brightness:	350 nits (typ.)
Contrast Ratio:	4000:1 (typ.)
Response Time:	8 ms
Viewing Angles:	H = 178, V = 178 (typ.)
Backlight:	DLED
Backlight Life:	30,000 Hours Min.
Hardness:	3H

INPUT

HDMI:	x 4
RGB / VGA:	x 1
DisplayPort:	x 1
Audio:	x1 PC audio (3.5 mm)
RS232:	x 1
PC Slot:	x 1 (optional VPC12-WPO-2)
IR:	x 1

OUTPUT

RS232:	x 1
IR:	x 1

LAN

RJ45:	x 1
-------	-----

USB

Type A:	x 1 for 5V/2A
2.0 Type A:	x 2 (USB Playback)
3.0 Type A:	x 1 (USB Playback)

SPEAKERS

10W x 2

COMPATIBILITY

VGA:	1920 x 1080
DisplayPort:	480i, 480p, 720p, 1080i, 1080p, 4K2K@30Hz
HDMI:	480i, 480p, 720p, 1080i, 1080p, 4K2K@60Hz

POWER

Voltage:	100-240 VAC +/- 10% Wide Range, 50-60Hz +/-3 Hz
Consumption:	Normal 165 W, Max 295 W

ERGONOMICS

Wall Mount (VESA®):	400 x 400mm ; Screw: M6*(10+X) mm. (X=thickness of wall mount plate)
---------------------	---

OPERATING CONDITIONS

Temperature (° C):	5°C to 40°C
Humidity:	20% ~ 80% non- condensing

DIMENSIONS

(W X H X D)

Physical (mm / inch):	1458.7 x 938.8 x 540 mm / 57.43 x 36.96 x 21.26 in. (with Stand)
Physical w/o Stand (mm / inch):	1458.7 x 834.7 x 81.6 mm / 57.43 x 32.86 x 3.21 in. (w/o Stand)
Packaging (mm / inch):	1655 x 1078 x 280 mm / 65.16 x 42.44 x 11.02 in

WEIGHT

Net (kg / lb):	28.9 kg / 63.71 lbs (with Stand)
Net w/o Stand (kg / lb):	24.8 kg / 54.67 lbs (w/o stand)
Gross (kg / lb):	34.84 kg / 76.80 lbs

REGULATIONS

Standard:	US NRTL with Canada, FCC, Energy star, Mexico CoC and energy , CE, CB, RoHS, ErP, REACH, WEEE, RCM
-----------	---

WHAT'S IN THE BOX?

1. CDE6510 commercial display
2. Remote Control with batteries
3. User manual CD wizard
4. Quick Start Guide
5. Power Cables
6. RS232 cable
7. RS232 daisy chain cable (2.4mm – 2.4mm)
8. IR sensor cable