

Key Features

Ultra HD Resolution | Built-in Multi-Core Media
Player with 8GB Storage | Embedded LAN, Optional
Wi-Fi, Internet Browser | ViewBoard® Cast Content
Sharing Software | Free Bundled vController™
Software




Product Description


The ViewSonic® CDE5010 is a 50" (50" viewable) 4K Ultra HD commercial display purpose-built to deliver eye-catching imagery for hotels, restaurants, retail, business, and more. With stunning 3840x2160 resolution, 350-nit high brightness, wide viewing angles, and dual 10W speakers, this display provides immersive, high-impact messaging wherever needed. In addition to HDMI, DVI, and VGA inputs to connect with various high definition devices, this display utilizes an integrated multi-core processor and 8GB of internal memory, allowing customers to playback multimedia content via USB without the need for a PC. To make life even easier, the bundled vController software offers easy maintenance and intuitive interfaces for remote management via a PC server or laptop, and flicker-free and blue light filter technologies help provide a comfortable viewing environment.



- | | | | | |
|---|-------------------|-------------------|-----------------|------------------|
| 1. Internal Speakers | 4. Power Switch | 8. USB 2.0 Type A | 12. HDMI 2.0 x2 | 16. RS232 In/Out |
| 2. VESA® Compatible Wall Mount 400 x 400 mm | 5. Menu Controls | 9. Audio In | 13. DVI In | |
| 3. AC In | 6. SD Reader | 10. PC Audio In | 14. IR In/Out | |
| | 7. USB 3.0 Type A | 11. VGA | 15. LAN | |



50"
DISPLAY



3840 x 2160
RESOLUTION



350 cd/m2
BRIGHTNESS

Contact Sales

- call: 888.881.8781
- email: salesinfo@viewsonic.com
- visit: viewsonic.com

Display:

Display Size (in.):	50
Viewable Area (in.):	50
Light Source:	DLED
Resolution:	3840 x 2160
Aspect Ratio:	16:9
Static Contrast Ratio:	4,000:1
Backlight Life (Hours):	30,000
Brightness:	350 cd/m2
Response Time (Typical GTG):	8ms
Viewing Angles:	178° horizontal, 178° vertical
Panel Surface:	Anti-glare, Hard coating (3H)

Embedded Player:

CPU:	Quad Core - Cortex A53
Memory:	2GB
Storage:	8GB eMMC
Interface:	OSD / Remote Control

Audio:

Internal Speakers:	10W (x2)
--------------------	----------

Connector:

HDMI 2.0(2), DVI-D(1), VGA(1), RCA Audio Out(1), 3.5mm Audio In(1), USB 3.0(1), USB 2.0(1), RS232(1), RS232 Out(1), Ethernet LAN (RJ45)(1), Micro SD Card Slot(1), IR in(1), IR out(1)
--

Power:

Voltage:	100-240 VAC +/- 10% Wide Range, 50-60Hz +/-3 Hz
Consumption (max):	175W
Consumption (typical):	140W
Stand-by:	<0.5W

Operating Conditions:

Temperature:	41-104° F (5 - 40° C)
Humidity (non-condensing):	20-80%

Weight (metric):

Net (kg):	14.9
Net Without Stand (kg):	13.0
Gross (kg):	16.5

Weight (imperial):

Net (lbs):	32.9
Net Without Stand (lbs):	28.7
Gross (lbs):	36.4

Dimensions (metric) (WxHxD):

Packaging (mm):	1282.0 x 845.0 x 203.0
Physical (mm):	1123.6 x 685.9 x 329.6
Physical Without Stand (mm):	1123.6 x 646.7 x 67.8

Dimensions (imperial) (WxHxD):

Packaging (in.):	50.5 x 33.3 x 8.0
Physical (in.):	44.2 x 27.0 x 13.0
Physical Without Stand (in.):	44.2 x 25.5 x 2.7

Mount:

VESA Compatible:	400 x 400 mm
------------------	--------------

General:

Warranty: Three-year limited warranty on parts, labor and backlight
Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.
PACKAGE CONTENTS: CDE5010, Remote control, CD User Manual, Quick Start Guide, Power cables, VGA cable, RS232 cable, IR sensor cable, RS232 daisy chain cable
Regulations: cULus, FCC, Energy Star 7.0, UL-MX-CoC, Mexico Energy
UPC: 766907990416

Accessories:

NMP-302WX, NMP-302w, NMP580-W, NMP620-P10, NMP620-P10X, NMP660, SC-A25R, VC10, VCB10, WMK-014, WMK-047-2, WMK-051, sc-a25x
--