



Key Features

Enhanced Touchscreen Performance | Immersive Stereo Sound |
myViewBoard™ Annotation Software | ViewBoard Cast Content Sharing
Software | SmartPort USB™



Product Description

Featuring 4K Ultra HD resolution and an advanced, next-generation touchscreen, the ViewSonic® ViewBoard® IFP7550 delivers incredible collaborative capabilities for 21st century boardrooms and classrooms. With integrated myViewBoard® annotation software and ViewBoard Cast streaming software, content creation and sharing has never been easier. What’s more, this ENERGY STAR certified display delivers optional slot-in PC capability for more computing-intensive interactive applications. A VESA-compatible design allows for installation on a wall mount, or on an optional trolley cart for more flexible installation in classrooms and meeting rooms.



75"
DISPLAY

RESOLUTION

20-Point
TOUCH INTERACTIVE

Contact Sales

- call: 888.881.8781
- email: salesinfo@viewsonic.com
- visit: viewsonic.com

Display:

Display Size (in.):	75
Viewable Area (in.):	74.5
Light Source:	LED
Resolution:	3840 x 2160
Aspect Ratio:	16:9
Static Contrast Ratio:	1,200:1
Backlight Life (Hours):	50,000
Brightness:	350 cd/m2
Response Time (Typical GTG):	8ms
Viewing Angles:	178° horizontal, 178° vertical
Panel Surface:	Anti-glare 7H tempered glass

Networking:

Ethernet LAN:	10/100 Mbps
---------------	-------------

Embedded Player:

Android Version:	7.0
GPU:	ARM Mali450 Quad Core
CPU:	ARM Quad Core Cortex A73
CPU Processor Speed:	1.2GHz
Memory:	2GB
Storage:	16GB
Interface:	OSD / Remote Control / Annotation overlay

Audio:

Internal Speakers:	10W (x2)
Woofers:	15W (x1)

Connector:

HDMI 2.0(3), HDMI Out(1), VGA(1), Composite RCA(1), 3.5mm Audio In(1), 3.5mm Audio Out(1), SPDIF Audio Out(1), USB 3.0(2), USB 2.0(4), Slot-in PC Slot(1), USB B Touch Port(2), RS232(1), Ethernet LAN (RJ45)(1), WIFI Module Slot(1)

Power:

Voltage:	100-240 VAC
Consumption (typical):	350W
Stand-by:	<0.5W

Controls:

On Screen Display:	Input, Volume, Backlight, Audio, Screen, Display, Adjust
Remote Control:	Volume, Channel, Source, Mute, Back, Input, Menu

Operating Conditions:

Temperature:	32-104° F (0 - 40° C)
Humidity (non-condensing):	10-90%

Touch:

Touch Technology:	Infrared
Touch Points:	20-Point Touch
Tip Detection:	Dual tips, 3mm and 8mm

Weight (metric):

Net (kg):	53.0
Gross (kg):	65.0

Weight (imperial):

Net (lbs):	116.8
Gross (lbs):	143.3

Dimensions (metric) (WxHxD):

Packaging (mm):	1930.0 x 1140.0 x 280.0
Physical (mm):	1710.0 x 1020.0 x 90.0

Dimensions (imperial) (WxHxD):

Packaging (in.):	76.0 x 44.9 x 11.0
Physical (in.):	67.3 x 40.2 x 3.5

Mount:

VESA Compatible:	600 x 400 mm
------------------	--------------

Additional Hardware:

Camera Mounting Bracket:	1
--------------------------	---

General:

Warranty: 3-year limited warranty on parts, labor and backlight, onsite warranty

Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.

PACKAGE CONTENTS: IFP7550 display, stylus pen x 2, power cable, HDMI cable, USB cable, AV cable, remote control with batteries, Camera plate, M8 screw x 8, Quick Start Guide

Regulations: cTUVus, FCC, ENERGY STAR, Mexico Energy, CE, CB, RoHS, ErP, WEEE

UPC: 766907901610

Accessories:

LB-STND-003, LB-STND-005-3, LB-WIFI-001, NMP250-WL, NMP250-WU, PD-IFP-001, PD-IFP-002, SW-050, SW-051, SW-110, SW-111, SW-UP-117, VBD100, VBH100, VBS100, VPC17-WP-6, WMK-047