

MSi®

GeForce RTX™ 4090 VENTUS 3X 24G







SPECIFICATIONS

Model Name	GeForce RTX™ 4090 VENTUS 3X 24G
Graphics Processing Unit	NVIDIA [®] GeForce RTX™ 4090
Interface	PCI Express [®] Gen 4
Core Clocks	Extreme Performance: 2535 MHz (MSI Center) Boost: 2520 MHz
CUDA® CORES	16384 Units
Memory Speed	21 Gbps
Memory	24GB GDDR6X
Memory Bus	384-bit
Output	DisplayPort x 3 (v1.4a) HDMI™ x 1 (Supports 4K@120Hz HDR, 8K@60Hz HDR, and Variable Refresh Rate as specified in HDMI 2.1a)
HDCP Support	Υ
Power consumption	450W
Power connectors	16pin x 1
Recommended PSU	850W
Card Dimension (mm)	322 x 136 x 62mm
Weight (Card / Package)	1675g / 2306g
DirectX Version Support	12 Ultimate
OpenGL Version Support	4.6
NVLink Support	N/A
Maximum Displays	4
G-SYNC® technology	Υ
Digital Maximum Resolution	7680 x 4320

FEATURES



Triple Fan

Three fans and a huge heatsink ensure a cool and quiet experience for you.



TORX FAN 4.0

A masterpiece of teamwork, fan blades work in pairs to create unprecedented levels of focused air pressure.



Core Pipe

Precision-machined heat pipes ensure max contact and spread heat along the full length of the heatsink.



Airflow Control

Don't sweat it, Airflow Control guides the air to exactly where it needs to be for maximum cooling.



Metal Backplate

Thermal pads under the sturdy metal backplate provide additional cooling while the flow-through ventilation reduces trapped heat.



Copper Baseplate


A solid nickel-plated copper baseplate transfers heat from the GPU to all heat pipes for better cooling.



MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.

CONNECTIONS



- ${\bf 1.\ DisplayPort}$
- 2. HDMI