



RGB-Illuminated 2.0 Speaker Set

Compact speaker set with bold design and RGB LED illumination

Key features

- 12W peak power (6 Watt RMS)
- RGB colour cycle illumination with on/off touch control
- Easy-to-reach volume control at the front
- Metal grille for extra protection
- USB powered: no wall power needed
- Works with every PC/laptop



#23379

What's in the box

- 2x speakers with cable attached
- Gaming sticker



System requirements

- 3.5 mm audio connection
- USB port (for power)













Go Bold and Compact

Coming in a compact design, the GXT 606 Javv RGB-Illuminated 2.0 Speaker Set boasts an adventurous camo look and colourful RGB lights that will get you in the mood for winning. Enjoy your computer audio in stereo without having to wear a headset. Easy does it: just plug the USB and aux cable into your laptop and you're ready to go.

Get Adventurous with Camo Design

Add some adventure to your desk setup with Javv. With its grey-toned design in classic camouflage print, this speaker set is bound to put the courage in your gaming session or the kick in your workflow. The metal grille on the front of both speakers adds a touch of toughness – both in looks and durability.





Command Your RGB Lights

Its sturdy looks are amplified by a mesmerising lightshow. Solid colours and breathing RGB that smoothly flows from one colour to the other; choose your favourite setting and simply turn off the lights via touch control on top of the speaker.





GENERAL			
Type of speaker	2.0	Height of main product (in mm)	175 mm
Width of main product (in mm)	78 mm	Depth of main product (in mm)	100 mm
Total weight	754 g	Weight of main unit	698 g
CONNECTIVITY			
Connection type	Wired	Bluetooth	False
Cable length power cable	180 cm	Cable length audio cable	180 cm
Cable length satellite cable	180 cm		
LIGHTING			
Lights	True	Light type	LED
Light modes	On/off		
SATELLITES			
Satellite Height (mm)	175 mm	Satellite Width (mm)	 78 mm
Satellite Depth (mm)	100 mm	Satellite Weight (gr)	349 gr
INPUT			
Power source	USB		
AUDIO	12.00		<u></u>
Power output (peak)	12 W	Power output (RMS)	6 W
	12 W 3 W	Power output (RMS) Frequency response	6 W 160 - 20000 Hz
Power output (peak) Power output - satellite		• • •	
Power output (peak) Power output - satellite (RMS)	3 W	Frequency response	160 - 20000 Hz
Power output (peak) Power output - satellite (RMS) Driver size	3 W 60 mm	Frequency response Driver units	160 - 20000 Hz 2
Power output (peak) Power output - satellite (RMS) Driver size Audio input Microphone built-in	3 W 60 mm 3.5 mm	Frequency response Driver units Headphone connection	160 - 20000 Hz 2 False
Power output (peak) Power output - satellite (RMS) Driver size Audio input	3 W 60 mm 3.5 mm	Frequency response Driver units Headphone connection	160 - 20000 Hz 2 False
Power output (peak) Power output - satellite (RMS) Driver size Audio input Microphone built-in <u>CONTROL</u>	3 W 60 mm 3.5 mm False	Frequency response Driver units Headphone connection Microphone connection	160 - 20000 Hz 2 False False
Power output (peak) Power output - satellite (RMS) Driver size Audio input Microphone built-in <u>CONTROL</u> Remote control	3 W 60 mm 3.5 mm False	Frequency response Driver units Headphone connection Microphone connection	160 - 20000 Hz 2 False False
Power output (peak) Power output - satellite (RMS) Driver size Audio input Microphone built-in <u>CONTROL</u> Remote control <u>PROTECTION</u> Waterproof	3 W 60 mm 3.5 mm False No	Frequency response Driver units Headphone connection Microphone connection	160 - 20000 Hz 2 False False
Power output (peak) Power output - satellite (RMS) Driver size Audio input Microphone built-in <u>CONTROL</u> Remote control <u>PROTECTION</u> Waterproof <u>HEADPHONE</u>	3 W 60 mm 3.5 mm False No	Frequency response Driver units Headphone connection Microphone connection Controls	160 - 20000 Hz 2 False False Lights on/off, volume
Power output (peak) Power output - satellite (RMS) Driver size Audio input Microphone built-in <u>CONTROL</u> Remote control <u>PROTECTION</u> Waterproof	3 W 60 mm 3.5 mm False No	Frequency response Driver units Headphone connection Microphone connection	160 - 20000 Hz 2 False False





FEATURES			
NFC	False	Hands-free phone calls	False
Tripod mount	False		
COMPATIBILITY			
Compatible Device Types	ELaptop, pc	Compatible Consoles	No
POWER			
Power saving	False	Power cable detachable	False







PRODUCT VISUAL 1



PRODUCT PICTORIAL 3



PRODUCT VISUAL 2



PRODUCT FRONT 3



PRODUCT PICTORIAL 1



PRODUCT PICTORIAL 2



PRODUCT ESHOT 1



PRODUCT FRONT 2



PACKAGE VISUAL 1



PRODUCT PICTORIAL 4



PRODUCT FRONT 1

PRODUCT EXTRA 1

