Fujitsu recommends Windows 10 Pro for business.

FUJITSU

Data Sheet FUJITSU Desktop ESPRIMO D7010

New small form factor PC in a more compact and space-saving design

The FUJITSU ESPRIMO D7010 Desktop is a high performance, secure small form factor PC with ultimate expandability, along with best-in-class connectivity. Faster operations and a new housing helps in space saving to create the perfect working desk. The USB Type C, flexible graphics options offers great connectivity. The 80Plus GOLD and 80Plus PLATINUM power supply helps to reduce environmental impact and energy bills.

Latest Intel® Chipset technology and higher memory speed

- High performance ensures faster operations and lower system response time
- Intel[®] B460 chipset with higher memory frequency of 2,933 MT/s

New housing and ultimate expandability

Easily customizable and expandable small form factor PC that enables more space saving

- 2x low profile (LP) or 1x LP/ 1x Full height (Riser) via BTO
- Space saving in width and depth with new 8.3 litres volume

Best-in-Class connectivity

Be flexible and stay productive in a hyper-connected world

- A Support of new USB Type C in front
- Flexible graphics options (VGA, DVI-D, HDMI, Type C)
- USB Type C support of 60W (optional to power a display)
- Legacy PS2, serial port, parallel port connectors as option

High security with integrated options

- Designed to protect data and hardware components against manipulation and theft
- Cable cover in addition to existing Smartcard reader, Erasedisk software
- Integrated Cabinet lock with Master key option
- Hole for pad lock and Kensington as standard for security

Low Power Consumption; Easy serviceability and usability

Reduced environmental impact and reduced energy bills; Features designed for easy access, control and use of the system

- 80Plus GOLD and 80Plus PLATINUM power supply efficiency with monitor outlet
- Tool-less access to components, easy change and Screw-less add on cards





Components

| Operating systems | |
|--------------------------------|---|
| Operating system pre-installed | Windows 10 Pro. Fujitsu recommends Windows 10 Pro for business. Windows 10 Home |
| Operating system notes | Windows 10 Support: After the end of the product life FUJITSU will continue to test and support all upcoming Window 10 releases for a period of maximum 5 years – depending on the available extension of hardware services through FUJITSU Warranty top ups. For details please see "FUJITSU Service Statement for Windows 10 Semi-Annual-Channel Support" at http://support.ts.fujitsu.com. |
| Processor | Intel® Core™ i9-10900 processor (10 Cores / 20 Threads, 2.80 GHz, 20 MB, Intel® UHD Graphics 630) ** |
| | Intel® Core™ i7-10700 processor (8 Cores / 16 Threads, 2.90 GHz, 16 MB, Intel® UHD Graphics 630) ** |
| | Intel® Core™ i5-10600 processor (6 Cores / 12 Threads, 3.30 GHz, 12 MB, Intel® UHD Graphics 630) * |
| | Intel® Core™ i5-10500 processor (6 Cores / 12 Threads, 3.10 GHz, 12 MB, Intel® UHD Graphics 630) * |
| | Intel® Core™ i5-10400 processor (6 Cores / 12 Threads, 2.90 GHz, 12 MB, Intel® UHD Graphics 630) * |
| | Intel® Core™ i3-10100 processor (4 Cores / 8 Threads, 3.60 GHz, 6 MB, Intel® UHD Graphics 630) * |
| | Intel® Celeron® processor G5905 (2 Cores / 2 Threads, 3.50 GHz, 4 MB, Intel® UHD Graphics 610) |
| | Intel® Pentium® Gold G6400 (2 Cores / 4 Threads, 4.00 GHz, 4 MB, Intel® UHD Graphics 610) |
| | *with Intel® Turbo Boost Technology 2.0 (clock speed and performance will vary depending on workload and other variables) |
| Ethernet (RJ-45)1 | |
| Memory modules | 4 GB (1 module(s) 4 GB) DDR4, unbuffered, non-ECC, 2,933 MT/s, UDIMM |
| | 8 GB (1 module(s) 8 GB) DDR4, unbuffered, non-ECC, 2,933 MT/s, UDIMM |
| | 16 GB (1 module(s) 16 GB) DDR4, unbuffered, non-ECC, 2,933 MT/s, UDIMM |
| | 32 GB (1 module(s) 32 GB) DDR4, unbuffered, non-ECC, 2,933 MT/s, UDIMM |
| Mass storage 2.5 inch size | SSD SATA III, 512 GB, 2.5-inch |
| | SSD SATA III, 256 GB, 2.5-inch |
| Mass Storage M.2 technology | SSD PCIe, 1024 GB M.2 NVMe module, SED |
| | SSD PCIe, 1024 GB M.2 NVMe module |
| | SSD PCIe, 512 GB M.2 NVMe module, SED |
| | SSD PCIe, 512 GB M.2 NVMe module |
| | SSD PCIe, 256 GB M.2 NVMe module, SED |
| | SSD PCIe, 256 GB M.2 NVMe module |
| | SSD PCIe, 128 GB M.2 NVMe module |
| Mass storage 3.5 inch size | HDD SATA III, 7,200 rpm, 2000 GB, 3.5-inch |
| | HDD SATA III, 7,200 rpm, 1000 GB, 3.5-inch, business critical |
| | HDD SATA III, 7,200 rpm, 1000 GB, 3.5-inch |
| Mass storage 2.5 inch size | HDD SATA III, 5,400 rpm, 500 GB, 2.5-inch |
| Hard disk notes | One Gigabyte equals one billion bytes, when referring to hard disk drive capacity. SSD (Solid State Disk) SED (Self-Encrypting Drive) |
| Graphics | NVIDIA® Quadro® P400 LP, 2 GB |
| | NVIDIA® GeForce® GTX 1650 |
| | MiniDP to DP Adapter Cable |
| Drives (optional) | BD Triple Writer SATA ultra slim (tray) |
| | DVD Super Multi ultra slim (tray) |
| | SD Card reader |

Interface add on cards/components (optional)

Gigabit Ethernet PCIe x1 WLAN 802.11ax (2x2) PCIe x1 LP and Bluetooth 5.0 (dedicated regions only) Dual serial card PCIe x1 LP

Base unit

| Base unit | ESPRIMO D7010 |
|-------------------------------|--|
| Mainboard | |
| Mainboard type | D3823-A2 |
| Formfactor | proprietary |
| Chipset | Intel® B460 |
| Processor socket | LGA 1200 |
| Processor quantity maximum | 1 |
| Supported capacity RAM (max.) | 128 GB |
| Memory slots | 4 DIMM (DDR4) |
| Memory frequency | 2,933 MT/s |
| Memory notes | Dual channel support For dual channel performance, 2 memory modules have to be ordered. Capacity per channel has to be the same. 2933 MHz may be clocked down to 2400MHz depending on processor and memory configuration |
| LAN | 10/100/1,000 MBit/s Realtek RTL8111H |
| BIOS version | AMI Aptio V UEFI Specification 2.6 |
| BIOS features | BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI) |
| Audio type | On board |
| Audio codec | Realtek ALC623 |
| Audio features | Internal speaker supports audio playback (optional), High Definition audio, 5.1 surround sound |
| I/O controller on board | |
| Serial ATA total | 4 |
| thereof SATA III | 4 |
| Controller functions | Serial ATA III (6 Gbit) NCQ AHCI |
| Interfaces | |
| Audio: line-in | 1 |
| Audio: line-out | 1 |
| Front audio: headset | 1 |
| USB 2.0 total | 4 |
| USB 3.2 Gen 1 (5 Gbps) total | 6 and 1 optional |
| USB 3.2 Gen 2 (10 Gbps) total | 2 |
| USB front | 2x USB 2.0; 1x USB 3.2 Gen 1; 1x USB 3.2 Gen 2; 1x USB 3.2 (Gen 2) Type-C (supports up to 15W) |
| USB rear | 2x USB 2.0; 4x USB 3.2 Gen 1; optional: additional 1x USB 3.2 Gen 1 Type-C (supports DisplayPort 1.4 and power delivery (PD) up to 15W or 60W (occupies PCIe x16 slot) |
| USB internal | 1x USB 2.0 or 1x USB 3.2 Gen 1 Type A |
| VGA | optional |
| DisplayPort | 2 |
| DVI | optional (DVI-D) |
| | |

| Interfacer | |
|--------------------------------|--|
| Interfaces | 1 (aptional carial part (Opin 16 buta FIFO 16FFO compatible)) |
| Serial (RS-232) | 1 (optional serial port (9pin, 16 byte FIFO, 16550 compatible)) |
| Mouse / Keyboard (PS/2) | 2 (optional) |
| Ethernet (RJ-45) | |
| Parallel | 1 (optional) (25pin with EPP and ECP) |
| Interface Module notes | Anytime USB charge functionality |
| Kensington Lock support | 1 |
| Input device / components | |
| Input devices (optional) | Keyboard Mouse |
| Drive bays | |
| Drive bays total | 3 |
| 2.5-inch internal bays | 1 |
| 5.25-inch external bays | 1 |
| Drive bay notes | 1x internal 3.5" bay optional (screwless), can be used via adapter for 1x or 2x 2.5" drives (screwless); 5.25" bay: for slim optical disc drive only; |
| M.2-2280 | 1 x on mainboard for SSD NVMe (PCle 3.0 x4; up to 32Gbit/s) |
| Slots | |
| PCI-Express 3.0 x4 (mech. x16) | 1 x (150 mm / 5.91 inch) |
| PCI-Express 3.0 x16 | 1 x (210 mm / 8.27 inch) Low profile or full height (via Riser card), optional |
| Graphics on board | |
| Graphics brand name | Intel® UHD Graphics 610, Intel® UHD Graphics 630 |
| Shared video memory | Up to half size of total system memory |
| TFT resolution (VGA) | Up to 1,920 x 1,080 pixel |
| TFT resolution (DVI) | up to 1,920 x 1,200 pixel |
| TFT resolution (DisplayPort) | Up to 4,096 x 2,304 pixel |
| TFT resolution (HDMI) | Up to 4,096 x 2,160 pixel (30 Hz) |
| Graphics features | Support for up to three independent displays DirectX® 12 HDCP support OpenCL™ 2.1 OpenGL® 4.5 For multi monitoring mode, graphics card and integrated graphics run in parallel DisplayPort interface supports Ver. 1.4 incl. Multi-Stream Digital audio formats are supported, including Dolby Digital Plus (7.1 channels) DVI-D interface supports audio output if connected to the HDMI interface of a display via suitable adapter cables (not included) Additional I/O connectors configurable, choice of DVI-D HDMI™ VGA USB Type-C™ (supports DisplayPort™ 1.4 and power delivery (PD) up to 15W) USB Type-C™ (supports DisplayPort™ 1.4 and power delivery (PD) up to 60W. Occupies PCIe x16 slot) |
| Graphics notes | up to 1 GB dedicated video memory (main memory owned and locked for graphics use) Tested resolutions, depending on display type additional resolutions and frequencies possible Shared memory depending on main memory size and operating system Resolution (color depth up to 32 Bit/pixel) For TFT we recommend using 60Hz |

| Electrical values | |
|--|--|
| Power efficiency note | Power supply officiency in $\%$ at $10\% / 20\% / 50\% / 100\%$ load |
| Power efficiency note | Power supply efficiency in % at 10% / 20% / 50% / 100% load 80Plus GOLD: |
| | for 230V ; 87/90/92/91 |
| | for 115V ; 86/89/91/88 |
| | 80Plus PLATINUM: |
| | for 230V ; 88/92/94/93 |
| | for 115V ; 87/91/92/91 |
| Rated voltage range | 100 V - 240 V |
| Rated frequency range | 50 Hz - 60 Hz |
| Operating voltage range | 90 V - 264 V |
| Operating line frequency range | 47 Hz - 63 Hz |
| Max. output of single power supply | GOLD: 280W; PLATINUM: 300 W |
| Power factor correction/active power | active |
| Monitor outlet | Switched for PLATINUM power supply |
| Power consumption | |
| Power consumption note | See white paper Energy Consumption |
| • | |
| Heat dissipation Heat dissipation notes | See white paper Energy Consumption |
| • | |
| Noise emission | |
| Related Processors for noise | Intel [®] Core™ i5-10600 processor |
| Standard noise emission | 8 GB, ODD, Windows 10 According to ISO 7779:2010, ECMA-74 |
| Standard noise notes / description | A-weighted sound power level Lwad (in B) / Workplace related A-weighted sound pressure level LpAm (in dB(A)) |
| Standard noise operation mode: CPU | for GOLD PSU: |
| 50% load | tbd B / tbd dB(A) Bystander; tbd dB(A) Operator position (HDD 3.5") |
| | tbd B / tbd dB(A) Bystander; tbd dB(A) Operator position (SSD M.2) |
| | for PLATINUM PSU: |
| | tbd B / tbd dB(A) Bystander; tbd dB(A) Operator position (HDD 3.5") |
| | tbd B / tbd dB(A) Bystander; tbd dB(A) Operator position (SSD M.2) |
| Dimensions / Weight / Environmental | |
| Dimensions (W x D x H) | 314 x 296 x 89 mm |
| | 12.36 x 11.65 x 3.51 inch |
| Operating position | horizontal / vertical (optional, feet needed) |
| Weight | approx. 8 kg |
| Weight (lbs) | approx. 17.64 lbs |
| Weight notes | Actual weight may vary depending on configuration |
| Operating ambient temperature | 10 - 35 °C (50 - 95 °F) |
| Operating relative humidity | 5 - 85 % (relative humidity) |
| Compliance | |
| Product | ESPRIMO D7010 |
| Model | DTG |
| Germany | GS (planned) |
| Europe | CE |
| USA/Canada | FCC Class B cTUVus |
| Global | RoHS (Restriction of hazardous substances) |
| | WEEE (Waste electrical and electronic equipment) |
| | Microsoft Operating Systems (HCT / HCL entry / WHQL) |
| | ENERGY STAR® in progress EPEAT® in progress (dedicated regions) |
| Compliance link | https://sp.ts.fujitsu.com/sites/certificates |
| | חננףגאיאף.נג.ועוונאונאיגעווונאועאיגעווונאעאיגאיאיאיאיאיאיאיאיאיאיאיאיאיאיאיאיאיא |

| Additional Software | |
|------------------------------------|---|
| | Adobe® Reader® (pdf reader) |
| Additional software (preinstalled) | Adobe® Reader® (pur reader) McAfee® LiveSafe™ (provides award-winning antivirus protection for your PC and much more. 30 days trial pre- installed) |
| | Microsoft Office (1 month trial for new Microsoft [®] Office 365 customers. Buy Microsoft Office.) |
| Additional software (optional) | Recovery DVD for Windows® |
| | Drivers & Utilities DVD (DUDVD) |
| | CyberLink PowerDVD BD (playback software for Blu-ray Disc™) |
| | CyberLink PowerDVD DVD (playback software for DVD) Nero Essentials XL |
| | Microsoft [®] Office Professional 2019 |
| | Microsoft [®] Office Home and Business 2019 |
| | (A Microsoft Account is required to activate each copy of these products. For purchase and activation only in the |
| | region in which it was acquired.) |
| Manageability | |
| Manageability technology | DeskUpdate Driver management |
| | PXE 2.1 Boot code |
| | Wake up from S5 (off mode) Intrusion switch (optional) |
| | WoL (Wake on LAN) |
| Manageability software | DeskView Client |
| | DeskView Instant BIOS Management |
| DeskView components | BIOS Management incl. Security |
| | Inventory Management Driver Management |
| | Alarm Management |
| Supported standards | DMI (Desktop Management Interface) |
| | SMBIOS (System Management BIOS) |
| | PXE (Preboot Execution Environment) |
| | WMI (Windows Management Instrumentation) |
| | WBEM (Web Based Enterprise Management) CIM (Common Information Model) |
| Manageability link | http://www.fujitsu.com/fts/manageability |
| Security | r (|
| Physical Security | Kensington Lock support |
| | Eye for padlock |
| | Integrated cabinet lock (optional) |
| | Cable Cover (optional; covers and secures the ports and cables on rear side) |
| System and BIOS Security | Embedded security (TPM 2.0) |
| | EraseDisk |
| | Credential Guard Ready and Device Guard Capable (Windows 10, v. 1809; requires 8 GB or more system RAM and SSD PCIe NVME) |
| | Write protect option for the Flash EPROM |
| | Control of all USB interfaces |
| | External USB ports can be disabled separately |
| | Control of external interfaces |
| User Security | User and supervisor BIOS password Hard disk password |
| | Access protection via external SmartCard reader (optional) |
| | Access protection via internal SmartCard reader (optional) |
| | AuthConductor Client Basic (secure authentication solution) |
| Miscellaneous | |
| | Keyboard on (Special Fujitsu keyboard required) |
| | Keyboard on with one key (KBPX Eco, KB521) |
| | Keyboard on with 2 keys (CTRL+CTRL) with PS2 or special USB keyboards |
| | Keyboard on with any key (USB) Thermal management |
| | Extended lifetime |
| | Internal dust filter (optional) |
| | |

Serviceability

| Serviceability | |
|--|--|
| | EasyFix EasyChange for single 3.5" HDD (optional) |
| | EasyChange for optical drives |
| Packaging information | |
| Packaging dimension (mm) | 499 x 296 x 439 mm |
| Packaging dimension (inch) | 19.65 x 11.65 x 17.28 inch |
| Max. quantity / pallet | 24 |
| Material - Weight (g) Carton | 1117 و |
| Material - Weight (lbs) Carton | 2.46 lbs |
| Material - Weight (g) EPS / PS | 225 g |
| Material - Weight (lbs) EPS / PS | 0.5 lbs |
| Material - Weight (g) PE | 25 g |
| Material - Weight (lbs) PE | 0.06 lbs |
| Packaging notes | printed user documentation is bleached in chlorine free process; Bulk packagaging for projects (optional) |
| Warranty | |
| Warranty period | 1 year |
| Warranty type | Bring-In / Onsite Service (depending on country) |
| Warranty Terms & Conditions | http://www.fujitsu.com/warranty |
| Product Support Services - the perfect e | xtension |
| Recommended Service | 9x5, Onsite Response Time: Next Business Day |
| Spare Parts availability | 5 years |
| Service Weblink | http://www.fujitsu.com/emeia/products/product-support-services/ |

Recommended Accessories

More information

Fujitsu products, solutions & services

In addition to FUJITSU Desktop ESPRIMO D7010, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about FUJITSU Desktop ESPRIMO D7010, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

www.fujitsu.com/emeia/ESPRIMO

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at http://www. fujitsu.com/global/about/environment



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http:// www.fujitsu.com/emeia/resources/navigation/ terms-of-use.html

Copyright 2020 Fujitsu Technology Solutions GmbH

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

Fujitsu Technology Solutions GmbH Website: www.fujitsu.com 2020-09-02 EM-ÉN

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html Copyright 2020 Fujitsu Technology Solutions GmbH