Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources		. , , .	_			
Supplier's name	e or trade mark:	DIGITUS				
Supplier's address: Product Management, Auf dem Schüffel 3, 58513 Lüdenscheid, DE						
Model identifie	r: DN-LIGHT					
Type of light so	urce:					
Lighting technology used:		LED	Non-directional or directional:	DLS		
Light source cap-type (or other electric interface)		DC3.5X1.35				
Mains or non-m	nains:	MLS	Connected light source (CLS):	No		
Colour-tuneable	e light source:	No	Envelope:	-		
High luminance	light source:	No				
Anti-glare shield	d:	No	Dimmable:	No		
Product parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		5	Energy efficiency class	F		
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		350 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	6 000		
On-mode power (P _{on}), expressed in W		5,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,26		
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80		
Outer	Height	40	Spectral power	See image		
dimensions	Width	235	distribution in the	in last page		
without	Depth	21				

	I	1				
separate		range 250 nm to 800				
control gear,		nm, at full-load				
lighting						
control parts						
and non-						
lighting						
control parts,						
if any						
(millimetre)						
Claim of equivalent power ^(a)	-	If yes, equivalent	-			
		power (W)				
		Chromaticity	0,321			
		coordinates (x and y)				
Parameters for directional light sources:						
Peak luminous intensity (cd)	150	Beam angle in	113			
		degrees, or the				
		range of beam				
		angles that can be				
		set				
Parameters for LED and OLED light sources:						
R9 colour rendering index value	4	Survival factor	-			
the lumen maintenance factor	-					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	0,00	Colour consistency	0			
		in McAdam ellipses				
Claims that an LED light	_(b)	If yes then	-			
source replaces a fluorescent		replacement claim				
light source without integrated		(W)				
ballast of a particular wattage.						
Flicker metric (Pst LM)	0,0	Stroboscopic effect	0,0			
		metric (SVM)				

(a)_{'-'} : not applicable;

(b)_{'-'} : not applicable;

