# HP P27h G4 FHD Monitor



## Extra-large screen size at an extra-small price

Give your content room to roam on the HP P27h G4 FHD Height Adjust Monitor. It combines business-class presentation features, comfort adjustability, stereo audio, and advanced connectivity in an affordable, contemporary design that's a standout on any desk.



#### Crisp images and clear sound for all your content

• Navigate documents and large spreadsheets and work in applications side by side on the 27-inch diagonal Full HD IPS screen with 1920 x 1080 resolution. Get convenient stereo audio at the display.

#### A beauty at any price

• Set a new style standard with a 3-sided micro-edge bezel for unlimited sightlines and virtually seamless multidisplay1 setups. See the screen clearly from almost anywhere with 178° viewing angles.

#### Featuring

- Find your best view with adjustable tilt settings, 100 mm of height adjustment, and 90° pivot rotation.
- Attach your HP Desktop Mini, HP Chromebox or select HP Thin Client directly behind the display.
- Filter blue light emission and shift colors to a warmer spectrum for more comfortable viewing with HP Low Blue Light mode. Adjust tilt for your best view.
- Free up valuable desk space with mounting options enabled by the 100-mm VESA pattern.
- Customize a total solution with options designed for your display, like the HP S101 Speaker Bar, which attaches easily to the lower bezel to add stereo audio without the desktop clutter.
- Energy efficiency and environmental sustainability are built into every ENERGY STAR® and TCO certified, EPEAT® 2019 registered, and low halogen display.
- Manage your display and make it work for you. HP Display Assistant allows you to quickly resize screen partitions so you can work in separate regions of the screen and helps deter theft by dimming a display that's disconnected without approval.
- We're just a call or click away. Rest assured that your IT investment is supported with our three-year standard limited warranty. To extend your protection, select an optional HP Care service.

## HP P27h G4 FHD Monitor Specifications Table







Brightness         250 mcs <sup>-1</sup> Contrast ratio         1000-11           Response Ratio         5 ms pray to gray <sup>-1</sup> Product colour         8back           Aspect ratio         15-91           Nation resolution         FED 1590 x 1000.           Resolution supported         1024 x 766, 1280 x 1024; 1280 x 720; 1280 x 800; 1360 x 766, 1480 x 900; 1600 x 900; 1600 x 900; 1600 x 1050; 1920 x 1080, 640 x 480, 720 x 400; 800 x 600 x 600 x 600 x 480, 720 x 400; 800 x 600	Display type	IPS
Contrast ratio   1000;11   Response Ratio   5 ms rays to gray of product colour   Black   Aspect ratio   16:9   Native resolution   Fib (1950 × 1000)   Resources supported   1024 × 768; 1280 × 1024; 1280 × 720; 1280 × 800; 1366 × 768; 1440 × 900; 1600 × 900; 1680 × 1050; 1920 × 1080; 640 × 480; 720 × 900; 800 × 600 × 800; 1360 × 900; 1680 × 1050; 1920 × 1080; 640 × 480; 720 × 900; 800 × 600 × 800; 1360 × 900; 1680 × 1050; 1920 × 1080; 640 × 480; 720 × 900; 800 × 600 × 800; 1360 × 900; 1680 × 1050; 1920 × 1080; 640 × 480; 720 × 900; 800 × 600 × 800; 1050; 920 × 1080; 640 × 480; 720 × 900; 800 × 600 × 800; 1050; 920 × 1080; 640 × 480; 720 × 900; 800 × 900; 1680 × 1050; 1920 × 1080; 640 × 480; 720 × 900; 800 × 900; 1680 × 1050; 1920 × 1080; 640 × 480; 720 × 900; 800 × 900; 1680 × 1050; 1920 × 1080; 640 × 480; 720 × 900; 800 × 900; 1680 × 1050; 1920 × 1080; 640 × 480; 720 × 900; 800 × 900; 1680 × 1050; 1920 × 1080; 640 × 480; 720 × 900; 800 × 900; 1680 × 1050; 1920 × 1080; 640 × 480; 720 × 900; 800 × 900; 1680 × 1050; 1920 × 1080; 640 × 480; 720 × 900; 800 × 900; 1680 × 1050; 1920 × 1080; 900 × 900; 1680 × 1050; 1920 × 1080; 900 × 900; 1680 × 1050; 900; 1680 × 1050; 900 × 900; 1680 × 1050; 900 × 900; 1680 × 1050; 900 × 900; 1680 × 1050; 900 × 900; 1680 × 1050; 900 × 900; 1680 × 900; 1680 × 1050; 900 × 900; 1680 × 1050; 900 × 900; 1680 × 900; 1680 × 900; 1680 × 1050; 900; 1680 × 1050; 900; 1680 × 1050;		250 nits <sup>1</sup>
Product colour         Black Appeter and 1657           Appeter and 1657         1657           Native resolution         F10 (1920 x 1080)           Resolutions supported         1024 x 768 1280 x 1280 x 720; 1280 x 800; 1366 x 769; 1440 x 900; 1600 x 900; 1680 x 1050; 1920 x 1080; 640 x 480, 720 x 400; 800 x 600           Display features         Asset controls on-screen controls; Plug and Play; User controls; Low blue light mode; Dual speakers (2W per channed); Anti-glare; Height adjustable           User controls         Brightness; Color controls Exit image control; Information; Menagement, Power control; Input control; Menu control           User controls         Brightness; Color control Exit image control; Information; Menagement, Power control; Input control; Menu control           Display size (diagonal)         68.6 cm (227)           Display size (diagonal, metric)         68.6 cm (227)           Comera         No integrated comes           Environmental         Operating immeriature 5 to 35°C; Operating functions; Color (2000)           Power         100 – 240 WcG, 5060 Rr.           Dimensions         62.01 x 21.16 x 37.14 cm (Without stand.)           Weight         5.12 kg (With stand.)           Physical security features         5.02 kg (With stand.)           Power         100 – 240 WcG, 5060 Rr.           Energy efficiency compliance         5.12 kg (With stand.)           Certificatio	Contrast ratio	1000:11
Product colour         Black           Aspect ratio         16,97           Native resolution         FHD (1920 x 1080)           Resolutions supported         10,24 x 768 1,280 x 1024,1280 x 720,1280 x 800,1366 x 768,1440 x 900,1600 x 900,1600 x 900,1500 x 1080,640 x 480,720 x 400,800 x	Response Ratio	5 ms gray to gray <sup>1</sup>
Native resolution   FID (1920 x 1080)   Resolutions supported   1024 x 768; 1280 x 1074; 1280 x 270; 1280 x 800; 1366 x 768; 1480 x 900; 1680 x 1050; 1320 x 1080; 640 x 480; 720 x 400; 800 x 480; 720 x 400; 800 x 800; 1366 x 768; 1480 x 900; 1680 x 1050; 1320 x 1080; 640 x 480; 720 x 400; 800 x 480; 720 x	Product colour	
1024 x 786, 1280 x 1024; 1280 x 702; 1280 x 800; 1366 x 768; 1440 x 900; 1600 x 900; 1680 x 1050; 1320 x 1080; 640 x 480; 720 x 400; 800 x 6008	Aspect ratio	16:9 <sup>1</sup>
Ago; 800 x 800 Bisplay features Ago; 800 x 800 Bisplay features Ago; 800 x 800 Ago; 800 x 800 Bisplay features Ago; 800 x 800 Bisplay features	Native resolution	FHD (1920 x 1080)
Spring   S	Resolutions supported	
Input signal  1 DisplayPort**1.2 in (with HDCP support); 1 HDM1.4 (with HDCP support); 1 VGA  Display size (diagonal)  66.6 cm (27)  Camera  No integrated camera  No integrated camera  Power  100 - 240 VMC 50/60 Hz  Dimensions  62.01 x 21, 16 x 37, 14 cm (Without stand.)  Weight  Physical security features  Security lock-ready*  Energy efficiency compilance  ENERGY STAR* certified; EPEAT* 2019 registered*  Energy efficiency compilance  ENERGY STAR* certified; EPEAT* 2019 registered*  Energy efficiency specifications  Ansenic-free display plass; Low halogen; Mercury-free display backlights; TCO Certified*  What's in the box  Monitor; DisplayPort** cable; HDMI cable; AC power cable  3 year limited warranty including 3 year of parts, labor, and next business-day onsite service. Terms and conditions vary by country.  Certification and gained  178*  Horizontal viewing angle  178*  Bezel  3-sided micro-edge  3-whet  11t: -5 to +23**  Proot  490  VESA mount compatible  Not touch-enabled  Not touch-enabled  Flicker-free  Yes  Low blue light modes  A+  Display scan frequency (vertical)  48-75 Hz  Display scan frequency (vertical)  66.6 cm (27)  Comparison  No integrated camera	Display features	
Display size (diagonal) 68.6 cm (27°) Display size (diagonal, metric) 68.6 cm (27°) Camera No integrated camera Environmental Operating temperature: 5 to 35°C; Operating humidity: 20 to 80% non-condensing; Power 100 - 240 MC 50/60 Hz Dimensions 62.01 x 21.16 x 37.14 cm (Without stand.) Weight 5.12 kg (With stand.) Physical security features Security lock-ready¹ Energy efficiency compliance ENERGY STAR™ certified; EPEAT™ 2019 registered¹ Every efficiency compliance ENERGY STAR™ certified; EPEAT™ 2019 registered¹ Every efficiency compliance Australian-New Zealand MEPS; BSNI; CB: CCC; CE: CEL; CSA; EAC; Energy STar; FCC; ICES; ISO 9241-307; KC; KCC; NOM; PSB; TUV-S; UL; VCC; Victiman MEPS; WEELE; ISC Sustainable impact specifications Arsenic-free display glass; Low haloger; Mercury-free display backlights; TCO Certified² What's in the box Monitor; DisplayPort™ cable; HDMI cable; AC power cable Warranty 3 very initial dwarranty including 3 year of parts, labor, and next business-day onsite service. Terms and conditions vary by country. Certain restrictions and exclusions apply. Pleels per inch (ppi) 82 ppi Vertical viewing angle 178° Horizontal viewing angle 178° Horizontal viewing angle 178° Bezel 3-sided micro-edge Swivel 1360° Tilt Tilt: 5 to +23° Plyot 190 Height adjustment range 100 mm VESA mounting VESA mount compatible Screen treatment Anti-glare Touch-enabled Not touch-enabled Flicker-free Yes Low blue light modes Yes (TüV certified) Energy efficiency, Class Area Display scan frequency (vertical) 48-75 Hz	User controls	Brightness; Color control; Exit; Image control; Information; Management; Power control; Input control; Menu control
Display size (diagonal, metric)   68.6 cm (27")	Input signal	1 DisplayPort™ 1.2 in (with HDCP support); 1 HDMI 1.4 (with HDCP support); 1 VGA
Camera         No integrated camera           Environmental         Operating temperature: 5 to 35°C; Operating temperature: 5 to 35°C; Operating humidity: 20 to 80% non-condensing;           Power         100 - 240 VAC 50/60 Hz           Dimensions         62.01 x 21.16 x 37.14 cm (Without stand.)           Weight         5.12 kg (With stand.)           Physical security features         Security lock-ready.3           Energy efficiency compliance         ENERGY STAR® certified; EPEAT® 2019 registered.4           Certification and compliance         Australian-New Zealand MEPS; ISSMI; (B; CCC; CE; CEL; CSA; EAC; Energy Star; FCC; ICES; ISO 9241-307; KC; KCC; NOM; PSB; TUV-5; UL; VCC; Victivaran MEPS; WEEE; ISC           Sustainable impact specifications         Airsenic-free display glass; Low halogen; Mercury-free display backlights; TCO Certified.2           Warranty         3 year limited warranty including 3 year of parts, labor, and next business-day onsite service. Terms and conditions vary by country. Certain restrictions and exclusions apply.           Pixels per inch (ppl)         82 ppi           Vertical viewing angle         178°           Bezel         3-sided micro-edge           Swivel         ±360°           Tilt         Tilt: -5 to +23°           Pivot         +90           Height adjustment range         100 mm           VESA mounting         VESA mount compatible <th>Display size (diagonal)</th> <th>68.6 cm (27")</th>	Display size (diagonal)	68.6 cm (27")
Environmental Operating temperature: 5 to 35°C; Operating temperature: 5 to 35°C; Operating humidity: 20 to 80% non-condensing;  Power 100 - 240 WC 50/50 H2  Dimensions 62.01 x 21.16 x 37.14 cm (Without stand.)  Weight 5.12 kg (With stand.)  Physical security features Security lock-ready <sup>3</sup> Energy efficiency compliance ENERGY 51RRe* (entified; EPEAT® 2019 registered <sup>4</sup> Certification and compliance Australian-New Zealand MEPs, 585M; CB; CCC; CE; CEL; CSA; EAC; Energy Star; FCC; KES, ISO 9241-307; KC; KCC; NDM; PSB; TUV-S; UL; VCC; Vietnam MEPS; WEEE; ISC  Sustainable impact specifications Arsenic-free display glass; Low haloger, Mercury-free display backlights; TOO Certified <sup>2</sup> What's in the box Monitor; DisplayPort <sup>34</sup> cable; HDMI cable; AC power cable  Warranty 3 year limited warranty including 3 year of parts, labor, and next business-day onsite service. Terms and conditions vary by country. Certain restrictions and exclusions apply.  Pixels per inch (ppi) 82 ppi  Vertical viewing angle 178*  Bezel 3-sided micro-edge  Swhel 2360°  Tilt Tilt-5 to +23*  Pivot 99  Height adjustment range 100 mm  VESA mounting VESA mount compatible  Screen treatment Anti-glare  Touch-enabled Not touch-enabled  Flicker-free Yes  Low blue light modes Yes (TÜV certified)  Energy efficiency class A+  Display scan frequency (forziontal)  Display scan frequency (forziontal)  Display scan frequency (vertical)  48-75 Hz	Display size (diagonal, metric)	68.6 cm (27")
Power 100 - 240 VAC 50/60 Hz Dimensions 62.01 x 21.16 x 37.14 cm (Without stand.)  Weight 5.12 kg (With stand.)  Physical security features Security lock-ready.³  Energy efficiency compliance ENERGY STAR® certified; EPEAT® 2019 registered.  Certification and compliance ENERGY STAR® certified; EPEAT® 2019 registered.  Certification and compliance Arsenic-free display glass; Low halogen; Mercury-free display backlights; TCO Certified.³  What's in the box Monitor; DisplayPort™ cable; HDMI cable; AC power cable  Warranty 3 year limited warranty including 3 year of parts, labor, and next business-day onsite service. Terms and conditions vary by country. Certain restrictions and exclusions apply.  Pixels per inch (pp)) 82 ppi  Horizontal viewing angle 178°  Horizontal viewing angle 178°  Horizontal viewing angle 178°  Horizontal viewing angle 178°  Pivot +90  Pivot +90  Pivot +90  Pivot Height adjustment range 100 mm  VESA mounting VESA mount competible  Screen treatment Anti-glare  Touch-enabled Not ouch-enabled  Flicker-free Yes  Low blue light modes  PicsQuestical viewing angle Art  Display scan frequency (horizontal) 48-75 Hz  Display scan frequency (horizontal)  Display scan frequency (vertical)	Camera	No integrated camera
Dimensions         62.01 x 21.16 x 37.14 cm (Without stand.)           Weight         5.12 kg (With stand.)           Physical security features         Security lock-ready³           Energy efficiency compliance         ENERGY STAR® certified; EPEAT® 2019 registered⁴           Certification and compliance         Australian-New Zealand MEPS; BSMI; CB; CCC; CE; CEL; CSA; EAC; Energy Star; FCC; ICES; ISO 9241-307; KC; KCC; NOM; PSB; TUV-S; UL; VCCI; Wetnam MEPS; WEEE; ISC           Sustainable impact specifications         Arsenic-free display glass; Low halogen; Mercury-free display backlights; TCO Certified²           Warranty         3 year limited warranty including 3 year of parts, labor, and next business-day onsite service. Terms and conditions vary by country. Certain restrictions and exclusions apply.           Pixels per inch (ppi)         82 ppi           Vertical viewing angle         178°           Horizontal viewing angle         178°           Bezel         3-sided micro-edge           Swivel         ±360°           Titl         Tit: -5 to +23°           Pivot         +90           Height adjustment range         100 mm           VESA mounting         VESA mount compatible           Screen treatment         Anti-glare           Touch-enabled         Not touch-enabled           Flicker-free         Yes           Low blue l	Environmental	
Weight         5.12 kg (With stand.)           Physical security features         Security lock-ready.³           Energy efficiency compliance         ENERGY STAR® certified; EPEAT® 2019 registered.⁴           Certification and compliance         Australian-New Zealand MEPS, BSMI; CB; CCC; CE; CEL; CSA; EAC; Energy Star; FCC; ICES; ISO 9241-307; KC; KCC; NOM; PSB; TUV-S; UL; VCCI; Vietnam MEPS, WEEE; ISC           Sustainable impact specifications         Arsenic-free display glass; Low halogen; Mercury-free display backlights; TCO Certified.²           What's in the box         Monitor; DisplayPort™ cable; HDMI cable; AC power cable           Warranty         3 year limited warranty including 3 year of parts, labor, and next business-day onsite service. Terms and conditions vary by country. Certain restrictions and exclusions apply.           Pixels per inch (ppi)         82 ppi           Vertical viewing angle         178°           Horizontal viewing angle         178°           Bezel         3-sided micro-edge           Swivel         ±360°           Tilt         Tilt: -5 to +23°           Pivot         +90           Height adjustment range         100 mm           VESA mount compatible           Screen treatment         Anti-glare           Touch-enabled         Not touch-enabled           Flicker-free         Yes           Low blue light	Power	100 - 240 VAC 50/60 Hz
Physical security features         Security lock-ready³           Energy efficiency compliance         ENERGY STAR® certified; EPEAT® 2019 registered⁴           Certification and compliance         Australian-New Zealand MEPS; BSMI; CB; CCC; CE; CEL; CSA; EAC; Energy Star; FCC; ICES; ISO 9241-307; KC; KCC; NOM; PSB; TUV-S; UL; VCC; Vertinam MerpSy; WEEE; ISO           Sustainable impact specifications         Arsenic-free display glass; Low halogen; Mercury-free display backlights; TCO Certified²           What's in the box         Monitor; DisplayPort™ cable; HDMI cable; AC power cable           Warranty         3 year limited warranty including 3 year of parts, labor, and next business-day onsite service. Terms and conditions vary by country. Certain restrictions and exclusions apply.           Pixels per inch (ppi)         82 ppi           Vertical viewing angle         178°           Horizontal viewing angle         178°           Bezel         3-sided micro-edge           Swhel         ±360°           Titt         Titt: -5 to +23°           Pivot         +90           Height adjustment range         VESA mount compatible           Screen treatment         Anti-glare           Touch-enabled         Not touch-enabled           Flicker-free         Yes           Low blue light modes         Yes (TÜV certified)           Energy efficiency class         A+	Dimensions	62.01 x 21.16 x 37.14 cm (Without stand.)
Energy efficiency compliance  ENERGY STAR® certified; EPEAT® 2019 registered  Australian-New Zealand MEPS; BSMI; CBC; CCE; CEL; CSA; EAC; Energy Star; FCC; ICES; ISO 9241-307; KC; KCC; NOM; PSB; TUV-S; UL; VCCI, Vietnam MEPS, WEEE; ISC  Sustainable impact specifications  Arsenic-free display glass; Low halogen; Mercury-free display backlights; TCO Certified  Warranty  Monitor; DisplayPort™ cable; HDMI cable; AC power cable  Warranty  3 year limited warranty including 3 year of parts, labor, and next business-day onsite service. Terms and conditions vary by country. Certain restrictions and exclusions apply.  Pixels per inch (ppi)  82 ppi  Vertical viewing angle  178°  Horizontal viewing angle  178°  Bezel  3-sided micro-edge  Swivel  ±360°  Tilt  Tilt: 5 to +23°  Pivot  +90  Height adjustment range  100 mm  VESA mounting  VESA mount compatible  Screen treatment  Anti-glare  Touch-enabled  Not touch-enabled  Flicker-free  Yes  Low blue light modes  Yes (TÜV certified)  Energy efficiency class  A+  Display scan frequency (vertical)  30-86 KHz  Display scan frequency (vertical)  48-75 Hz	Weight	5.12 kg (With stand.)
Australian-New Zealand MEPS; BSMI; CB; CCC; CE; CEL; CSA; EAC; Energy Star; FCC; ICES; ISO 9241-307; KC; KCC; NOM; PSB; TUV-S; UL; VCC; Vietnam MEPS; WEEE; ISC  Sustainable impact specifications  What's in the box  Monitor; DisplayPort™ cable; HDMI cable; AC power cable  Warranty  3 year limited warranty including 3 year of parts, labor, and next business-day onsite service. Terms and conditions vary by country. Certain restrictions and exclusions apply.  Pixels per inch (ppi)  82 ppi  Vertical viewing angle  178°  Horizontal viewing angle  178°  Bezel  3-sided micro-edge  Swivel  ±360°  Tilt  Tilt: -5 to +23°  Pivot  +90  Height adjustment range  100 mm  VESA mounting  VESA mounting  VESA mount compatible  Screen treatment  Anti-glare  Touch-enabled  Not touch-enabled  Hicker-Free  Low blue light modes  Yes (TÜV certified)  Energy efficiency class  A+  Display scan frequency (vertical)  48-75 Hz	Physical security features	Security lock-ready <sup>3</sup>
Sustainable impact specifications Arsenic-free display glass; Low halogen; Mercury-free display backlights; TCO Certified²  What's in the box Monitor; DisplayPort™ cable; HDMI cable; AC power cable  Warranty Al year limited warranty including 3 year of parts, labor, and next business-day onsite service. Terms and conditions vary by country. Certain restrictions and exclusions apply.  Pixels per inch (ppi) 82 ppi Vertical viewing angle 178° Horizontal viewing angle 178° Bezel 3-sided micro-edge Swivel ±360° Tilt Tilt: 5 to +23° Pivot +90 Height adjustment range 100 mm  VESA mounting VESA mount compatible Screen treatment Anti-glare Touch-enabled Not touch-enabled Flicker-free Low blue light modes Yes (TÜV certified) Energy efficiency class A+ Display scan frequency (vertical) 48-75 Hz	Energy efficiency compliance	ENERGY STAR® certified; EPEAT® 2019 registered <sup>4</sup>
What's in the box       Monitor; DisplayPort™ cable; HDMI cable; AC power cable         Warranty       3 year limited warranty including 3 year of parts, labor, and next business-day onsite service. Terms and conditions vary by country. Certain restrictions and exclusions apply.         Pixels per inch (ppi)       82 ppi         Vertical viewing angle       178°         Horizontal viewing angle       178°         Bezel       3-sided micro-edge         Swivel       ±360°         Tilt       Tilt: -5 to +23°         Pivot       +90         Height adjustment range       100 mm         VESA mounting       VESA mount compatible         Screen treatment       Anti-glare         Touch-enabled       Not touch-enabled         Flicker-free       Yes         Low blue light modes       Yes (TÜV certified)         Energy efficiency class       A+         Display scan frequency (vortical)       48-75 Hz	Certification and compliance	
Warranty     3 year limited warranty including 3 year of parts, labor, and next business-day onsite service. Terms and conditions vary by country. Certain restrictions and exclusions apply.       Pixels per inch (ppi)     82 ppi       Vertical viewing angle     178°       Horizontal viewing angle     178°       Bezel     3-sided micro-edge       Swivel     ±360°       Tilt     Tilt: -5 to +23°       Pivot     +90       Height adjustment range     100 mm       VESA mounting     VESA mount compatible       Screen treatment     Anti-glare       Touch-enabled     Not touch-enabled       Flicker-free     Yes       Low blue light modes     Yes (TÜV certified)       Energy efficiency class     A+       Display scan frequency (horizontal)     30-86 KHz       Display scan frequency (vertical)     48-75 Hz	Sustainable impact specifications	Arsenic-free display glass; Low halogen; Mercury-free display backlights; TCO Certified <sup>2</sup>
Pixels per inch (ppi) 82 ppi  Vertical viewing angle 178°  Horizontal viewing angle 178°  Bezel 3-sided micro-edge  Swivel ±360°  Tilt Tilt: -5 to +23°  Pivot +90  Height adjustment range 100 mm  VESA mounting VESA mount compatible  Screen treatment Anti-glare  Touch-enabled Not touch-enabled Flicker-free Yes  Low blue light modes Yes (TÜV certified) Energy efficiency class A+  Display scan frequency (vertical) 328 A  Pixel ppi 178°  178°	What's in the box	Monitor; DisplayPort™ cable; HDMI cable; AC power cable
Vertical viewing angle 178° Horizontal viewing angle 178°  Bezel 3-sided micro-edge  Swivel ±360°  Tilt Tilt: -5 to +23° Pivot +90 Height adjustment range 100 mm  VESA mounting VESA mount compatible  Screen treatment Anti-glare  Touch-enabled Not touch-enabled  Flicker-free Yes Low blue light modes Yes (TÜV certified)  Energy efficiency class A+  Display scan frequency (horizontal) 30-86 KHz  Display scan frequency (vertical) 48-75 Hz	Warranty	
Horizontal viewing angle 178°  Bezel 3-sided micro-edge  Swivel ±360°  Tilt Tilt: -5 to +23°  Pivot +90  Height adjustment range 100 mm  VESA mounting VESA mount compatible  Screen treatment Anti-glare  Touch-enabled Not touch-enabled  Flicker-free Yes  Low blue light modes Yes (TÜV certified)  Energy efficiency class A+  Display scan frequency (horizontal) 30-86 KHz  Display scan frequency (vertical) 48-75 Hz	Pixels per inch (ppi)	82 ppi
Bezel 3-sided micro-edge  Swivel ±360°  Tilt Tilt: -5 to +23°  Pivot +90  Height adjustment range 100 mm  VESA mounting VESA mount compatible  Screen treatment Anti-glare  Touch-enabled Not touch-enabled  Flicker-free Yes  Low blue light modes Yes (TÜV certified)  Energy efficiency class A+  Display scan frequency (horizontal) 30-86 KHz  Display scan frequency (vertical) 48-75 Hz	Vertical viewing angle	178°
Swivel ±360°  Tilt Tilt: -5 to +23°  Pivot +90  Height adjustment range 100 mm  VESA mounting VESA mount compatible  Screen treatment Anti-glare  Touch-enabled Not touch-enabled  Flicker-free Yes  Low blue light modes Yes (TÜV certified)  Energy efficiency class A+  Display scan frequency (horizontal) 30-86 KHz  Display scan frequency (vertical) 48-75 Hz	Horizontal viewing angle	178°
TiltTilt: -5 to +23°Pivot+90Height adjustment range100 mmVESA mountingVESA mount compatibleScreen treatmentAnti-glareTouch-enabledNot touch-enabledFlicker-freeYesLow blue light modesYes (TÜV certified)Energy efficiency classA+Display scan frequency (horizontal)30-86 KHzDisplay scan frequency (vertical)48-75 Hz	Bezel	3-sided micro-edge
Pivot +90  Height adjustment range 100 mm  VESA mounting VESA mount compatible  Screen treatment Anti-glare  Touch-enabled Not touch-enabled  Flicker-free Yes  Low blue light modes Yes (TÜV certified)  Energy efficiency class A+  Display scan frequency (horizontal) 30-86 KHz  Display scan frequency (vertical) 48-75 Hz	Swivel	±360°
Height adjustment range 100 mm  VESA mounting VESA mount compatible  Screen treatment Anti-glare  Touch-enabled Not touch-enabled  Flicker-free Yes  Low blue light modes Yes (TÜV certified)  Energy efficiency class A+  Display scan frequency (horizontal) 30-86 KHz  Display scan frequency (vertical) 48-75 Hz	Tilt	Tilt: -5 to +23°
VESA mounting     VESA mount compatible       Screen treatment     Anti-glare       Touch-enabled     Not touch-enabled       Flicker-free     Yes       Low blue light modes     Yes (TÜV certified)       Energy efficiency class     A+       Display scan frequency (horizontal)     30-86 KHz       Display scan frequency (vertical)     48-75 Hz	Pivot	+90
Screen treatment Anti-glare Touch-enabled Not touch-enabled Flicker-free Yes Low blue light modes Yes (TÜV certified) Energy efficiency class A+ Display scan frequency (horizontal) 30-86 KHz Display scan frequency (vertical) 48-75 Hz	Height adjustment range	100 mm
Touch-enabled Not touch-enabled Flicker-free Yes Low blue light modes Yes (TÜV certified) Energy efficiency class A+ Display scan frequency (horizontal) 30-86 KHz Display scan frequency (vertical) 48-75 Hz	VESA mounting	VESA mount compatible
Flicker-free Yes  Low blue light modes Yes (TÜV certified)  Energy efficiency class A+  Display scan frequency (horizontal) 30-86 KHz  Display scan frequency (vertical) 48-75 Hz	Screen treatment	Anti-glare
Low blue light modesYes (TÜV certified)Energy efficiency classA+Display scan frequency (horizontal)30-86 KHzDisplay scan frequency (vertical)48-75 Hz	Touch-enabled	Not touch-enabled
Energy efficiency class A+  Display scan frequency (horizontal) 30-86 KHz  Display scan frequency (vertical) 48-75 Hz	Flicker-free	Yes
Display scan frequency (horizontal) 30-86 KHz Display scan frequency (vertical) 48-75 Hz	Low blue light modes	Yes (TÜV certified)
Display scan frequency (vertical) 48-75 Hz	Energy efficiency class	A+
	Display scan frequency (horizontal)	30-86 KHz
Pixel pitch 0.311 mm	Display scan frequency (vertical)	48-75 Hz
	Pixel pitch	0.311 mm

## HP P27h G4 FHD Monitor

## Accessories and services (not included)

HP Quick Release Bracket 2



Use the HP Quick Release Bracket 2 to attach your HP Desktop Mini to an HP display and a variety of stands, arms or wall mounts. The failsafe "Sure-Lock" mechanism snaps the PC securely in place, and can be further secured with a theft-deterrent security screw. Crisp, clear, high-resolution monitors for the business environment.

Product number: 6KD15AA

**HP Single Monitor Arm** 



The HP Single Monitor Arm is the perfect desk accessory for your work life. Sleek and streamlined, the HP Single Monitor Arm is designed to complement the way you work. Crisp, clear, high-resolution monitors for the business environment.

Product number: BT861AA

HP 5 year Next business day Onsite Standard Monitor Hardware Support



Receive 5 years of next business day onsite HW Support from an HP-qualified technician for your computing device, if the issue cannot be solved remotely. **Product number: U7935E** 

## HP P27h G4 FHD Monitor

### Messaging Footnotes

- <sup>2</sup> HP Desktop Mini, HP Chromebox, and HP Thin Client sold separately. Requires HP B300 PC Mounting Bracket for Monitors, sold separately.
- <sup>3</sup> Mounting hardware sold separately.
- 4 Each accessory sold separately.

  5 Based on US EPEAT® registration according to IEEE 1680.1-2018 EPEAT®. Status varies by country. Visit www.epeat.net for more information.
- 6 External power supplies, power cords, cables and peripherals are not Low Halogen. Service parts obtained after purchase may not be Low Halogen.

  7 HP Care Packs sold separately. Service levels and response times for HP Care Packs may vary depending on your geographic location. Service starts on date of hardware purchase. Restrictions and limitations apply. For details, visit www.hp.com/go/cpc. HP Services are governed by the applicable HP terms and conditions of service provided or indicated to Customer at the time of purchase. Customer may have additional statutory rights according to applicable local laws, and such rights are not in any way affected by the HP terms and conditions of service or the HP Limited Warranty provided with your HP Product.

#### **Technical Specifications Footnotes**

- 1 All specifications represent the typical specifications provided by HP's component manufacturers, actual performance may vary either higher or lower.
- 2 External power supplies, power cords, cables and peripherals are not Low Halogen. Service parts obtained after purchase may not be Low Halogen.

  3 Lock is sold separately.

  4 EPEAT® 2019 registered where applicable. EPEAT® registration varies by country. See www.epeat.net for registration status by country.

  5 Monitors produced until September 2020 are delivered with VGA cable and HDMI cable. Monitors produced from September 2020 are delivered with DisplayPort™ cable and HDMI cable.

#### Sign up for updates hp.com/go/getupdated

