





TS-h2483XU-RP-E2136-128G  CPU Intel® Xeon® E-2136 6-core 3.3 GHz processor (burst up to 4.5 GHz)  CPU Architecture 64-bit x86  Floating Point Unit Yes  Encryption Engine Yes (AES-NI)  System Memory 128 GB UDIMM DDR4 ECC (4 x 32GB)  Maximum Memory 128 GB (4 x 32 GB)  Memory Slot 4 x UDIMM DDR4  Flash Memory 5GB (Dual boot OS protection)  Drive Bay 24 x 3.5-inch SATA 6Gb/s, 3Gb/s  Drive Compatibility 3.5-inch bays: 3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives  Hot-swappable Yes
CPU Architecture 64-bit x86  Floating Point Unit Yes  Encryption Engine Yes (AES-NI)  System Memory 128 GB UDIMM DDR4 ECC (4 x 32GB)  Maximum Memory 128 GB (4 x 32 GB)  Memory Slot 4 x UDIMM DDR4  Flash Memory 5GB (Dual boot OS protection)  Drive Bay 24 x 3.5-inch SATA 6Gb/s, 3Gb/s  Drive Compatibility 3.5-inch bays: 3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives
Floating Point Unit  Encryption Engine  Yes (AES-NI)  System Memory  128 GB UDIMM DDR4 ECC (4 x 32GB)  Maximum Memory  128 GB (4 x 32 GB)  Memory Slot  4 x UDIMM DDR4  Flash Memory  5GB (Dual boot OS protection)  Drive Bay  24 x 3.5-inch SATA 6Gb/s, 3Gb/s  Drive Compatibility  3.5-inch bays: 3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives
Encryption Engine Yes (AES-NI)  System Memory 128 GB UDIMM DDR4 ECC (4 x 32GB)  Maximum Memory 128 GB (4 x 32 GB)  Memory Slot 4 x UDIMM DDR4  Flash Memory 5GB (Dual boot OS protection)  Drive Bay 24 x 3.5-inch SATA 6Gb/s, 3Gb/s  Drive Compatibility 3.5-inch bays: 3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives
System Memory 128 GB UDIMM DDR4 ECC (4 x 32GB)  Maximum Memory 128 GB (4 x 32 GB)  Memory Slot 4 x UDIMM DDR4  Flash Memory 5GB (Dual boot OS protection)  Drive Bay 24 x 3.5-inch SATA 6Gb/s, 3Gb/s  Drive Compatibility 3.5-inch bays: 3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives
Maximum Memory  128 GB (4 x 32 GB)  Memory Slot  4 x UDIMM DDR4  Flash Memory  5GB (Dual boot OS protection)  Drive Bay  24 x 3.5-inch SATA 6Gb/s, 3Gb/s  Drive Compatibility  3.5-inch bays: 3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives
Memory Slot 4 x UDIMM DDR4  Flash Memory 5GB (Dual boot OS protection)  Drive Bay 24 x 3.5-inch SATA 6Gb/s, 3Gb/s  Drive Compatibility 3.5-inch bays: 3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives
Flash Memory 5GB (Dual boot OS protection)  Drive Bay 24 x 3.5-inch SATA 6Gb/s, 3Gb/s  Drive Compatibility 3.5-inch bays: 3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives
Drive Bay  24 x 3.5-inch SATA 6Gb/s, 3Gb/s  Drive Compatibility  3.5-inch bays: 3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives
Drive Compatibility  3.5-inch bays: 3.5-inch SATA hard disk drives 2.5-inch SATA solid state drives
3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives
Hot-swappable Yes
SSD Cache Acceleration Yes Support
GPU pass-through Yes
Gigabit Ethernet Port 4 (RJ45)
10 Gigabit Ethernet Port 2 x 10GbE SFP+ SmartNIC port, 2 x 10GBase-T port
Wake on LAN (WOL) Yes
Jumbo Frame Yes
PCIe Slot  5 Slot 1: PCIe Gen 2 x4 (PCH) Slot 2: PCIe Gen 3 x4 (CPU) Slot 3: PCIe Gen 2 x4 (PCH) Slot 4: PCIe Gen 3 x8 (CPU) Slot 5: PCIe Gen 2 x4 (PCH)

USB 3.2 Gen 2 (10Gbps) Port	2 x Type-C USB 3.2 Gen 2 10Gbps 4 x Type-A USB 3.2 Gen 2 10Gbps
Form Factor	4U Rackmount
LED Indicators	HDD 1-24, Status, LAN, storage expansion port status
Buttons	Power, Reset
Dimensions (HxWxD)	176.15 × 481.04 × 672.02 mm
Weight (Net)	20.67 kg
Weight (Gross)	28.56 kg
Operating temperature	0 - 40 °C (32°F - 104°F)
Storage Temperature	-20 - 70°C (-4°F - 158°F)
Relative Humidity	5-95% RH non-condensing, wet bulb: 27°C (80.6°F)
Power Supply Unit	800W(x2), 100-240V
Power Consumption: Operating Mode, Typical	168.97 W
Fan	System fan: 3 x 80mm, 12VDC
System Warning	Buzzer
Max. Number of Concurrent Connections (CIFS) - with Max. Memory	10000

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications.

 $Warning: Using \ unsupported \ modules \ may \ degrade \ performance, \ cause \ errors, \ or \ prevent \ the \ operating \ system \ from \ starting.$ 

Environment: Refer to ISO 7779; Maximum HDD loaded; Bystander Position; Average data from 1 meter in front of operating NAS. Product images are for illustrative purposes only and may differ from the actual product. Due to differences in monitors, colors of products may also appear different to those shown on the site.

Designs and specifications are subject to change without notice.

<sup>\*</sup> Sound Level Test