

**PowerMust 600 / 800 LCD Line Int., Schuko or IEC**

PM 600 / 800 LCD



Backside PM 600 / 800 LCD IEC



Backside PM 600 / 800 LCD Schuko

**Features**

- Line Interactive UPS
- Touch Screen LCD to display UPS information
- Compact size (30,0 x 10,1 x 14,2cm)
- Microprocessor control guarantees high reliability
- Discharge and overcharge protection
- Auto restart while AC is recovering
- Off mode charging
- Visual and audible Alarm system
- Cold start function

## PowerMust 600 / 800 LCD Line Int., Schuko

### Specification

MODEL	PowerMust 600 LCD	PowerMust 800 LCD
<b>INPUT</b>		
Capacity	600VA/360W	800VA/480W
Nominal Voltage	220/230/240VAC	
Voltage Range	162-290 VAC	
Frequency Range	50/60 Hz $\pm$ 1 Hz (auto sensing)	
<b>OUTPUT</b>		
AC Voltage Regulation (Batt. Mode)	220 / 230 /240 $\pm$ 10%	
Frequency Range (Batt. Mode)	50 / 60 Hz $\pm$ 1 Hz	
Transfer Time	Typical 2-6 ms	
Waveform (Batt. Mode)	Simulated Sine Wave	
Protection	Overload, discharge and overcharge protection	
<b>BATTERY</b>		
Battery Type	12 V / 7 AH x1	12 V / 9 AH x 1
Recharge Time	4 hours to 90% capacity	
Backup Time (at 100W load)	16 min.	20 min.
<b>AUDIBLE ALARM</b>		
Battery Mode	Sounding every 10 seconds	
Low Battery at battery mode	Sounding every second	
Fault	Continuously sounding	
Battery replacement	Sounding every 2 seconds	
Overload	Sounding every 0.5 second	
<b>PHYSICAL</b>		
Dimension, D x W x H (mm)	300 x 101 x 142	
Net Weight (kgs)	4,5	5,0
<b>ENVIRONMENT</b>		
Operation Humidity	0-90% RH @ 0-40 $^{\circ}$ C (non-condensing)	
Noise Level	Less than 40 dB	
<b>INTERFACE</b>		
Power Cord Connector	Schuko input powercord	
Outlet	Schuko 2 x or 4 x IEC	
Phoneline/ Network protection	RJ11	
USB port	Yes	
LED/LCD	LCD	
<b>MANAGEMENT</b>		
USB Port	Windows <sup>®</sup> 2000/2002/XP/Vista/2008/7/8/10, Linux and MAC	