

Data Sheet FUJITSU Display B32-9 TS UHD

Powerful FUJITSU Display B32-9 TS UHD.
Bringing design projects to the next level with the power of high resolution!

Successful design projects become standard due to FUJITSU Display B32-9 TS UHD with its 4K UHD resolution and other powerful features to support high level and complex projects.

Experience 4K UHD (3840 x 2160) resolution with next generation IPS panel technology for a precise color matching and 10 bit warrants high color performance.

Due to its brilliant resolution and large surface, our largest B-Line Display meets even the high requirements in the field of designing with high-end 2D & 3D, specialized design projects and observation scenarios.

Working in an elegant work environment with possible multi-monitor setups thanks to state-of-the-art ultra-thin bezel housing.

Best ergonomics and flexibility based on 5-in-1 stand base allows users to tilt, swivel and adjust height of the display. The cable guide and appliance for PC backpack enable a complete workspace solution.

DisplayView™ software enables you to configure your monitor by mouse click or from administrator by SCCM tools.

Being certified with Energy Star 8.0, you can save energy, costs and reduce CO² footprint, without compromising performance.













Technical details

| Special features | |
|------------------------------------|---|
| | In-Plane Switching (IPS) technology, Low blue light mode, Eco button, 5-in-1 Stand, Always available USB (in operating and standby mode), DisplayView™ Software, 24/7 usage, Cable guide, Integrated speakers |
| Ergonomic stand | |
| Stand | 5-in-1 Stand |
| Height adjust range | 130 mm |
| Picture height over desk (min) | 45 mm |
| Picture height over desk (min) | 45 mm |
| Filt angle | -5° / +25° |
| Swivel angle | 345° |
| Picture performance | |
| Panel and backlit | In-Plane Switching (IPS) technology/LED |
| Screen Surface Treatment | Anti-glare, 3H hard coating |
| Contrast - typical | 1,000:1 |
| Contrast - advanced | 20,000,000:1 |
| Response time gray to gray typical | 5 ms (in Video mode) |
| /iewing angle (h/v) - typical | 178°/178° CR10:1 |
| Color performance | 1.07 billion (8bit + A-FRC) |
| Brightness - typical | 350 cd/m ² |
| Size and resolution | |
| Aspect ratio | 16:9 |
| Diagonal Size | 80 cm (31.5-inch) |
| Resolution (native) | 3,840 x 2,160 pixel |
| Resolution (interpolated) | 2,560 x 1,440 pixel, 1,920 x 1,080 pixel, 1,680 x 1,050 pixel, 1,400 x 900 pixel, 1,280 x 1,024 pixel, 1,024 x 768 |
| | pixel, 800 x 600 pixel, 720 x 400 pixel, 640 x 480 pixel |
| Picture size | 697 x 392 mm |
| Pixel Pitch | 0.1816 mm |
| requencies | |
| Horizontal | 30 - 134 kHz |
| /ertical | 24 - 76 Hz |
| Connectivity | |
| DisplayPort | 1 x DisplayPort 1.2 |
| HDMI | 2 x HDMI 2.0 |
| Audio signal output | 3.5 mm stereo phone jack for head phone |
| Audio sound output | 2 x 3 W |
| JSB downstream | 2 x USB 3.2 gen 1 (5 Gbps) |
| JSB upstream | 1 x USB 3.2 gen 1 (5 Gbps) |
| Ease-of-use menu | |
| Votes | 6 tactile keys on front side |
| Direct Access Keys | Menu, ECO, Input, Mode, Audio, Brightness |
| anguages | Arabic, Czech, Danish, Dutch, English, Finnish, French, German, Italian, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Japanese, Chinese simply, Chinese traditional |
| Brightness / Contrast | Brightness, Contrast, Black level, ACR |
| Лоde | sRGB, Office, Photo, Video, Low Blue Light, Custom |
| Color | 5000K, 6500K, 7500K, Native, RGB Adjust |
| OSD | Language, OSD-Timeout, OSD rotation |
| Image adjust | Sharpness, Saturation, Hue, Expansion |
| Audio | Mute, Volume, Input for HDMI and DP interface |
| Information | Model name, Serial number, Signal input, Resolution/mode, Display mode, Color Temperature, ACR Status |

| Advanced settings | Overdrive, DDC/CI, Status LED, Factory Recall |
|---------------------------------------|--|
| Power consumption (typical, w/o sound | |
| Soft switch off | 0.14 W |
| Power save mode | 0.21 W |
| Operating with EPA settings | 29.91 W |
| Total Energy Consumption (ETEC) | 92.88 kWh/year |
| Power supply | integrated |
| Power notes | Speakers off, USB not connected ETEC and EPA refer to ENERGY STAR® 8.0 Power save mode according to EEI test conditions |
| Electrical values | <u> </u> |
| Rated voltage range | 100 V - 240 V |
| Rated frequency range | 50 Hz - 60 Hz |
| Protection class | 1 |
| Compliance | |
| Model | B32-9T |
| Global | ENERGY STAR® 8.0, TCO Certified Displays 8.0, EPEAT® Bronze (dedicated regions), TÜV Low Blue Light Certified, TÜV Flicker Free Certified, Zero bright and dark pixel faults, Subpixel faults according to ISO9241-307 (Pixel fault class I) |
| Еигоре | Energy Efficiency Class: B, EN 62368-1, CE certification according to EC Directive 2004/108/EEC, RoHS, WEEE, IT-Eco-Declaration |
| Germany | TÜV GS |
| USA/Canada | FCC Class B, cTUVus |
| Compliance link | https://sp.ts.fujitsu.com/sites/certificates |
| Dimensions / Weight / Environmental | |
| Dimension without stand (W x D x H) | 715.2 x 52.55 x 423.13 mm |
| | 28.16 x 2.07 x 16.66 inch |
| Dimension with stand (W x D x H) | 715.2 x 269.37 x 545.03 mm |
| | 28.16 inch x 10.61 x 21.46 inch |
| Weight (unpacked) | 9.8 kg |
| Weight (Monitor only) | 9.54 kg |
| Operating ambient temperature | 5 - 35 °C (41 - 95 °F) |
| Operating relative humidity | 10 - 85 % (non condensing) |
| Miscellaneous | |
| Miscellaneous | VESA DDC/ CI, Flat Display Mounting Interface VESA MIS-D 100 C, Kensington lock prepared |
| Color | Matt black |
| Package content | High block |
| Display delivered accessories | DisplayPort data cable 1.8 m HDMI cable 1.8 m USB-cable 1.8 m (USB-A to USB-B) Power cable for wall socket (Euro-Schuko-Type CEE7) 1.8 m Quickstart flyer Safety notes |
| Display delivered accessories notes | Power cable with IEC-60320-C13, 3-pin connector on display side Data cables and USB cable detachable on display User manual and DisplayView Software is available via download |
| Packaging information | |
| Packaging dimension (mm) | 800 x 249 x 519 mm |
| Packaging dimension (inch) | 31.5 x 9.8 x 20.43 inch |
| Order information | |
| Order Code | S26361-K1696-V160 |
| EAN Code | 4063872126731 |
| | |
| Warranty period | 3 years (depending on country) |

| Warranty type | Collect & Return Service (depending on country specific requirements) |
|-----------------------------|---|
| Warranty Terms & Conditions | http://www.fujitsu.com/warranty |
| Spare Parts availability | 5 years after end of product life |
| Service Weblink | http://www.fujitsu.com/emeia/products/product-support-services/ |

More information

Fujitsu products, solutions & services

In addition to FUJITSU Display B32-9 TS UHD, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about FUJITSU Display B32-9 TS UHD, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

www.fujitsu.com/emeia/products/computing/ peripheral/displays

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at http://www.fujitsu.com/global/about/environment/



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html

Copyright 2020 Fujitsu Technology Solutions GmbH

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

Fujitsu Technology Solutions GmbH Website: www.fujitsu.com 2020-11-20 EM-EN All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html
Copyright 2020 Fujitsu Technology Solutions GmbH