



Model Name

X1 2000 Digital Projector

Unique Selling Point

- * 4K UHD resolution
- * **8.3 Million Pixels** (meet CTA 4K UHD Display Requirement)
- * 4K Upscaling function
- * **Philips ColorSpark HLD LED***
- * **DCI-P3 Color Space**
- * CinemaMaster Video Enhancer
- * 1.5X big zoom lens
- * H/V lens shift

Trade Mark



Projection System	DLP 4K UHD	
Resolution	3840 x 2160 with XPR technology	
Display Pixels	8.3 million pixels	
Brightness	2200 AL	
FOFO Contrast Ratio	50,000:1	
Display Color	1.07 Billion Colors	
Lens	F = 2.05 - 2.37 f = 20.54 - 30.31	
Aspect Ratio	16:9	
Throw Ratio	1.36 - 2.03 (100" @ 3m)	
Image Size (Clear Focus / Maximum)	95"~180" / 300"	
Zoom Ratio	1.5:1	
Lamp Type	PHILIPS HLD	
Lamp Mode (Normal/Eco)*	20,000 hours**	
Lens Shift	Vertical: ± 65% / Horizontal: ± 27%	
Horizontal Frequency	15 - 102KHz	
Vertical Scan Rate	23 - 120Hz	
Color Space	DCI-P3	
HDMI Compatibility	HDTV Compatibility	VGA (640 x 480) to 4K UHD (3840 x 2160)
	Video Compatibility	480i/p 60Hz, 576i/p 50Hz, 720p 50/60Hz, 1080i 50/60Hz, 1080p 24/25/30/50/60Hz, 2160p 24/25/30/50
Interface	PC (D-Sub)	x 1
	HDMI	x 2 (HDMI 1: HDMI 2.0 & HDCP 2.2; HDMI 2: HDMI 1.4a & HDCP 1.4)
	USB (Type mini B)	x 1 (Service)
	LAN	x 1
	RS232	x 1
	DC 12V Trigger	x 2
	IR Receiver	x 2 (Front & Back)
	IR in	x 1
Physical	Dimensions (L x W x H)	470.7 x 224.9 x 564.7 mm
	Weight	18.5 Kg (40.8 lbs)
Power	Power Supply	AC100 to 240 V, 50 to 60 Hz
	Power Consumption	Normal 530W, Eco 290W, Network Standby <3W, Standby <0.5W
Audible Noise (Normal/Economic)	31 / 23 dBA (under silence mode)	
On-Screen Display Languages	Arabic/Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/ Hindi/ Hungarian/ Italian/ Indonesian/ Japanese/ Korean/ Norwegian/ Polish/ Portuguese/ Romanian/ Russian/ Simplified Chinese/Spanish/ Swedish/ Turkish/ Thai/ Traditional Chinese (28 Languages)	

Picture Modes

*** ISF Disabled: Bright / Vivid / Cinema / **DCI-P3** / Game / User 1 / User 2

**** ISF Enabled: Bright / Vivid / Cinema / **DCI-P3** / Game / User 1 / User 2 / **ISF Night** / ISF Day

	Standard	Optional
Accessories	Lens Cover	Spare Lamp Kit
	Remote Control with Battery	Ceiling Mount 5JJFY10.001
	Power Cord (by region)	Anamorphic lens
	User Manual CD	
	Quick Start Guide	
	Warranty Card	

Environmental Notice

Lamp in this product contains mercury. To dispose of the product or used lamps, consult your local environment authorities for regulations or see www.lamprecycle.org.

* ColorSpark is a trademark of Philips Lighting Holding B.V.

** Lamp life results will vary depending on environmental conditions and usage. Actual product's features and specifications are subject to change without notice.

*** Default picture mode is **DCI-P3**.

**** When ISF is enable, default picture mode is **ISF Night**.