

i-SENSYS X 1238P Series

DESKTOP DEVICES DELIVERING A PROFESSIONAL PRINT EXPERIENCE

Versatile A4 black and white laser printers to complement larger office print solutions













i-SENSYS X 1238P Series

PRODUCTIVITY

- Intuitive control with either 5-line LCD or 5" colour touchscreen display
- · Fast print speeds
- Double-sided printing as standard
- Customisable display with Application Library

SECURITY

- Embedded user authentication safeguards device access
- Secure Print prevents unauthorised viewing of printed material
- Verify System at Start-up enhances device integrity



- Support for Apple Air Print and Mopria
- Compatible with Google Cloud Print and the Canon PRINT Business app
- Print directly from USB
- Streamline print processes with uniFLOW Online software*

COMPACT DESIGN

- Small footprint and weight allow for any office configuration
- Add additional cassettes for enhanced input capacity without compromising on device size
- All-in-one space saving toner cartridge lasts for longer

(a) CONTROL AND MAINTENANCE

- Flexible user management solutions for business administrators and IT department
- Remote access to device control functions
- · Toner status tool reduces downtime

*Available with the i-SENSYS X 1238P only

QUICK FACTS

i-SENSYS X 1238Pr

- 5-line LCD display
- Print Speed: 38ppm (A4)
- Print resolution: up to 1,200 x 1,200 dpi
- Automatic double-sided printing
- Network, USB and Wi-Fi connectivity connectivity
- Max paper input capacity: 900 sheets

i-SENSYS X 1238P

- 5-inch/12.7cm TFT LCD touchscreen
- Print Speed: 38ppm (A4)
- Print resolution: up to 1,200 x 1,200 dpi
- Automatic double-sided printing
- Network, USB, Wi-Fi, and QR code connectivity
- uniFLOW compatibility
- Max paper input capacity: 900 sheets

SERVICES

CORE

Perform routine office operations safely and with ease, utilising embedded software including uniFLOW Online Express and other available services offering complete device maintenance and support





HARDWARE

<u>2</u>23)

SERVICES

BESPOKE

Choose a tailored service to suit your business needs by removing unnecessary print management burdens. Consult with Canon experts about your specific requirements to find a fitting Print Managed Services option

ENHANCED

Expand cloud capabilities with uniFLOW Online, Canon's all-in-one print management system



TECHNICAL SPECIFICATIONS

i-SENSYS X 1238P Series

PRINTER ENGINE

Print speed

Printing method Print resolution Warm-up time First Page Out Time Recommended Monthly Print Volume Duty cycle

Print margins Advanced printing features

MEDIA HANDLING Paper input (Standard)

Paper input (Option) Paper output Media types

Media sizes

Media weights

Double sided printing

GENERAL FEATURES Power requirements Power consumption

Noise level

Single sided: Up to 38 ppm (A4) Up to 63.1 ppm(A5-Landscape) Double sided : Up to 31.9 ipm (A4)

Monochrome laser beam printing

Up to 1200 x 1200 dpi

Approx. 14 seconds or less from power on

Approx: 5.5 seconds or less 750 - 4,000 pages per month

80,000 pages

5 mm-top, bottom, left and right

Secure Print
Print from USB memory key (JPEG/TIFF/PDF)
Barcode Print¹
Google Cloud Print Ready
iOS: AirPrint, Canon PRINT Business app
Android; Mopria certified, Canon Print Service
Plug-in, Canon PRINT Business app

250-sheet cassette 100-sheet multi-purpose tray

550-sheet cassette

150-sheet

Plain paper, Recycled paper, Heavy Paper, Thin paper, Label, Post card, Envelope

Cassette (Standard and optional):

A4, A5, A5 (Landscape), A6, B5, Legal, Letter, Executive, Statement, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, Foolscap, 16K, Custom sizes: Min. 105 x 148 mm Max. 216.0 x 355.6

Multi-purpose tray:
A4, A5, A5 (Landscape), A6, B5, Legal, Letter,
Executive, Statement, OFFICIO, B-OFFICIO,
M-OFFICIO, GLTR, GLGL, Foolscap, 16K, Indexcard,
Envelope (COM10, Monarch, C5, DL),
Custom sizes: Min 76.2 x 127 mm Max. 216.0 x 355.6
mm.

Cassette (standard and optional): 60 to 120 g/m^2 Multi-purpose tray: 60 to 163 g/m^2

A4, Legal, Letter, OFFICIO, B-OFFICIO, M-OFFICIO,

A4, Legal, Letter, C GLGL, Foolscap Custom size - Min. 210 x 279.4 mm Max. 216.0 x 355.6 mm

60 to 120 g/m²

220-240V(±10%) 50/60Hz (±2Hz)

Maximum: Approx. 1,330 W Standby: Approx. 9 W Sleep mode: Approx. 0.9 W Typical Electricity Consumption (TEC): 0.33 kWh/week?

For detailed information relating to Lot26 regulation, please go to: http://www.canon-europe.com/For_Work/Lot26/index.aspx

Sound Pressure² Active: 54 dB Standby: Inaudible³

Sound Power²: Active: 68 dB Standby: Inaudible³ Dimensions (W x D x H)

Weight

Operating environment

Control panel

i-SENSYS X 1238P: 438 mm x 373 mm x 312 mm i-SENSYS X 1238Pr: 401 mm x 373 mm x 250 mm

i-SENSYS X 1238P: Approx. 9.2 Kg i-SENSYS X 1238Pr: Approx. 8.8 Kg

Temperature: 10 to 30°C (50 to 86°F) Humidity 20 to 80% RH (no condensation)

i-SENSYS X 1238P: 12.7 cm LCD Colour Touch Screen i-SENSYS X 1238Pr: 5 Line LCD, 3 LED (Job, Error, Energy saver), Buttons, 10-key numeric keypad

CONTROLLER

Processor Speed Memory

Printer Languages

Fonts

Interface and connectivity

Software and Printer Management

800MHz x 2

1GB

UFRII, PCL 5e4, PCL6, Adobe® PostScript3

93 PCL fonts, 136 PS fonts

USB 2.0 Hi-Speed, 10BASE-T/100BASE-TX/1000Base-T, Wireless 802.11b/g/n, Wireless Direct Connection

i-SENSYS X 1238P:

i-SENSYS X 1238P: Remote User Interface (RUI), Department ID Management,

Toner Status Tool.

iW Enterprise Management Console: Server-based software for centralised management of a fleet of devices eMaintenance: embedded RDS allows remote

eMaintenance services such as meter capture automatic consumables management and remote diagnostics.

Universal Log-in Manager / uniFLOW online / uniFLOW online Express / uniFLOW compatibility / Application Library

i-SENSYS X 1238Pr: Remote User Interface (RUI), Department ID Management,

Department ID Management,
Toner Status Tool,
IW Enterprise Management Console: Server-based
software for centralised management of a fleet of
devices
eMaintenance: embedded RDS allows remote

eMaintenance services such as meter capture automatic consumables management and remote

diagnostics. Operating Systems Compatibility

Windows* 10 / Windows* 8.1 / Windows* 7 / Server* 2019 / Server* 2016 / Server* 2012R2 / Server* 2012 / Server* 2008R2 / Server* 2008 Mac OS X version 10.9.5 & up / Mac OS 10.15 & up Linux*

CONSUMABLES All-in-One cartridges

ACCESSORIES/ OPTIONS

Items

TONER TO8 (11,000 pages⁶)

i-SENSYS X 1238Pr: Cassette Feeding Module-AH1 Barcode Printing Kit-E1E

i-SENSYS X 1238P: Cassette Feeding Module-AH1 MiCard Multi (Card reader for identification with RFID or magnetic cards with uniFLOW) Micard Plus (Card reader for identification with RFID or magnetic cards with uniFLOW) MiCard Attachment kit-B1 Barcode Printing Kit-E1E i-SENSYS X 1238P:

Notes:

- Accessory Barcode Printing Kit-E1E is required
- Declared noise emission in accordance with ISO 9296
- [3] Inaudible means that the emission sound pressure level for a bystander is lower than absolute standard for background noise in accordance with ISO 7779
- A Canon PCL5e driver is not supplied, however PCL5e commands are supported on the device.
- [5] Web distribution only. Driver will be available from second half 2020 onwards.
- [6] Based on ISO/IEC 19752
- As per US ENERGY STAR® version3.0



Software & Solutions









Compatibility











Canon Inc. canon.com Canon Europe canon-europe.com English edition © Canon Europa N.V.,2020