

## imagePROGRAF GP-6600S

# PRECISION PALETTE, CRAFTING BRILLIANCE

A revolution in printing premium posters for chain retail & franchised stores, as well as print service providers with a sustainable 60" large format printer - where accuracy meets vibrancy. Unlock an eye-catching spectrum of colours with PANTONE™ precision, thanks to the innovative new LUCIA PRO II ink³, especially orange ink. Get sustained productivity without compromising on image quality and longevity.

#### Professional image quality

Dive into a world of vivid corporate colours that captivate, paired with enhanced black density that brings more depth to your premium posters. The imagePROGRAF GP-6600S goes beyond ink - it provides total colour accuracy, perfect colour gradation and highlights a wide PANTONE™ coverage²

#### Increased durability

Preserve your premium posters for 200 years<sup>4</sup> with better light fastness using high light-resistance ink. Improve image robustness with high scratch resistant ink helps ensure your prints last a lifetime

 $^{1}\mathsf{PANTONE}^{\text{\tiny{TM}}}$  is a trademark or registered trademark of Pantone LLC.

<sup>2</sup>PANTONE FORMULA GUIDE Solid Coated colour gamut coverage rate is 96% for GP-6600S/4600S/2600S, when using Premium Semi-Glossy Paper 2 with imagePROGRAF printer driver at [High] [Color Correction Off]; coverage rate is 82% when using Heavyweight Coated Paper HG with imagePROGRAF printer driver at [High] [Color Correction Off]

Five of the seven inks are newly developed. The matte black and orange inks are the same as those used by the imagePROGRAF GP-2000/4000.

<sup>4</sup>When using Canon Heavyweight Coated Paper HG 145gsm. Predicted value calculated in accordance with the indoor light resistance test method and life evaluation criteria of the digital colour photographic print image preservation evaluation method (JEITA CP-390IB) published by JEITA (Japan Electronics and Information Technology Industries Association).

<sup>5</sup>EPEAT Gold registered in the U.S.

658.9% reduction of polystyrene in packaging if second roll unit is included.

#### Enhanced productivity

Transform printing workflows with easier media handling and simplified settings. Enhance efficiency with dual rolls, auto media loading, mirrored ink arrangement with high speed printing. With new print head monitoring function and auto alignment adjustment, masterpieces are created with confidence without image deterioration

#### Improved sustainability

Protect the environment by using less power during both operation and power-off. It is EPEAT Gold rated<sup>5</sup> and its packaging reduces 89.5% of polystyrene usage<sup>6</sup>



### **TECHNICAL SPECIFICATIONS**

## imagePROGRAF GP-6600S

PRINTER TECHNOLOGY

7 Colours 60" Printer Type

Canon Bubblejet on Demand 12 colours integrated type (12 chips per print head x 1 print head) Print Technology

Print Resolution 2,400 x 1,200 dpi

Number of Nozzles 18,432 nozzles (MBK/C/M/Y/O:1536nozzles x2, PBK/GY:1536nozzles x1)

±0.1% or less Line Accuracy User adjustments necessary. Printing environment and media must match those used for the adjustments.

 $600\ \mbox{dpi}\ \mbox{x}\ 2$  includes Non-firing nozzle detection and compensation system

Ink Droplet Size Ink Canacity

Sales Ink: 160ml / 330ml / 700m

OS Compatability

Others supported job submission protocol

Printer Languages

PDF (Ver.1.7), JPEG (Ver. JFIF 1.02)

Standard Interfaces

IEEE802.3 (10BASE-T) Wireless LAN¹: IEEE802.11n/IEEE802.11g/IEEE802.11b

MEMORY

500 GB (Encrypted HDD)

Coated paper (A0)

Glossy Photo Paper (A0) 2:56 (Fast) 4:44 (Standard)

MEDIA HANDLING

Media Width

Media Feed and Output

Media Thickness Roll/Cut: 0.07mm - 0.8mm

Minimum Printable Length Roll paper: 101.6mm (Cross and canvas paper: 200mm) Cut sheet: 203.2mm

Maximum Printable Length

Maximum Media Roll Diameter

Media Core Size

Margins Recommended area

minimum 4pl per colour

Bundled Starter Ink: 2310ml (330ml for each colour)

Pigment inks : 7 colours (Matte Black, Photo Black, Cyan, Magenta, Yellow, Grey, Orange)

32 Bit: Windows?, Windows 81, Windows 10 64 Bit: Windows?, Windows 81, Windows 10, Windows 11, Windows Server 2008R2, 2012, 2012R2, 2016, 2019, 2022 Apple MacIntosh: macOS 10.15.7-macOS 13

Apple AirPrint

USB A Port: USB Memory (Direct Print) for PDF/JPEG files
USB B Port: Hi-Speed USB
Ethernet: IEEE802.3ab(1000base-T), IEEE802.3u(100BASE-TX)/

Standard Memory

Expansion slot : No

PRINTING SPEED Plain paper (A0): 0:48 (Level 5)

1:24 (Fast) 2:24 (Standard)

Upper Roll Paper: One Roll, Upper-loading, Front Output Lower Roll Paper: One Roll, Upper-loading, Front Output Cut Sheet: Upper-loading, Front Output (Manual feed using media locking lever)

Roll paper: 152.4 - 1524mm Cut sheet: 152.4 - 1524mm

Roll paper: 18m (varies according to the OS and

application) Cut sheet: 1.6m

170mm

Internal diameter of roll core: 2"/3"

Roll paper: Top: 20mm, Bottom: 3mm, Side: 3mm Cut sheet (Others): Top: 20mm, Bottom:20mm, Side:3mm

Margins Printable area Roll paper: Top: 3mm, Bottom: 3mm, Side: 3mm

Roll paper (borderless): Top: Omm, Bottom: Omm, Side: Omm Cut sheet: Top: 3mm, Bottom: 12.7mm, Side: 3mm

Roll Paper: Two rolls. Automatic switching is possible Roll Paper, Cut Sheet: Manual switching is possible Cut Sheet: 1 sheet

Dual direction roll take up unit allowing print surface to be wound inside or outside of the roll Media Take-Up Roll Unit

[Recommended] 515mm(JIS B2), 728mm(JIS B1), 1030mm(JIS B0), 594mm(ISO A1), 841mm(ISO A0), 10", 14", 17", 24", 36", 42", 44", 50", 54", 60"

[Printable] 257mm(JIS B4), 297mm(ISO A3), 329mm(ISO A3+), 364mm(JIS B3/B4), 420mm(ISO A2), 6", 8", 12", 15", 16", 18", 20", 22", 30", 34", 300mm, 500mm, 600mm, 800mm, 1000mm

Other than above, free size borderless printing is supported on

only roll paper by user definition

Standard position: 1 sheet Flat position: A2 landscape, glossy paper less than 10 sheets, coated paper less than 20 sheets (excludes strong curled condition)

POWER AND OPERATING REQUIREMENTS

Operating Environment

Maximum number of delivered

Borderless Printing Width

(Roll Only)

Power Supply Power Consumption

Operation: 94W or less Sleep mode: 2.2W or less Default setting for the time to enter the Sleep mode: Approx. 5

minutes Power off: 0.1W or less

Temperature: 15-30°C, Humidity: 10-80% RH

(no dew condensation)

Operation: Approx. 49dB(A) (Measured based on ISO7779 Photo Glossy Paper HG/Standard/60") Accoustic Noise (Power/Pressure)

Standby: 35 dB(A) or less

Operation: 6.6 Bels or less (Measured based on ISO7779 Photo Glossy Paper HG/Standard/60")

CE mark, UKCA mark **Environment Certificates** CB certfication, EPEAT GOLD<sup>2</sup>

DIMENSIONS AND WEIGHT

Physical Dimensions and Weight

Main unit + Stand

1999×984×1168 mm (Basket Opened)

1999×766×1168 mm (Basket Closed)

169 kg (including Roll Holder Set, excluding ink and print head) Packaged Dimensions and Weight

Printer (Main unit with pallet): 2227  $\times$  915  $\times$  1025 mm, 218kg Roll unit: 2133  $\times$  562  $\times$  461 mm, 42kg

WHAT'S INCLUDED

What's in the Box?

Printer, Printer Stand, 1 Print head, Power Cable, 1 Set of starter ink tanks, Installation Guide, Safety/Standard Environment leaflet, LFP Eur Address Sheet, Important Information Sheet, Stack Printer Stand Setup Guide, Notice for PosterArtist WEB

Software Included Software available as Download from Web.

OPTIONS

Optional Items 2"/3" Roll Holder: RH2-66 Roll Unit: RU-63

CONSUMABLES User Replaceable Items

Ink Tank: MBK/Orange: PFI-2100(160ml)/PFI-2300(330ml)/ PFI-2700(700ml) Others:PFI-3100(160ml)/PFI-3300(330ml)/ PFI-3700(700ml) Print Head: PF-10 Cutter Blade: CT-07 Maintenance Cartridge: MC-30

<sup>1</sup>Please refer to user manual how to activate/deactivate the wireless LAN <sup>2</sup>EPEAT Gold registered in the U.S.

#### Disclaimer

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice." and "All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended.











canon.com Canon Europe canon-europe.com English edition

© Canon Europa N.V., 2024

Canon Inc.