

- Supports all renowned RGB synchronization systems
- Rainbow RGB fan with a +5V addressable LED connector
- High-Performance (90% Eff. @230V) RGB Gaming

The highly innovative **Photon GOLD series** are aimed at gamers and enthusiasts, looking for the ultimate in power, longevity, performance and of course, RGB lighting effects and all this at a highly affordable price.

The +5V addressable LED connector of the PSU offers an extreme wide range of lightening modes and effects, supports all renowned RGB lightening synchronization systems such as **ASUS™ AURA SYNC**, **MSI™ MYSTIC LIGHT SYNC**, **ASROCK™ POLYCHROME SYNC** and **GIGABYTE™ RGB FUSION**.

Photon GOLD series in addition provide a vast number of predefined and MB-independent lightening modes and effects, which are set via a button on the rear of the power supply while a minute toggle switch, equally located on the rear of the PSU allows the choice between the M/B RGB control (if available) or the integrated modes and effects. With its vast amount of extra-long cables and an **efficiency of 90% @230V**, the models of the **Photon GOLD series** stands out as a perfect RGB gaming solutions.



Technical data





Model	Photon Gold 750W
Artikel no.	GDP-750C-RGB
EAN code	0753263075901
Weight (without/with package)	2.30 kg / 2.60 kg
Specification	ATX 12V 2.3
Form factor	PS II
Efficiency	>90%
PFC	Active PFC (0.9) (only 230V)
Fan	140mm silent RGB Rainbow fan
Lightning modes	14x dynamic modes integrated
Dimension (DxWxH)	160mm x 150mm x 87mm
Security	AFC (Automatic Fanspeed Control) OPP (Overload protection) OVP (Overvoltage protection) SCP (Short-circuit protection) SIP (Surge & Inrush Protection) UVP (Undervoltage protection)
Warranty	24 Months

Output data

Photon Gold 750W	AC Input	200-240V 47- 63Hz 5A				
	DC Output	+3.3V	+5V	+12V	-12V	+5VSB
	Max. Current	22A	22A	62A	0.3A	2.5A
	Max. Combined Power	120W		744W	3.6W	12.5W
		750W				

* The listed specifications may be altered at any point in time without any pre-notice.

** Chieftec® is a registered trademark. All other brands and/or logos are property of the respective owners.

	Cable	Connectors	Length (mm)
	24 PIN (20+4)	1	550
	8 PIN PCI-E (6+2)	4	2x 550/150
	8 PIN EPS	1	550
	SATA	8	2x 550/150/150/150
	MOLEX	3	550/150/150/150
	FLOPPY	1	
	RGB LED PIN	1	550

Certification



* The listed specifications may be altered at any point in time without any pre-notice.

** Chieftec® is a registered trademark. All other brands and/or logos are property of the respective owners.