

Colorful productivity. Seamless set up.

Get a blazing fast color printer and easy set up with LaserJet Pro.



This printer is intended to work only with cartridges that have a new or reused HP chip, and it uses dynamic security measures to block cartridges using a non-HP chip. Periodic firmware updates will maintain the effectiveness of these measures and block cartridges that previously worked. A reused HP chip enables the use of reused, remanufactured, and refilled cartridges. More at: http://www.hp.com/learn/ds

Highlights

- Fast print speed (33 ppm A4)
- HP Wolf Pro security
- Automatic two-sided printing standard
- High monthly duty cycle (50,000 pages)



Maximum productivity in full color

- Support your business workteam with this compact, high-performing, color printer, ideal for up to 10 users.
- Step up your workflow with blazing fast speed to meet high-demand environments.
- Avoid interruptions with Wi-Fi® that intelligently looks for the most stable connection to stay on-line. 1
- Look professional on every page with high-quality printing, true-to-life colors and sharp details.²

Quickly set up your printers.

- Quickly set up your printers so you can focus more on your business.
- Streamlined set up makes it easy for your team to set up and get back to what matters.

Advance your security with HP Wolf Pro


- Get printer fleet security out of the box. Preconfigured settings mean it's ready when you are.
- Add a layer of security. PIN/pull option authenticates your print jobs only when you're present.
- Strengthen and simplify compliance. This upgrade/solution applies your business policies across the fleet.⁵

Sustainable printing 6,7,8

- Redesigned Original HP TerraJet Cartridge for reduced plastic use and energy consumption when printing. 8,9
- Trim your paper use. Default duplex setting prints on both sides of each page.
- Reduce your footprint. HP Auto-On/Auto-Off technology optimizes printer energy usage and costs.¹⁰
- We take recycling full circle. Our toner cartridges reuse plastic and can be mailed back after use.

Product walkaround

- 1. Automatic 2-sided printing
- 2. Print speeds up to 33 ppm A4, 300-sheet standard paper capacity
- 3. Twist and click speed dial with 4-line LCD
- 4. Walk-up USB for print
- 5. Pre-configured security settings
- 6. HP Smart app for productivity in your hand
- 7. Designed for workteams of up to 10 users
- 8. More true-to-life colors with HP TerraJet Toner
- 9. Dual-band Wi-Fi® with self-heal, and Ethernet



Accessories, Supplies and Support

Supplies	W2200A HP 220A Black Original LaserJet Toner Cartridge (~ 2,000 pages)
	W2200X HP 220X Black Original LaserJet Toner Cartridge (~7,500 pages)
Accessories	28N93A HP Color LaserJet 550 Sheet Paper Tray
	U51Y5E HP 3 year Next Business Day Onsite Service for Color LaserJet Pro 420x U51YGPE - HP 1 year Post Warranty Next Business Day Onsite Service for Color LaserJet Pro 420x

Technical specifications

Section Fig. 1997 Fi		
Miles	Model	HP Color Laserset Pro 4202dw Printer
Page		4RASEF
Procession		Print
March Marc		4-line LCD with rotational dial with push button for menu selection
Resp. May 1997 1997		
1809 1809	Print technology	Laser
March Seath Color (1900 - 19	Print speed	Black (A4, normal): Up to 33 ppm (Colour (A4, normal): Up to 33 ppm : Black (A4, duplex): Up to 29 ipm Colour (A4, duplex): Up to 29 ipm
March 1997 1	First page out	Black (A4, ready): As fast as 9.5 sec Colour (A4, ready): As fast as 10.5 sec; Black (A4, sleep): As fast as 10.2 sec Colour (A4, sleep): As fast as 10.5 sec
Anders data colonies weekenst promote livening and colonies and coloni	Print resolution	Black (best). Up to 600 x 600 dpj; Up to 38,400 x 600 enhanced dpj Colour (best). Up to 600 x 600 dpj ; Technology. HP ImageREt 2400, PANTONE® calibrated
Section Sect	Monthly duty cycle	Up to 50,000 pages A4; Recommended monthly page volume: 750 to 4,000
Framework (1997) The State of the State S	Printer smart software features	Automatic duplex, collation, watermarks, printable forms, quiet mode, HP premium print quality mode, accepts a variety of paper sizes and types
Memory to CATO Interface 150 ACT STATE ACT STA	Standard print languages	HP PCL 6, HP PCL 5e, HP Postscript level 3 emulation, PDF, URF, PWG Raster, Native Office
Section 19 Across 19 Acros	Fonts and typefaces	111 scalable TrueType fonts
Page	Print area	Print margins Top: 4.23 mm, Bottom: 4.23 mm, Left: 4.23 mm, Left: 4.23 mm; Maximum print area: 212 x 352 mm
Security of the Control of the Contr	Duplex printing	Automatic
Section 1997 Se	Fax	
Section Sect	Fax	No
Section Company Comp	Processor speed	1200 MHz
Segontial resource countries Segontial resource countries Segontial resource countries Segontial resource processing Seg	Connectivity	<u> </u>
Support of records in particus DEFENDENCE CONTROL TO PROVIDE THE PROPERTY DEFENDENCE AND PROVIDED AND PROVID	Standard	1 Bluetooth Low Energy, 1 Gigabit Ethernet 10/100/1000 Base-TX network; 1 Hi-Speed USB 2.0 (device); 1 Hi-Speed USB 2.0 (host); 1 Wi-Fi 802.11b[g/n; 1 Wi-Fi 802.3az; 1 Wi-Fi Direct; Walk-up USB; Auto-crossover Ethernet
Section Compatible Proteins Controlled Section Cont	Mobile printing capability	HP Smart App; Apple AirPrint™; Mobile Apps; Mopria™ Certified, Wireless Direct Printing
Memory Month Mon	Supported network protocols	TCP/IP, IPv4, IPv6, Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Web Services Printing, Apple AirPrint ¹⁰⁴ , Mopria, IPP Print; Discovery; SLP, Bonjour, Web Services Discovery; IP Config: IPv4 (DHCP, AutolP, Manual), IPv6 (Stateless Link-Local and via Router, Stateful via DHCPv6), SSL Security and Certificate management; Management: SNMPv1, SNMPv2, SNMPv3, HTTPHTTPS, Syslog
Number of piper Tropic Number of piper Tropic Number of piper Tropic Number of piper Tropic Nedia Space Piper Bood, brockurs, obered, glossy, letterhead, petro, piper, pipe	Network capabilities	Yes, via built-in 10/100/1000Base-Tx Ethernet, Gigabit; Auto-crossover Ethernet; Authentication via 802.1x; 802.11ac (Wi-F15)
Sender of paper tonys Sender 2 - Novirum 3 Notes topo. Notes topo. Open board, boutune, colored, glossy, litterhoad, prices, part progrands, progrands, progrands, progrands, progrands, post conditions, more objects. Gloss See Outune method Simples, Circle 176, 275, 272 172 102 165, 356 mm; Tang 2-588 1-888 mm to 2 16 -356 mm; Colored 176, 275 000 148 to 2 16 -356 mm; Dangels (els trays); 148 x 148 mm to 2 16 x 356 mm. Seed abunding Seed seed of the progrands of the progrands of the progrands of the progrands of the progrand of the progrands of the progr	Memory	Standard: 512 MB NAND Flash, 512 MB DRAM; Maximum: 512 MB DRAM; Maximum: 512 MB NAND Flash, 512 MB DRAM; Maximum: 512 MB DRAM; Maximum: 512 MB NAND Flash, 512 MB NAND Fla
Page from to notine closed gloss interfaced gloss inter	Media handling	<u> </u>
Section Section 1. Section From Conference Surveyor. Page 1.21 for 2.16 is 1.35 mm Page 2.00 is 1.40 mm 2.21 co. 1.40 mm 2.21 co. 1.40 mm 2.20 is 1.40 mm 2.20 is 1.50 mm Page 2.00 is 1.40 mm 2.20 is 1.40 mm Page 2.00 is	Number of paper trays	Standard 2 ;Maximum: 3
Section Functions Section 1.50 gift Policy Section (1.50 gift per post rate), to 9.00 gift PP Octavities of policy live of to 1.50 gift per post rate, to 9.00 gift PP Octavities of policy live of to live group years papers They Species Section (1.50 gift per post rate), to 9.00 gift PP Octavities of policy live of too live group years papers Section 1.50 gift per post rate, to 9.00 gift PP Octavities (1.50 gift per post live group years papers) White control 1.50 gift per post rate of the per post rate of the per post live group years of the per post	Media types	Paper (bond, brochure, colored, glossy, letterhead, photo, plain, preprinted, prepunched, recycled, rough), postcards, labels, envelopes
Models seeglif Models (Sto 16 fils glief fee to 17 fils glief fee to 17 fils glief fee to 16 glief fee to 16 glief fee to 17 fils glief fee to 16 glief fee to 18 glief fee t	Media size	Custom (metric): Simplex: Tray 1: 76.2 x 127 to 216 x 356 mm; Tray 2: 98 x 148 mm to 216 x 356 mm; optional Tray 3: 100 x 148 to 216 x 356 mm; Optional Unit 216 x 356 mm; Optional Tray 3: 100 x 148 to 216 x 356 mm; Optional Unit 216 x 356 mm; Optional Un
report capacity Tray 1: Sheetes SQL envelopes: 5 Tray 2: Sheetes 250, envelopes: 10 Tray 2: Sheetes 250, envelopes: 10 Tray 2: Sheetes 250, envelopes in 10 Tray 2: Sheetes 250, envelopes 250,	Media handling	Standard input: 50-sheet multipurpose tray, 250-sheet input tray Standard output: 150-sheet output bin Optional input: Optional 550-sheet tray
Output Capacity Standard Up to 150 Sheets Envisiopes Up to 20 anvelopes Maximum CU) to 150 Sheets Compatible operating systems Windows 11; Windows Clear OS, Android, CS, Mobile OS, macKD 151 Catalism, macKD 11 Big Sur, macKD 12 Monterey, Lauce Citric Chrome OS Compatible network of Call shallow To Mindows Severy SS, Moved LIMPS Common	Media weight	60 to 163 g/m² (up to 176 g/m² postcards, up to 200 g/m² HP Color laser glossy photo papers)
Output Capacity Standard Up to 150 Sheets Envisiopes Up to 20 anvelopes Maximum CU) to 150 Sheets Compatible operating systems Windows 11; Windows Clear OS, Android, CS, Mobile OS, macKD 151 Catalism, macKD 11 Big Sur, macKD 12 Monterey, Lauce Citric Chrome OS Compatible network of Call shallow To Mindows Severy SS, Moved LIMPS Common	Input capacity	Tray 1: Sheets: 50; envelopes: 5 Tray 2: Sheets: 250; envelopes: 10 Tray 3: Sheets: 550 Maximum: Up to 850 sheets (with Optional 550-sheet tray)
Compatible operating systems Windows 11. Windows 10. Windows Client OS, Android, OS, Mobile OS, marció 11. Dis Catalina, marció 11. Bis Sur, marció 12. Monteres Christo, Chr	Output capacity	Standard: Up to 150 sheets Envelopes: Up to 20 envelopes Maximum: Up to 150 sheets
Minimum system requirements Minimum system requirements see minimum system requireme	Compatible operating systems	Windows 11; Windows 10; Windows Client 05; Android; 105; Mobile 05; mac05 10.15 Catalina; mac05 11 Big Sur; mac05 12 Monterey, Linux; Citric; Chrome 05
Mac 2 dia available hard dive space, internet connection or USB port, internet browner, For additional OS hardware requirements see applic.com; Software included No software solutions are included in the Box only on Inter/Phy.com or Nttp://Pbz.pc.com or Nttp:	Compatible network operating systems	Windows Server; SAP; Novell; UNIX; Citric Linux
HP Web JetAdmin Software; Security Manager, HP SIMP Proxy Agent (Part of HP WebJetAdmin); HP WS Pro Proxy Agent (Part of HP WebJetAdmin); Smart Printer Administrator Resource Kit for HP Smart Universal Print Driver (Driver Configuration; Utility – Driver; Deployment — Printer weight — 1-03 kg	Minimum system requirements	
Dimensions and weight Printer dimensions (W V D x H) Minimum 42 x 427 x 288 mm; Maximum 421 x 636 x 420mm Printer dimensions (W V D x H) Printer dimension	Software included	No software solutions are included in the Box only on http://rp.com or http://123.hp.com
Printer dimensions (W x D x H) Minimum 421 x 427 x 28B mm; Maximum: 421 x 636 x 42Dmm Printer weight -16.33 kg Operating environment Temperature: 10 to 25.2°C Humidity: 30 to 70% RH (non-condensing) Storage conditions Temperature: 20 to 40°C Acoustice Acoustice Acoustic power emissions: 6.2 8(A) Acoustic pressure emissions: 51 dB(A) Requirements: 220-volt input voltage: 220 to 240 VAC (+-1 10%), 50/604z (+-3 Hz); Consumption: 590 wasts (active printing), 17 wasts (sleep), 0.7 wasts (sleep),	Printer management	HP Web JetAdmin Software; Security Manager; HP SNMP Proxy Agent (Part of HP WebJetAdmin); HP WS Pro Proxy Agent (Part of HP WebJetAdmin); Smart Printer Administrator Resource Kit for HP Smart Universal Print Driver (Driver Configuration; Utility - Driver; Deployment Utility -
Printer weight -16.33 kg Operating environment Temperature: 20 to 32.5°C Humidity: 30 to 70% RH (non-condensing) Storage conditions Temperature: 20 to 40°C Acoustic® Acoustic power emissions: 6.2 BiAl Acoustic pressure emissions: 51 dBiAl Acoustic® Acoustic power emissions: 6.2 BiAl Acoustic pressure emissions: 51 dBiAl Requirements: 220-obj timpst voltage: 220 to 240 WC (*1 10%), 50/60Hz (*-13 Hz); Consumption: 580 waits feeting point voltage: 220 to 240 WC (*-1 10%), 50/60Hz (*-13 Hz); Consumption: 580 waits feeting point voltage: 220 to 240 WC (*-1 10%), 50/60Hz (*-13 Hz); Consumption: 580 waits feeting point voltage: 220 to 240 WC (*-1 10%), 50/60Hz (*-13 Hz); Consumption: 580 waits feeting point voltage: 220 to 240 WC (*-1 10%), 50/60Hz (*-13 Hz); Consumption: 580 waits feeting point voltage: 220 to 240 WC (*-1 10%), 50/60Hz (*-13 Hz); Consumption: 580 waits feeting point voltage: 220 to 240 WC (*-1 10%), 50/60Hz (*-13 Hz); Consumption: 580 waits feeting point voltage: 220 to 240 WC (*-1 10%), 50/60Hz (*-13 Hz); Consumption: 580 waits feeting point voltage: 220 to 240 WC (*-1 10%), 50/60Hz (*-13 Hz); Consumption: 580 waits feeting point voltage: 220 to 240 WC (*-1 10%), 50/60Hz (*-13 Hz); Consumption: 580 waits feeting point voltage: 220 to 240 WC (*-1 10%), 50/60Hz (*-13 Hz); Consumption: 580 waits feeting point voltage: 220 to 240 WC (*-1 10%), 50/60Hz (*-13 Hz); Consumption: 580 waits feeting point voltage: 220 to 240 WC (*-1 10%), 50/60Hz (*-13 Hz); Consumption: 580 waits feeting point voltage: 220 to 240 WC (*-1 10%), 50/60Hz (*-13 Hz); Consumption: 580 waits feeting point voltage: 220 to 240 WC (*-1 10%), 50/60Hz (*-1 10%)	Dimensions and weight	1
Temperature 10 to 32.5°C Humidity. 30 to 70% RH (non-condensing)	Printer dimensions (W x D x H)	Minimum 421 x 427 x 288 mm; Maximum: 421 x 636 x 420mm
Temperature -20 to 40°C Acoustic power emissions 6.2 B(A) Acoustic pressure emissions 51 dB(A)	Printer weight	~16.33 kg
Temperature -20 to 40°C Acoustic power emissions 6.2 B(A) Acoustic pressure emissions 51 dB(A)	Operating environment	Temperature: 10 to 32.5°C Humidity: 30 to 70% RH (non-condensing)
Acoustic power emissions 6.2 E/Al Acoustic pressure emissions 5.1 del(A) Requirements 220-voit input voitage 220 to 240 UAC (1/- 10%), 50/60Hz (1/- 31%). Requirements 220-voit input voitage 220 to 240 UAC (1/- 10%), 50/60Hz (1/- 31%). Requirements 220-voit input voitage 220 to 240 UAC (1/- 10%), 50/60Hz (1/- 31%). Requirements 220-voit input voitage 220 to 240 UAC (1/- 10%), 50/60Hz (1/- 31%). Requirements 220-voit input voitage 220 to 240 UAC (1/- 10%), 50/60Hz (1/- 31%). Requirements 220-voit input voitage 220 to 240 UAC (1/- 10%), 50/60Hz (1/- 31%). Requirements 220-voit input voitage 220 to 240 UAC (1/- 10%), 50/60Hz (1/- 31%). Requirements 220-voit input voitage 220 to 240 UAC (1/- 31%). Requirements		
Requirements: 220-volt input voltage: 220 to 240 W.C. (+/- 10%), 50/60Hz (-/- 3 Hz); Consumption: 580 watts factive printing), 17 watts (ready), 0.7 watts (bleep), 0.7 watts (HP auto-off/watu-on), 0.07 watts (auto-off/manual-on), 0.07 watts (off); Typical Electricity Consumption: 580 watts factive printing), 17 watts (ready), 0.7 watts (bleep), 0.7 watts (bleep), 0.7 watts (HP auto-off/watu-on), 0.07 watts (auto-off/manual-on), 0.07 watts (off); Typical Electricity Consumption: 580 watts (bleep), 0.7 w		Suppose Control of Con
Energy savings feature technology HP Auto-On/Auto-Off Technology, Instant-on Technology LL(LI, US/Canada); PCM (Australia); TUM and GS Mark (Germany); Department of Industrial Standards of Cambodia; Bureau of Standards. Metrology and Inspection Ministry of Economic Affairs - BSMI (Talwan); Certificate of China Compulsory Product Certification - CCC (China); Bureau of Industrial Standards. See Special Post of Standards. Metrology and Inspection Ministry of Economic Affairs - BSMI (Talwan); Certificate of China Compulsory Product Certification - CCC (China); Bureau of Industrial Standards. See Special Standards. Metrology and Inspection Ministry of Economic Affairs - BSMI (Talwan); Certificate of China Compulsory Product Certification - CCC (China); Bureau of Industrial Standards. See Special Standards. Metrology and Inspection Ministry of Economic Affairs - BSMI (Talwan); Certificate of China Compulsory Product Certification - CCC (China); Bureau of Industrial Standards. See Special Standards. Metrology and Inspection Ministry of Economic Affairs - BSMI (Talwan); Certificate of China Compulsory Product Certification - CCC (China); Bureau of Industrial Standards. See Special Standards. Metrology and Inspection Ministry of Economic Affairs - BSMI (Talwan); Certificate of China Compulsory Product Certification - CCC (China); Bureau of Industrial Standards. See Special Standards. Metrology and Inspection Ministry of Economic Affairs - BSMI (Talwan); Certificate of China Compulsory Product Certification - CCC (China); Bureau of Industrial Standards. See Special St		Requirements: 220-voit input voltage: 220 to 240 VAC (+/- 10%), 50/60Hz (+/- 3 Hz); Consumption: 980 waits factive printing), 17 waits (seady), 0.7 waits (HP auto-off/auto-on), 0.07 waits (auto-off/manual-on), 0.07 waits (off); Typical Electricity Consumption (TEO: 0.37 Volk/InVeste (Blue Angel); 0.395 Volk/InVest (Elengy Star 3.0);
ULYLIL (US/Canada); RCM (Australia); TUV and GS Mark (Germany); Department of Industrial Standards of Camboda; Bureau of Standards, Metrology and Inspection Ministry of Economic Affairs - BSMI (Talwan); Certificate of China Compulsory Product Certification - CCC (China); Bureau of Indian Standards - BIS Registration (India); PSB (Singapore); Eastern European country approvals; Celebration (Ditter Standards) (PSB 2502) (Entraliance) (Lass B. CSP 3202) (Entral	Energy savings feature technology	
Country of origin Made in Vetnam What's in the box ³ #ARBEF HP Color Laser let Pro 4202/dw Printer: 4 preinstalled introductory HP Laser let Toner Cartridges (Black: 1,200 pages; Cyan, Magenta, Yellow: 1,000 pages); In-box documentation (Reference guide, Setup Card), Regulatory Ryer; HP printer software is available at https://www.hp.com/support; Power cord; USR cable. Warranky One-year Bench/Deport Repair warranty. Warranky and support options in your region. (warrank)	-	UL/LUL (US/Canada); RCM (Australia); TUV and GS Mark (Germany); Department of Industrial Standards of Cambodia; Bureau of Standards, Metrology and Inspection Ministry of Economic Affairs - 85M (Talwan); Certificate of China Compulsory Product Certification - CCC (China); Bureau of Indan Standards - 818 Registration (India); PSB (Singapore); Eastern European country approvals; CE Marking; Other Safety & EMC Certification approvals as required by individual countries. Electromagnetic emission standards (SPR 92.2200 file (International) (Jess 6, 187.82.2015 Class 8 + A11.2020, CISPR 35.2016 (International) (FN 55035.2017 + A11.2020, EN IEC 61000-3-2.2019, EN 61000-3-3.2013+A1.2019 + A2.2021, FCC 47 CFR Part 1 S Class B, (ES-003, Issue 7 Class B. Other EMC approvals as required by individual countries. If ECO Declaration Blue Angel compilant* (Yes, Blue Angel DE-UZ 219—only ensured when using Original PP supplies Telecom compilance* (Selecon Wireless; FCC 47 CFR Part 1 S Subpart C & E.) (RSS-Gen Issue 4/RSS 247 Issue 2, 2017 & RSS 102 Issue 5, 2015; EN 301 489-1 V.2.2.3; EN 301 489-1
What's in the box ³ 4888F HP Cofor Laser Jet Pro 4202dw Printer, 4 preinstalled introductory HP Laser Jet Toner Cartridges (Black: 1,200 pages; Cyan, Magenta, Vellow: 1,000 pages), in-box documentation (Reference guide, Setup Card), Regulatory (hyer; HP printer software is available at https://www.hp.com/support power cord; USR cable. Water about One-year Bench/Deport Regular warranty. Water avarranty. Water	Country of origin	
One-year Bench/Depot Repair warranty. Warranty and support options vary by product, country and local legal requirements. Contact your Contractual Vendor or go to https://www.hp.com/support to learn about HP award winning service and support options in your region. (warranty code 4E; warranty ID A033)		48ABBF HP Color Laser Jet Pro 4202dw Printer; 4 preinstalled introductory HP Laser Jet Toner Cartridges (Black: 1,200 pages; Cyan, Magenta, Yellow: 1,000 pages), In-box documentation (Reference guide, Setup Card), Regulatory flyer; HP printer software is available at
	Warranty	One-year Bench/Depot Repair warrantly. Warrantly and support options vary by product, country and local legal requirements. Contact your Contractual Vendor or go to https://www.hp.com/support to learn about HP award winning service and support options in your region. (warrant code 4E; warrantly ID A033)

Footnotes

- 1 Wireless operations are compatible with 2.4 GHz and 5.0 GHz operations only. Learn more at hp.com/go/mobileprinting. Wi-Fi is a registered trademark of Wi-Fi Alliance®. Supports both 5.0 GHz and 2.4 GHz using up to 12 nonoverlapping channels vs only 3 non-overlapping channels for 2.4 GHz only. Supports 5.0 GHz band (up to 150 mbps) vs 2.4 GHz band (up to 72.2 mbps). Internet access required and must be purchased separately ² Standard print mode for HP Color LaserJet Pro series with HP TerraJet technology compared to predecessors. See hp.com/TerraJetcolors.
- ³ HP Web Jetadmin is available for download at no additional charge at hp.com/go/webjetadmin.
- ⁵ HP JetAdvantage Security Manager must be purchased separately. To learn more, please visit hp.com/go/securitymanager
- 6 HP calculations based on ENERGY STAR® normalized TEC data comparing HP Laser Jet 200-500 series printers at launch. See hp.com/ecosmart.

 7 Internet access required and must be purchased separately. Wireless operations are compatible with 2.4 GHz and 5.0 GHz operations only. Supports both 5.0 GHz and 2.4 GHz using up to 112 non-overlapping channels vs. only 3 non-overlapping channels for 2.4 GHz only. Supports 5.0 GHz band (up to 150 mbps) v. 2.4 GHz band (up to 72.2 mbps). Learn more at: www.hp.com/go/mobileprinting
- B Plastic reduction calculated per page based on cartridge weight in grams and stated yield in HP TerraJet Cartridges compared to predecessors. See hp.com/TerraJet/plasticreductions.

 HP Calculations based on Energy Star® normalized TEC data in HP TerraJet Cartridges compared to predecessors. See hp.com/TerraJetenergysaving.
- ¹⁰ HP Auto-On/Auto-Off Technology capabilities subject to printer and settings; may require a firmware upgrade.

Technical specifications disclaimers

- 1 EPEAT® registered where applicable, EPEAT registration varies by country. See http://www.epeat.net for registration status by country. Please be aware that HP Laser Jet Pro 4201 and MFP 4301 series products are ENERGY STAR 3.0 certified in the US and the functionally equivalent HP LaserJet Pro 4202 and MFP 4302 series meet ecolabel energy efficiency limits.
- ² Typical Electricity Consumption (TEC) rating represents the typical electricity consumed by a product during 1 week, measured in kilowatt-hours (kWh). ENERGY STAR TEC data based on 115V test result; Blue Angel TEC based on 230V test result.
- ³ For yield information on the cartridge(s) included with your printer, see http://www.hp.com/go/toneryield. Yield values measured in accordance with ISO/IEC 19798 and continuous printing. Actual yields vary considerably based on images printed and other factors.

 ⁵ Values based on 115V test results based on Energy Star test method.
- ⁶ Configuration tested: base model, simplex printing, A4 paper at an average of 34 ppm.
- ⁷ Measured using ISO 24734 Feature Test, A5 Landscape Feed. Speed may vary based on content, PC, media orientation, and media type.

© Copyright 2023 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

