HP LaserJet Enterprise MFP M725 series



Ideal for large workgroups who need a high-performance, reliable MFP that prints on a range of paper sizes up to A3, and helps speed work with robust scanning capabilities, a convenient colour touchscreen and powerful manageability features.





HP LaserJet Enterprise 700 MFP M725dn



HP LaserJet Enterprise 700 MFP M725f



HP LaserJet Enterprise 700 MFP M725z



HP LaserJet Enterprise 700 MFP M725z+

Empower teams to do more – print, scan, copy and fax on paper sizes up to A3 – from a desktop MFP

- Stay focused on work paper capacity up to 4,600 sheets and high-capacity cartridges limit interruptions.
- Get impressive document quality with near edge-to-edge printing and a convenient, built-in stapler
- Print what you need, even on the go from your smartphone or tablet – using HP ePrint⁵ or Apple Airprint[™].6

Quicken your business pace.

- Set a swift pace use this powerful MFP to keep your work moving. Save time and make your job easier, using HP Quick Sets.
- Efficiently capture the right content: automatically remove blank pages, preview, edit and control jobs on the large colour touchscreen.
- Incorporate paper documents into digital workflows easily send scans to fax³, email, network folders or USB. Print right from a memory device via the USB port.

Simplify fleet management and safeguard devices using world-class tools.

- Monitor your devices with industry-leading tools, including HP Web Jetadmin.⁷ Help protect data both in transit and at rest.
- Enhance security with PIN printing. Add safeguards via the hardware integration pocket. Integrate tomorrow's solutions with ease.
- Add security tools such as card and badge readers via the hardware integration pocket.⁸

- Reduce energy use with Instant-on Technology.
- Reduce paper use by up to 50%, using automatic two-sided printing. Reduce waste scan, store and distribute documents digitally.

ENERGY STAR® aualified ed with products that use traditional fusing

- ¹ Maximum paper capacity of 4,600 sheets; requires the purchase of optional paper tray accessories.
 ² High-capacity cartridges are optional for the HP LaserJet Enterprise 700 MFP Series M725.
 ³ Fax capabilities are available with an optional fax card on the HP LaserJet Enterprise MFP M725dn.
 ⁴ In-line stapler is not available on the HP LaserJet Enterprise MFP M725dn or M725f.

 - ⁵ Requires and internet control of the time base of the printer and HP ePrint account registration (for a list of eligible printers, supported documents and image types and other HP ePrint details, see www.hpconnected.com). Mobile devices require Internet connection and email capability. May require wireless access point. Separately purchased data plans or usage fees may apply. Print times and connection speeds may vary. Some HP LaserJet printers may require firmware
- upgrades upports the following devices running iOS 4.2 or later: iPad®, iPad® 2, iPhone® (3GS or later) or iPod touch® (3rd generation or later). Works with HP's AirPrint-enabled printers and requires the printer be connected to the same network as your iOS device. Wireless performance is dependent upon physical environment and distance from the access point. AirPrint, the AirPrint Logo, iPad, iPhone and iPod touch are trademarks of Apple® Inc., registered in the U.S. and other countries.

⁷ HP Web Jetadmin is free and can be downloaded at www.hp.com/go/webjetadmin.
⁸ Solutions deployed through the hardware integration pocket may require additional purchase.

Product walkaround

- HP LaserJet Enterprise 700 color MFP M775z+:
- 1. 100-sheet automatic document feeder
- 2. Intuitive 20.3 cm (8-inch) pivoting light touch SVGA colour control
- panel with FutureSmart firmware and scan preview
- 3. Hardware integration pocket for solution integration
- 4. Easy-access USB port to save and print files directly
- 5. In-line stapler/stacker for stapling up to 30-pages and a 500-sheet output trav
- 6. Standard 250-sheet stacker output bin
- 7. Front door allows convenient access to print cartridge
- Built-in automatic two-sided printing
 2 x 250-sheet input tray 2 and tray 3
- 10. 3,500-sheet high-capacity feeder with cabinet for a 4,100-sheet total input capacity
- 11. 100-sheet multipurpose tray 1 handles up to 100 pages
- 12. Fax port
- 13. 800 MHz processor, 1 GB standard memory (Expandable to 1,5 GB)
- 14. HP High Performance Encrypted Hard Drive
- 15. Hi-Speed USB 2.0 printing port
- 16. HP Jetdirect Gigabit Ethernet print server





Series at a glance



HP LaserJet Enterprise 700 MFP M725dn

- Print, copy, scan, digital send
- print/copy speed of up to 41 ppm
- up to 1200 x 1200 dpi
- 1024 MB RAM
- 800 MHz processor
- 1 HP High Performance Secure Hard Disk
- 1 Hi-Speed USB 2.0 Host
- 1 Hi-Speed USB 2.0 Device
- 2 Internal USB 2.0 Host
- 1 Gigabit Ethernet 10/100/1000Base-T
- 1 Foreign Interface (FIH)
- 1 Hardware Integration Pocket
- 100-sheet multipurpose tray
- 2 x 250-sheet input trays
- 250-page output tray
- 100-sheet Automatic Document Feeder (ADF)



HP LaserJet Enterprise 700 MFP M725f

- As HP LaserJet Enterprise MFP M725dn, with built-in fax
 - 1 x 500-sheet tray
- 1 x 500-sheet feeder, cabinet and stand



HP LaserJet Enterprise 700 MFP

- As HP LaserJet Enterprise MFP M725dn, with built-in fax
- 500-sheet inline stapler/stacker • 3 x 500-sheet paper feeder and stand.




HP LaserJet Enterprise 700 MFP M725z+

- As HP LaserJet Enterprise MFP M725dn, with built-in fax
- 500-sheet inline stapler/stacker
- 3500-sheet feeder and stand.
- M725z

Recommended accessories





growing work groups with simple, robust paper input accessories that enable media versatility, from A5, A4, legal and up to A3, and allow longer printing without reloading paper.



HP LaserJet 1x500-sheet

Support the productivity of growing work groups with

simple, robust paper input

longer printing without

reloading paper.

accessories that enable media

versatility, from A5, A4, legal and up to A3, and allow

Feeder with Cabinet and Stand

CF243A



CF242A

HP LaserJet 3x500-sheet Feeder and Stand HP LaserJet 3x500-sheet Paper Trays mean you spend less time loading paper and more time printing. Meet the printing needs of a high-volume printing environment with the 3x500-sheet paper feeder and stand.



CF245A HP LaserJet 3500-sheet High-capacity Input Tray Feeder and Stand

Support the productivity of growing work groups with this high-performance, robust input feeder and stand. The additional 3,500-sheet paper capacity allows users to spend more time focusing on business and less time reloading paper.



C8091A HP Staple Cartridge Refill

HP Staple Cartridge Refills give you more for your money and ensure you don't have to worry about frequent cartridge replacement. Each refill contains 5000 staples.

CC487A

HP LaserJet MFP Analog Fax Accessory 500 Improve workteam productivity and make information sharing more efficient. Simply add embedded analog fax functionality to your HP LaserJet MFP¹ to send and receive documents quickly, easily and securely.

Ordering information



HP LaserJet Enterprise 700 MFP M725dn (CF066A)

HP LaserJet Enterprise MFP M725dn; HP Black LaserJet Toner Cartridge (~10,000 pages); Printer documentation and software on CD-ROM; Installation guide, Support flyer, Warranty card; Power cord; 2x250-sheet trays.



HP LaserJet Enterprise 700 MFP M725f (CF067A)

HP LaserJet Enterprise MFP M725f; HP Black LaserJet Toner Cartridge (~10,000 pages); Printer documentation and software on CD-ROM; Installation guide, Support flyer, Warranty card; Power cord; Fax cable; 2x250-sheet trays; 1x500 sheet feeder; cabinet and stand; Built-in fax.



HP LaserJet Enterprise 700 MFP M725z (CF068A)

HP LaserJet Enterprise MFP M725z; HP Black LaserJet Toner Cartridge (~10,000 pages); Printer documentation and software on CD-ROM; Installation guide, Support flyer, Warranty card; Power cord; Fax cable; 2x250-sheet trays; 3x500-sheet Paper feeder and stand; 500-sheet inline Stapler/Stacker; Built-in fax.



HP LaserJet Enterprise 700 MFP M725z+ (CF069A)

HP LaserJet Enterprise MFP M725z+; HP Black LaserJet Toner Cartridge (~10,000 pages); Printer documentation and software on CD-ROM; Installation guide, Support flyer, Warranty card; Power cord; Fax cable; 2x250-sheet trays; 1 x 3500-sheet Feeder and Stand; 500-sheet inline Stapler/Stacker; Built-in fax

Accessories, Supplies and Support

Accessories	
CF239A	HP LaserJet 500-sheet Feeder and Tray
CF243A	HP LaserJet 1x500-sheet Feeder with Cabinet and Stanc
CF242A	HP LaserJet 3x500-sheet Feeder and Stand
CF245A	HP LaserJet 3500-sheet High-capacity Input Tray Feeder and Stand
C8091A	HP Staple Cartridge Refil
CC487A	HP LaserJet MFP Analog Fax Accessory 500
L2718A	HP 100 ADF Roller Replacement Ki
Connectivity	,
J8021A	HP Jetdirect ew2500 802.11b/g Wireless Print Serve
J8026A	HP Jetdirect 2700w USB Wireless Print Server

Supplies CF214A

HP 14A Black Laserlet Toner Cartridge Average cartridge yields 10,000 standard pages. Declared yield based on ISO/IEC 19752 and continuous printing. HP 14X Black LaserJet Toner Cartridge HP 14X Black LaserJet Toner Cartridge Average cartridge yields 17,500 standard pages. Declared yield based on ISO/IEC 19752 and continuous printing. CF214X CF254A HP Laserlet CF254A 220V Maintenance/Fuser Kit 200,000 pages

Service & support UTA05E - HP 3 year Next Business Day LaserJet M725 MFP Hardware

Support U7A06E - HP 4 year Next Business Day LaserJet M725 MFP Hardware

Support U7A07E - HP 5 year Next Business Day LaserJet M725 MFP Hardware Support U7A09E - HP 3 year 4 hour 13x5 LaserJet M725 MFP Hardware Support

U7Y72PE - HP 1 year Post Warranty Next Business Day LaserJet M725 MFP Hardware Support

MPP Hardware Support U7Y73PE - HP 2 year Post Warranty Next Business Day LaserJet M725 MPP Hardware Support U7Y75PE - HP 1 year Post Warranty 4 hour 13x5 LaserJet M725 MFP Hardware Support

For a complete list of supplies, accessories and services, please refer to http://www.hp.com For workflow, device management and other solutions, please visit the Global Solutions catalog: www.hp.com/go/gsc

Declared yield value in accordance with ISO/IEC 19752. Actual yields vary considerably based on images printed and other factors. For more information, visit hp.com/go/learnaboutsupplies.

Count on dependable support to create the best image possible. We can help you enhance your printing and imaging environment, protect your IT investment, and grov your business—with expert support that's affordable, personal, and tailored to your needs through HP Care Pack Services.

Technical specifications

Print technology Print speed							
Print speed		Laser					
	First page out: black: As fast as 10 se	ec					
		A4 black: Up to 41 ppm Exact speed varies depending on the system configuration, software application, driver and document complexity.					
				ending on the system configuration, software application,			
	driver, and document complexity.						
Processor	800 MHz						
Memory	1 GB. Expandable to 1.5 GB through 512 MB industry-standard DIMM						
Hard disk	Standard, embedded HP High-Performance Secure Hard Disk, minimum 320 GB; AES 256 hardware encryption or greater; Secure erase capabilities (Secure File Erase-Temporary Job Files, Secure Erase-Jo Data, Secure ATA Erase-Disk)						
Print	Data, secure AIX Erase-Disk) Quality HP ProRes 1200 (1200 x 1200 dpi), HP FastRes 1200 (1200 dpi quality), HP Resolution Enhancement technology, 600 x 600 dpi, 300 x300 dpi						
	Resolution	Black: Up to 1200 x 1200 dpi	1200 (1200 upi quality), Til Resolution Enhancement	eciniology, 000 x 000 dpi, 000 x 000 dpi			
	Printer languages	HP PCL 6; HP PCL 5e; HP Postscript Level 3 emul					
	Typetaces/tonts	Typefaces/fonts 105 internal TrueType fonts scalable in HP PCL, 92 internal scalable fonts in HP Postscript Level 3 emulation (Euro symbol builtin); 1 internal Unicode Fonts (Andole Mono Victor Director Control Con					
	WorldType); 2 Internal Windows Vista 8 Fonts (Calibri, Cambria); additional font solutions available via third-party flash memory cards; HP LaserJet Fonts and IPDS Emulation available at hp.com/go/laserjetfonts						
	Duty cycle (monthly, A4)	rty cycle (monthly, A4) Up to 200,000 pages					
	Recommended monthly page volume	volume 5000 to 20,000					
	Print margins (mm)	Top: 2 mm. Left: 2 mm. Right: 2 mm. Bottom: 2 mm 308 x 465.9 mm					
Fax							
τux	M725dn: Optional; M725f: Yes; M725z: Yes; M725z+: Yes; Modem speed 33.6 kbps						
			5/EC (Annex II) with CE Marking (Europe); FCC Part 68;	other Telecom approvals as required by individual countries			
	Fax memory	Up to 100 pages					
		Standard: 204 x 98 dpi. Fine: 204 x 196 dpi, 256 levels of grey. Superfine: 300 x 300 dpi, 256 levels of grey. Photo: 300 x 300 dpi (400 x 400 dpi for received faxes					
		only) k dialing Up to 100 numbers (each can contain 100 numbers)					
Digital sending							
Scan		(.prn, .pcl, .cht)					
	Features	Features Standard: Scan to E-mail; Save to Network Folder; Save to USB drive; Send to FTP; Send to LAN Fax; Send to Internet Fax; Local Address Book; SMTP over SSL. Optional:					
		Optional via HP Digital Sending Software (HP DSS); Send to folder; Send to workflow; Send to printer; Authentication; Digital fax (send to LAN, Internet); OCR; Local					
		Address Book	laue)				
scan		Up to 50 ppm (black and white), up to 30 ppm (colour) Up to 20 ipm (black and white), up to 15 ipm (colour)					
		Flatbed, ADF. Colour scanning:Yes					
		Optical: Up to 600 dpi					
		24-bit 256					
Сору		A4 black: Up to 41 cpm					
F)		600 x 600 dpi					
		Up to 9999 copies					
		25 to 400%		<u></u>			
Media handling		Capacity sheets: 100; envelopes: 10; labels: 100;	Weight 60 to 199 g/m ²	Size A4; A5; B4 (JIS); B5 (JIS); 76.2 x 127 to 312 x 469.9			
		transparencies: 100; postcards: 10	6616 177 g/ III	mm			
	Tray 2 s	sheets: 250	60 to 120 g/m ²	A4; A5;, B4 (JIS); B5 (JIS); 148 x 210 to 297 x 363			
	Tray 3		60 to 120 g/m²	mm A3; A4; A5; B4 (JIS); B5 (JIS); 148 x 210 to 297 x			
	nuy 5		0010 120 g/m	431 mm			
	ADF	sheets: 100	45 to 199 g/m ²	A3; A4; A4-R; A5; A6; B4 (JIS); B5 (JIS); B6 (JIS); 10			
	Output	Envelance: Units 50 anvelance		x 15 cm; 13 x 18 cm			
	Duplex printing: Automatic (standard)	Output: Envelopes: Up to 50 envelopes Durlex priorition: Automatic (strandard)					
Media types			per), bond, cardstock, envelope, labels, transparency, v	ellum			
Interface and connectivity							
,	Optional: HP Jetdirect ew2500 802.1	Standard: 2 Hi-Speed USB 2.0 Host; 1 Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/1000T network; 1 Foreign Interface; 1 Hardware Integration Pocket; 2 Internal USB Host Optional: HP Jetdirect ew2500 802.11b/g Wireless Print Server J8021A; HP Jetdirect 2700w USB Wireless Print Server J8026A					
Operating systems compatibility				erver 2008 R2 (64-bit), Windows Server 2012 (64-bit); Mac			
		OS X v10.6, OS X Lion, OS X Mountain Lion; For the latest operating system support see: Citrix® and Windows Terminal Services (hp.com/go/upd); Novell® (novell.com/iprint); Linux (hplip.net); UNIX®					
	(hp.com/go/unix, hp.com/go/unixmodelscripts, hp.com/go/jetdirectunix_software); SAP device types (hp.com/go/sap/drivers, hp.com/go/sap/print); HP ePrint Mobile Driver (hp.com/go/eprintmobiledriver). Recent printer drivers for all supported operating systems are available at hp.com/go/ljMFPM725_software						
	(hp.com/go/eprintmobiledriver) Rec	(in)comy go/epinimicolitearier), excert primer arrens for an supported operating systems are available an in)com/ go/ipinr/wr/25_software Windows 8, Windows 7, Windows Server 2003 (SPI +), Windows Server 2008, Windows Server 2008 R2, Windows Server 2012 (64-bit); 200 MB available hard					
				22 Windows Server 2012 (64-bit): 200 MB available bard			
Minimum system requirements	Windows 8, Windows 7, Windows V	/ista, Windows XP (SP2+), Windows Server 2003 (SP1+), Windows Server 2008, Windows Server 2008 I	R2, Windows Server 2012 (64-bit); 200 MB available hard GB available hard disk space; operating system compatible			
	Windows 8, Windows 7, Windows V disk space; operating system compati	/ista, Windows XP (SP2+), Windows Server 2003 (SP1+), Windows Server 2008, Windows Server 2008 I				
Minimum system requirements Standard software	Windows 8, Windows 7, Windows V disk space; operating system compati hardware system requirements, CD-RC Windows Installer, HP PCL 6 discrete	fista, Windows XP (SP2+), Windows Server 2003 (ible hardware system requirements, see microsoft.cc DM/DVD-ROM or Internet, see apple.com driver, Mac Software Link to Web (Postscript emula	SP1+), Windows Server 2008, Windows Server 2008 I m. Mac OS X 10.6, OS X Lion, OS X Mountain Lion; 1 tion driver & Installer on Web), Note: No Mac Software	GB available hard disk space; operating system compatible inbox			
Minimum system requirements Standard software Control panel	Windows 8, Windows 7, Windows V disk space; operating system compati hardware system requirements, CD-RC Windows Installer, HP PCL 6 discrete 20.3 cm touchscreen, LCD (colour gro	fista, Windows XP (SP2+), Windows Server 2003 (ible hardware system requirements, see microsoft.cc DM/DVD-ROM or Internet, see apple.com driver, Mac Software Link to Web (Postscript emula aphics); rotating (adjustable angle) display; illuminc	SP1+), Windows Server 2008, Windows Server 2008 I m. Mac OS X 10.6, OS X Lion, OS X Mountain Lion; 1 tion driver & Installer on Web), Note: No Mac Software ted Home button (for quick return to the Home menu); E	GB available hard disk space; operating system compatible inbox asy Access USB; Hardware Integration Pocket			
Minimum system requirements Standard software	Windows 8, Windows 7, Windows V disk space, operating system compati- hardware system requirements, CD-RC Windows Installer, HP PCL 6 discrete 20.3 cm touchscreen, LCD (colour gra Requirements:Input voltage: 220 to 2	(sta, Windows XP (SP2+), Windows Server 2003 (ible hardware system requirements, see microsoft.cc DM/DVD-ROM or Internet, see apple.com driver, Mac Software Link to Web (Postscript emula aphics); rotating (adjustable angle) display; Illuminc 40 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz). Consum	SP1+), Windows Server 2008, Windows Server 2008 m. Mac OS X 10.6, OS X Lion, OS X Mountain Lion; 1 tion driver & Installer on Web), Note: No Mac Software teld Home button (for quick return to the Home menu); E ption:890 watts (active print/copy), 39 watts (ready), 6	GB available hard disk space; operating system compatible inbox asy Access USB; Hardware Integration Pocket 5 watts (sleep), 0.3 watts (off). Typical Electricity Consumption			
Minimum system requirements Standard software Control panel	Windows 8, Windows 7, Windows V disk space; operating system compati- hardware system requirements, CD-RC Windows Installer, HP PCL 6 discrete 20.3 cm touchscreen, ICD (colour gr Requirements:Input voltage: 220 to 2 (TEC): 4.39 KWh/Week. Power requi	fista, Windows XP (SP2+), Windows Server 2003 (bible hardware system requirements, see microsoft.cc M/DVD-ROM or Internet, see apple.com driver, Mac Software Link to Web (Postscript emula aphics); rotating (adjustable angle) display; illominc 40 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz). Consum irements are based on the country/region where the second second second second second second second second second 40 VAC (+/- 10%).	SP1+), Windows Server 2008, Windows Server 2008 m. Mac OS X 10.6, OS X Lion, OS X Mountain Lion; 1 tion driver & Installer on Web), Note: No Mac Software teld Home button (for quick return to the Home menu); E ption:890 watts (active print/copy), 39 watts (ready), 6	GB available hard disk space; operating system compatible inbox asy Access USB; Hardware Integration Pocket			
Minimum system requirements Standard software Control panel Power	Windows 8, Windows 7, Windows V disk space; operating system compati- hardware system requirements, CD-R Windows Installer, HP PCL 6 discrete 20.3 cm touchscreen, LCD (colour gra Requirements:Input voltage: 220 to 2. (TEC): 4.39 kWh/Week. Power requi subject to change, see hp.com/suppc	fista, Windows XP (SP2+), Windows Server 2003 (bible hardware system requirements, see microsoft.cc DM/DVDROM or Internet, see apple.com driver, Mac Software Link to Web (Postscript emula aphics); rotating (adjustable angle) display; illuminc 40 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz). Consum irements are based on the country/region where the oft for current information.	SP1+), Windows Server 2008, Windows Server 2008 I m. Mac OS X 10.6, OS X Lion, OS X Mountain Lion; 1 tion driver & Installer on Web), Note: No Mac Software ted Home button (for quick return to the Home menu); E ption:890 watts (active print/copy), 39 watts (ready), 6 a printer is sold. Do not convert operating voltages; this	GB available hard disk space; operating system compatible inbox asy Access USB; Hardware Integration Pocket 5 watts (sleep), 0.3 watts (off). Typical Electricity Consumption will damage the printer and void the product warranty. Values			
Minimum system requirements Standard software Control panel	Windows 8, Windows 7, Windows V disk space, operating system compati- hardware system requirements, CD-RC Windows Installer, HP PCL 6 discrete 20.3 cm touchscreen, LCD (colour gra Requirements:Input voltage: 220 to 2 (TEC): 4.39 kWh/Week. Power requi subject to change, see hp.com/suppc Out of package: M725dn: 614 x 645	fista, Windows XP (SP2+), Windows Server 2003 (bible hardware system requirements, see microsoft.cc DM/DVDROM or Internet, see apple.com driver, Mac Software Link to Web (Postscript emula aphics); rotating (adjustable angle) display; illuminc 40 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz). Consum irements are based on the country/region where the oft for current information.	SP1+), Windows Server 2008, Windows Server 2008 I m. Mac OS X 10.6, OS X Lion, OS X Mountain Lion; 1 tion driver & Installer on Web), Note: No Mac Software ted Home button (for quick return to the Home menu); E ption:890 watts (active print/copy), 39 watts (ready), 6 a printer is sold. Do not convert operating voltages; this	GB available hard disk space; operating system compatible inbox asy Access USB; Hardware Integration Pocket 5 watts (sleep), 0.3 watts (off). Typical Electricity Consumption will damage the printer and void the product warranty. Values			
Minimum system requirements Standard software Control panel Power	Windows 8, Windows 7, Windows V disk space, operating system compati- hardware system requirements, CD-R Windows Installer, HP PCL 6 discrete 20.3 cm touchscreen, ICD (colour gr Requirements: Input voltage: 220 to 2: (TEC): 4.39 kWh/Week. Power requi subject to change, see hp.com/suppo Out of package: M725dn : 614 x 645 760 x 1522 mm; M725z : 856 x 760	fista, Windows XP (SP2+), Windows Server 2003 (bible hardware system requirements, see microsoft.cc M/DVD-RON or Internet, see apple.com driver, Mac Software Link to Web (Postscript emula aphics); rotating (adjustable angle) display; illumita 40 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz). Consum rements are based on the country/region where the nt for current information. 9 x 609 mm; M7251 ; 745 x 681 x 1160 mm; M725 x 1553 mm; M7251 ;	SP1+), Windows Server 2008, Windows Server 2008 I m. Mac OS X 10.6, OS X Lion, OS X Mountain Lion; 1 tion driver & Installer on Web), Note: No Mac Software ted Home button (for quick return to the Home menu); E ption:890 watts (active print/copy), 39 watts (ready), 6 a printer is sold. Do not convert operating voltages; this	GB available hard disk space; operating system compatible inbox asy Access USB; Hardware Integration Pocket 5 watts (sleep), 0.3 watts (off). Typical Electricity Consumption will damage the printer and void the product warranty. Values 2 mm; Packaged: M725dn: 760 x 745 x 832 mm; M725f: 856 x			
Minimum system requirements Standard software Control panel Power Dimensions (w x d x h)	Windows 8, Windows 7, Windows V disk space, operating system compati- hardware system requirements, CD-R Windows Installer, HP PCL 6 discrete 20.3 cm touchscreen, ICD (colour gr Requirements: Input voltage: 220 to 2: (TEC): 4.39 kWh/Week. Power requi subject to change, see hp.com/suppo Out of package: M725dn : 614 x 645 760 x 1522 mm; M725z : 856 x 760	fista, Windows XP (SP2+), Windows Server 2003 (bible hardware system requirements, see microsoft.cc M/DVD-RON or Internet, see apple.com driver, Mac Software Link to Web (Postscript emula aphics); rotating (adjustable angle) display; illumita 40 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz). Consum rements are based on the country/region where the nt for current information. 9 x 609 mm; M7251 ; 745 x 681 x 1160 mm; M725 x 1553 mm; M7252 ;	SP1+), Windows Server 2008, Windows Server 2008 I m. Mac OS X 10.6, OS X Lion, OS X Mountain Lion; 1 tion driver & Installer on Web), Note: No Mac Software ted Home button (for quick return to the Home menu); E ption:890 watts (active print/copy), 39 watts (ready), 6 a printer is sold. Do not convert operating voltages; this 5z; 745 x 681 x 1192 mm; M725z+; 745 x 681 x 1192	GB available hard disk space; operating system compatible inbox asy Access USB; Hardware Integration Pocket 5 watts (sleep), 0.3 watts (off). Typical Electricity Consumption will damage the printer and void the product warranty. Values 2 mm; Packaged: M725dn : 760 x 745 x 832 mm; M725f : 856 x			
Minimum system requirements Standard software Control panel Power Dimensions (w x d x h) Weight	Windows 8, Windows 7, Windows V disk space, operating system compati- hardware system requirements, CD-R Windows Installer, HP PCL 6 discrete 20.3 cm touchscreen, ICD (colour gr Requirements:Input voltage: 220 to 2. (TEC): 4.39 kWh/Week. Power requi subject to change, see hp. com/suppo- Out of package: M725dn: 614 x 647 760 x 1522 mm; M725a: 856 x 760 Out of package: M725dn: 54.11 kg; HP Web Jetadmin, HP Utility (Mac) Management security: SNMPV3, SSL/	fista, Windows XP (SP2+), Windows Server 2003 (lible hardware system requirements, see microsoft.cc M/DVD-ROM or Internet, see apple.com driver, Mac Software Link to Web (Postscript emula aphics); rotating (adjustable angle) display; illumine dV AC (+/-10%), 50/60 Hz (+/-2 Hz). Consum irements are based on the country/region where the of for current information. 7 x 609 m; M725f; 745 x 681 x 1160 mm; M725 x 1553 mm; M725r; 45 x 660 x 1553 mm; M725f; 87.1 kg; M725r; 92.35 kg; M725z+; 102. /TLS, 802.1X authentication (EAP-PEAP, EAP-TLS), II	SP1+), Windows Server 2008, Windows Server 2008 m. Mac OS X 10.6, OS X Lion, OS X Mountain Lion; 1 tion driver & Installer on Web), Note: No Mac Software sted Home button (for quick return to the Home menu); E pion:890 watts (active print/copy), 39 watts (ready), 6 a printer is sold. Do not convert operating voltages; this 5z: 745 x 681 x 1192 mm; M725z+: 745 x 681 x 1192 42 kg; Packaged: M725dn: 68.6 kg; M725f: 105.4 kg;	GB available hard disk space; operating system compatible inbox asy Access USB; Hardware Integration Pocket 5 watts (sleep), 0.3 watts (off). Typical Electricity Consumption will damage the printer and void the product warranty. Values 2 mm; Packaged: M725dn: 760 x 745 x 832 mm; M725f: 856 x			
Minimum system requirements Standard software Control panel Power Dimensions (w x d x h) Weight Printer management Security management	Windows 8, Windows 7, Windows V disk space; operating system compati- hardware system requirements, CD-RC Windows Installer, HP PCL 6 discrete 20.3 cm touchscreen, ICD (colour grc Requirements:Input voltage: 220 to 2 (TEC): 4.39 kWh/Week. Power requi subject to change; see hp.com/suppc Out of package: M725dn : 54.14 kg4 760 x 1522 mm; M725dn : 54.11 kg; HP Web Jetadmin, HP Utility (Mac) Management security: SNMPv3, SSL/ WJA-10 IPsec Configuration using IPs	(rista, Windows XP (SP2+), Windows Server 2003 (bible hardware system requirements, see microsoft.cc M/DVD-ROM or Internet, see apple.com driver, Mac Software Link to Web (Postscript emula aphics); rotating (adjustable angle) display; illumina dVAC (+/. 10%), 50/60 Hz (+/.2 Hz). Consum irrements are based on the country/region where the not for current information. 7x 609 mm; M7251; 745 x 681 x 1160 mm; M725 x 1553 mm; M725z+: 856 x 760 x 1553 mm; M7251; 87.1 kg; M725z+ 325 kg; M725z+: 102. //TLS, 802.1X authentication (EAP. PEAP, EAP.TLS), II ee Plug-in	SP1+), Windows Server 2008, Windows Server 2008 ym. Mac OS X 10.6, OS X Lion, OS X Mountain Lion; 1 tion driver & Installer on Web), Note: No Mac Software ted Home button (for quick return to the Home menu); E ption:890 watts (active print/copy), 39 watts (ready), 6 e printer is sold. Do not convert operating voltages; this 5z; 745 x 681 x 1192 mm; M725z+: 745 x 681 x 1192 42 kg; Packaged: M725dn: 68.6 kg; M725f: 105.4 kg; PP over TLS, IPsec/Firewall with Certificate, Pre-Shared K	GB available hard disk space; operating system compatible inbox asy Access USB; Hardware Integration Pocket 5 watts (sleep), 0.3 watts (off). Typical Electricity Consumption will damage the printer and void the product warranty. Values 2 mm; Packaged: M725dn : 760 x 745 x 832 mm; M725f : 856 x M725z : 113 kg; M725z +: 122 kg; ey Authentication, and Kerberos Authentication; Support for			
Minimum system requirements Standard software Control panel Power Dimensions (w x d x h) Weight Printer management	Windows 8, Windows 7, Windows V disk space; operating system compati- hardware system requirements, CD-RC Windows Installer, HP PCL 6 discrete 20.3 cm touchscreen, ICD (colour grc Requirements:Input voltage: 220 to 2 (TEC): 4.39 kWh/Week. Power requi subject to change; see hp.com/suppc Out of package: M725dn : 54.14 kg4 760 x 1522 mm; M725dn : 54.11 kg; HP Web Jetadmin, HP Utility (Mac) Management security: SNMPv3, SSL/ WJA-10 IPsec Configuration using IPs	(sta, Windows XP (SP2+), Windows Server 2003 (bible hardware system requirements, see microsoft.cc M/DVD-ROM or Internet, see apple.com driver, Mac Software Link to Web (Postscript emula aphics); rotating (adjustable angle) display; illuminc dv VAC (+/- 10%), 50/60 Hz (+/- 2 Hz). Consum irements are based on the country/region where the or for current information. 2 x 600 mm; M725f: 745 x 681 x 1160 mm; M724 x 1553 mm; M725z+ 856 x 760 x 1553 mm; M725f: 87.1 kg; M725z: 92.35 kg; M725z+ 102. /TLS, 802.1X authentication (EAP- PEAP, EAP-TLS), II eer Plug-in . Recommended operating temperature: 10 to 32.	SP1+), Windows Server 2008, Windows Server 2008 ym. Mac OS X 10.6, OS X Lion, OS X Mountain Lion; 1 tion driver & Installer on Web), Note: No Mac Software ted Home button (for quick return to the Home menu); E ption:890 watts (active print/copy), 39 watts (ready), 6 e printer is sold. Do not convert operating voltages; this 5z; 745 x 681 x 1192 mm; M725z+: 745 x 681 x 1192 42 kg; Packaged: M725dn: 68.6 kg; M725f: 105.4 kg; PP over TLS, IPsec/Firewall with Certificate, Pre-Shared K	GB available hard disk space; operating system compatible inbox asy Access USB; Hardware Integration Pocket 5 watts (sleep), 0.3 watts (off). Typical Electricity Consumption will damage the printer and void the product warranty. Values 2 mm; Packaged: M725dn : 760 x 745 x 832 mm; M725f : 856 > M725z : 113 kg; M725z +: 122 kg;			
Minimum system requirements Standard software Control panel Power Dimensions (w x d x h) Weight Printer management Security management	Windows 8, Windows 7, Windows V disk space, operating system compati- hardware system requirements, CD-RC Windows Installer, HP PCL 6 discrete 20.3 cm touchscreen, LCD (colour gra Requirements:Input voltage: 220 to 2. (TEC): 4.39 kWh/Week. Power requi subject to change, see hp.com/suppc Out of package: M725dn: 614 x 647 760 x 1522 mm; M725a: 856 x 760 Out of package: M725dn: 54.11 kg; HP Web Jetadmin, HP Utility (Mac) Management security: SNMPV3, SSL), WJA-10 IPsec Configuration using IPs Operating temperature: 10 to 32.5°C	(sta, Windows XP (SP2+), Windows Server 2003 (bible hardware system requirements, see microsoft.cc M/DVD-ROM or Internet, see apple.com driver, Mac Software Link to Web (Postscript emula aphics); rotating (adjustable angle) display; illuminc dv VAC (+/- 10%), 50/60 Hz (+/- 2 Hz). Consum irements are based on the country/region where the or for current information. 2 x 600 mm; M725f: 745 x 681 x 1160 mm; M724 x 1553 mm; M725z+ 856 x 760 x 1553 mm; M725f: 87.1 kg; M725z: 92.35 kg; M725z+ 102. /TLS, 802.1X authentication (EAP- PEAP, EAP-TLS), II eer Plug-in . Recommended operating temperature: 10 to 32.	SP1+), Windows Server 2008, Windows Server 2008 ym. Mac OS X 10.6, OS X Lion, OS X Mountain Lion; 1 tion driver & Installer on Web), Note: No Mac Software ted Home button (for quick return to the Home menu); E ption:890 watts (active print/copy), 39 watts (ready), 6 e printer is sold. Do not convert operating voltages; this 5z; 745 x 681 x 1192 mm; M725z+: 745 x 681 x 1192 42 kg; Packaged: M725dn: 68.6 kg; M725f: 105.4 kg; PP over TLS, IPsec/Firewall with Certificate, Pre-Shared K	GB available hard disk space; operating system compatible inbox asy Access USB; Hardware Integration Pocket 5 watts (sleep), 0.3 watts (off). Typical Electricity Consumption will damage the printer and void the product warranty. Values 2 mm; Packaged: M725dn : 760 x 745 x 832 mm; M725f : 856 x M725z : 113 kg; M725z +: 122 kg; ey Authentication, and Kerberos Authentication; Support for			
Minimum system requirements Standard software Control panel Power Dimensions (w x d x h) Weight Printer management Security management Operating environment Acoustics	Windows 8, Windows 7, Windows V disk space, operating system compati- hardware system requirements, CD-RC Windows Installer, HP PCL 6 discrete 20.3 cm touchscreen, ICD (colour gra Requirements:Input voltage: 220 to 2. (TEC): 4.39 kWh/Week. Power requi- subject to change, see hp.com/suppc Out of package: M725dn: 614 x 647 760 x 1522 mm; M725a: 856 x 760 Out of package: M725dn: 54.11 kg; HP Web Jetadmin, HP Utility (Mac) Management security: SNMPA; SSL) WJA-10 IPsec Configuration using IPs Operating temperature: 10 to 32.5°C to 60°C. Storage humidity: 10 to 90 Accoustic Pressure Emissions: 6.8 B(A) Acoustic Pressure Emissions: 54 dB(A)	(sta, Windows XP (SP2+), Windows Server 2003 (ible hardware system requirements, see microsoft.cc M/DVD-ROM or Internet, see apple.com driver, Mac Software Link to Web (Postscript emula aphics); rotating (adjustable angle) display; illuminc dv VAC (+/- 10%), 50/60 Hz (+/- 2 Hz). Consum terments are based on the country/region where the ort for current information. 2 x 600 mm; M725f: 745 x 681 x 1160 mm; M724 x 1553 mm; M725z+ 856 x 760 x 1553 mm; M725f: 87.1 kg; M725z: 92.35 kg; M725z+ 102. /TLS, 802.1X authentication (EAP- PEAP, EAP-TLS), II ee: Plug-in . Recommended operating temperature: 10 to 32. % RH	SP1+), Windows Server 2008, Windows Server 2008 1 m. Mac OS X 10.6, OS X Lion, OS X Mountain Lion; 1 tion driver & Installer on Web), Note: No Mac Software sted Home button (for quick return to the Home menu); E ption:890 watts (active print/copy), 39 watts (ready), 6 a printer is sold. Do not convert operating voltages; this 5z: 745 x 681 x 1192 mm; M725z+: 745 x 681 x 1192 42 kg; Packaged: M725dn: 68.6 kg; M725f: 105.4 kg; PP over TLS, IPsec/Firewall with Certificate, Pre-Shared K 5°C . Operating humidity: 20 to 80% RH . Operating h	GB available hard disk space; operating system compatible inbox asy Access USB; Hardware Integration Pocket .5 watts (sleep), 0.3 watts (off). Typical Electricity Consumption will damage the printer and void the product warranty. Values 2 mm; Packaged: M725dn: 760 x 745 x 832 mm; M725f: 856 x M725z: 113 kg; M725z+: 122 kg; ey Authentication, and Kerberos Authentication; Support for umidity recommended: 30 to 70% RH . Storage temperature: 0			
Minimum system requirements Standard software Control panel Power Dimensions (w x d x h) Weight Printer management Security management Operating environment	Windows 8, Windows 7, Windows V disk space, operating system compati- hardware system requirements, CD-R Windows Installer, HP PCL 6 discrete 20.3 cm touchscreen, ICD (colour gr Requirements:Input voltage: 220 to 2: (TEC): 4.39 kWh/Week. Power requi subject to change, see h.com/suppo- Out of package: M725dn : 614 x 647 760 x 1522 mm; M725z : 856 x 760 Out of package: M725dn : 54.11 kg; HP Web Jetadmin, HP Utility (Mac) Management security: SNMPv3, SSL, WJA-10 IPsec Configuration using IPs Operating temperature: 10 to 32.5°C to 60°C. Storage humidity: 10 to 90 Acoustic Poswer Emissions: 64 B(A) Acoustic Pressure Emissions: 54 dB(A) CISPR 22:2008 / EN 55022:2010 (fista, Windows XP (SP2+), Windows Server 2003 (bible hardware system requirements, see microsoft.cc M/DVD-ROM or Internet, see apple.com driver, Mac Software Link to Web (Postscript emula aphics); rotating (adjustable angle) display; Illumine dv Vac (+/- 10%), 50/60 Hz (+/- 2 Hz). Consum irements are based on the country/region where the of for current information. P x 609 mm; M725f: 745 x 681 x 1160 mm; M724 x 1553 mm; M725f: 745 x 681 x 1160 mm; M725 x 1553 mm; M725f: 745 x 681 x 1160 mm; M724 x 1553 mm; M725f: 92.35 kg; M725z+: 102. /TLS, 802.1X authentication (EAP-PEAP, EAP-TLS), II ece Plug-in C. Recommended operating temperature: 10 to 32. % RH	SP1+), Windows Server 2008, Windows Server 2008 I m. Mac OS X 10.6, OS X Lion, OS X Mountain Lion; 1 tion driver & Installer on Web), Note: No Mac Software ted Home button (for quick return to the Home menu); E pion:800 watts (active print/copy), 39 watts (ready), 6 a printer is sold. Do not convert operating voltages; this 5z: 745 x 681 x 1192 mm; M725z+: 745 x 681 x 1192 42 kg; Packaged: M725dn: 68.6 kg; M725f: 105.4 kg; P over TLS, IPsec/Firewall with Certificate, Pre-Shared K 5°C . Operating humidity: 20 to 80% RH . Operating h 009; EN 61000-3-3 :2008; EN 55024:1998+A1+A2;	GB available hard disk space; operating system compatible inbox asy Access USB; Hardware Integration Pocket 5 watts (sleep), 0.3 watts (off). Typical Electricity Consumption will damage the printer and void the product warranty. Values 2 mm; Packaged: M725dn: 760 x 745 x 832 mm; M725f: 856 x M725z: 113 kg; M725z+: 122 kg; ey Authentication, and Kerberos Authentication; Support for umidity recommended: 30 to 70% RH . Storage temperature: 0 EMC Directive 2004/108/EC with CE Marking (Europe); other			
Minimum system requirements Standard software Control panel Power Dimensions (w x d x h) Weight Printer management Security management Operating environment Acoustics	 Windows 8, Windows 7, Windows V disk space, operating system compati- hardware system requirements, CD-RC Windows Installer, HP PCL 6 discrete 20.3 cm touchscreen, LCD (colour gra Requirements:Input voltage: 220 to 2 (TEC): 4.39 kWh/Week. Power requi- subject to change, see hp.com/suppc Out of package: M725dn: 614 x 647 760 x 1522 mm; M725dn: 563 x 740 Dat of package: M725dn: 563 x 740 Vidy Jong Color and Statistical Statistical Statistical Windows 10 Pisec Configuration using IB Operating temperature: 10 to 32.5°C to 60°C. Storage humidity: 10 to 90 Acoustic Pressure Emissions: 54 B(A) Acoustic Pressure Emissions: 54 dB(A) CISPR 22:2008 / EN 55022:2010 (EMC approvals as required by indivi 	(sta, Windows XP (SP2+), Windows Server 2003 (bible hardware system requirements, see microsoft.cc M/DVD-ROM or Internet, see apple.com driver, Mac Software Link to Web (Postscript emula aphics); rotating (adjustable angle) display; illumina dv VAC (+/- 10%), 50/60 Hz (+/- 2 Hz). Consum irements are based on the country/region where the oth for current information. 9x 609 mm; M725f: 745 x 681 x 1160 mm; M722 x 1553 mm; M725z+: 856 x 760 x 1553 mm; M725f: 87.1 kg; M725z: 92.35 kg; M725z+: 102. /TLS, 802.1X authentication (EAP- PEAP, EAP-TLS), II ec. Plug-in C. Recommended operating temperature: 10 to 32. % RH	SP1+), Windows Server 2008, Windows Server 2008 m. Mac OS X 10.6, OS X Lion, OS X Mountain Lion; 1 lion driver & Installer on Web), Note: No Mac Software sted Home button (for quick return to the Home menu); E pion:890 watts (active print/copy), 39 watts (ready), 6 a printer is sold. Do not convert operating voltages; this sz: 745 x 681 x 1192 mm; M725z+: 745 x 681 x 1192 42 kg; Packaged: M725dn: 68.6 kg; M725f: 105.4 kg; PP over TLS, IPsec/Firewall with Certificate, Pre-Shared K 5°C . Operating humidity: 20 to 80% RH . Operating h D09; EN 61000-3:3 :2008; EN 55024:1998+A1+A2; 2005 +A1; EN60950-1: 2006 +A11:2009 +A1:2010	GB available hard disk space; operating system compatible inbox asy Access USB; Hardware Integration Pocket .5 watts (sleep), 0.3 watts (off). Typical Electricity Consumption will damage the printer and void the product warranty. Values 2 mm; Packaged: M725dn: 760 x 745 x 832 mm; M725f: 856 x M725z: 113 kg; M725z+: 122 kg; ey Authentication, and Kerberos Authentication; Support for umidity recommended: 30 to 70% RH . Storage temperature: 0 EMC Directive 2004/108/EC with CE Marking (Europe); other +A12:2011; IEC 60825-1:2007 (Class 1 Laser/Led Product);			
Minimum system requirements Standard software Control panel Power Dimensions (w x d x h) Weight Printer management Security management Operating environment Acoustics	 Windows 8, Windows 7, Windows V disk space, operating system compati- hardware system requirements, CD-RC Windows Installer, HP PCL 6 discrete 20.3 cm touchscreen, LCD (colour gra Requirements:Input voltage: 220 to 2 (TEC): 4.39 kWh/Week. Power requi- subject to change, see hp.com/suppc Out of package: M725dn: 614 x 647 760 x 1522 mm; M725dn: 563 x 740 Dat of package: M725dn: 563 x 740 Vidy Jong Color and Statistical Statistical Statistical Windows 10 Pisec Configuration using IB Operating temperature: 10 to 32.5°C to 60°C. Storage humidity: 10 to 90 Acoustic Pressure Emissions: 54 B(A) Acoustic Pressure Emissions: 54 dB(A) CISPR 22:2008 / EN 55022:2010 (EMC approvals as required by indivi 	<pre>fista, Windows XP (SP2+), Windows Server 2003 (ible hardware system requirements, see microsoft.cc M/DVD-ROM or Internet, see apple.com driver, Mac Software Link to Web (Postscript emula aphics); rotating (adjustable angle) display; illuminc dv VAC (+/- 10%), 50/60 Hz (+/- 2 Hz). Consum irements are based on the country/region where the ort for current information. 7 x 609 mm; M725f: 745 x 681 x 1160 mm; M72f x 1553 mm; M725f: 745 x 681 x 1160 mm; M72f x 1553 mm; M725f: 745 x 681 x 1160 mm; M72f x 1553 mm; M725f: 745 x 681 x 1160 mm; M72f x 1553 mm; M725f: 745 x 681 x 1160 mm; M72f x 1553 mm; M725f: 745 x 681 x 1160 mm; M72f x 1558 mm; M725f: 745 x 681 x 1160 mm; M72f x 1558 mm; M725f: 92.35 kg; M725fz+ 102. /TLS, 802.1X authentication (EAP-PEAP, EAP-TLS), II ecc Plugin 2. Recommended operating temperature: 10 to 32. % RH</pre>	SP1+), Windows Server 2008, Windows Server 2008 m. Mac OS X 10.6, OS X Lion, OS X Mountain Lion; 1 lion driver & Installer on Web), Note: No Mac Software sted Home button (for quick return to the Home menu); E pion:890 watts (active print/copy), 39 watts (ready), 6 a printer is sold. Do not convert operating voltages; this sz: 745 x 681 x 1192 mm; M725z+: 745 x 681 x 1192 42 kg; Packaged: M725dn: 68.6 kg; M725f: 105.4 kg; PP over TLS, IPsec/Firewall with Certificate, Pre-Shared K 5°C . Operating humidity: 20 to 80% RH . Operating h D09; EN 61000-3:3 :2008; EN 55024:1998+A1+A2; 2005 +A1; EN60950-1: 2006 +A11:2009 +A1:2010	GB available hard disk space; operating system compatible inbox asy Access USB; Hardware Integration Pocket 5 watts (sleep), 0.3 watts (off). Typical Electricity Consumption will damage the printer and void the product warranty. Values 2 mm; Packaged: M725dn: 760 x 745 x 832 mm; M725f: 856 x M725z: 113 kg; M725z+: 122 kg; ey Authentication, and Kerberos Authentication; Support for umidity recommended: 30 to 70% RH . Storage temperature: 0 EMC Directive 2004/108/EC with CE Marking (Europe); other			

http://www.hp.com/uk



© Copyright 2013 Hewlett-Packad Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors, or omissions contained herein.