

# **HP LaserJet Enterprise M806 Printer series**

Ideal for boosting productivity and efficiency across your business. Equip your teams to handle even the biggest print jobs guickly with HP's top-of-the line A3 printer – and print while on the go. Your investment is protected with easy upgrades.









### Boost productivity: give workgroups the speed they need.

- Print big jobs fast at up to 56 ppm A4, and easily thanks to the extra-large input capacity of up to 4,600 pages<sup>3</sup>. Versatile paper handling options include a stapler/stacker/hole punch and booklet maker4.
- Simplify tasks with the right touch equip users to fly through tasks with the large 10.9 cm (4.3-inch) colour touchscreen
- Simplicity all around make it easy for all to print with one common driver<sup>5</sup>.
- Don't wait, just print right away and save energy with Instant-on Technology.

#### Invest once, expand easily.

- Keep a close watch, even from afar monitor and control printers centrally with HP Web Jetadmin<sup>6</sup>.
- Apply fleet-wide policies to protect all your HP devices with the HP Imaging and Printing Center<sup>7</sup>.
- Safeguard your printers right away with HP Instant-on Security<sup>8</sup>, and protect the sensitive data sent to your printer with the HP High-Performance Secure Hard Disk<sup>9</sup>.
- Prints with a positive ID authenticate users at the device to help secure print jobs.

#### **Experience greater efficiency with mobile** printing.

- Mobile printing is simple with wireless direct printing<sup>1</sup>, and enable touch-to-print convenience from a mobile device<sup>2</sup>
- Let employees print from mobile devices with built-in print capability or HP ePrint app and software<sup>10</sup>.
- Printing made Apple® simple let users print wirelessly from an iPad<sup>®</sup>, iPhone<sup>®</sup>, or iPod touch<sup>®11</sup>.

<sup>1</sup> Wireless direct printing is standard in the HP Laser Jet Enterprise M806x+ D7P69A, and may be added as an option to the HP Laser Jet Enterprise M806dn and M806x+ CZ245A. Mobile device may require an app or driver. Wireless performance is dependent on physical environment and distance from the printer. For details, see hp.com/go/wirelessprinting.

<sup>2</sup> Touch-to-print capability is standard in the HP LaserJet Enterprise M806x+ D7P69A model, and may be added as an option to the HP LaserJet Enterprise M806dn and M806x+ CZ245A. Mobile device must support near field communications-enabled printing.

<sup>3</sup> Maximum paper capacity of 4.600 sheets is standard in the HP Laser Jet Enterprise M806x+ D7P69A and M806x+ CZ245A and available in the HP Laser Jet Enterprise M806dn model with the optional 3.500-sheet high-capacity input trav <sup>4</sup> 2 bin stapler/stacker, 2 bin stapler/stacker/hole punch and booklet maker are optional accessories. Please purchase separately

<sup>5</sup> The HP Universal Print Driver is free and available for download at hp.com/go/upd.

<sup>6</sup> HP Web Jetadmin is free and available for download at hp.com/go/webjetadmin

<sup>7</sup> HP Imaging and Printing Security Center must be purchased separately.
<sup>8</sup> HP Instant-on Security is part of HP Imaging and Printing Security Center, which must be purchased separately

<sup>9</sup> HP High-Performance Secure Hard Drive is not available on the HP LaserJet Enterprise M806dn and can't be purchased separately. <sup>10</sup> Local printing requires mobile device and printer to be on the same network or have a direct wireless connection to printer. Wireless performance is dependent upon physical environment and distance from access point. Wireless operations are

compatible with 2.4 GHz operations only. Remote printing requires an Internet connection to an HP Web-connected printer. App or software and HP ePrint account registration may also be required. Wireless broadband use requires separately purchased service contract for mobile devices. Check with service provider for coverage and availability in your area. See hp.com/go/mobileprinting for more details. <sup>11</sup> Supports OS X<sup>®</sup> Lion, OS X Mountain Lion, and the following devices running iOS 4.2 or later: iPad<sup>®</sup> (all models), iPhone<sup>®</sup> (3GS or later), and iPod touch<sup>®</sup> (third generation or later). Works with HP's AirPrint-enabled printers and requires the printer be

connected to the same network as your 05 X or iOS device. Wireless performance is dependent on physical environment and distance from the access point. OS X, iPad, iPhone, and iPod touch are trademarks of Apple® Inc., registered in the United States and other countries. AirPrint™ and the AirPrint logo are trademarks of Apple Inc.








# **Product walkaround**

- 1. Intuitive 10.9 cm (4.3 in) colortouchscreen control panel
- 2. 500-page output bin
- 3. Hardware integration pocket (HIP) for solution integration
- 4. 100-sheet face-up straight-through output bin
- 5. Easy front-door access to HP all-in-one toner cartridge
- 6. Built-in automatic two-sided printing
- 7. Two 500-sheet input trays support media up to A3 (11 x 17 in)
- 8. 3,500-sheet high-capacity input tray supports A4/letter media 9. Easy-access USB port to print files directly
- 10. 100-sheet multipurpose tray handles media up to 220 g/m2 (53 lb bond)
- 11. Right-side doors provide access for clearing jams
- 12. 800 MHz processor, 1 GB standard memory
- 13. HP High-Performance Secure Hard Disk
- 14. Access port for optional Kensington-style lock
- 15. USB port (for connecting third-party devices)
- 16. Hi-Speed USB 2.0 printing port
- 17. HP Jetdirect Gigabit Ethernet print server
- 18. Foreign interface harness (for connecting third-party devices)






# Series at a glance



#### HP LaserJet Enterprise M806dn Printer

- print speed A4 black: up to 56 ppm (duplex: up to 56 ipm)
- print speed A3 black: up to 28 ppm
- up to 1200 x 1200 dpi (HP FastRes 1200)
- 1 GB RAM expandable to 1.5 GB
- 800 MHz processor
- 2 Hi-Speed USB 2.0 Host
- 1 Hi-Speed USB 2.0 Device
- 1 Gigabit Ethernet 10/100/1000T network
- 1 Foreign Interface
- 1 Hardware Integration Pocket
- 2 Internal USB Host
- Two 500-sheet input trays
- 100-sheet multi-purpose tray





- as HP LaserJet Enterprise M806dn with:
- 320 GB HP High-Performance Secure Hard Disk • 3,500 sheet High-capacity tray (tray 4: 1500 sheets A4 or letter only, tray 5: 2000 sheets A4 or letter onlv)
- as HP LaserJet Enterprise M806dn with:
- Near Field Communications (NFC) Module for wireless direct printing
- 320 GB HP High-Performance Secure Hard Disk
- 3,500 sheet High-capacity tray (tray 4: 1500 sheets . A4 or letter only, tray 5: 2000 sheets A4 or letter only)

## **Recommended accessories**



HP LaserJet 3500-sheet High-

productivity of growing work

sheet paper capacity allows

focusing on business and less time reloading paper.

users to spend more time

aroups with this high-

capacity Input Tray Support the

performance, robust input feeder

and stand. The additional 3,500-

C3F79A

CZ285A HP LaserJet Booklet Maker/ Finisher

The HP LaserJet Booklet Maker/ Finisher provides the ability to create more complex finished documents in-house without the time and expense of going to an outside service.



CZ994A HP LaserJet Stapler/Stacker The HP Laser let

Stapler/Stacker provides automatic stapling and stacking for improved efficiency and increased output capacity.



CZ996A HP LaserJet Stapler/Stacker with 2/4 hole punch The HP LaserJet Stapler/Stacker with 2/4 hole punch provides automatic stapling and stacking for improved efficiency and increased output capacity.



C8091A **HP Staple Cartridge Refill** HP Staple Cartridge Refills give you more for your money and ensure you don't have to worry about frequent cartridge replacement. Fach refill

contains 5000 staples.

# **Ordering information**



HP LaserJet Enterprise M806dn Printer (CZ244A) HP LaserJet M806dn Printer: HP Black LaserJet Toner Cartridge (~34.5K pages): Hardware Install Guide, Support flver, Warranty card; Printer documentation and driver on CD-ROM; power cord



HP LaserJet Enterprise M806x+ NFC/Wireless Direct Printer (D7P69A)

HP LaserJet M806x+ Printer: HP Black LaserJet Toner Cartridge (~34.5K pages); Hardware Install Guide, Support flyer, Warranty card; Printer documentation and driver on CD-ROM; power cord; NFC module



HP LaserJet Enterprise M806x+ Printer (CZ245A)

HP LaserJet M806x+ Printer: HP Black LaserJet Toner Cartridge (~34,5K pages); Hardware Install Guide, Support flver, Warranty card; Printer documentation and driver on CD-ROM; power cord

# Accessories, Supplies and Support

C3F79A	HP LaserJet 3500-sheet High-capacity Input Tray				
CZ285A	HP LaserJet Booklet Maker/Finisher				
CZ994A	HP LaserJet Stapler/Stacke				
CZ996A	HP LaserJet Stapler/Stacker with 2/4 hole punch				
C8091A	HP Staple Cartridge Refil				
CC383A	HP 2-pack 2000-staple Cartridge				
Connecti	vity				
J8026A	HP Jetdirect 2700w USB Wireless Print Serve				
J8029A	HP Jetdirect 2800w NFC/Wireless Direct Accessory				

#### Supplies

C2H57A HP LaserJet 220V Maintenance/Fuser Kit CF325X HP 25X High Yield Black Original LaserJet Toner Cartridge

#### Service & support

U8C50E - HP 3 year Next Business Day LaserJet Enterprise M806 Hardware Support U8C53E - HP 3 year 4 hour 9x5 LaserJet Enterprise M806 Hardware Support U8C51E - HP 4 year Next Business Day LaserJet Enterprise M806 Hardware Support U8C52E - HP 5 year Next Business Day LaserJet Enterprise M806 Hardware Support U8C71PE - HP 1 year Post Warranty Next Business Day LaserJet Enterprise M806 Hardware Support **U8C72PE** - HP 2 year Post Warranty Next Business Day Laser Jet Enterprise M806 Hardware Support

U8C73PE - HP 1 year Post Warrant 4 hour 9x5 9x5 LaserJet Enterprise M806 Hardware Support

For a complete list of supplies, accessories and services, please refer to http://www.hp.com For workflow, device management and other solutions, please visit the Global Solutions catalog: www.hp.com/go/gsc

Declared yield value in accordance with ISO/IEC 19752. Actual yields vary considerably based on images printed and other factors. For more information, visit hp.com/go/learnaboutsupplies. Actual yields vary considerably based on images printed and other

factors. For details see hp.com/go/learnaboutsupplies Count on dependable support to create the best image possible. We can help you enhance your printing and imaging environment, protect your IT investment, and grow your business—with expert support that's affordable, personal, and tailored to your

needs through HP Care Pack Services

# **Technical specifications**

Print technology	Laser						
Print speed	First page out black (A4): As fast as 8.5 sec A4 black: Up to 56 ppm (duplex: up to 56 ipm); A3 black: Up to 28 ppm						
	Measured using ISO/IEC 24734, excludes first set of test documents. For more information see hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application,						
Processor	driver, and document complexity. 800 MHz						
Memory	1 GB. Expandable to 1.5 GB through 1 GB industry-standard DIMM						
	320 GB HP High-Performance Secure Hard Disk (only on D7P69A and CZ245A)						
Hard disk Print							
Print	Quality         HP FastRes 1200 (1200 dpi quality), 600 x 600 dpi with HP Resolution Enhancement technology           Resolution         Black: Up to 1200 x 1200 dpi						
	Printer languages HP PCL 6, HP PCL 5e, HP Postscript Level 3 emulation, native PDF printing (v 1.4)						
	Typefaces/fonts 105 internal TrueType fonts scalable in HP PCL; 92 internal scalable fonts in HP Postscript Level 3 emulation (Euro symbol built-in); 1 internal Unicode Fonts (Andale						
	Mono WorldType); 2 Internal Windows Vista 8 Fonts (Calibri, Cambria); additional font solutions available via third-party flash memory cards; HP Laser Jet Fonts and IF						
	Emulation available at hp.com/go/laserjetfonts Duty cycle (monthly, A4) Up to 300,000 pages						
	Recommended monthly page volu						
	Print margins (mm)	Top: 2.0 mm. Left: 2.0 mm. Right: 2.0 mm. Bottom	n: 2.0 mm				
Media handling	Input:	Capacity	Weight	Size			
	Tray 1	sheets: 100; envelopes: 100; labels: 100	60 to 220 g/m <sup>2</sup>	A3, A4, A5, RA3, B4, B5, post cards (JIS double);			
	T	-haster 500: lebeler II	C0 += 100 =/==2	envelopes (DL, C5, B5); 98 x 191 to 312 x 470 mm			
	Tray 2, 3 Tray 4, 5	sheets: 500; labels: small quantities CZ244A: optional High-capacity Input tray, tray 4:	60 to 199 g/m² 60 to 199 g/m²	A3; A4; A5; B4; B5; 148 × 210 to 297 × 431.8 mm <b>CZ244A:</b> Optional High-capacity Input, Tray 4/5; A4.			
	11dy 4, 5	sheets: 1500 (A4 only), tray 5: sheets: 2000 (A4	66 (6 155 g/m	210 to 297 mm; <b>D7P69A:</b> High-capacity Input, Tray			
		only); <b>D7P69A:</b> High-capacity Input tray, tray 4:		4/5: A4, 210 to 297 mm; <b>CZ245A:</b> as D7P69A			
		sheets: 1500 (A4 only), tray 5: sheets: 2000 (A4		product;			
		only); CZ245A: as D7P69A product;					
	Output:	Sheets: Up to 600 sheets. Transparencies: Up to 100	sheets				
	Duplex printing: Automatic (standard)						
Media types		ain, preprinted, prepunched, recycled, rough), labels, ca					
Interface and connectivity	Standard: C2244A: 2 Hi-Speed USB 2.0 Host; 1 Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10000 network; 1 Foreign Interface; 1 Hardware Integration Pocket; 2 Internal USB Host; D7P69A: 2						
	Hi-Speed USB 2.0 Host; 1 Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/1000T network; 1 NFC/Wireless (accessory included); 1 Foreign Interface; 2 Internal USB Host; CZ245A: 2 Hi-Speed USB 2.0 Located USB 2.0 Device; 1 Gigabit Ethernet 10/100/1000T networks; 1 NFC/Wireless (accessory included); 1 Foreign Interface; 2 Internal USB Host; CZ245A: 2 Hi-Speed USB 2.0 Located USB 2.0 Device; 1 Gigabit Ethernet 10/100/1000T networks; 1 NFC/Wireless (accessory included); 1 Foreign Interface; 2 Internal USB Host; CZ245A: 2 Hi-Speed USB 2.0 Located USB 2.0 Device; 1 Gigabit Ethernet 10/100/1000T networks; 1 NFC/Wireless (accessory included); 1 Foreign Interface; 2 Internal USB Host; CZ245A: 2 Hi-Speed USB 2.0 Located USB 2.0 Device; 1 Gigabit Ethernet 10/100/1000T networks; 1 NFC/Wireless (accessory included); 1 Foreign Interface; 2 Internal USB Host; CZ245A: 2 Hi-Speed USB 2.0 Located USB 2.0 Device; 1 Gigabit Ethernet 10/100/1000T networks; 1 NFC/Wireless (accessory included); 1 Foreign Interface; 2 Internal USB Host; CZ245A: 2 Hi-Speed USB 2.0 Located USB 2.0 Device; 1 Gigabit Ethernet 10/100/1000T networks; 1 NFC/Wireless (accessory included); 1 Foreign Interface; 2 Internal USB Host; CZ245A: 2 Hi-Speed USB 2.0 Located USB 2.0 Device; 1 Gigabit Ethernet; 10/100/100T networks; 1 NFC/Wireless (accessory included); 1 Foreign Interface; 2 Internal USB 4.0 Device; 1 Gigabit Ethernet; 10/100/100T networks; 1 NFC/Wireless (accessory included); 1 Foreign Interface; 2 Internal USB 4.0 Device; 1 Gigabit Ethernet; 10/100/100T networks; 1 NFC/Wireless; 1 Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet; 10/100/100T networks; 1 NFC/Wireless; 1 Hi-Speed 2.0 Device; 1 Gigabit Ethernet; 10/100/100T networks; 1 NFC/Wireless; 1 Hi-Speed 2.0 Device; 1 Gigabit Ethernet; 10/100/100T networks; 1 HI-Speed 2.0 Device; 1 Gigabit Ethernet; 10/100/100T networks; 1 NFC/Wireles; 1 HI-Speed 2.0 Device; 1 Gigabit Ethernet; 10/100/100T networks; 1 HI-Speed 2.0 Device; 1 HI-Speed 2.0 Device; 1 HI-Speed 2.0 Device; 1 HI-Speed 2.0 Device; 1 HI-Speed 2.						
Operating systems compatibility	Host; 1 Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/1000T network; 1 Foreign Interface; 1 Hardware Integration Pocket; 2 Internal USB Host; Windows 8 (32-bit/64-bit), Windows 7 (32-bit/64-bit), Windows Vista (32-bit/64-bit), Windows XP (SP2 or higher) (32-bit/64-bit), Windows Server 2012 (64-bit), Windows Server 2008 (32-bit/64-bit),						
operating systems compatibility				10.8 Mountain Lion. For the latest operating system support see: AirPrint™			
				ware Driver (hp.com/go/eprintsoftware); Linux (hplip.net); Novell			
			print); UNIX (hp.com/go/unix); UNIX Je	tDirect (hp.com/go/jetdirectunix_software). Laser Jet driver information and			
	support available at: hp.com/support/ljiM806; hp.com/go/hpsc; hp.com/support						
Network operating systems compatibility				x <sup>®</sup> MetaFrame Server; Novell <sup>®</sup> 5.1 or higher; RED HAT Linux 7.x or higher;			
	Solaris® 2.5 or higher (SPARC® systems only): SUSE Linux 8.x or higher; Windows 2003 SP2+ (Windows Server 2003 SP2+; Windows Services; Windows Vista (32-bit and 64-bit); Windows 2003 SP2+ (Windows Server 2003 SP2+; Windows Services; Windows Vista (32-bit and 64-bit); Windows 2003 SP2+ (Vista Vista V						
	Vista Ready; Windows XP SP3+ 64-bit; Windows XP SP3+ Home; Windows XP SP3+ Home; Windows XP SP3+ Professional; Windows XP SP3+ Professional and Windows Vista; Windows 7 SP1 or greater (32-bit and 64-bit); Windows 8 (32-bit and 64-bit); Windows Server 2008 (32-bit and 64-bit); Windows Server 2008 R2 (64-bit); Windows Server 2012 (64-bit). For Microsoft IPv6 compatibility use						
	Carbon and events, windows 20 (22-bit and events, windows server accord (22-bit and events, windows server accord (24-bit), windows 2000 (22-bit and events), windows server accord (24-bit), windows 2000 (24-bit)), windows 2000 (24-bit), windows 2000 (24-bit)), windows 2000 (24-bit)), windows 2000 (24-bit), windows 2000 (24-bit)), windows 2000						
	Windows 2003, Windows XP Home		Windows 8, Windows 7 SP1+, Windows Vista, Windows Server 2003 (SP1+), Windows Server 2008, Windows Server 2008 R2 (64 bit), Windows Server 2012 (64-bit), Windows XP (SP2+); CD-ROM or DVD				
Minimum system requirements	Windows 8, Windows 7 SP1+, Wind	dows Vista, Windows Server 2003 (SP1+), Windows Ser					
Minimum system requirements	Windows 8, Windows 7 SP1+, Wind drive, or Internet connection; Dedic	dows Vista, Windows Server 2003 (SP1+), Windows Ser ated universal serial bus (USB 1.1 or 2.0), or network o	onnection; 200 MB available hard dis	k space; Operating system compatible hardware system requirements see			
Minimum system requirements	Windows 8, Windows 7 SP1+, Wind drive, or Internet connection; Dedic microsoft.com. Mac OS X v10.6.8, 4	dows Vista, Windows Server 2003 (SP1+), Windows Ser ated universal serial bus (USB 1.1 or 2.0), or network c OS X 10.7.5 Lion, OS X 10.8 Mountain Lion; 1 GB of avai	onnection; 200 MB available hard dis lable hard-disk space; CD-ROM or DV	k space; Operating system compatible hardware system requirements see			
	Windows 8, Windows 7 SP1+, Wind drive, or Internet connection; Dedic microsoft.com. Mac OS X v10.6.8, or network connection (Operating	dows Vista, Windows Server 2003 (SP1+), Windows Ser cated universal serial bus (USB 1.1 or 2.0), or network c OS X 10.7.5 Lion, OS X 10.8 Mountain Lion; 1 GB of avai system compatible hardware system requirements see	onnection; 200 MB available hard dis lable hard-disk space; CD-ROM or DV	k space; Operating system compatible hardware system requirements see			
Standard software	Windows 8, Windows 7 SP1+, Wind drive, or Internet connection; Dedic microsoft.com. Mac OS X v10.6.8, or network connection (Operating HP PCL 6 Discrete Printer Driver, Ma	dows Vista, Windows Server 2003 (SP1+), Windows Ser cated universal serial bus (USB 1.1 or 2.0), or network c 0S X 10.7.5 Lion, OS X 10.8 Mountain Lion; 1 GB of avai system compatible hardware system requirements see ac SW Link to Web (Mac Installer), Windows Installer	onnection; 200 MB available hard dis lable hard-disk space; CD-ROM or DV apple.com)	k space; Operating system compatible hardware system requirements see D drive, or Internet connection; Dedicated universal serial bus (USB 1.1 or 2.0),			
Standard software Control panel	Windows 8, Windows 7 SP1+, Winc drive, or Internet connection; Dedi microsoft.com. Mac OS X v10.6.8, or network connection (Operating HP PCL 6 Discrete Printer Driver, M. 10.9 cm colour LCD with resistive t	dows Vista, Windows Server 2003 (SP1+), Windows Ser cated universal serial bus (USB 1.1 or 2.0), or network c OS X 10.7.5 Lion, OS X 10.8 Mountain Lion; 1 GB of avai system compatible hardware system requirements see ac SW Link to Web (Mac Installer), Windows Installer ouchscreen; rotating (adjustable angle) display; illumin:	onnection; 200 MB available hard dis lable hard-disk space; CD-ROM or DV apple.com)	k space; Operating system compatible hardware system requirements see			
Standard software Control panel Power	Windows 8, Windows 7 SP1+, Winc drive, or Internet connection; Dedi microsoft.com. Mac OS X v10.6.8, or network connection (Operating HP PCL 6 Discrete Printer Driver, M 10.9 cm colour LCD with resistive t Requirements: Input Voltage: 220	dows Vista, Windows Server 2003 (SP1+), Windows Ser cated universal serial bus (USB 1.1 or 2.0), or network c OS X 10.7.5 Lion, OS X 10.8 Mountain Lion; 1 GB of avai system compatible hardware system requirements see ac SW Link to Web (Mac Installer), Windows Installer ouchscreen; rotating (adjustable angle) display; illumin: to 240 VAC, SO/60 Hz, 5.5 A	onnection; 200 MB available hard dis lable hard-disk space; CD-ROM or DV apple.com) ated capacitive Home button (for quic	k space; Operating system compatible hardware system requirements see D drive, or Internet connection; Dedicated universal serial bus (USB 1.1 or 2.0),			
Standard software Control panel Power	Windows 8, Windows 7 SP1+, Winc drive, or Internet connection; Dedi microsoft.com. Mac GS X v10.6.8, or network connection (Operating HP PCL 6 Discrete Printer Driver, M 10.9 cm colour LCD with resistive t Requirements: Input Voltage: 220 Out of package: <b>CZ244A</b> : 1055 x 6	dows Vista, Windows Server 2003 (SP1+), Windows Ser cated universal serial bus (USB 1.1 or 2.0), or network or SX 10.7.5 Lion, OS X 10.8 Mountain Lion; 1 G B of avai system compatible hardware system requirements see ac SW Link to Web (Mac Installer), Windows Installer ouchscreen; rotating (adjustable angle) display; Illumin: to 240 VAC, 50/50 Hz, 5.5 A 548 x 635 mm; <b>D7P69A</b> : 1095 x 715 x 1040 mm; <b>CZ</b>	onnection; 200 MB available hard dis lable hard-disk space; CD-ROM or DV apple.com) ated capacitive Home button (for quic 245A: 1095 x 715 x 1040 mm;	k space; Operating system compatible hardware system requirements see D drive, or Internet connection; Dedicated universal serial bus (USB 1.1 or 2.0),			
Standard software Control panel Power Dimensions (w x d x h)	Windows 8, Windows 7 SP1+, Winc drive, or Internet connection; Dedi microsoft.com. Mac GS x 1016.8, or network connection (Operating HP PCL 6 Discrete Printer Driver, M. 10.9 cm colour LCD with resistive t Requirements: Input Voltage: 220 Out of package: C2244A: 1095 x / Packaged: C2244A: 856 x 760 x 9	dows Vista, Windows Server 2003 (SP1+), Windows Ser cated universal serial bus (USB 1.1 or 2.0), or network or SX 10.7, 5L ion, QS X 10.8 Mountain Lion; 1 G Bof avai system compatible hardware system requirements see ac SW Link to Web (Mac Installer), Windows Installer ouchscreen; rotating (adjustable angle) display; illumin to 240 VAC, S0/60 Hz, 5.5 A 648 x 635 mm; <b>D7P69A</b> : 1095 x 715 x 1040 mm; <b>CZ2</b> 478 mm; <b>D7P69A</b> : 856 x 790 x 1368 mm; <b>CZ245A</b> : 8	onnection; 200 MB available hard dis lable hard-disk space; CD-ROM or DV apple.com) ated capacitive Home button (for quic 245A: 1095 x 715 x 1040 mm;	k space; Operating system compatible hardware system requirements see D drive, or Internet connection; Dedicated universal serial bus (USB 1.1 or 2.0),			
Standard software Control panel Power	Windows 8, Windows 7 SP1+, Winc drive, or Internet connection; Dedi microsoft.com. Mac OS X v10.6.8, or network connection (Operating: HP PCL 6 Discrete Printer Driver, Mi 10.9 cm colour LCD with resistive t Requirements: Input Voltage: 220 Out of package: (Z244A: 365 x 760 x 9 Out of package: (Z244A: 365 x 760 x 9	dows Vista, Windows Server 2003 (SP1+), Windows Ser cated universal serial bus (USB 1.1 or 2.0), or network c OS X 10.7.5 Lion, OS X 10.8 Mountain Lion; 1 GB of avai system compatible hardware system requirements see ac SW Link to Web (Mac Installer), Windows Installer ouchscreen; rotating (adjustable angle) display; Illumin; to 240 VAC, 50/60 Hz, 5.5 A 548 x 635 mm; <b>D7P69A</b> : 1095 x 715 x 1040 mm; <b>CZ</b> 787 mm; <b>D7P69A</b> : 856 x 790 x 1368 mm; <b>CZ245A</b> : 8 <b>D7P69A</b> : 108.4 kg; <b>CZ245A</b> : 108.4 kg;	onnection; 200 MB available hard dis lable hard-disk space; CD-ROM or DV apple.com) ated capacitive Home button (for quic 245A: 1095 x 715 x 1040 mm;	k space; Operating system compatible hardware system requirements see D drive, or Internet connection; Dedicated universal serial bus (USB 1.1 or 2.0),			
Standard software Control panel Power Dimensions (w x d x h) Weight	Windows 8, Windows 7 SP1+, Winc drive, or Internet connection; Dedi microsoft.com. Mac OS X v10.6.8, or network connection (Operating) HP PCL 6 Discrete Printer Driver, Mi 10.9 cm colour LDD with resistive t Requirements: Input Voltage: 220 Out of package: CZ244A: 1065 x 4 Packaged: CZ244A: 856 x 760 x 9 Out of package: CZ244A: 88.84 kg; D71	dows Vista, Windows Server 2003 (SP1+), Windows Ser cated universal serial bus (USB 1.1 or 2.0), or network or SX 10.7, 5L ion, QS X 10.8 Mountain Lion; 1 G Bof avai system compatible hardware system requirements see ac SW Link to Web (Mac Installer), Windows Installer ouchscreen; rotating (adjustable angle) display; illumin to 240 VAC, S0/60 Hz, 5.5 A 648 x 635 mm; <b>D7P69A</b> : 1095 x 715 x 1040 mm; <b>CZ2</b> 478 mm; <b>D7P69A</b> : 856 x 790 x 1368 mm; <b>CZ245A</b> : 8	onnection; 200 MB available hard dis lable hard-disk space; CD-ROM or DV apple.com) ated capacitive Home button (for quic 245A: 1095 x 715 x 1040 mm;	k space; Operating system compatible hardware system requirements see D drive, or Internet connection; Dedicated universal serial bus (USB 1.1 or 2.0),			
Standard software Control panel Power Dimensions (w x d x h) Weight Printer management	Windows 8, Windows 7 SP1+, Winc drive, or Internet connection; Dedi microsoft.com. Mac GS X v10.6.8, or network connection (Operating HP PCL 6 Discrete Printer Driver, M 10.9 cm colour LCD with resistive t Requirements: Input Voltage: 220 Out of package: <b>(Z244A:</b> 105 × 6 Packaged: <b>(Z244A:</b> 856 × 760 × 8 Out of package: <b>(Z244A:</b> 854 kg; <b>D7</b> ] HP Web Jetadmin; HP Utility (Mac)	dows Vista, Windows Server 2003 (SP1+), Windows Ser cated universal serial bus (USB 1.1 or 2.0), or network o SX 10.7.5 Lion, QS X 10.8 Mountain Lion; 1 G B of avail system compatible hardware system requirements see a SW Link to Web (Mac Installer), Windows Installer ouchscreen; rotating (adjustable angle) display; Illumini to 240 VAC, 50/50 Hz, 5.5 A 548 x 635 mm; <b>D7P69A</b> : 1095 x 715 x 1040 mm; <b>CZ</b> 778 mm; <b>D7P69A</b> : 1856 x 790 x 1368 mm; <b>CZ245A</b> : 8 <b>D7P69A</b> : 10.8.4 kg; <b>CZ245A</b> : 108.4 kg; <b>P69A</b> : 130.87 kg; <b>CZ245A</b> : 130.67 kg;	onnection; 200 MB available hard dis lable hard-disk space; CD-ROM or DV : apple.com) ated capacitive Home button (for quic 245A: 1095 x 715 x 1040 mm; 56 x 790 x 1368 mm;	k space; Operating system compatible hardware system requirements see D drive, or Internet connection; Dedicated universal serial bus (USB 1.1 or 2.0), k return to the Home menu); Easy Access USB; Hardware Integration Pocket			
Standard software Control panel Power Dimensions (w x d x h) Weight Printer management	Windows 8, Windows 7 SP1+, Winc drive, or Internet connection; Dedi microsoft.com. Mac GS Xv 10.6.8, or network connection (Operating HP PCL 6 Discrete Printer Driver, M. 10.9 cm colour LCD with resistive t Requirements: Input Voltage: 220 Out of package: C2244A: 1095 x / Packaged: C2244A: 856 x 760 x 9 Out of package: C2244A: 76.1 kg; Packaged: C2244A: 88.84 kg; D7I HP Web Jetadmin; HP Utility (Mac) C2244A: Identity Management: Ka	dows Vista, Windows Server 2003 (SP1+), Windows Ser cated universal serial bus (USB 1.1 or 2.0), or network of SX 10.7, 5L ion, OS X 10.8 Mountain Lion; 1 G 60 daval system compatible hardware system requirements see ac SW Link to Web (Mac Installer), Windows Installer ouchscreen; rotating (adjustable angle) display; Illumin: to 240 VAC, 50/60 Hz, 5.5 A 548 x 635 mm; <b>D7P69A</b> : 1095 x 715 x 1040 mm; <b>CZ2</b> 778 mm; <b>D7P69A</b> : 856 x 790 x 1368 mm; <b>CZ245A</b> : 8 <b>D7P69A</b> : 108.4 kg; <b>CZ245A</b> : 108.4 kg; <b>P69A</b> : 130.87 kg; <b>CZ245A</b> : 130.67 kg; erberos authentication, LDAP authentication, 1000 use	onnection; 200 MB available hard dis lable hard-disk space; CD-ROM or DV apple.com) ated capacitive Home button (for quic 245A: 1095 x 715 x 1040 mm; 56 x 790 x 1368 mm; r PIN codes, optional HP Access Contr	k space; Operating system compatible hardware system requirements see D drive, or Internet connection; Dedicated universal serial bus (USB 1.1 or 2.0) :k return to the Home menu); Easy Access USB; Hardware Integration Pocket 			
Standard software Control panel Power Dimensions (w x d x h) Weight Printer management	Windows 8, Windows 7 SP1+, Winc drive, or Internet connection; Dedi microsoft.com. Mac OS X v10.6.8, or network connection (Operating) HP PCL 6 Discrete Printer Driver, Mi 10.9 cm colour LCD with resistive t Requirements: Input Voltage: 2201 Out of package: C2244A: 1095 x ( Packaged: C2244A: 1095 x ( Packaged: C2244A: 856 x 760 x S Out of package: C2244A: 86.8 4 kg) DT) HP Web Jetadmin; HP Utility (Mac) C2244A: Identity Management: Kc	dows Vista, Windows Server 2003 (SP1+), Windows Ser tated universal serial bus (USB 1.1 or 2.0), or network of SX 10.7.5 Lion, OS X 10.8 Mountain Lion; 1 GB of avail system compatible hardware system requirements see ac SW Link to Web (Mac Installer), Windows Installer ouchscreen; rotating (adjustable angle) display; illumin to 240 VAC, 50/60 Hz, 5.5 A 548 x 635 mm; <b>D7F69A</b> : 1095 x 715 x 1040 mm; <b>C2</b> 478 mm; <b>D7F69A</b> : 856 x 790 x 1368 mm; <b>C2245A</b> : 8 <b>D7P69A</b> : 108.4 kg; <b>C2245A</b> : 108.4 kg; <b>P69A</b> : 130.87 kg; <b>C2245A</b> : 130.67 kg; erberos authentication, LDAP authentication, 1000 use (cate, Pre-Shared Key, and Kerberos authentication, Sup	onnection; 200 MB available hard dis lable hard-disk space; CD-ROM or DV apple.com) ated capacitive Home button (for quic 245A: 1095 x 715 x 1040 mm; 56 x 790 x 1368 mm; r PIN codes, optional HP Access Contr oports WJA-10 IPsec configuration Pic	k space; Operating system compatible hardware system requirements see D drive, or Internet connection; Dedicated universal serial bus (USB 1.1 or 2.0) k return to the Home menu); Easy Access USB; Hardware Integration Pocket			
Standard software Control panel Power Dimensions (w x d x h) Weight Printer management	Windows 8, Windows 7 SP1+, Winc drive, or Internet connection; Dedi microsoft.com. Mac GS X 10.6.8, or network connection (Operating HP PCL 6 Discrete Printer Driver, M. 10.9 cm colour LCD with resistive t Requirements: Input Voltage: 2201 Out of package: C2244A: 1095 x ( Packaged: C2244A: 856 x 760 x 9 Out of package: C2244A: 1055 x ( Packaged: C2244A: 856 x 760 x 9 Det fpackage: C2244A: 95 x 760	dows Vista, Windows Server 2003 (SP1+), Windows Ser cated universal serial bus (USB 1.1 or 2.0), or network or SX 10.7.5 Lion, QS X 10.8 Mountain Lion; 1 G B di avai system compatible hardware system requirements see ac SW Link to Web (Mac Installer), Windows Installer ouchscreen; rotating (adjustable angle) display; Illumini to 240 VAC, 50/50 Hz, 5.5 A 548 x 635 mm; <b>D7P69A:</b> 1095 x 715 x 1040 mm; <b>CZ</b> 778 mm; <b>D7P69A:</b> 155 x 70 x 1368 mm; <b>CZ245A:</b> 8 <b>D7P69A:</b> 10.8.4 kg; <b>CZ245A:</b> 10.6.7 kg; <b>P69A:</b> 130.87 kg; <b>CZ245A:</b> 130.67 kg; erberos authentication, LDAP authentication, 1000 use icate, Pre-Shared Key, and Kerberos authentication, Suj ta: Storage Encryption, SL/TLS, Encrypted Credential	onnection; 200 MB available hard dis lable hard-disk space; CD-ROM or DV apple.com) ated capacitive Home button (for quic 245A: 1095 x 715 x 1040 mm; 56 x 790 x 1368 mm; r PIN codes, optional HP Access Contr opports WJA-10 IPsec configuration Plu ; Device: Security lock slot, USB port	k space; Operating system compatible hardware system requirements see D drive, or Internet connection; Dedicated universal serial bus (USB 1.1 or 2.0) :: k return to the Home menu); Easy Access USB; Hardware Integration Pocket or and 3rd party advanced authentication solutions (e.g., badge readers); ug-in, 802.1X authentication (EAP-PEAP, EAP-TLS), SNMPv3, HTTPS, disablement, Hardware Integration Pocket for security solutions; Security			
Standard software Control panel Power Dimensions (w x d x h) Weight Printer management	Windows 8, Windows 7 SP1+, Winc drive, or Internet connection; Dedi microsoft.com. Mac GS Xv 10.6.8, or network connection (Operating HP PCL 6 Discrete Printer Driver, M. 10.9 cm colour LCD with resistive t Requirements: Input Voltage: 220 Out of package: C2244A: 1095 x / Packaged: C2244A: 856 x 760 x 9 Out of package: C2244A: 1085 x / Packaged: C2244A: 88.84 kg; D7I HP Web Jetadmin; HP Utility (Mac) C2244A: Identity Management: K Network: IPSec/firewall with Certificates, Access Control List; Da Management: Compatible with HP	dows Vista, Windows Server 2003 (SP1+), Windows Ser cated universal serial bus (USB 1.1 or 2.0), or network of SX 10.7, 5L ion, OS X 10.8 Mountain Lion; 1 G 60 dava system compatible hardware system requirements see ac SW Link to Web (Mac Installer), Windows Installer ouchscreen; rotating (adjustable angle) display; Illumin: to 240 VAC, 50/60 Hz, 5.5 A 548 × 635 mm; <b>D7P69A</b> : 1095 × 715 × 1040 mm; <b>CZ2</b> 478 mm; <b>D7P69A</b> : 856 × 790 × 1368 mm; <b>CZ245A</b> : 8 <b>D7P69A</b> : 108.4 kg; <b>CZ245A</b> : 108.4 kg; <b>P69A</b> : 130.87 kg; <b>CZ245A</b> : 130.67 kg; erberos authentication, LDAP authentication, 1000 use icate, Pre-Shared Key, and Kerberos authentication, Su ta: Storage Encryption, SSL/TLS, Encrypted Credentials Imaging & Printing Security Center; <b>D7P69A</b> : Identity 1	onnection; 200 MB available hard dis lable hard-disk space; CD-ROM or DV apple.com) ated capacitive Home button (for quic 2458: 1095 x 715 x 1040 mm; 56 x 790 x 1368 mm; r PIN codes, optional HP Access Contr oports WIA-10 IPsec configuration PL ganagement: Kerberos authenticatio	k space; Operating system compatible hardware system requirements see D drive, or Internet connection; Dedicated universal serial bus (USB 1.1 or 2.0) :k return to the Home menu); Easy Access USB; Hardware Integration Pocket col and 3rd party advanced authentication solutions (e.g., badge readers); ug-in, 802.1X authentication (EAP-PEAP EAP-TLS), SNMPV3, HTTPS, disablement, Hardware Integration Pocket for security solutions; Security n, LDAP authentication; 1000 user PIN codes, optional HP Access Control and			
Standard software Control panel Power Dimensions (w x d x h) Weight Printer management	Windows 8, Windows 7 SP1+, Winc drive, or Internet connection; Dedi microsoft.com. Mac OS X v10.6.8, or network connection (Operating HP PCL 6 Discrete Printer Driver, Mi 10.9 cm colour LCD with resistive t Requirements: Input Voltage: 2201 Out of package: C2244A: 1095 x ( Packaged: C2244A: 180.84 kg) D1 HP Web Jetadmin; HP Utility (Mac) C2244A: Identity Management: K Network: IPSec/firewall with HP Management: Compatible with HP ard party advanced authentication	dows Vista, Windows Server 2003 (SP1+), Windows Ser tated universal serial bus (USB 1.1 or 2.0), or network of SX 10.7.5 Lion, OS X 10.8 Mountain Lion; 1 GB of avail system compatible hardware system requirements see ac SW Link to Web (Mac Installer), Windows Installer ouchscreen; rotating (adjustable angle) display; illumini to 240 VAC, 50/60 Hz, 5.5 A 548 x 635 mm; <b>D7P69A</b> : 1095 x 715 x 1040 mm; <b>CZ</b> 78 mm; <b>D7P69A</b> : 856 x 790 x 1368 mm; <b>CZ245A</b> : 8 <b>D7P69A</b> : 108.4 kg; <b>CZ245A</b> : 108.4 kg; <b>P69A</b> : 130.87 kg; <b>CZ245A</b> : 130.67 kg; erberos authentication, LDAP authentication, 1000 use icate, Pre-Shared Key, and Kerberos authentication, Suj ta: Storage Encryption, SSL/TLS, Encrypted Credentials Imaging & Printing Security Center; <b>D7P69A</b> : Identity I solution (e.g., badge readers); Network: IPSec/fireval	onnection; 200 MB available hard dis lable hard-disk space; CD-ROM or DV apple.com) ated capacitive Home button (for quic <b>245A:</b> 1095 x 715 x 1040 mm; 56 x 790 x 1368 mm; r PIN codes, optional HP Access Contr ports WJA-10 IPsec configuration PL ; Device: Security lock slot, USB port + Management: Kerberos authenticatio uith Certificate, Pre-Shared Key, and	k space; Operating system compatible hardware system requirements see D drive, or Internet connection; Dedicated universal serial bus (USB 1.1 or 2.0), k return to the Home menu); Easy Access USB; Hardware Integration Pocket			
Standard software Control panel Power Dimensions (w x d x h) Weight Printer management	Windows 8, Windows 7 SP1+, Winc drive, or Internet connection; Dedi microsoft.com. Mac GS X v10.6.8, or network connection (Operating HP PCL 6 Discrete Printer Driver, M. 10.9 cm colour LCD with resistive t Requirements: Input Voltage: 220 Out of package: C2244A: 1095 x 6 Packaged: C2244A: 1055 x 6 Packaged: C2244A: 856 x 760 x 9 Out of package: C2244A: 1075 x 6 Packaged: C2244A: 88.84 kg; D7 HP Web Jetadmin; HP Utility (Mac) C2244A: Identity Management: K. Network: IPSec/firewall with Certifi Certificates, Access Control List; Da Management: Compatible with HP 3rd party advanced authentication 802.1X authentication (EAP-PEAP,	dows Vista, Windows Server 2003 (SP1+), Windows Ser tated universal serial bus (USB 1.1 or 2.0), or network of SX 10.7.5 Lion, OS X 10.8 Mountain Lion; 1 GB of avail system compatible hardware system requirements see ac SW Link to Web (Mac Installer), Windows Installer ouchscreen; rotating (adjustable angle) display; illumini to 240 VAC, 50/60 Hz, 5.5 A 548 x 635 mm; <b>D7P69A</b> : 1095 x 715 x 1040 mm; <b>CZ</b> 78 mm; <b>D7P69A</b> : 856 x 790 x 1368 mm; <b>CZ245A</b> : 8 <b>D7P69A</b> : 108.4 kg; <b>CZ245A</b> : 108.4 kg; <b>P69A</b> : 130.87 kg; <b>CZ245A</b> : 130.67 kg; erberos authentication, LDAP authentication, 1000 use icate, Pre-Shared Key, and Kerberos authentication, Suj ta: Storage Encryption, SSL/TLS, Encrypted Credentials Imaging & Printing Security Center; <b>D7P69A</b> : Identity I solution (e.g., badge readers); Network: IPSec/fireval	onnection; 200 MB available hard dis lable hard-disk space; CD-ROM or DV apple.com) ated capacitive Home button (for quic 245A: 1095 x 715 x 1040 mm; 56 x 790 x 1368 mm; r PIN codes, optional HP Access Contr ports WIA-10 IPsec configuration PI ;; Device: Security lock slot, USB port 1 Management: Kerberos authenticatio I with Certificate, Pre-Shared Key, and Lisk; Data: Storage Encryption, Secur	k space; Operating system compatible hardware system requirements see D drive, or Internet connection; Dedicated universal serial bus (USB 1.1 or 2.0), k return to the Home menu); Easy Access USB; Hardware Integration Pocket 0 and 3rd party advanced authentication solutions (e.g., badge readers); ug-in, 802.1X authentication (EAP-PEAP EAP-TLS), SNMPV3, HTTPS, disablement, Hardware Integration Pocket For security solutions; Security n, LDAP authentication, 1000 user PIN codes, optional HP Access Control and Kerberos authentication, Supports WJA-10 IPsec configuration Plug-in, e Frase, SSL/TLS, Encrypted Credentials; Device: Security lock slot, USB port			
Standard software Control panel Power Dimensions (w x d x h) Weight Printer management Security management	<ul> <li>Windows 8, Windows 7 SP1+, Winc drive, or Internet connection; Dedi microsoft.com. Mac GS Xv10.6.8, or network connection (Operating)</li> <li>HP PCL 6 Discrete Printer Driver, M.</li> <li>10.9 cm colour LCD with resistive t</li> <li>Requirements: Input Voltage: 220</li> <li>Out of package: C2244A: 1095 xt</li> <li>Packaged: C2244A: 1095 xt</li> <li>Packaged: C2244A: 1055 xt</li> <li>Packaged: C2244A: 1</li></ul>	dows Vista, Windows Server 2003 (SP1+), Windows Server 2003 (SP1+), Windows Server 2003 (SP1+), Windows Server 2010 (St 10.7, 51.00, QS 10.8 Mountain Lion; 1 G 60 dava system compatible hardware system requirements see ac SW Link to Web (Mac Installer), Windows Installer ouchcreen; rotating (adjustable angle) display; Illumin: to 240 VAC, 50/60 Hz, 5.5 A 548 × 635 mm; <b>D7P69A</b> : 1095 × 715 × 1040 mm; <b>CZ2</b> 458 × 635 mm; <b>D7P69A</b> : 1095 × 715 × 1040 mm; <b>CZ2</b> 478 mm; <b>D7P69A</b> : 856 × 790 × 1368 mm; <b>CZ245A</b> : 8 <b>D7P69A</b> : 108.4 kg; <b>P69A</b> : 130.87 kg; <b>CZ245A</b> : 130.67 kg; erberos authentication, LDAP authentication, 1000 use icate, Pre-Shared Key, and Kerberos authentication, Suf TLas, Enrrypted Credentials Imaging & Printing Security Center; <b>D7P69A</b> : identify solutions (e.g., badge readers); Network: IPSec/firewal EAP-TLS), SMMP3, HTTPS, Certificates, Access Control Pocket for security solutions; Security Management C	onnection; 200 MB available hard dis lable hard-disk space; CD-ROM or DV apple.com) ated capacitive Home button (for quic 245A: 1095 x 715 x 1040 mm; 56 x 790 x 1368 mm; r PIN codes, optional HP Access Contr sports WJA-10 IPsec configuration PL Management: Kerberos authenticatio I with Certificate, Pre-Shared Key, and I with Certificate, Pre-Shared Key, and ompatible with HP Imaging & Printing	k space; Operating system compatible hardware system requirements see D drive, or Internet connection; Dedicated universal serial bus (USB 1.1 or 2.0) :: k return to the Home menu); Easy Access USB; Hardware Integration Pocket :: gain, 80.2.1X authentication (EAP-PEAP EAP-TLS), SNMPV3, HTTPS, disablement, Hardware Integration Pocket For security solutions; Security n, LDAP authentication, 1000 user PIN codes, optional HP Access Control and Kerberos authentication, Supports WJA-10 IPsec configuration Plug-in, e Frase, SSL/TLS, Encrypted Credentials; Device: Security lock slot, USB port			
Standard software Control panel Power Dimensions (w x d x h) Weight Printer management Security management	Windows 8, Windows 7 SP1+, Winc drive, or Internet connection; Dedi microsoft.com. Mac GS x 1016.8, or network connection (Operating) HP PCL 6 Discrete Printer Driver, M. 10.9 cm colour LCD with resistive t Requirements: Input Voltage: 2201 Out of package: C2244A: 1095 x 1 Packaged: C2244A: 8056 x 760 x 9 Out of package: C2244A: 76.1 kg; Packaged: C2244A: 88.84 kg; D71 HP Web Jetadmin; HP Utility (Mac) C2244A: Identity Management: K Network: IPSec/firewall with Certifi Certificates, Access Control List; Db Management: Compatible with HP 3rd party advanced authentication 802.1X authentication (EAP-PEAP, disablement, Hardware Integration Operating temperature: 10 to 32.5	dows Vista, Windows Server 2003 (SP1+), Windows Ser tated universal serial bus (USB 1.1 or 2.0), or network of SX 10.7.5 Lion, OS X 10.8 Mountain Lion; 1 G B of avail system compatible hardware system requirements see a SW Link to Web (Mac Installer), Windows Installer ouchscreen; rotating (adjustable angle) display; Illumini to 240 VAC, 50/60 Hz, 5.5 A 548 x 633 mm; <b>D7P69A</b> : 1095 x 715 x 1040 mm; <b>CZ2</b> 778 mm; <b>D7P69A</b> : 856 x 790 x 1368 mm; <b>CZ245A</b> : 8 <b>D7P69A</b> : 10.8.4 kg; <b>CZ245A</b> : 10.8.4 kg; <b>P69A</b> : 130.87 kg; <b>CZ245A</b> : 130.67 kg; erberos authentication, LDAP authentication, 1000 use (cate, Pre-Shared Key, and Kerberos authentication, Suj tat: Storage Encryption, SSL7LTS, Encrypted Credential Imaging & Printing Security Center; <b>D7P69A</b> : Identity I solutions (e.g., badge readers); Network: IPSec/firewal EAP-TLS), SNMPV3, HTTPS, Certificates, Access Control Pocket for security solutions; Security Management: C 9°C. Recommended operating temperature: 10 to 32.5' 0% RH	onnection; 200 MB available hard dis lable hard-disk space; CD-ROM or DV apple.com) ated capacitive Home button (for quic 245A: 1095 x 715 x 1040 mm; 56 x 790 x 1368 mm; r PIN codes, optional HP Access Contr sports WJA-10 IPsec configuration PL Management: Kerberos authenticatio I with Certificate, Pre-Shared Key, and I with Certificate, Pre-Shared Key, and ompatible with HP Imaging & Printing	k space; Operating system compatible hardware system requirements see D drive, or Internet connection; Dedicated universal serial bus (USB 1.1 or 2.0) :k return to the Home menu); Easy Access USB; Hardware Integration Pocket 			
Standard software Control panel Power Dimensions (w x d x h) Weight Printer management Security management Operating environment Acoustics	Windows 8, Windows 7 SP1+, Winc drive, or Internet connection; Dedi microsoft.com. Mac GS Xv 10.6.8, or network connection (Operating HP PCL 6 Discrete Printer Driver, M. 10.9 cm colour LCD with resistive t Requirements: Input Voltage: 220: Out of package: CZ244A: 1095 x ( Packaged: CZ244A: 1095 x ( Packaged: CZ244A: 856 x 760 x 9 Out of package: CZ244A: 1095 x ( Packaged: CZ244A: 88.84 kg; D7I HP Web Jetadmin; HP Utility (Mac) CZ244A: Identity Management: Kk Network: IPSec/firewall with Certificates, Access Control List; Da Management: Compatible with HP 3rd party advanced authentication 802.1X authentication (EAP-PEAP, disablement, Hardware Integration Operating temperature: 10 to 32.5 to 40°C. Storage humidity: 10 to 9 Acoustic Power Emissions: 7.2 B(A Acoustic Presure Emissions: 55 di	dows Vista, Windows Server 2003 (SP1+), Windows Server 2003 (SP1+), Windows Server 2003 (SP1+), Windows Server 2004 (SP1+), Windows Server 2005 X10.7, 51 Loin, QS X10.8 Mountain Lion; 1 G B of avail system compatible hardware system requirements see ac SW Link to Web (Mac Installer), Windows Installer ouchscreen; rotating (adjustable angle) display; illumin: to 240 VAC, 50/60 Hz, 5.5 A 548 × 635 mm; <b>D7P69A</b> : 1095 × 715 × 1040 mm; <b>CZ2</b> 478 mm; <b>D7P69A</b> : 856 × 790 × 1368 mm; <b>CZ245A</b> : 8 <b>D7P69A</b> : 108.4 kg; <b>CZ245A</b> : 108.4 kg; <b>P69A</b> : 130.87 kg; <b>CZ245A</b> : 130.67 kg; erberos authentication, LDAP authentication, 1000 use (cate, Pre-Shared Key, and Kerberos authentication, SU ta: Storage Encryption, SSL/TLS, Encrypted Credentials Imaging & Printing Security Center; <b>D7P69A</b> : Identity i solutions (e.g., badge readers): Network: IPSec/firewal EAP-TLS), SNMP43, HTTPS, Cerlitates, Access Control Pocket for security solutions; Security Management: C*C. Recommended operating temperature: 10 to 32.5' 096 RH	onnection; 200 MB available hard dis lable hard-disk space; CD-ROM or DV apple.com) ated capacitive Home button (for quic <b>r45A:</b> 1095 x 715 x 1040 mm; 56 x 790 x 1368 mm; r PIN codes, optional HP Access Contr oports WJA-10 IPsec configuration PIL ; Device: Security lock slot, USB port Management: Kerberos authentricatio List; Data: Storage Encryption, Secur List; Data: Storage Encryption, Secur ompatible with HP Imaging & Printing PC. Operating humidity: 10 to 80% RH	k space; Operating system compatible hardware system requirements see D drive, or Internet connection; Dedicated universal serial bus (USB 1.1 or 2.0) :k return to the Home menu); Easy Access USB; Hardware Integration Pocket 			
Standard software Control panel Power Dimensions (w x d x h) Weight Printer management Security management Operating environment Acoustics	<ul> <li>Windows 8, Windows 7 SP1+, Winc drive, or Internet connection; Dedi microsoft.com. Mac GS Xv10.6.8, or network connection (Operating)</li> <li>HP PCL 6 Discrete Printer Driver, M.</li> <li>10.9 cm colour LCD with resistive t</li> <li>Requirements: Input Voltage: 220</li> <li>Out of package: CZ244A: 1055 x ( Packaged: CZ244A: 1045 x ( Package</li></ul>	dows Vista, Windows Server 2003 (SP1+), Windows Ser cated universal serial bus (USB 1.1 or 2.0), or network of SX 10.7.5 Lion, OS X 10.8 Mountain Lion; 1 G B of avail system compatible hardware system requirements see a SW Link to Web (Mac Installer), Windows Installer ouchscreen; rotating (adjustable angle) display; Illumini to 240 VAC, 50/60 Hz, 5.5 A 548 x 633 mm; <b>D7P69A</b> : 1095 x 715 x 1040 mm; <b>CZ2</b> 778 mm; <b>D7P69A</b> : 856 x 790 x 1368 mm; <b>CZ245A</b> : 8 <b>D7P69A</b> : 108.4 kg; <b>CZ245A</b> : 108.4 kg; <b>P69A</b> : 130.87 kg; <b>CZ245A</b> : 130.67 kg; erberos authentication, LDAP authentication, 1000 use (cate, Pre-Shared Key, and Kerberos authentication, Su ta: Storage Encryption, SLTLTS, Encrypted Credential Imaging & Printing Security Center; <b>D7P69A</b> : Identity I solutions (e.g., badge readers); Network: IPSec/firewal EAP-TLS), SNMPV3, HTTPS, Certificates, Access Control Pocket for security solutions; Security Management: C 9°C. Recommended operating temperature: 10 to 32.5' 0% RH ) 3(A) Class A), EN 61000-3-2:2006 +A1:2009 +A2:2009; EN gulatory standards: IEC 60950-1:2005 +A1; ENG950	onnection; 200 MB available hard dis lable hard-disk space; CD-ROM or DV apple.com) ated capacitive Home button (for quic 245A: 1095 x 715 x 1040 mm; 56 x 790 x 1368 mm; r PIN codes, optional HP Access Contr Soft XIA-10 IPsec configuration PL Management: Kerberos authenticatio I with Certificate, Pre-Shared Key, and I with Certificate, Pre-Shared Key, and ompatible with HP Imaging & Printing YC. Operating humidity: 10 to 80% RH	k space; Operating system compatible hardware system requirements see D drive, or Internet connection; Dedicated universal serial bus (USB 1.1 or 2.0) :k return to the Home menu); Easy Access USB; Hardware Integration Pocket :k return to the Home menu); Easy Access USB; Hardware Integration Pocket :g and 3rd party advanced authentication solutions (e.g., badge readers); ug-in, 802.1X authentication (EAP-PEAP EAP-TLS), SNMPv3, HTTPS, disablement, Hardware Integration Pocket for security solutions; Security n, LDAP authentication, 1000 user PIN codes, optional HP Access Control and 1 Kerberos authentication, Supports WIA-10 IPsec configuration Plug-in, e Fraes, SSL/TLS, Encrypted Credentials; Device: Security lock slot, USB port g Security Center; <b>C2245A</b> : as D7P69A product; 1. Operating humidity recommended: 10 to 80% RH . Storage temperature: 0 EEMC Directive 2004/108/EC with CE Marking (Europe); other EMC approvals as :2011; IEC 60825-1:2007 (Class 1 Laser/Led Product); EN 60825-1:2007			
Standard software Control panel Power Dimensions (w x d x h) Weight Printer management Security management Operating environment Acoustics	Windows 8, Windows 7 SP1+, Winc drive, or Internet connection; Dedi microsoft.com. Mac GS Xv 10.6.8, or network connection (Operating HP PCL 6 Discrete Printer Driver, M. 10.9 cm colour LCD with resistive t Requirements: Input Voltage: 220: Out of package: CZ244A: 1095 x ( Packaged: CZ244A: 1085 x ( Packaged: CZ244A:	dows Vista, Windows Server 2003 (SP1+), Windows Server 2003 (SP1+), Windows Server 2003 (SP1+), Windows Server 2003 (SP1+), Windows Server 2005 X10.7, 5L ion, QS X10.8 Mountain Lion; 1 G & D dawi System compatible hardware system requirements see ac SW Link to Web (Mac Installer), Windows Installer ouchscreen; rotating (adjustable angle) display; Illumin: to 240 VAC, 50/60 Hz, 5.5 A 548 × 635 mm; <b>D7P69A</b> : 1095 × 715 × 1040 mm; <b>CZ2</b> 478 mm; <b>D7P69A</b> : 856 × 790 × 1368 mm; <b>CZ245A</b> : 8 <b>D7P69A</b> : 108.4 kg; <b>CZ245A</b> : 108.4 kg; <b>PF69A</b> : 108.8 kg; <b>CZ245A</b> : 108.4 kg; <b>PF69A</b> : 130.87 kg; <b>CZ245A</b> : 130.67 kg; erberos authentication, LDAP authentication, 1000 use (cate, Pre-Shared Key, and Kerberos authentication, SU ta: Storage Encryption, SSL/TLS, Encrypted Credentials Imaging & Printing Security Center; <b>D7P69A</b> : Identity i solutions (e.g., badge readers); Network: IPSec/firewal EAP-TLS), SNMPV3, HTTPS, Certificates, Access Control Pocket for security solutions; Security Management: C *C (C. Recommended operating temperature: 10 to 32.5' 00% RH d).	onnection; 200 MB available hard dis lable hard-disk space; CD-ROM or DV apple.com) ated capacitive Home button (for quic 245A: 1095 x 715 x 1040 mm; 56 x 790 x 1368 mm; r PIN codes, optional HP Access Contr Soft XIA-10 IPsec configuration PL Management: Kerberos authenticatio I with Certificate, Pre-Shared Key, and I with Certificate, Pre-Shared Key, and ompatible with HP Imaging & Printing YC. Operating humidity: 10 to 80% RH	k space; Operating system compatible hardware system requirements see D drive, or Internet connection; Dedicated universal serial bus (USB 1.1 or 2.0) k return to the Home menu); Easy Access USB; Hardware Integration Pocket of and 3rd party advanced authentication solutions (e.g., badge readers); ug-in, 802.1X authentication (EAP-PEAP; EAP-TLS), SNMPv3, HTTPS, disablement, Hardware Integration Pocket for security solutions; Security n, LDAP authentication, 1000 user PIN codes, optional HP Access Control and J Kerberos authentication, Supports WJA-10 IP-sec configuration Plug-in, e Erase, SSL/TLS, Encrypted Credentials; Device: Security lock slot, USB port g Security Center; <b>C2245A</b> : as D7P69A product; 4. Operating humidity recommended: 10 to 80% RH . Storage temperature: 0			
Standard software Control panel Power Dimensions (w x d x h) Weight Printer management Security management Operating environment Acoustics Certifications	Windows 8, Windows 7 SP1+, Winc drive, or Internet connection; Dedi microsoft.com. Mac GS X 10.6.8, or network connection (Operating HP PCL 6 Discrete Printer Driver, M. 10.9 cm colour LCD with resistive t Requirements: Input Voltage: 220 Out of package: <b>C2244A</b> : 1055 x ( Packaged: <b>C2244A</b> : 1055 x ( Packaged: <b>C2244A</b> : 856 x 760 x 9 Out of package: <b>C2244A</b> : 656 x 760 x 9 Packaged: <b>C2244A</b> : 88.84 kg; <b>D7</b> HP Web Jetadmin; HP Utility (Mac) <b>C2244A</b> : Identity Management: K Network: IPSec/firewall with Certificates, Access Control List; Da Management: Compatible with HP 3rd party advanced authentication 302.1X authentication (EAP-PEAP, disablement, Hardware Integration: Operating temperature: 10 to 32.5 to 40%C. Storage humidity: 10 to 9 Acoustic Pressure Emissions: 7.2 B/A Acoustic Pressure Emissions: 7.2 di A (Class 1 Laser/LED Product); G5 Ce individual countries. ENERGY STAR	dows Vista, Windows Server 2003 (SP1+), Windows Ser cated universal serial bus (USB 1.1 or 2.0), or network of SX 10.7.5 Lion, QS X 10.8 Mountain Lion; 1 G Bof avail system compatible hardware system requirements see ac SW Link to Web (Mac Installer), Windows Installer ouchscreen; rotating (adjustable angle) display; Illumini to 240 VAC, 50/50 Hz, 5.5 A 548 x 635 mm; <b>D7P69A</b> : 1095 x 715 x 1040 mm; <b>CZ</b> 278 mm; <b>D7P69A</b> : 1655 x 790 x 1368 mm; <b>CZ245A</b> : 8 <b>D7P69A</b> : 10.8.4 kg; <b>CZ245A</b> : 10.6.7 kg; <b>P69A</b> : 130.87 kg; <b>CZ245A</b> : 130.67 kg; erberos authentication, LDAP authentication, 1000 use icate, Pre-Shared Key, and Kerberos authentication, Suj ta: Storage Encryption, SSL/TLS, Encrypted Credentials Imaging & Printing Security Center; <b>D7P69A</b> : Identity i solutions (e.g., badge readers); Network: IPSec/firewal EAP-TLS), SNMPv3, HTTPS, Certificates, Access Control Pocket for security solutions; Security Management: C 9C. Recommended operating temperature: 10 to 32.5' 0% RH ) G(A) Class A), EN 61000-3-2: 2006 +A1:2009 +A2:2009; EN gualatory standards: IEC 60950-1:2005 +A1; EN60950 rtificate (Germany, Europe); IEC 62479:2010; EN 62479; Yes	onnection; 200 MB available hard dis lable hard-disk space; CD-ROM or DV apple.com) ated capacitive Home button (for quic <b>245A:</b> 1095 x 715 x 1040 mm; 56 x 790 x 1368 mm; r PIN codes, optional HP Access Contr sports WJA-10 IPsec configuration Plu ; Device: Security lock slot, USB port - WIA-10 IPsec configuration Plu ; Device: Security lock slot, USB port - Wanagement: Kerberos authenticatio uith Certificate, Pre-Shared Key, and List; Data: Storage Encryption, Secur ompatible with HP Imaging & Printing ?C . Operating humidity: 10 to 80% RF 61000-3-3 :2008; EN 55024:2010; -1: 2006 +A11:2009 +A1:2010 +A12 2:2010; Low Voltage Directive 2006/5	k space; Operating system compatible hardware system requirements see D drive, or Internet connection; Dedicated universal serial bus (USB 1.1 or 2.0) k return to the Home menu); Easy Access USB; Hardware Integration Pocket of and 3rd party advanced authentication solutions (e.g., badge readers); ug-in, 802.1X authentication (EAP-PEAP, EAP-TLS), SNMPv3, HTTPS, disablement, Hardware Integration Pocket for security solutions; Security n, LDAP authentication, 1000 user PIN codes, optional HP Access Control and J Kerberos authentication, Supports WJA-10 IP-sec configuration Plug-in, e Erase, SSL/TLS, Encrypted Credentials; Device: Security lock slot, USB port g Security Center; <b>C2245A</b> : as D7P69A product; 4. Operating humidity recommended: 10 to 80% RH. Storage temperature: 0 EMC Directive 2004/108/EC with CE Marking (Europe); other EMC approvals as :2011; IEC 60825-1:2007 (Class 1 Laser/Led Product); EN 60825-1:2007 35/EC with CE Marking (Europe); other safety approvals as required by			
Standard software Control panel Power Dimensions (w x d x h) Weight Printer management Security management Operating environment Acoustics	Windows 8, Windows 7 SP1+, Winc drive, or Internet connection; Dedi microsoft.com. Mac GS X 10.6.8, or network connection (Operating HP PCL 6 Discrete Printer Driver, M. 10.9 cm colour LCD with resistive t Requirements: Input Voltage: 220 Out of package: <b>C2244A</b> : 1055 x ( Packaged: <b>C2244A</b> : 1055 x ( Packaged: <b>C2244A</b> : 856 x 760 x 9 Out of package: <b>C2244A</b> : 656 x 760 x 9 Packaged: <b>C2244A</b> : 88.84 kg; <b>D7</b> HP Web Jetadmin; HP Utility (Mac) <b>C2244A</b> : Identity Management: K Network: IPSec/firewall with Certificates, Access Control List; Da Management: Compatible with HP 3rd party advanced authentication 302.1X authentication (EAP-PEAP, disablement, Hardware Integration: Operating temperature: 10 to 32.5 to 40%C. Storage humidity: 10 to 9 Acoustic Pressure Emissions: 7.2 B/A Acoustic Pressure Emissions: 7.2 di A (Class 1 Laser/LED Product); G5 Ce individual countries. ENERGY STAR	dows Vista, Windows Server 2003 (SP1+), Windows Ser cated universal serial bus (USB 1.1 or 2.0), or network of SX 10.7.5 Lion, OS X 10.8 Mountain Lion; 1 G B of avail system compatible hardware system requirements see ac SW Link to Web (Mac Installer), Windows Installer ouchscreen; rotating (adjustable angle) display; Illumini to 240 VAC, 50/60 Hz, 5.5 A 548 x 635 mm; <b>D7P69A</b> : 1095 x 715 x 1040 mm; <b>CZ2</b> 778 mm; <b>D7P69A</b> : 1095 x 715 x 1040 mm; <b>CZ2</b> 788 mm; <b>D7P69A</b> : 1095 x 715 x 1040 mm; <b>CZ2</b> 798 mm; <b>D7P69A</b> : 1095 x 715 x 1040 mm; <b>CZ2</b> 798 mm; <b>D7P69A</b> : 108.4 kg; <b>P69A</b> : 130.87 kg; <b>CZ245A</b> : 130.67 kg; erberos authentication, LDAP authentication, 1000 use cate, Pre-Shared Key, and Kerberos authentication, Suj ta: Storage Encryption, SSLTLS, Encrypted Credential Imaging & Printing Security Center; <b>D7P69A</b> : Identity I solutions (e.g., badge readers); Network: IPSec/firewal EAP-TLS), SNMPV3, HTTBS, Certificates, Access Control 1 Pocket for security solutions; Security Management: C 9°C. Recommended operating temperature: 10 to 32.51 0% RH 3(A) Class A), EN 61000-3-2:2006 +A1:2009 +A2:2009; EN gulatory standards: IEC 60950-1:2005 +A1; EN60950 rtificate (Germany, Europe); IEC 62479:2010; EN 62479; 2VA	onnection; 200 MB available hard dis lable hard-disk space; CD-ROM or DV apple.com) ated capacitive Home button (for quic <b>245A:</b> 1095 x 715 x 1040 mm; 56 x 790 x 1368 mm; r PIN codes, optional HP Access Contr sports WJA-10 IPsec configuration Plu ; Device: Security lock slot, USB port - WIA-10 IPsec configuration Plu ; Device: Security lock slot, USB port - Wanagement: Kerberos authenticatio uith Certificate, Pre-Shared Key, and List; Data: Storage Encryption, Secur ompatible with HP Imaging & Printing ?C . Operating humidity: 10 to 80% RF 61000-3-3 :2008; EN 55024:2010; -1: 2006 +A11:2009 +A1:2010 +A12 2:2010; Low Voltage Directive 2006/5	k space; Operating system compatible hardware system requirements see D drive, or Internet connection; Dedicated universal serial bus (USB 1.1 or 2.0 :k return to the Home menu); Easy Access USB; Hardware Integration Pocket 			

http://www.hp.com/uk

© Copyright 2013 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.