


Key **Features**

- Ultrawide 21:9 ratio, 105" screen in 5K resolution for enhanced multitasking and collaboration
- Seamless video conferencing with comprehensive 8-mic array
- Pen-on-paper writing experience with Ultra Fine Touch Technology, up to 40 touch points
- Effortless wireless screen sharing of up to 9 devices with vCast
- 2 USB-C ports for enhanced productivity



Product **Description**

The ViewBoard IFP105S delivers an expansive interactive experience with its 21:9 aspect ratio and stunning 5K resolution. The 105" display allows for multitasking with split-screen functionality, enhancing collaboration and productivity. With highly responsive 40-point touch capabilities, every input is registered naturally and intuitively. Enjoy seamless wireless screen casting and sharing through vCast. Designed for both in-person and hybrid collaboration, the ViewBoard IFP105S is an ideal solution for meeting rooms, enabling seamless presentations, ideation, and decision-making.





Visit Us

www.viewsonic.com

PM	viewsonic.com/eu/products/sheet/IFP105S		
DISPLAY		POWER	
Panel Size:	105"	Voltage:	100-240VAC +/- 10% Wide Range
Panel Type:	TFT LCD Module with DLED	Consumption:	On: 275W(typ.) / Off: <0.5W
ranei Type.	Backlight, VA	ERGONOMICS	
Display Area (mm):	2449.92(H) x 1033.56 (V) (104.6"diagonal)	Wall Mount (VESA®):	1000 x 400
Aspect Ratio:	21:9	OPERATING CONDITIONS	
Resolution:	WUHD 5120x2160(Pixels)	Temperature (° C):	0°C to 40°C
Colors:	1.07B colors	Humidity:	20% ~ 80% RH non-condensing
Brightness:	400 nits (typ.)	DIMENSIONS (W X H X D)	
Contrast Ratio:	4000:1(Typ.) 5000:1(Min. with DCR enabled)	Physical (inch / mm):	98.71 x 44.49 x 4.06 in / 2507.2 x 1130.1 x 103.2mm
Response Time:	6.5ms	Packaging (inch / mm):	105.19 x 51.38 x 11.02 in / 2668 x 1305 x 280mm
Viewing Angles:	H = 178, V = 178 (Typ.)	WEIGHT	
Backlight Life:	30,000 Hours (Min.)	Net (lb / kg):	201.5lb/91.4Kg
Surface Treatment:	Panel Hard Coating 3H Glass Anti-Glare 7H	Gross (lb / kg):	225.1lb/115.7Kg
Bezel:	19.5/19.5/29.8/41.2 mm	REGULATIONS	
Orientation:	Landscape	cTUVus,FCC/ICES003, LBL(low EMC, CB, RoHS Green BOM, R- EEL, WEEE, BSMI	blue light filter), FF(Flicker free), CE oHS DoC, ErP, REACH SVHC List, DoC,
PLATFORM		ENERGY STAR VERSION	
Processor:	Octa-Core CPU (A76*4 + A55*4)	ES 8.0	
RAM:	8GB LPDDR	PACKAGE CONTENTS	
Storage:	64GB eMMC	3m power cord by ship area	
TOUCH			ton,
Type/ Tech:	IR Recognition	2. Remote control with AAA battery	
Touch Resolution:	32767 x 32767	3. 3m touch USB cable	
Touch Point:	Windows: 40 Android: 20	4. Touch pen x 2	
INPUT		5. Quick Start Guide + Complia	nce statement
HDMI:	x4 (Rear x3 :HDMI 2.0 with CEC; Rear x 1 HDMI 2.1 with CEC)	6. RS232 adapter 7. Clamp x 5	
DisplayPort:	1	·	
Audio:	1	8. Camera Plate	
MIC(Microphone):	Built-in 8 Array Microphone	9. Screw x 6 (2 for camera , 4 f	or wall mount)
RS232:	1	10. HDMI cable 3m	
OPS:	X1 OPS Slot		
WiFi:	X1 Module Slot		
OUTPUT			
HDMI:	1		
Audio:	1		
SPDIF:	1		
LAN	1		
LAIN	V2 (inv1: autv1: 1000m for		
RJ45:	X2 (inx1; outx1; 1000m for Android/PC; 100m for type-C)		
USB			
Type A:	USB2.0 x 1 (Bottom) (for FW upgrade) USB3.0 x 6 (Top x 2 + Rear x 2 +		
Tura Di	Front x2), all support Smart USB		
Type B:	3 (Bottom x 1; Rear x 2) 2 [Rearx1: PD65W(65W with OPS, 100W without OPS) + DP1.2 + Data +		
Type C:	10M/100M sharing; Front x1:PD15W + DP1.2 + Data + 10M/100M sharing]		
SPEAKERS		_	
16W x 2 + 15W x 1 subwoofer			
TOP CAMERA PLATE			
Yes			
EMBEDDED OS		_	
Android 13			
BUNDLE SOFTWARE			
Wireless Presentation with Touch Feedback: Viewboard Cast:	Single screen sharing with Chromecast or up to 9 devices with vCast Sender or Airplay. No additional download is required to cast using Airplay or Chromecast.		
SPECIAL FEATURES			
All in and USB parts	Vac		

Copyright © ViewSonic Corporation 2000-2023. All rights reserved.

All-in-one USB port:

Light Sensor:

One Click to Cloud Drive:
Simple LAN sharing between IFP and slot-in device:

Yes

(10/100/1000M) (USB Type-C 10/100, Android & PC 10/100/1000)