Key Features

- 3rd generation laser phosphor technology with up to a 30,000hour lifespan
- Designed for Xbox with 1440p
 @ 120Hz for an unrivaled
 gaming experience
- True 4K HDR immersive visual experience with up to a 300" screen
- 3,500 ANSI Lumens offering bright images in any environment
- High native contrast ratio through 0.65" DMD chip



Product **Description**

Transform any home into a cinematic experience with the LX700-4K laser home projector. Adopting the 3rd generation laser phosphor technology with 3,500 ANSI Lumens and up to 30,000 hours lifespan, it delivers vibrant and bright visuals without the need for lamp replacement. This projector is designed for Xbox, supporting Xbox-exclusive resolution and refresh rate combinations for a seamless gaming experience. With the support of 1440p at a 120Hz refresh rate, it strikes a perfect balance of visual quality and fluidity that gamers love. Experience enhanced visual depth on a screen size of up to 300" with a high native contrast ratio through 0.65" DMD chip. The LX700-4K features V lens shift, 1.36x optical zoom, H/V keystone, and 4 corner adjustment, allowing you to easily set up a big screen tailored to your preferences.



- 1. Lens Shift Control Knob
- 2. Zoom Ring
- 3. Keypad







4. Top IR 5. Front IR 6. Lens 7. Focus Ring 11. 12V Trigger 12. Zoom Ring 13. Audio Out 14. DC In

Visit Us

www.viewsonic.com



SPECIFICATION

OTHERS

SPECIFICATION		OTHERS	
Native Resolution:	3840x2160	Power Supply Voltage:	Power adaptor: Input: 100~240V Output: 19.5VDC / 9.23A
Brightness:	3500 (ANSI Lumens)		
Contrast Ratio: Display Color:	3000000:1 1.07 Billion Colors	Power Consumption:	Normal: 180W Standby: <0.5W
Light Source Type:	Laser Phosphor	Operating Temperature:	0~40°C
Light Source Life (hours) with		Carton:	Brown
Normal Mode:	20000	Net Weight:	3.30kg
Light Source Life (hours) with SuperEco Mode:	30000 (Eco)	Gross Weight:	4.70kg
Lens:	F=2.51-2.93, f=15.985- 21.423mm	Dimensions (WxDxH) with Adjustment Foot:	286x216x129mm
Projection Offset:	137%+/-10%	Packing Dimensions:	400x280x155mm
Throw Ratio:	1.06-1.45	OSD Language:	English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, Arabic, Vietnamese, Greek, Norsk. Total 23 languages
Optical Zoom:	1.36x		
Digital Zoom:	0.8x-2.0x		
Image Size:	30"-300"		
Throw Distance:	1-7m □(100"@2.35m)		
Keystone:	H:+/-30° , V:+/-30°		
Lens Shift V. Range:	+15%, -0%	User Guide Language:	English, S-Chinese, T-Chinese, Indonesian, Finish, French, German, Italian, Japanese, Korean, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Arabic, Czech, Thai, Vietnamese, total 20 languages
Audible Noise (Normal):	31dB		
Audible Noise (Eco):	26dB		
Input Lag:	4.2ms		
Resolution Support:	VGA(640 x 480) to 4K(3840 x 2160)		
HDTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 2160p	STANDARD ACCESSORY	
Horizontal Frequency:	15K-135KHz	Power Cord:	1
Vertical Scan Rate:	23-240Hz	Remote Control:	1 (w/ backlit)
INPUT		QSG:	Yes
HDMI:	2		
	(HDMI 2.0/ HDCP 2.2)	Lens Cover:	Yes (CN Only)
OUTPUT	4	Warranty Card:	Yes (CN Only)
Audio-out (3.5mm):	1 (-100)	OPTIONAL ACCESSORY	DIWMK 007
Audio-out (HDMI ARC):	1 (eARC) (Share with HDMI Input)	Wall/Ceiling Mount: Carry Bag:	PJ-WMK-007 PJ-CASE-008
Speaker:	15W		
USB Type A (Power):	1 (5V/1.5A)		
12V Trigger (3.5mm):	1		
CONTROL			
RS232 (DB 9-pin male):	1		
USB Type A (Services):	1 (share with USB A Output)		

