



APC NetShelter Switched Rack PDU, 1U, 1PH, 3.7kW 230V 16A or 3.3kW 208V 16A, 8 C13 outlets, C20 cord

AP7921B

Overview	•
----------	---

Presentation	This APC Switched Rack PDU power distribution unit has a wide range of standardized PDU features
	that increase network efficiency, manageability and functionality. The output and input connections
	are (8)C13. Network management capabilities allow you to configure and manage rack PDUs from
	remote locations. It has has a local current monitoring display that gives a visible warning in case of an

overload. The remote individual outlet control provides real-time monitoring of connected loads. It has a multi-tier user access that enables you to restrict unauthorized use of outlets. This rack has a single input power source making it easy to install.

Lead time Usually in Stock

Main

Main input voitage	200 V
	208 V
	230 V

PDU type	Switched
Main Output Voltage	208 V

Input Connection Type IEC 60320 C20 Number of rack unit 1U

Cable length 2.50 m

Number of cables

Provided equipment Installation guide

Rack mounting brackets

Black

Physical

Colour

Colour	DIACK
Height	4.4 cm
Width	44.5 cm
Depth	10.8 cm
Net weight	2.27 kg
Mounting location	Front Rear
Mounting preference	No preference
Mounting mode	Rack-mounted

Mounting position

ı	r	٦	n		1 T
		•	ν	·	4 L

[In] rated current	16 A
Permissible voltage	200240 V
Input current limits	20 A
Load capacity	3680 VA
Network frequency	50/60 Hz

Output

Number of power socket outlets 8 IEC 60320 C13

Conformance

Product certifications	cUL listed CE CSA GOST IRAM MIC UL listed VDE VCCI
Standards	EN 55022 class A EN 55024 EN 61000-3-2 EN 61000-3-3

Environmental

Ambient air temperature for operation	045 °C
Relative humidity	095 %
Operating altitude	010000 ft
Ambient air temperature for storage	-2565 °C
Storage Relative Humidity	095 %
Storage altitude	0.0015240.00 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7 cm
Package 1 Width	34.3 cm
Package 1 Length	47 cm
Package 1 Weight	3.45 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Circularity Profile	End of Life Information	
Optimized Energy Efficiency	Energy efficient product	
Take-back	Take-back program available	
Contractual warranty		
Warranty	2 years repair or replace	

Recommended replacement(s)