

BUSINESS PRODUCTIVITY MONITOR Summit MS321UP

BE YOUR WINDOW TO THE WORLD







SPECIFICATIONS

PANEL SIZE 32" (81.29 cm) PANEL RESOLUTION 3840x2160 (UHD) REFRESH RATE 60Hz RESPONSE TIME 4ms (GTG) PANEL TYPE IPS BRIGHTNESS (NITS) 400 nits (TYP) VESA Certified DisplayHDR 6 VIEWING ANGLE 178°(H) / 178°(V) ASPECT RATIO 16:9 CONTRAST RATIO 1000:1 (TYP) SRGB 136% sRGB / 95% DCI-P3 (CIE 1976) ACTIVE DISPLAY AREA (MM) 708.48 (H) x 398.52 (V) PIXEL PITCH (H X V) 0.1845(H)x0.1845(V) SURFACE TREATMENT Anti-glare DISPLAY COLORS 1.07 Billion COLOR BIT 10 bits (8 bits + FRC) VIDEO PORTS 1x DP(1.2) 2x HDMI (2.0b) 1x Type C (DP a mode with PD : 5V/3A)	
REFRESH RATE 60Hz RESPONSE TIME 4ms (GTG) PANEL TYPE IPS BRIGHTNESS (NITS) 400 nits (TYP) VESA Certified DisplayHDR 6 VIEWING ANGLE 178°(H) / 178°(V) ASPECT RATIO 16:9 CONTRAST RATIO 1000:1 (TYP) SRGB 136% sRGB / 95% DCI-P3 (CIE 1976) ACTIVE DISPLAY AREA (MM) 708.48 (H) x 398.52 (V) PIXEL PITCH (H X V) 0.1845(H)x0.1845(V) SURFACE TREATMENT Anti-glare DISPLAY COLORS 1.07 Billion COLOR BIT 10 bits (8 bits + FRC) VIDEO PORTS 1x DP(1.2) 2x HDMI (2.0b) 1x Type C (DP a mode with PD : 5V/3A)	100
RESPONSE TIME 4ms (GTG) PANEL TYPE IPS BRIGHTNESS (NITS) 400 nits (TYP) VESA Certified DisplayHDR (CONTRAST RATIO VIEWING ANGLE 178°(H) / 178°(V) ASPECT RATIO 16:9 CONTRAST RATIO 1000:1 (TYP) sRGB 136% sRGB / 95% DCI-P3 (CIE 1976) ACTIVE DISPLAY AREA (MM) 708.48 (H) x 398.52 (V) PIXEL PITCH (H X V) 0.1845(H)x0.1845(V) SURFACE TREATMENT Anti-glare DISPLAY COLORS 1.07 Billion COLOR BIT 10 bits (8 bits + FRC) VIDEO PORTS 1x DP(1.2) 2x HDMI (2.0b) 1x Type C (DP a mode with PD : 5V/3A)	
PANEL TYPE IPS BRIGHTNESS (NITS) 400 nits (TYP) VESA Certified DisplayHDR (E VIEWING ANGLE 178°(H) / 178°(V) ASPECT RATIO 16:9 CONTRAST RATIO 1000:1 (TYP) sRGB 136% sRGB / 95% DCI-P3 (CIE 1976) ACTIVE DISPLAY AREA (MM) 708.48 (H) x 398.52 (V) PIXEL PITCH (H X V) 0.1845(H)x0.1845(V) SURFACE TREATMENT Anti-glare DISPLAY COLORS 1.07 Billion COLOR BIT 10 bits (8 bits + FRC) VIDEO PORTS 1x DP(1.2) 2x HDMI (2.0b) 1x Type C (DP a mode with PD : 5V/3A)	00
BRIGHTNESS (NITS) 400 nits (TYP) VESA Certified DisplayHDR 6 VIEWING ANGLE 178°(H) / 178°(V) ASPECT RATIO 16:9 CONTRAST RATIO 1000:1 (TYP) sRGB 136% sRGB / 95% DCI-P3 (CIE 1976) ACTIVE DISPLAY AREA (MM) 708.48 (H) x 398.52 (V) PIXEL PITCH (H X V) 0.1845(H)x0.1845(V) SURFACE TREATMENT Anti-glare DISPLAY COLORS 1.07 Billion COLOR BIT 10 bits (8 bits + FRC) VIDEO PORTS 1x DP(1.2) 2x HDMI (2.0b) 1x Type C (DP a mode with PD : 5V/3A)	00
VIEWING ANGLE 178°(H) / 178°(V) ASPECT RATIO 16:9 CONTRAST RATIO 1000:1 (TYP) sRGB 136% sRGB / 95% DCI-P3 (CIE 1976) ACTIVE DISPLAY AREA (MM) 708.48 (H) x 398.52 (V) PIXEL PITCH (H X V) 0.1845(H)x0.1845(V) SURFACE TREATMENT Anti-glare DISPLAY COLORS 1.07 Billion COLOR BIT 10 bits (8 bits + FRC) VIDEO PORTS 1x DP(1.2) 2x HDMI (2.0b) 1x Type C (DP a mode with PD : 5V/3A)	00
ASPECT RATIO 16:9 CONTRAST RATIO 1000:1 (TYP) sRGB 136% sRGB / 95% DCI-P3 (CIE 1976) ACTIVE DISPLAY AREA (MM) 708.48 (H) x 398.52 (V) PIXEL PITCH (H X V) 0.1845(H)x0.1845(V) SURFACE TREATMENT Anti-glare DISPLAY COLORS 1.07 Billion COLOR BIT 10 bits (8 bits + FRC) VIDEO PORTS 1x DP(1.2) 2x HDMI (2.0b) 1x Type C (DP a mode with PD : 5V/3A)	
CONTRAST RATIO 1000:1 (TYP) sRGB 136% sRGB / 95% DCI-P3 (CIE 1976) ACTIVE DISPLAY AREA (MM) 708.48 (H) x 398.52 (V) PIXEL PITCH (H X V) 0.1845(H)x0.1845(V) SURFACE TREATMENT Anti-glare DISPLAY COLORS 1.07 Billion COLOR BIT 10 bits (8 bits + FRC) VIDEO PORTS 1x DP(1.2) 2x HDMI (2.0b) 1x Type C (DP a mode with PD : 5V/3A)	
sRGB 136% sRGB / 95% DCI-P3 (CIE 1976) ACTIVE DISPLAY AREA (MM) 708.48 (H) x 398.52 (V) PIXEL PITCH (H X V) 0.1845(H)x0.1845(V) SURFACE TREATMENT Anti-glare DISPLAY COLORS 1.07 Billion COLOR BIT 10 bits (8 bits + FRC) VIDEO PORTS 1x DP(1.2) 2x HDMI (2.0b) 1x Type C (DP a mode with PD : 5V/3A)	
ACTIVE DISPLAY AREA (MM) 708.48 (H) x 398.52 (V) PIXEL PITCH (H X V) 0.1845(H)x0.1845(V) SURFACE TREATMENT Anti-glare DISPLAY COLORS 1.07 Billion COLOR BIT 10 bits (8 bits + FRC) VIDEO PORTS 1x DP(1.2) 2x HDMI (2.0b) 1x Type C (DP a mode with PD : 5V/3A)	
PIXEL PITCH (H X V) 0.1845(H)x0.1845(V) SURFACE TREATMENT Anti-glare DISPLAY COLORS 1.07 Billion COLOR BIT 10 bits (8 bits + FRC) VIDEO PORTS 1x DP(1.2) 2x HDMI (2.0b) 1x Type C (DP a mode with PD : 5V/3A)	
SURFACE TREATMENT Anti-glare DISPLAY COLORS 1.07 Billion COLOR BIT 10 bits (8 bits + FRC) VIDEO PORTS 1x DP(1.2) 2x HDMI (2.0b) 1x Type C (DP a mode with PD : 5V/3A)	
DISPLAY COLORS 1.07 Billion COLOR BIT 10 bits (8 bits + FRC) VIDEO PORTS 1x DP(1.2) 2x HDMI (2.0b) 1x Type C (DP a mode with PD : 5V/3A)	
COLOR BIT10 bits (8 bits + FRC)VIDEO PORTS1x DP(1.2) 2x HDMI (2.0b) 1x Type C (DP a mode with PD : 5V/3A)	
VIDEO PORTS1x DP(1.2) 2x HDMI (2.0b) 1x Type C (DP a mode with PD : 5V/3A)	
mode with PD : 5V/3A)	
3x USB 3 2 Gen 1 Type A 1x USB 3 2 Gen 1	lt
USB Ports Type B	
Audio Interface 1x Mic-in 1x Headphone-out 1x Audio com	20
Card Reader Yes, SD card supported	
Control 5 Ways Joystick Navigator / Macro-key	
KENSINGTON LOCK Yes	
VESA MOUNTING 100 x 100 mm	
POWER TYPE PowerAdaptor	
POWER INPUT 100~240V, 50~60Hz	
ADJUSTMENT (TILT) -5° ~ 20°	
ADJUSTMENT (SWIVEL) -35° ~ 35°	
ADJUSTMENT (HEIGHT) 0 ~ 100mm	
DIMENSION (W X H X D) 727.10 x 235.00 x 460.78 mm (28.63 x 9.2 18.14 inch)	5 x
CARTON DIMENSION (W X H X D) 955 x 180 x 543 mm (37.6 x 7.09 x 21.38 inch)	
WEIGHT (NW / GW) 9.7kg (21.38 lbs) / 13.8 kg (30.42 lbs)	
PC, Mac, PS5 [™] , PS4 [™] , Xbox, Mobile, Notebook * All trademarks and the register trademarks are the property of their respective owners.	

FEATURES



Anti-Flicker technology

MSI Anti-Flicker technology provides a very comfortable viewing experience by reducing the amount of screen flicker.



Allows an accurate condition for precise editing

Type C Display

Allows you to connect the latest devices more conveniently and with less trouble.

32" 4K UHD



View your applications, spreadsheets, and more with a perfect 32 inches screen and experience a breathtaking screen that comes with 4K UHD resolution

Smart Brightness



Automatically detect surrounding ambient light levels to adjust the on-screen brightness for your viewing comfort

Active Noise Cancellation (ANC) Mic Design

The Active Noise Cancellation function improves your conference call or online chatting experience & quality

Productivity Intelligence App (P.I.)



The Productivity Intelligence App (P.I.) provides the smartest tool, KVM function, color & display mode to you while working with it every day

Adjustable stand



Adjust the stand to the angle that is most suitable for you to keep yourself work comfortably





BUSINESS PRODUCTIVITY MONITOR

Summit MS321UP

BE YOUR WINDOW TO THE WORLD

Note

Display Port: 3840 x2160 (Up to 60Hz) HDMI: 3840 x2160 (Up to 60Hz) Type C: 3840 x2160 (Up to 60Hz)

CONNECTIONS

