



Professional 2-inch direct thermal label printers

TD-2310D203 / TD-2320D203 / TD-2320D300 / TD-2350D203 /
TD-2350D300 / TD-2320DSA203 / TD-2320DSA300 /
TD-2350DSA203 / TD-2350DSAH300 / TD-2320DFC203 /
TD-2350DFC203

Data Sheet

TD-2D Series

Increasing productivity and reducing costs are priorities in any workplace. And when it comes to label printing, the TD-2D printers combine proven desktop printer performance with new levels of efficiency to help you do more for less.

With a range of specialised features and print resolution of up to 300dpi, the TD-2D is the perfect label printer for retail, healthcare, warehousing, logistics and manufacturing – plus any other sector where you need to be able to print high-quality receipts or labels at your desk or on the move.

Key Features:

- High speed printing of up to 152.4mm/sec (6ips)
- Two power options: AC adaptor and optional rechargeable battery³
- Easy to connect with USB (Type C) and RS232C¹ built in as standard
- Auto media configuration for easy setup
- Customisable with various options (label peeler, cutter, battery)³
- Direct thermal printing on a range of media including Linerless⁵

Multiple types of media supported

High speed printing



Customisable options

Pre-installed cutter with label taken sensor (Linerless models)³

Easy connectivity

General

Carton contents	TD-2D series printer AC power cord & adaptor USB (A-C) cable Documentation Media discs Label support ⁵
Language support	English, German, Italian, French, Dutch, Spanish, Portuguese, Norwegian, Finnish, Danish, Swedish, Polish

Dimensions & Weights

Without carton	TD-2310D: 119(w) x 224(d) x 158(h) 1.46Kg
	TD-2320D: 119(w) x 224(d) x 158(h) 1.50Kg
	TD-2350D: 119(w) x 224(d) x 158(h) 1.53Kg
	TD-2320DSA/2350DSA: 119(w) x 224(d) x 176(h) 1.77Kg
	TD-2350DSAH: 153(w) x 280(d) x 176(h) 1.94Kg
	TD-2320DFC: 119(w) x 256(d) x 158(h) 1.79Kg
	TD-2350DFC: 119(w) x 256(d) x 158(h) 1.82Kg

Built In Features

Printing Method	Direct Thermal
Printing speed	Up to 152.4mm/second (6ips)
Maximum print width / length	59mm(w) x 3000mm(l)
Minimum media width	15mm 39mm (Linerless models) ⁵
Maximum media width	63mm
Maximum roll diameter	127mm
Print resolution	203dpi (TD-2310D203/TD-2320D203/TD-2350D203/TD-2320DSA203/TD-2350DSA203/TD-2320DFC203/TD-2350DFC203) 300dpi (TD-2320D300/TD-2350D300/TD-2320DSA300/TD-2350DSAH300)
Memory	256 MB RAM / 32 MB FLASH (TD-2130D203) 256 MB RAM / 64 MB FLASH
Interfaces	USB (Type C), RS-232C¹ (All models) 10/100Base TX, USB Host (TD-2320D203 / TD-2320D300/ TD-2350D203 /TD-2350D300 /TD-2320DSA203 /TD-2320DSA300 / TD-2350DSA203 /TD-2350DSAH300/TD-2320DFC203) Bluetooth Version.5.2 MFi Wireless LAN IEEE802.11a/b/g/n supporting 2.4GHz and 5GHz (TD-2350D203 /TD-2350D300/TD-2350DSA203 / TD-2350DSAH300/TD-2350DFC203)

Bluetooth Profile	SPP(Serial Port Profile), OPP, HCRP, GATT (Low Energy) iAP support : Yes
WLAN Security	Authentic method (encryption scheme) Infrastructure mode: (Personal) WEP, WPA-PSK (TKIP/AES), WPA2-PSK (AES), WPA3-SAE (AES) (Enterprise) EAP-FAST, PEAP, EAP-TLS, EAP-TTLS Wireless direct: WPA2-PSK (AES)
Operating system support	Microsoft Windows® 10, Windows® 11 Microsoft Windows® Server 2016/2019/2022 Linux
SDK Support	Windows® B-PAC SDK. iOS®, Android Information available at https://support.brother.com/g/s/es/dev/en/index.html?c=eu
Printer commands	P-touch Template, ESC/P, Raster and ZPL 2, EPL 2, DPL, CPCL emulations
Built in fonts (ESC/P)	Fixed: Letter Gothic Bold, Helsinki, Gothic Scalable: Letter Gothic Regular, Helsinki, Brussels, Gothic, San Diego, Brougham
Built in fonts (P-Touch template)	Scalable: Letter Gothic Regular, Helsinki, Brussels, Gothic
Built in fonts (ZPL)	Fixed: Letter Gothic Bold, Symbol, OCR-A, OCR-B Scalable: Utah Condensed Bold
Built in barcodes (ESC/P)	Linear: CODE 39, ITF (I-2/5), EAN-8(JAN8), EAN-13(JAN13), UPC-A, UPC-E, CODABAR (NW-7), CODE 128, GS1-128(UCC/EAN 128), UPC and EAN 2 or 5 digit extensions, CODE93, POSTNET, MSI GS1 Databar (RSS14, RSS14 Stacked, RSS14 Truncation, RSS14 Stacked Omnidirection), GS1 Databar (RSS Limited) GS1 Databar (RSS Expanded, RSS Expanded Stacked) 2-dimensional: QR Code (model 1, model 2, micro QR), Maxicode, PDF417 (Standard, Truncate, MicroPDF417) Data Matrix (ECC200 Square, ECC200 Rectangular) Aztec
Built in barcodes (P-Touch template)	Linear: CODE 39, ITF (I-2/5), EAN-8(JAN8), EAN-13(JAN13), UPC-A, UPC-E, CODABAR (NW-7), CODE 128, GS1-128(UCC/EAN 128), POSTNET, GS1 Databar (RSS14, RSS14 Stacked, RSS14 Truncation, RSS14 Stacked Omnidirection), GS1 Databar (RSS Limited) GS1 Databar (RSS Expanded, RSS Expanded Stacked) 2-dimensional: QR Code (model 1, model 2, micro QR), Maxicode, PDF417 (Standard, Truncate, MicroPDF417) Data Matrix (ECC200 Square, ECC200 Rectangular) Aztec

Built in barcodes (ZPL)	Linear: CODE 39, ITF(I-2/5), EAN-8(JAN8), EAN-13(JAN13), UPC-A, UPC-E, CODABAR (NW-7), CODE 11, CODE 128, GS1-128(UCC/EAN 128), UPC and EAN 2 or 5 digit extensions, CODE93, POSTNET, MSI GS1 Databar (RSS14, RSS14 Stacked, RSS14 Truncation, RSS14 Stacked Omnidirection), GS1 Databar (RSS Limited) GS1 Databar (RSS Expanded, RSS Expanded Stacked) LOGMARS, Standard 2 of 5, Industrial 2 of 5
	2-dimensional: QR Code, Maxicode, PDF417 (Standard, MicroPDF417) Data Matrix (ECC200 Square) Aztec

Supplies*

Die cut labels⁶	BDE-1J026051-102 (1900 labels per roll each at 51 x 26mm in white)
Receipt paper⁶	BDL-7J000058-102 continuous roll at 58mm x 101.6m

Optional Accessories

RS-232C adaptor	PA-SCA-002 (RJ25 to DB9M serial adaptor)
Battery	PA-BT-004 ³ (Li-ion battery) PA-BB-004 ³ (battery base) PA-BC-004 (single battery charger)
Label peeler	PA-LP-008 ^{3 6}
Cutter / Linerless Cutter	PA-CU-007 ^{3 6} / PA-LCU-001 ⁵
Thermal print head	203dpi: PA-HU2-002 ² 300dpi: PA-HU3-002 ²
Platen Roller / Linerless Platen Roller	203dpi: PA-PR2-002 ⁶ / PA-LPR2-001 ⁵ 300dpi: PA-PR3-002 ⁶ / PA-LPR3-001 ⁵
Standard AC adaptor	PA-AD-005
Healthcare AC adaptor	PA-AD-006
Keyboard Unit	PA-KU-001 ⁴

¹ When using the RS-232C interface with a external barcode reader it must be used in conjunction with the PA-SCA-002 (RJ25 to DB9M serial adaptor)

² Can be used to upgrade/downgrade any TD-2D model, resolution must match the correct platen roller.

³ Not compatible with TD-2310D203.

⁴ Only compatible with DSA models

⁵ TD-2320DFC203 / TD-2350DFC203 only (Linerless models)

⁶ Not compatible with TD-2320DFC203 / TD-2350DFC203 (Linerless models)

* For additional supplies request please contact your local Brother sales office.

Model Comparison

	TD-2310D203	TD-2320D203 / TD-2320D300 / TD-2320DFC203	TD-2350D203 / TD-2350D300 / TD-2350DFC203	TD-2320DSA203/ TD-2320DSA300	TD- 2350DSA203	TD- 2350DSAH300
Maximum print width	59mm	59mm	59mm	59mm	59mm	59mm
Print resolution	203dpi	203dpi / 300 dpi / 203dpi	203dpi / 300dpi / 203dpi	203dpi / 300dpi	203dpi	300dpi
Printing speed	6ips (152mm/sec)	6ips (152mm/sec)	6ips (152mm/sec)	6ips (152mm/sec)	6ips (152mm/sec)	6ips (152mm/sec)
USB (Type C) / USB Host	Yes / No	Yes / Yes	Yes / Yes	Yes / Yes	Yes / Yes	Yes / Yes
Serial	Yes	Yes	Yes	Yes	Yes	Yes
Wired LAN	-	Yes	Yes	Yes	Yes	Yes
Bluetooth	-	-	Yes	-	Yes	Yes
Wi-Fi	-	-	Yes	-	Yes	Yes
LCD	-	-	Yes	-	-	-
Touch Panel Display				Yes	Yes	Yes
Carry Handle	-	-	-	-	-	Yes

All specifications are correct at the time of printing and are subject to change without notice. Brother and the Brother logo are both trademarks of Brother Industries, Ltd., registered in Japan and certain other countries. Any trade names, logos and product names of other companies appearing are trade names or trademarks of those respective companies.

BIE Product Planning: Last updated 01/11/2024