

TravelMate P216-51-G2 Specifications (v4-0-3)			
Category	Description	Footnotes	
Operating 1 system	Windows 11 Pro (Acer recommends Windows 11 Pro for business.) Windows 11 Home		
CPU and chipset 1	Intel <sup>®</sup> Core <sup>™</sup> 7 processor 150U (12 MB Smart Cache, 1.8 GHz		
	Performance-core with Intel® Turbo Boost Technology 2.0 up to 5.4 GHz), supporting hybrid core architecture with Performance-core and Efficient-core		
	Intel <sup>®</sup> Core <sup>™</sup> 5 processor 120U (12 MB Smart Cache, 1.4 GHz		
	Performance-core with Intel® Turbo Boost Technology 2.0 up to 5.0 GHz), supporting hybrid core architecture with Performance-core and Efficient-core		
	Intel <sup>®</sup> Core <sup>™</sup> 3 processor 100U (10 MB Smart Cache, 1.2 GHz		
	Performance-core with Intel® Turbo Boost Technology 2.0 up to 4.7 GHz), supporting hybrid core architecture with Performance-core and Efficient-core		
<b>Memory</b> 1, 2, 3	Dual-channel DDR5 SDRAM support		
	Up to 64 GB of DDR5 system memory		
	Memory Frequency: Up to 5200 MT/s		
Display	16.0" display with IPS (In-Plane Switching) technology, WUXGA 1920 x	4	
	1200, high-brightness (400 nits) Acer ComfyView <sup>™</sup> LED-backlit TFT LCD		
	16:10 aspect ratio, sRGB 100%		
	Wide viewing angle up to 170 degrees		
	Slim and narrow border design		
	Mercury free, environment friendly		
	16.0" display with IPS (In-Plane Switching) technology, WUXGA 1920 x	4	
	1200, Acer ComfyView <sup>™</sup> LED-backlit TFT LCD		
	16:10 aspect ratio, color gamut NTSC 45%		
	Wide viewing angle up to 170 degrees		
	Mercury free, environment friendly		
Graphics	Intel <sup>®</sup> Graphics	5	
	Graphics Special Technology#		
	H.265/HEVC, VP9, AV1 Encode and Decode		
	OpenGL 4.5		
	OpenCL 3.0		
	DirectX 12		
Audio	DTS® Audio, featuring optimized bass response and micro-speaker		
	distortion prevention		

TravelMate P216-51-G2 Specifications (v4-0-3)		
	<ul> <li>Acer Purified.Voice technology with AI noise reduction in dual built-in microphones. Features include far-field pickup, dynamic noise reduction through neural network, adaptive beam forming, and predefined personal and conference call modes.</li> <li>Acer TrueHarmony technology for lower distortion, wider frequency range, headphone-like audio and powerful sound</li> </ul>	
Storage	Solid state drive	
	SSD slot: 2	1, 6
	• 256 GB / 512 GB / 1 TB, PCle Gen4, 16 Gb/s, NVMe	1, 6
	Hard disk drive	
	Optional 2 <sup>nd</sup> HDD 1 TB, 2.5-inch 5400 RPM	
Webcam 1	Video conferencing	
	UFC with	
	T-Type USB FHD camera + IR camera	
	Compatible with Windows only	
	• 1920 x 1080 resolution	
	1080p HD video at 60 fps with Temporal Noise Reduction     Dual Mia (22 gams) 22 gams)	
	• Dual Mic (33 mm + 33 mm)	
	• 78 x 3.2 (5.2) x 3 mm UFC with	
	T-Type HD camera	
	Compatible with Windows only	
	1280 x 720 resolution	
	720p HD video at 30 fps with Temporal Noise Reduction	
	Blue Glass lens	
	• Dual Mic (33 mm + 33 mm)	
	• 78 x 3.2 (5.2) x 3 mm	
Wireless and 1	WPAN	
networking	Supports Bluetooth <sup>®</sup> 5.3 or above	
	Supports Bluetooth LE Audio (LC3).	
	WLAN	
	Intel® Wi-Fi 6E Wireless LAN	
	• 802.11 a/b/g/n/ac/ax	
	Band: 2.4 GHz, 5 GHz, and 6 GHz	
	2x2 MU-MIMO technology	
	Intel vPro® Essentials	
	Intel® Connectivity Performance Suite (ICPS)	
	Intel® Wi-Fi 6E Wireless LAN	
	• 802.11 a/b/g/n/ac/ax	
	Band: 2.4 GHz, 5 GHz, and 6 GHz	
	2x2 MU-MIMO technology	
	WWAN	
	<ul> <li>LTE FDD: B1/B2/B3/B4/B5/B7/B8/B12/B13/B14/B17/B18/B19/B20/ B25/B26/B28/B29/B30/B32/B66/B71</li> </ul>	

TravelMate P216-51-G2 Specifications (v4-0-3)			
	<ul> <li>LTE TDD: B34/B38/B39/B40/B41/B42/B43/B46/B48</li> <li>WCDMA/HSPA+: B1/B2/B3/B4/B5/B6/B8/B19</li> <li>Support up to LTE DL Cat.12</li> <li>LTE Data Rate: Maximum download 600 Mbps, upload 150 Mbps</li> <li>WCDMA Data Rate: Maximum download 384 kbps, upload 384 kbps</li> <li>DC-HSPA+: Maximum download 42 Mbps</li> <li>eSIM is included</li> <li>LAN</li> <li>Gigabit Ethernet, Wake-on-LAN ready</li> </ul>		
Security	Acer ProShield Plus security manager includes:  • Data Protection: File & Description and Decryption, Personal Security Drive  • Data Removal: File Shredding  • Security Alert: Invalid Access Alert, Security Report Acer Bio-Protection fingerprint solution, featuring computer protection and Windows Hello Certification  Discrete Trusted Platform Module (TPM) solution  Camera shutter  BIOS user, supervisor, SSD passwords  Kensington lock slot		
Dimensions and weight	<ul> <li>Dimensions <ul> <li>359.3 (W) x 261.07 (D) x 19.95/22.95 (H) mm (14.15 x 10.28 x 0.79/0.9 inches)</li> </ul> </li> <li>Weight <ul> <li>1.74 kg (3.84 lbs.) with 3-cell battery pack</li> <li>1.79 kg (3.95 lbs.) with 3-cell battery pack</li> </ul> </li> <li>(Notes: 1.74Kg By IPS sRBG 100% LCD / 1x SODIMM with the lowest weight SKU , weight varient by other generic LCD selection &amp; mp; SODIMM quantity (with 53Wh battery pack))</li> </ul>		
l	Power adapter  USB Type-C 65 W PD AC adapter:  • 108 (W) x 46 (D) x 29.5 (H) mm (4.25 x 1.81 x 1.16 inches)  • 5 V / 3 A or 9 V / 3 A or 12 V / 3 A or 15 V / 3 A or 20 V / 3.25 A as output power  • 250 g with 150 cm DC cable  Battery  • 53 Wh 3-cell Li-ion battery  • Supports Fast Charging technology  • For models with WUXGA Panel + SSD  Battery life:  Up to 12 hours (based on MobileMark® 2025 test results)  Up to 21 hours (based on web browsing test results)  • 65 Wh 3-cell Li-ion battery	11	

TravelMate P216-51-G2 Specifications (v4-0-3)			
	For models with WUXGA Panel + SSD		
	Battery life:		
	Up to 14.5 hours (based on MobileMark® 2025 test results)		
	Up to 26 hours (based on video playback test results)		
	Up to 26 hours (based on web browsing test results)		
Input and control	Keyboard		
	99-/100-/103-key Acer backlit keyboard with international language		
	support, with indicators of CapsLock and F4/Microphone mute		
	99-/100-/103-key Acer keyboard layout with international language support		
	including indicators of CapsLock and F4/Microphone mute		
	Control Keys		
	Copilot Key		
	TravelMate Sense Key		
	Microphone mute key		
	Bio-Protection fingerprint reader	1	
	TouchPad		
	Multi-gesture secure touchpad, supporting two-finger scroll; pinch;		
	gestures to open Cortana, Action Center, multitasking; Fingerprint		
	application commands		
	Windows Hello Certification		
	Microsoft Precision Touchpad certification		
	• * OceanGlass™ Touchpad		
Input and output	USB Type-C		
	Two USB Type-C <sup>™</sup> ports		
	USB Type-C <sup>™</sup> port supporting:		
	DisplayPort over USB-C		
	• Thunderbolt™ 4		
	USB charging 5 V; 3 A		
	<ul><li>USB charging 5 V; 3 A</li><li>DC-in port 20 V; 65 or 100 W</li></ul>		
	• DC-in port 20 V; 65 or 100 W		
	DC-in port 20 V; 65 or 100 W USB Standard A		
	DC-in port 20 V; 65 or 100 W  USB Standard A  Two USB Standard-A ports, supporting:		
	<ul> <li>DC-in port 20 V; 65 or 100 W</li> <li>USB Standard A</li> <li>Two USB Standard-A ports, supporting:</li> <li>One port for USB 3.2 Gen 1</li> </ul>		
	<ul> <li>DC-in port 20 V; 65 or 100 W</li> <li>USB Standard A</li> <li>Two USB Standard-A ports, supporting:</li> <li>One port for USB 3.2 Gen 1</li> <li>One port for USB 3.2 Gen 1 featuring power off USB charging</li> </ul>		
	<ul> <li>DC-in port 20 V; 65 or 100 W</li> <li>USB Standard A</li> <li>Two USB Standard-A ports, supporting:</li> <li>One port for USB 3.2 Gen 1</li> <li>One port for USB 3.2 Gen 1 featuring power off USB charging</li> <li>Thunderbolt<sup>™</sup> port</li> </ul>		
	<ul> <li>DC-in port 20 V; 65 or 100 W</li> <li>USB Standard A</li> <li>Two USB Standard-A ports, supporting:</li> <li>One port for USB 3.2 Gen 1</li> <li>One port for USB 3.2 Gen 1 featuring power off USB charging</li> <li>Thunderbolt<sup>™</sup> port</li> <li>HDMI<sup>®</sup> 2.0 port with HDCP support</li> </ul>		
	<ul> <li>DC-in port 20 V; 65 or 100 W</li> <li>USB Standard A</li> <li>Two USB Standard-A ports, supporting:         <ul> <li>One port for USB 3.2 Gen 1</li> <li>One port for USB 3.2 Gen 1 featuring power off USB charging</li> </ul> </li> <li>Thunderbolt<sup>™</sup> port</li> <li>HDMI<sup>®</sup> 2.0 port with HDCP support</li> <li>microSD<sup>™</sup> Card reader</li> </ul>		
	<ul> <li>DC-in port 20 V; 65 or 100 W</li> <li>USB Standard A</li> <li>Two USB Standard-A ports, supporting:         <ul> <li>One port for USB 3.2 Gen 1</li> <li>One port for USB 3.2 Gen 1 featuring power off USB charging</li> </ul> </li> <li>Thunderbolt<sup>™</sup> port</li> <li>HDMI<sup>®</sup> 2.0 port with HDCP support</li> <li>microSD<sup>™</sup> Card reader</li> <li>SmartCard reader slot</li> </ul>		
	<ul> <li>DC-in port 20 V; 65 or 100 W</li> <li>USB Standard A</li> <li>Two USB Standard-A ports, supporting:         <ul> <li>One port for USB 3.2 Gen 1</li> <li>One port for USB 3.2 Gen 1 featuring power off USB charging</li> </ul> </li> <li>Thunderbolt<sup>™</sup> port</li> <li>HDMI<sup>®</sup> 2.0 port with HDCP support</li> <li>microSD<sup>™</sup> Card reader</li> <li>SmartCard reader slot</li> <li>3.5 mm headphone/speaker jack, supporting headsets with built-in</li> </ul>		
	<ul> <li>DC-in port 20 V; 65 or 100 W</li> <li>USB Standard A</li> <li>Two USB Standard-A ports, supporting:         <ul> <li>One port for USB 3.2 Gen 1</li> <li>One port for USB 3.2 Gen 1 featuring power off USB charging</li> </ul> </li> <li>Thunderbolt<sup>™</sup> port</li> <li>HDMI<sup>®</sup> 2.0 port with HDCP support</li> <li>microSD<sup>™</sup> Card reader</li> <li>SmartCard reader slot</li> </ul> <li>3.5 mm headphone/speaker jack, supporting headsets with built-in microphone</li>		
Sensors	<ul> <li>DC-in port 20 V; 65 or 100 W</li> <li>USB Standard A</li> <li>Two USB Standard-A ports, supporting:         <ul> <li>One port for USB 3.2 Gen 1</li> <li>One port for USB 3.2 Gen 1 featuring power off USB charging</li> </ul> </li> <li>Thunderbolt<sup>™</sup> port</li> <li>HDMI<sup>®</sup> 2.0 port with HDCP support</li> <li>microSD<sup>™</sup> Card reader</li> <li>SmartCard reader slot</li> <li>3.5 mm headphone/speaker jack, supporting headsets with built-in microphone</li> <li>Ethernet (RJ-45) port</li> </ul>		
Sensors Windows 13 Desktop Apps	<ul> <li>DC-in port 20 V; 65 or 100 W</li> <li>USB Standard A</li> <li>Two USB Standard-A ports, supporting:         <ul> <li>One port for USB 3.2 Gen 1</li> <li>One port for USB 3.2 Gen 1 featuring power off USB charging</li> </ul> </li> <li>Thunderbolt<sup>™</sup> port</li> <li>HDMI<sup>®</sup> 2.0 port with HDCP support</li> <li>microSD<sup>™</sup> Card reader</li> <li>SmartCard reader slot</li> <li>3.5 mm headphone/speaker jack, supporting headsets with built-in microphone</li> <li>Ethernet (RJ-45) port</li> <li>DC-in jack for AC adapter</li> </ul>		

## **TravelMate P216-51-G2 Specifications (v4-0-3)** Acer Control Center Acer QuickPanel • TravelMate Sense **Options and Accessory** accessories Support Acer Vero MST Dock M32 - Dimension: 180 (W) x 82 (D) x 24.8 (H) mm ((7.09 x 3.23 x 0.98 inches) · Weight: 232 g (0.52 lbs) - Built with 65% Post-consumer Recycled (PCR) Plastic · Support for one display via DP 1.4; one display via HDMI 2.0 · Support for up to two 4K-60Hz external multi-displays (HBR3 PC supporting DSC) · One USB-C upstream port to host · One USB-C downstream port for device (data only with USB3.2 Gen1) · Two USB-A 3.2 Gen1 (one support BC1.2) · One USB-A 2.0 - Gigabit Ethernet (RJ45) port (1000/100/10Mbps) Up to 65W power supply delivering to system · Audio Combo Jack · 1 m USB Type-C cable · Support for VESA mount · 90W Power Adapter Support Add-on features for M32 · LED behavior aligned with the host power status · Power button mirrors the host's System MAC address pass-through to Dock

- · Wake-On-LAN from Sleep/Hibernate/Off mode
- · PXE boot via Dock LAN port

#### Support Acer Vero MST Dock M33

- Dimension: 180 (W) x 82 (D) x 24.8 (H) mm ((7.09 x 3.23 x 0.98 inches)
- · Weight: 232 g(0.52 lbs)
- · built with 65% post-consumer recycled (PCR) plastic
- · Support two display with DP 1.4, one display with HDMI 2.0
- Support up to three 4K-30Hz external multi-displays (HBR3 PC supporting DSC)
- · One USB-C upstream port to host
- · One USB-C downstream port for device (data only with USB3.2 Gen2)
- · two USB-A 3.2 Gen2 (one support BC1.2)
- · two USB-A 3.2 Gen1
- Gigabit Ethernet (RJ45) port (1000/100/10Mbps)
- Up to 100W power supply delivering to system (65W PD when dock IO port full loaded)
- · Audio Combo Jack
- · 1 m USB Type-C cable
- · support VESA mount
- · 135W Power Adapter

TravelMate P216-51-G2 Specifications (v4-0-3)		
	Support Add-on features for M33	
	LED behavior aligned with the host power status	
	Power button mirrors the host's	
	· System MAC address pass-through to Dock	
	· Wake-On-LAN from Sleep/Hibernate/Off mode	
	PXE boot via Dock LAN port	
	SIM Card Tray Ejector Pin	
System	ENERGY STAR®	
compliance	Wi-Fi <sup>®</sup>	
	EPEAT® registered	14
Warranty	One-year International Travelers Warranty (ITW)	
Quality and	Temperature and humidity	
reliability tests	Hinge life	
	Weight and pressure	
	Acoustics	
	Spillage	
	Free drop	
	Shock and vibration	
	Electrostatic discharge immunity	
	Keyboard-switch life	
	MTBF (mean time between failures)	
	Military Reliability Test: Mechanical Shock, Transit Drop (Packaged) 122	
	cm (MIL-STD 810H)	
	Military Reliability Test: Mechanical Shock, Transit Drop (Unpackaged)	
	122 cm (MIL-STD 810H)	
	Military Reliability Test: Vibration (MIL-STD 810H)	
	Military Reliability Test: Sand and Dust (MIL-STD 810F)	
	Military Reliability Test: Salt Fog (MIL-STD 810H)	
	Military Reliability Test: Humidity (MIL-STD 810H)	
	Military Reliability Test: Rain (MIL-STD 810H)	
	Military Reliability Test: Low Temperature (MIL-STD 810H)	
	Military Reliability Test: High Temperature (MIL-STD 810H)	15
	Military Reliability Test: Low Pressure (Altitude) (MIL-STD 810H)	

- 1. Specifications vary depending on model.
- 2. Shared system memory may be allocated to support graphics, depending on system memory size and other factors. Actual system memory available to the operating system will be reduced by any memory used by the graphics solution and resources required by the operating environment.
- 3. Memory speed may vary, depending on the CPU, chipset or memory fitted.
- 4. All brands and product names mentioned herein include trademarks of their respective companies and are used solely to describe or identify the products.
- 5. Not all features indicated are supported on all SKUs
- 6. 1 GB is 1 billion bytes. Actual formatted capacity is less and may vary depending on preloaded materials and operating environment. Acer Recovery Management uses a portion of the stated hard disk capacity as dedicated backup space.

### **TravelMate P216-51-G2 Specifications (v4-0-3)**

- 7. Minor variations in system dimensions are possible due to the manufacturing process.
- 8. Weight may vary depending on product configuration, vendor components, manufacturing variability, and selected options.
- 9. Listed battery life is based on testing using video playback. The test clip loops and continues to run, without interruption or any other inputs, until the battery is drained. Stated battery life is for comparison purpose only. Actual battery life varies by model, configuration, applications, video chip format and features used. A battery's maximum capacity decreases with time and use. Battery life test configuration: Intel® Core™ 3 processor 100U, Intel® Graphics, WUXGA, SSD only, 8GB of DDR5 memory. Battery life test condition: LCD brightness 150 nits, connected headphones, WLAN off, Bluetooth off and Better Battery Mode on.
- 10. Listed battery life is based on testing using Web browsing. The test clip loops the loading of 50 selected websites using Microsoft Edge every 30 seconds, until the battery is drained. Stated battery life is for comparison purpose only. Actual battery life varies by model, configuration, applications, video chip format and features used. A battery's maximum capacity decreases with time and use. Battery life test configuration: Intel® Core™ 3 processor 100U, Intel® Graphics, WUXGA, SSD only, 8GB of DDR5 memory. Battery life test condition: 100 nits LCD brightness, 50% speaker volume, WLAN on, Bluetooth on, no WW direct Internet connection.
- 11. The listed battery life is tested by Google according to this formula (the test loops and continues running until the battery is drained): The first 60% of the test period is 1) Browsing: A new web page is loaded every minute. The web page is scrolled down to the first "page fold" (the bottom of the part of a web page that is visible on an average screen a depth of around 600 pixels) every 10 seconds, then scrolled back up at the same rate. The next 20% of the test period is 2) Email: Gmail is loaded in the foreground tab and audio is streamed from a background tab. The next 10% is 3) Documents: Various Google Docs are loaded. The final 10% is 4) Online Video: A full-screen 720p YouTube video is played
- 12. Actual battery life may vary considerably by specifications, depending on product model, configuration, applications, power management settings, operating conditions, and features utilized. Performance variation also arises based on components in use, which includes but is not limited to the processor, RAM capacity, storage, display and resolution, etc.
- 13. Bundled software may vary depending on hardware configuration, OS and regional availability.
- 14. EPEAT® registration varies by country. See http://www.epeat.net/ for registration status for each country.
- 15. MIL-STD 810G/H is a testing protocol conducted in controlled settings and does not guarantee future performance in all situations. Do not attempt to simulate these tests, as damage resulting from this will not be covered by Acer's standard warranty.

In a continuing effort to improve the quality of our products, information in this document is subject to change without notice. Images shown are only representations of some of the configurations available for this model. Availability may vary depending on region.

As a phenomenon known to thin-film transistors (TFTs), liquid crystal displays (LCDs) commonly exhibit a small number of discoloration dots, as so-called "non-conforming pixels." This phenomenon is a limitation of TFT LCD technology, not a product defect, and as such is not covered by Acer's warranty.

© 2024. All rights reserved.

Microsoft and Windows are registered trademarks of Microsoft Corporation.

### **TravelMate P216-51-G2 Specifications (v4-0-3)**

Arc, Arria, Celeron, Cyclone, eASIC, Intel Ethernet, Intel, the Intel logo, Intel Agilex, Intel Atom, Intel Core, Intel Evo, Intel Inside, the Intel Inside logo, Intel Optane, Intel vPro, Iris, Killer, MAX, Movidius, Pentium, Intel RealSense, Intel Select Solutions, Intel Si Photonics, Stratix, the Stratix logo, Tofino, Ultrabook, Xeon are trademarks of Intel Corporation or its subsidiaries.

#### **About Acer**

Founded in 1976, Acer is one of the world's top ICT companies with a presence in more than 160 countries. As Acer evolves with the industry and changing lifestyles, it is focused on enabling a world where hardware, software and services will fuse with one another, creating ecosystems and opening up new possibilities for consumers and businesses alike. Acer's 7,500 employees are dedicated to the research, design, marketing, sale, and support of products and solutions that break barriers between people and technology. Please visit www.acer.com for more information.



































# **Appendix**

v2-0-2 (Ver. 2)

Wireless and networking

About

Power adapter and battery

Input and control

Input and output

Options and accessories

Dimensions and weight

v3-0-3 (Ver. 3)

Wireless and networking

v4-0-3 (Ver. 4)

No changes found!