






SKU	V246HLbd
 Monitor	
Professional	  
<i>Sub Model</i>	V246HL
<i>Product line</i>	V6 Series
General	
Display Type	Flat screen/TFT
Dimensions (WxHxD mm)	567x422.2x206.8
Min. Profile Thickness mm	19
Net Weight (kg)	3.9
Gross Weight (kg)	5.44
Colour	Black
Display	
Panel Technology	TN+Film
Crystalbrite	No
Size cm	61
Size Inch	24
Format	16:9
Display dimensions (mm)	531x299
Pixel Pitch (mm)	0.276
Resolution	1920x1080@60Hz
Frequency (H/V)	30-80KHz/55-75Hz
PPI	92
Rsp time (ms)	5
Contrast	100M:1
Brightness (cd/m2)	250
H/V° CR 10:1	170/160
H/V° CR 5:1	176/170
Colors (M)	16.7
NTSC (%)	72
Backlight type	LED
OS Certification	Win8 compliant
Video Input	
Input Signal	VGA + DVI (w/HDCP)
Audio Output	
Speaker	No
Miscellaneous	
VESA Wall Mounting	100x100
Kensington Support	Yes
Tilt	-5°~25°
Swivel degrees	No
Hgt Adj (mm)	No
Pivot degrees	No
MTBF Hours @ 25°C	30000
Power Supply	
Power Supply	Internal
Energy Star Type	ES6.0
Off/Standby (W)	0.35
Sleep (W)	0.45
Min On (W)	20.9
Max (W)	-
Mercury (mg)	0
Lead	Presence*
Manufacturer Guarantee	
Service and Support	EMEA Commercial (3yr)
Certificates	CE, TÜV GS, ISO9241-307
TCO Certification	TCO6.0
Pallet and Container Loading	
Pallet qty (pcs)	80
Pallet Size (WxHxD) cm	120.4x106.3x225
Container loading 20"/40"	800/1680
Other Features	
Included video cables	VGA
Package dimension	62.9x42.2x12.1