V52HD 5,000 ANSI Lumens 1080p Laser Installation Projector - ViewSonic Europe



Key Features

- 3rd generation laser phosphor technology with up to a 30,000-hour lifespan
- 5,000 ANSI Lumens offering bright images in any environment
- Up to 300" ultra large screen with lower cost-perinch
- Compact size and light weight reducing cost of transportation and installation
- Installation flexibility: 1.3x optical zoom, H/V keystone, 360° projection, and portrait mode



Product **Description**

The V52HD belongs to ViewSonic's Luminous Superior series, a lamp-free high-brightness projector lineup designed for commercial and educational spaces. With its adoption of the 3rd generation laser phosphor technology, it delivers 5,000 ANSI Lumens for up to 30,000 hours, ensuring bright and vivid images without lamp replacement. The lamp-free design offers an eco-friendly and cost-effective solution, while the projector's lightweight and compact design reduces transportation costs. With up to 300" projection in 1080p Full HD with high native contrast, it is well-suited for boardrooms, lecture halls, and public spaces. This projector features a 1.3x optical zoom, H/V keystone, 4 corner adjustment, 360° projection, and a portrait mode for easy setup and versatile applications.



3/17/25, 10:04 AM

V52HD 5,000 ANSI Lumens 1080p Laser Installation Projector - ViewSonic Europe

			Lanopo
SPECIFICATION	1. Front IR	OTHERS	
Projection System:	0.65" 1080P	Power Supply Voltage:	Input: 100~240V Output: 19.5VDC / 11.79A
Native Resolution: Brightness:	1920x1080 5000 (ANSI Lumens)	Power Consumption:	Normal: 210W Standby: <0.5W
Contrast Ratio:	2,000,000:1	Operating Temperature:	0~40°C
Display Color:	1.07 Billion Colors		
		Carton:	Brown
Light Source Type:	Laser Phosphor	Net Weight:	3.00kg
Light Source Life (hours) with Normal Mode:	20000	<i>I.</i> Gross Weight: Dimensions (WxDxH) with	4.70kg
Light Source Life (hours) with SuperEco Mode:	30000 (Eco)	Adjustment Foot:	286x216x129mm
Lens:	F=2.43-2.78, f=16.90- 21.61mm	Packing Dimensions: OSD Language:	400x280x155mm English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T- Chinese, S- Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, Arabic, Vietnamese, Hungarian, Norsk, total 23 languages
Projection Offset:	132%+/-5%		
Throw Ratio:	1.13-1.47		
Optical Zoom:	1.3X		
Digital Zoom:	0.8x-2.0x		
Image Size:	30"-300"		
Throw Distance:	0.75-9.76m (100"@2.50m)	User Guide Language:	English, S-Chinese, T- Chinese, Indonesian, Finish, French, German, Italian, Japanese, Korean, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Arabic, Czech, Thai, Vietnamese, total 20 languages
Keystone:	H:+/-30°, V:+/-30°		
Audible Noise (Normal):	32dB		
Audible Noise (Eco):	26dB		
Input Lag:	33.3ms	STANDARD ACCESSORY	0 0
Resolution Support:	VGA(640 x 480) to WUXGA RB(1920 x 1200)	Power Cord:	1
	*RB-Reduced Blanking	Remote Control:	1
HDTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p	QSG:	Yes
Horizontal Frequency:	15K-102KHz	Warranty:	*Warranty offered may differ from market to market
Vertical Scan Rate:	24-120Hz	OPTIONAL ACCESSORY	
NPUT		Wall/Ceiling Mount:	PJ-WMK-007
HDMI:	2 (HDMI 1.4/ HDCP 1.4)	Carry Bag:	PJ-CASE-008
OUTPUT			
Audio-out (3.5mm):	1		
Speaker:	15W		
USB Type A (Power):	1 (5V/1.5A)		
CONTROL			
RS232 (DB 9-pin male):	1		
USB Type A (Services):	1 (share with USB A Output)		