

Key Features

- Lightweight, compact, and portable design with protective sleeve for easy and safe transport
- Easily extend display to a larger screen from mobile devices
- HDMI and USB-C inputs for flexible connectivity
- Find your perfect view every time with the foldable stand
- USB-C one cable flexible display setup



*External power adaptor required for power charging

Product **Description**

The ViewSonic VA1650 is a lightweight, portable 16" Full HD portable monitor with USB-C connectivity for power charging. Designed to boost productivity on the go, extend your screen from a phone, tablet, or laptop to a larger display anytime, anywhere. The included protective sleeve makes it effortless to safely carry and protect your monitor, whether traveling, relaxing outdoors, or simply moving around your home.

- 1. USB Type (Power) 2. USB Type C 3. HDMI

- 4. Speaker

Visit Us

www.viewsonic.com

AIVI	VA 1030 TO COD-C LIGHT	veignt i ortable Monitor - viewooni	c Lulope
DISPLAY		OPERATING CONDITIONS	
Display Size (in.):	16	Temperature:	32°F to 104°F (0°C to 40°C)
Viewable Area (in.):	15.6	Humidity (non-condensing):	20% to 90%
Panel Type:	IPS Technology	WALL MOUNT	
Resolution:	1920 x 1080	VESA Compatible:	Customized, 75 mm
Resolution Type:	FHD (Full HD)	INPUT SIGNAL	
Static Contrast Ratio:	1,000:1 (typ)	Frequency Horizontal:	HDMI (v1.4): 15 ~ 82KHz, Type C: 24 ~ 82KHz
Dynamic Contrast Ratio:	50M:1	For any and Marking I.	HDMI (v1.4): 50 ~ 75Hz, Type (
Light Source:	LED	Frequency Vertical:	50 ~ 75Hz
Brightness:	250 cd/m² (typ)	VIDEO INPUT	
Colors:	16.7M	Digital Sync:	TMDS - HDMI (v1.4), Micro- Packet - Type C
Color Space Support:	8 bit (6 bit + FRC)	ERGONOMICS	,
Aspect Ratio:	16:9	Tilt (Forward/Back):	20° / 45°
Response Time (Typical GTG):	7ms	WEIGHT (IMPERIAL)	
Viewing Angles:	178° horizontal, 178° vertical	Net (lbs):	1.5
Backlight Life (Hours):	30000 Hrs (Min)	Net Without Stand (lbs):	1.5
Curvature:	Flat	Gross (lbs):	3.3
Refresh Rate (Hz):	60	WEIGHT (METRIC)	
Low Blue Light:	Software solution	Net (kg):	0.7
Flicker-Free:	Yes	Net Without Stand (kg):	0.7
0.1.0	NTSC: 45% size (Typ)	Gross (kg):	1.5
Color Gamut:	sRGB: 64% size (Typ)	DIMENSIONS (IMPERIAL) (W	
Pixel Size:	0.179 mm (H) x 0.179 mm (V)	Packaging (in.):	16.4 x 11.4 x 2.1
Surface Treatment:	Anti-Glare, Hard Coating (3H)	Physical (in.):	14.09 x 8.29 x 0.55
COMPATIBILITY		Physical Without Stand (in.):	14.09 x 8.29 x 0.55
PC Resolution (max):	1920x1080	DIMENSIONS (METRIC) (WXI	
Mac® Resolution (max):	1920x1080	Packaging (mm):	416 x 290 x 54
PC Operating System:	Windows 10/11 certified; macOS tested	Physical (mm):	357.8 x 210.5 x 13.9
Mac® Resolution (min):	1920x1080	Physical Without Stand (mm):	357.8 x 210.5 x 13.9
CONNECTOR		GENERAL	
USB 3.2 Type C DisplayPort Alt mode only :	1 (65W power charger)	Regulations:	CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC,
3.5mm Audio Out:	1		UkrSEPRO
HDMI 1.4:	1	PACKAGE CONTENTS:	VA1650 x1, USB Type-C Cable (Male-Male) x1, Quick Start Guide x1, Sleeve case x1
Power in:	USB Type C (power only)	Recycle/Disposal:	Please dispose of in accordance
AUDIO		1100yolo/Blopodal.	with local, state or federal laws
Internal Speakers:	1Watts x2	Warranty:	*Warranty offered may differ from market to market
Eco Mode (Conserve):	6W		
Eco Mode (optimized):	6.5W		
Consumption (typical):	7W		
Consumption (max):	8.5W		
Voltage:	DC 5V/9V/12V/15V/20V		
Stand-by:	0.5W		
•			
Power Supply:	External (Optional)		
CONTROLS	Lever nuch key: Un. Enter		
Physical Controls:	Lever push key: Up, Enter, Down, Return (power)		
On Screen Display:	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu		