

Key **Features**

- Ergonomic flexibility with quickrelease stand
- 100Hz Refresh rate delivers fluid visuals
- vDisplay Manager productivity software for maximized multitasking
- Dual front facing speakers for clear audio
- HDMI, DisplayPort, VGA, and USB3.2 ports for extended connectivity



Product **Description**

The ViewSonic VG2240 is a 22" Full HD ergonomic business monitor designed to increase productivity and efficiency within the home and office workspace. Providing the full spectrum of ergonomic flexibility, the VG2240 can tilt, swivel, pivot, and height adjustment to adapt to any setup or workflow, while the built-in vDisplay Manager productivity software delivers efficient multi-tasking ability and streamlined display control. Dual front-facing speakers ensure a perfect audio-visual experience to provide teams with quality remote communication and collaboration. The beautifully designed display includes a 3-sided narrow bezel for uninterrupted viewing in multi-monitor display setups as well HDMI. DisplayPort, VGA, and USB3.2 connectivity. Complete with an easy-to-install quick release stand that reduces setup time to only a few minutes, the VG2240 offers a high-performance, purpose-built display solution designed for workspace productivity.



- 1. Menu Control Panel
- 2. VESA Compatible(Wall Mount 100 x
- 100mm) 3. AC In 4. Line-in
- 5. Headphone
- 6. Display Port1.2
- 7. HDMI

- 8. D-Sub 9. USB 3.0 Up Stream(Type B) 10. USB 3.0 Down Stream(Type A) 11. USB 3.0 Down Stream(Type A)
- Visit Us

www.viewsonic.com



Display Size (in.): 22 Viewable Area (in.): 21.5 Panel Type: VA Technology Resolution: 1920 x 1080 Resolution Type: FHD (Full HD)	Physical Controls: On Screen Display:	Key 1 (eye), Key 2, Key 3, Key 4, Key 5, Key 6 (power) Input Select, Audio Adjust, ViewMode, Color Adjust, Manual
Panel Type: VA Technology Resolution: 1920 x 1080		Input Select, Audio Adjust,
Resolution: 1920 x 1080	On Screen Display:	
Resolution Type: FHD (Full HD)	OPERATING CONDITIONS	Image Adjust, Setup Menu
		32°F to 104°F (0°C to 40°C)
Static Contrast Ratio: 3,000:1 (typ)	Temperature:	, ,
Dynamic Contrast Ratio: 80M:1	Humidity (non-condensing):	20% to 90%
Light Source: LED	WALL MOUNT VESA Compatible:	100 x 100 mm
Brightness: 250 cd/m² (typ)	INPUT SIGNAL	100 X 100 IIIII
Colors: 16.7M	Frequency Horizontal:	RGB Analog: 24 ~ 82KHz, HDMI (v1.4): 24 ~ 110KHz, DisplayPort (v1.2): 24 ~ 110KHz
Color Space Support: 8 bit true		
Aspect Ratio: 16:9		
Response Time (Typical GTG): 5ms	Frequency Vertical:	RGB Analog: 50 ~ 75Hz, HDMI (v1.4): 50 ~ 100Hz, DisplayPort (v1.2): 50 ~
Response Time (GTG w/OD): 5ms	VIDEO INDUT	100Hz
Viewing Angles: 178º horizontal, 178º vertical	VIDEO INPUT	TMDS HDMI (vd. 4) DCLE
Backlight Life (Hours): 30000 Hrs (Min)	Digital Sync:	TMDS - HDMI (v1.4), PCI-E - DisplayPort (v1.2)
Curvature: Flat	Analog Sync:	Separate/Composite/SOG - RGB
Refresh Rate (Hz): 100		Analog
Low Blue Light: Software solution	ERGONOMICS	
Flicker-Free: Yes	Height Adjust (mm):	130
NTSC: 72% eize (Tvn) ePCR: 103%	Swivel:	120°
Color Gamut: N13C. 72% size (Typ) side. 103% size (Typ)	Tilt (Forward/Back):	-5° / 40°
Pixel Size: 0.249 mm (H) x 0.241 mm (V)	Pivot (Right/Left):	90° / 90°
Surface Treatment: Anti-Glare, Hard Coating (3H)	WEIGHT (IMPERIAL)	
COMPATIBILITY	Net (lbs):	11.5
PC Resolution (max): 1920x1080	Net Without Stand (lbs):	6.2
Mac® Resolution (max): 1920x1080	Gross (lbs):	16.8
PC Operating System: Windows 10/11 certified; macOS	WEIGHT (METRIC)	
testeu	Net (kg):	5.2
Mac® Resolution (min): 1920x1080	Net Without Stand (kg):	2.8
CONNECTOR	Gross (kg):	7.6
VGA: 1	DIMENSIONS (IMPERIAL) (W	
USB 3.2 Type A Down Stream: 4	Packaging (in.):	21.9 x 14.9 x 8.3
USB 3.2 Type B Up Stream: 1	Physical (in.):	19.7 x 15.23~19.56 x 8.1
3.5mm Audio In: 1	Physical Without Stand (in.):	19.7 x 11.6 x 2
3.5mm Audio Out: 1	DIMENSIONS (METRIC) (WXF	·
HDMI 1.4: 1	Packaging (mm):	556 x 379 x 210
DisplayPort: 1	Physical (mm):	501 x 386.85~496.96 x 206
Power in: 3-pin Socket (IEC C14 / CEE22)	Physical Without Stand (mm):	501 x 294 x 51
AUDIO	GENERAL	
Internal Speakers: 2Watts x2		cTUVus, FCC-B, ICES003, Energy Star, EPEAT, CEC, NOM, Mexico
POWER	Regulations:	Energy, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, TCO 9.0, EAC,
Eco Mode (Conserve): 12.35W		UkrSEPRO
Eco Mode (optimized): 14.43W	PACKAGE CONTENTS:	VG2240 x1, 3-pin Plug (IEC C13 / CEE22) x1, HDMI Cable (v1.4; Male- Male) x1, USB A/B Cable (v3.2; Male- Male) x1, Audio Cable (Male-Male) x1, Quick Start Guide x1
Consumption (typical): 17.18W		
0		
Consumption (max): 18.89W		Please dispose of in accordance with
Voltage: AC 100-240V	Recycle/Disposal:	
. , ,	Recycle/Disposal:	local, state or federal laws.
Voltage: AC 100-240V	Recycle/Disposal: Warranty:	local, state or federal laws. *Warranty offered may differ from market to market
Voltage: AC 100-240V Stand-by: 0.5W	, ,	*Warranty offered may differ from
Voltage: AC 100-240V Stand-by: 0.5W Power Supply: Internal Power Supply	Warranty:	*Warranty offered may differ from market to market

Copyright © ViewSonic Corporation 2000-2024. All rights reserved.

