

Key Features

- Instant, secure access to your digital workspace using Windows Hello
- Crystal-clear video with 5MP webcam, privacy cover, dual microphones, and stereo speakers
- QHD resolution and 120Hz refresh rate deliver ultra-smooth, razor-sharp visuals for meetings and multitasking
- USB-C port simplifies connections for audio, video, and data transfer
- USB 3.2 hub with 1 USB-C upstream, 3 USB downstream ports, HDMI, and DisplayPort inputs for seamless multi-device connectivity



Product **Description**

The VG2741V-2K is a 27" QHD (2560 x 1440) USB-C video conferencing monitor with Windows Hello, designed to deliver secure, high-quality virtual meetings straight out of the box. With facial recognition login via Windows Hello, users can sign in quickly and securely—reducing password fatigue and minimizing the risk of visual hacking. A built-in 5MP adjustable webcam, dual microphones, and dual 2W speakers provide sharp video and clear audio for professional-grade conferencing. The webcam's ±5° vertical tilt ensures perfect framing, while the built-in privacy cover safeguards user privacy when the camera is not in use. The monitor supports streamlined connectivity with a USB-C upstream port for video, audio, and data, plus HDMI, DisplayPort, and three USB 3.2 downstream ports—making it ideal for both home and office environments. The VG2741V-2K combines a sharp QHD resolution with a 120Hz refresh rate for ultra-smooth, pixel-precise visuals—ideal for video conferencing, multitasking, and media playback. Eye ProTech+ technology helps reduce fatigue with low blue light and flicker-free viewing. For additional productivity, it supports vDisplay Manager for on-screen control and vSplit for efficient window layout management—both available via the ViewSonic Display Portal. With full ergonomic adjustability including height, tilt, swivel, and pivot, the VG2741V-2K adapts to your setup for long-lasting comfort and flexible workflows.

- 1. Menu Control Panel
- 3. VESA Compatible(Wall Mount 100
- 5 HDMI

- 7. USB 3.2 Up Stream (Type C) 8. USB 3.2 Down Stream (Type A)
- Audio Out
 UsB Type C (Quick Charging)
 Microphones
 Is R Sensors

Visit Us www.viewsonic.com

DISPLAY	2/41V-2K 2/ QHD USB-C Video Coniere
Display Size (in.):	27
Viewable Area (in.):	27
Panel Type:	IPS Technology
Resolution:	2560 x 1440
Resolution Type:	QHD (Quad HD)
Static Contrast Ratio:	1,500:1 (typ)
Dynamic Contrast Ratio:	50M:1
Light Source:	LED
Brightness:	250 cd/m² (typ)
Colors:	16.7M
Color Space Support:	8 bit (6 bit + Hi-FRC)
Aspect Ratio:	16:9
Response Time (Typical GTG):	4ms
Response Time (GTG w/OD):	3.9ms
Viewing Angles:	178° horizontal, 178° vertical
Backlight Life (Hours):	30000 Hrs (Min)
Curvature:	Flat
Refresh Rate (Hz):	120
Variable Refresh Rate Technology:	Yes
Low Blue Light:	Hardware solution
Flicker-Free:	Yes
Color Gamut:	DCI-P3: 85% coverage (Typ) NTSC: 85% size (Typ) sRGB: 120% size (Typ)
Pixel Size:	0.233 mm (H) x 0.233 mm (V)
Surface Treatment:	Anti-Glare, Hard Coating (3H)
COMPATIBILITY	, , , , , , , , , , , , , , , , , , , ,
PC Resolution (max):	2560x1440
Mac® Resolution (max):	2560x1440
PC Operating System:	Windows 10/11 certified; macOS tested
Mac® Resolution (min):	2560x1440
CONNECTOR	
USB 3.2 Type A Down Stream:	2
USB 3.2 Type C Down stream:	1 (15W power charger)
USB 3.2 Type C Up Stream; DisplayPort Alt mode :	1
3.5mm Audio Out:	1
HDMI 2.0:	1
DisplayPort:	1
Power in:	3-pin Socket (IEC C14 / CEE22)
AUDIO	
Internal Speakers:	2Watts x2
POWER	
Eco Mode (Conserve):	17W
Eco Mode (optimized):	21W
Consumption (typical):	25W
Consumption (max):	70W
Voltage:	AC 100-240V
Stand-by:	0.5W
Power Supply:	Internal Power Supply
ADDITIONAL HARDWARE	
Kensington Lock Slot:	1
Webcam:	5.0M pixel
Cable Organization:	Yes
Microphone: CONTROLS	Yes
Physical Controls:	Key 1 (volume down), Key 2, Key 3, Key 4, Key 5, Key 6 (power) Input Select, Audio/MIC Adjust, ViewMode, Color Adjust,
On Screen Display:	Manual Image Adjust, Setup Menu
OPERATING CONDITIONS	
Temperature:	32°F to 104°F (0°C to 40°C)
Humidity (non-condensing): NALL MOUNT	20% to 90%
VESA Compatible:	100 x 100 mm
NPUT SIGNAL	
Frequency Horizontal:	30 ~ 230KHz
Frequency Vertical:	48 ~ 120Hz
VIDEO INPUT Digital Sync:	TMDS - HDMI (v2.0), PCI-E - DisplayPort (v1.4), Micro-
Digital Office	Packet - Type Č

ERGONOMICS	
Height Adjust (mm):	150
Swivel:	90°
Tilt (Forward/Back):	-5° / 20°
Pivot (Right/Left):	90° / 90°
WEIGHT (IMPERIAL)	
Net (lbs):	11.7
Net Without Stand (lbs):	8.2
Gross (lbs):	17.9
WEIGHT (METRIC)	
Net (kg):	5.3
Net Without Stand (kg):	3.7
Gross (kg):	8.1
DIMENSIONS (IMPERIAL) (WX	(HXD)
Packaging (in.):	27.6 x 20.7 x 4.9
Physical (in.):	24.15 x 15.78~21.69 x 8.11
Physical Without Stand (in.):	24.15 x 15.3 x 2.33
DIMENSIONS (METRIC) (WXH	XD)
Packaging (mm):	700 x 525 x 125
Physical (mm):	613.3 x 400.9~550.9 x 206.1
Physical Without Stand (mm):	613.3 x 388.7 x 59.2
GENERAL	
Regulations:	Energy Star, EPEAT, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO
PACKAGE CONTENTS:	VG2741V-2K x1, 3-pin Plug (IEC C13 / CEE22) x1, HDMI Cable (v2.0; Male-Male) x1, USB Type-C Cable (Male- Male; with Type-A adapter) x1, Quick Start Guide x1
Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
Warranty:	*Warranty offered may differ from market to market
Power Management:	Energy Star standards, EPEAT