



Mini GaN Charger 70W

2x USB-C® PD 70W
1x USB-A QC 3.0



Charge Faster, Pack Lighter

The ultimate 70W wall charger, designed to charge up to four devices simultaneously with speed and efficiency.

With its 2 USB-C ports and USB-A ports, this charger is capable of powering up to four devices at the same time, making it ideal for both work and travel.

Verbatim Mini GaN Chargers feature an advanced chipset that allows for an even more compact design than regular GaN chargers without sacrificing power. This innovative technology not only reduces the charger's size but also minimises heat generation, delivering safer and more efficient charging in a portable form factor. It supports USB Power Delivery 3.0, PPS, and Quick Charge 3.0, 4, and 4+ standards.

The compact design includes foldable US prongs, and replaceable EU and UK plugs, making it travel-ready.

Built from flame-resistant polycarbonate, it comes in eco-friendly packaging with a 2-year warranty.



PPS
Support



Charge
3 Devices



Multi-Plug
Included



Compact
Design



General Information			
Approx. product dimensions LxWxH	53.9 x 31 x 53.9 mm		
Product weight	115 g		
Product material	PC flame retardant material V0		
Colour	Black		
Input Plug Formats	US (Type A) / EU (Type C) / UK (Type G)		
Supported devices	Laptop, iPhone, iPad, Smartphones, Tablet PCs, MP3/MP4 players, smartwatch, etc.		
RoHS REACH	Yes		
Certifications	CE/LVD/FCC/CB		
Power			
Input	100-240 V AC 50/60Hz 1.8A (Max)		
Total Output	70 W Max		
Charging Mode	USB-C: PPS/PD3.0/ ,QC4+QC3.0/QC2.0, AFC,FCP,SCP, Apple 2.4A USB-A: QC3.0, QC2.0, AFC, FCP, SCP, Apple 2.4A		
Single Port Output			
USB-C1 Output PD 3.0 (PPS supported)	3.3V-11V/3A, 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/3.5A (70 W Max)		
USB-C2 Output PD 3.0 (PPS supported)	3.3V-11V/3A, 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/3.5A (70 W Max)		
USB-A Output	5V/3A, 9V/3A, 10V/2.25A, 12V/2.5A, 20V/1.5A (30 W Max)		
Multiport Output	USB-C1 PD 3.0	USB-C2 PD 3.0	USB-A QC 3.0
USB-C1+USB-C2	45 W Max	20 W Max	-
USB-C1+USB-A	45 W Max	-	18 W Max
USB-C2+USB-A	-	45 W Max	18 W Max
USB-C1+USB-C2+USB-A	30 W Max	20 W Max	18 W Max



US
Type A



UK
Type G



EU
Type C



Safety

Output short circuit protect	Yes
Over-voltage protection	Yes
Over-current protection	Yes
Over-temperature protection	Yes

Directives

Electromagnetic compatibility	2014/30/EC
Low voltage protection	2014/35/EC
General product safety	2001/95/EC
RoHS directive	2011/65/EC
Annex II	2015/863/EC
Test standards	EN 55032:2015+A11:2020+A1:2020 EN 55035:2017+A11:2020 EN 61000-3-2:2019+A2:2021 EN 61000-3-3:2013+A1:2019+A2:2021 EN IEC 62386-1:2020+A11:2020

Storage and Operating Conditions

Storage temperature	-20°C to +80°C
Operating temperature	-10°C to +40°C
Operating humidity	5%(0°)~90%(40°)RH

PN	Description	Tariff Code	Bar Code	EAN128 Code	EAN14 Code
32229	Mini GaN Charger 70W 3 Port US plug with EU and UK adaptors	85366990	023942322290	(02)00023942322290(37)10(91)892 (02)00023942322290(37)20(91)892	20023942322294 50023942322295

Logistic Information

Product Dimensions: L x W x H	53.9 x 31 x 53.9 mm
Product Weight:	115 g
Units per Pack:	1
Pack Dimensions:	110 x 47 x 123 mm
Pack Weight:	230 g
Packs per Inner Carton:	10
Inner Carton Dimensions: L x W x H	265 x 255 x 130 mm
Inner Carton Weight:	2630 g
Packs per Outer Carton:	20
Outer Carton Dimensions: L x W x H	560 x 270 x 290 mm
Outer Carton Weight:	1520 g
Outer Cartons per Layer:	8
Layers per Pallet:	4
Units per Pallet:	1280



Pack Contents

- Verbatim GaN Charger
- EU and UK plug Adapter
- Quick Start Guide



INDOOR USE ONLY.

Warranty

2 year limited warranty

For more information, please contact your key account manager

Publication date: 18/02/2025
© 2025 Verbatim. All rights reserved.
All brand names are registered trademarks of their respective owners.
Unauthorized use strictly prohibited.
Specifications are subject to change without prior notice.

