

INFORMATION



34" UWQHD curved monitor with USB-C dock, LAN, KVM switch and 15cm height adjustable stand

The XCB3497WQSNP is a 34-inch curved monitor that incorporates a KVM switch and a USB-C dock to simplify your workspace. The KVM switch enhances multitasking by allowing you to control multiple computers from a single monitor, keyboard, and mouse. The USB-C dock reduces cable clutter and simplifies connectivity even further, allowing a single cable to carry video, data, and power to charge your notebook. Additionally, when the monitor is connected to a LAN network, your notebook automatically gains network access. The VA panel technology delivers high contrast and deep black levels and wide viewing angles for consistent image quality regardless of your position for a richer and more vivid viewing experience.

For optimal comfort, the 15cm height-adjustable stand allows you to customize the screen position, while the Flicker-Free panel and Blue Light reduction function help minimize eye strain.



Easy multi-device control with KVM

Easily switch between multiple computers using one monitor, keyboard, and mouse, making multitasking smooth and efficient.



USB-C dock for tidy desk & easy connectivity

Connect everything with just one cable — handle video, data, and power while keeping your desk clean and organized.



Curved for immersive viewing

Step into an immersive, natural viewing setup that minimizes distortion and reduces eye strain during long work or entertainment sessions.



Multitasking with ultrawide QHD

Get more space to multitask, compare documents side by side, or fully immerse in your content without switching windows.

01

DISPLAY CHARACTERISTICS

Panel VA panel, matte finish Curved 1500R Native resolution 3440 x 1440 @120Hz (4.9 megapixel UWQHD, DisplayPort & USB-C) Aspect ratio 21:9 Panel brightness 350 cd/m² Static contrast 3000:1 Advanced contrast 80M:1 Response time (MPRT) Viewing zone horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89° Colour support 16.7mln (sRGB: 99%; NTSC: 93%)
Curved 1500R Native resolution 3440 x 1440 @120Hz (4.9 megapixel UWQHD, DisplayPort & USB-C) Aspect ratio 21:9 Panel brightness 350 cd/m² Static contrast 3000:1 Advanced contrast 80M:1 Response time (MPRT) Viewing zone horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°
Native resolution 3440 x 1440 @120Hz (4.9 megapixel UWQHD, DisplayPort & USB-C) Aspect ratio 21:9 Panel brightness 350 cd/m² Static contrast 3000:1 Advanced contrast 80M:1 Response time (MPRT) Viewing zone horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°
Aspect ratio Panel brightness 350 cd/m² Static contrast 3000:1 Advanced contrast 80M:1 Response time (MPRT) Viewing zone horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°
Panel brightness 350 cd/m² Static contrast 3000:1 Advanced contrast 80M:1 Response time (MPRT) Viewing zone horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°
Static contrast 3000:1 Advanced contrast 80M:1 Response time (MPRT) Viewing zone horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°
Advanced contrast Response time (MPRT) Viewing zone horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°
Response time (MPRT) Viewing zone horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°
(MPRT) Viewing zone horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°
Colour support 16.7mln (sRGB: 99%; NTSC: 93%)
Horizontal Sync 30 - 180kHz
Viewable area W x H 797.2 x 333.7mm, 31.3 x 13.1"
Pixel pitch 0.232mm
Colour matte, black



INTERFACES / CONNECTORS / CONTROLS

Signal input	HDMI x2 (1x v.2.0 and 1x v. 1.4, 3440x1440 @100Hz, 2560x1440 @120Hz) DisplayPort x1 (v.1.4, 3440 x 1440@ 120Hz) USB-C x1 (3440 x 1440@ 120Hz, PD 95W)
USB HUB	x4 (2x Type A v.3.2 Gen 1 (5Gbps, 4.5W) 2x Type C (5Gbps, 7.5W))
USB-C DOCK	x1 (Power delivery 95W, LAN, USB v. 3.2 (Gen 1, 5Gbit))
HDCP	yes
Headphone connector	yes
RJ45 (LAN)	x1



FEATURES

KVM switch	h yes
Blue light reduce	er yes
Flicker fre	e yes
Adaptive Syn suppo	
Ext	a i-Style Colour
OSD language	s EN, DE, FR, ES, IT, RU, JP, CZ, NL, PL
Control button	Joystick: Power/Menu (Centre), Forward/Signal Select, Backward, Left/i-Style colour/FCO/Bluel ight Beducer, Bight/Volume

picture adjust (brightness, contrast, Eco, ACR, OD, AdaptiveSync, motion blur reduction, X-Res technology, black tuner), colour settings (6-axis, i-Style colour, blue light reducer, gamma, RGB range, colour temp.,), OSD (OSD H. position, OSD V. position, OSD time, OSD background, DDC/CI control, display information), language, miscellaneous (sharpness, video mode adjust, opening logo, power LED, Mac address, USB charge, USB C speed), KVM (HDMI1, HDMI2, DisplayPort, USB C), input select, audio settings (volume, mute audio), recall

Speakers 2 x 5W

Convenience Kensington-lock™ prepared, DDC2B

04 MECHANICAL

Display position swivel, tilt adjustments

Height adjustment 150mm

Swivel stand 90°; 45° left; 45° right

Tilt angle 23° up; 5° down

VESA mounting 100 x 100mm

Cable management ye system



Cables power, USB, HDMI, DP, USB-C

Other quick start guide, safety guide

POWER MANAGEMENT

Power supply unit internal

Power supply AC 100 - 240V, 50/60Hz

Power usage 55W typical, 0.5W stand by, 0.3W off mode

7 SUSTAINABILITY

Regulations TCO Certified, CE, TÜV-GS, EAC, VCCI-B, PSE, RoHS support, ErP, WEEE, REACH,

UKCA

Energy efficiency F class (Regulation (EU) 2017/1369)

EPEAT Silver *registration varies by country, go to www.epeat.net for details

REACH SVHC above 0.1%: Lead

08 DIMENSIONS / WEIGHT

Product dimensions 807 x 426 (576) x 245.5mm

WxHxD

Box dimensions W x 928 x 480 x 186mm

H x D

Weight (without box) 9.7kg

Weight (with box) 14.1kg





All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects. © IIYAMA CORPORATION. ALL RIGHTS RESERVED