

C7000

The VersaLink C7000 Colour Printer is built on Xerox[®] ConnectKey[®] Technology. For more information, go to **www.connectkey.com**.



| System Specifications | VersaLink C7000N | VersaLink C7000DN |
|--|---|---|
| One-Sided Speed A4 / 210 x 297 mm A3 / 297 x 420 mm | Up to 35 ppm (pages per minute) long edge feed (LEF) Up to 19 ppm | |
| Two-Sided Speed A4 / 210 x 297 mm A3 / 297 x 420 mm | NA | Up to 35 ppm (pages per minute) long edge feed (LEF) Up to 13 ppm |
| Monthly Duty Cycle ¹ | Up to 153,000 pages / month ¹ | |
| Recommended Average Monthly Print Volume ² | Up to 10,000 pages | |
| Hard Drive | 320 GB HDD (Optional) | |
| Processor | 1.05 GHz Dual-Core | |
| Memory | 2 GB | |
| Connectivity | Ethernet 10/100/1000 Base-T, High-speed USB 3.0, Wi-Fi 802.11n/g/b/a and Wi-Fi Direct with optional Wi-Fi Kit (concurrent wired and wireless connections supported), NFC Tap-to-Pair | |
| Controller Features | Configuration Cloning, Xerox Extensible Interface Platform®, Xerox App Gallery, Xerox® Standard Accounting Tool, Role Based Permissions, Convenience Authentication Enabled, Online Support | |
| Device Specifications | | |
| Electrical Requirements | | |
| Europe | Voltage : 220-240V +/- 10 % Frequency: 50 Hz +/-3 % , 8A | |
| Power Consumption | | |
| Printing ³ | 1.6 kWh | |
| Standby Mode ³ | 94 Watts or less | |
| Sleep Mode ³ | 1.4 watts or less | |

| Operating Environment | | | | |
|---|---|------------------------|-----------|---------|
| Required Temperature Range (Storage) | 0° to 35° C | | | |
| Required Temperature Range (Operating) | 10 to 32° C | | | |
| Required Relative Humidity | 10% to 85% | | | |
| Sound Power Levels | Printing: 6.75 B(A) or less Standby: 4.10 B(A) or less | | | |
| | Full System (including finisher) Printing: 7.52 B(A) Standby: 4.10 B(A) | | | |
| Sound Pressure Levels | Printing: 52.5 dB(A) Standby: 26.0 dB(A) | | | |
| | Full System (including finisher) Printing: 60.0 dB(A) Standby: 26.0 dB(A) | | | |
| Boot Time (from Off to UI Ready) | As fast as 98 seconds | | | |
| Warm-up Time (from Sleep to UI Ready) | As fast as 12 seconds | | | |
| Dimensions and Weight (Unpackaged) | Width | Depth | Height | Weight |
| Base Unit | 590 mm | 670.8 mm | 637 mm | 54.3 kg |
| Base Unit with Single Tray with Stand Module | 615.7 mm | 670.8 mm | 1118.6 mm | 77.6 kg |
| Base Unit with Three Tray Module | 615.7 mm | 670.8 mm | 1118.6 mm | 81.8 kg |
| Base Unit with Three Tray Module and Integrated Office Finisher | 615.7 mm | 670.8 mm | 1118.6 mm | 97.6 kg |
| Certifications | • | | • | |
| To view the latest list of certificatio | ns, go to <mark>www.xerox.com</mark> / | /OfficeCertifications. | | |
| Print | | | | |
| First-print-out Time | As fast as 7.6 seconds Colour | | | |
| | As fast as 5.1 seconds B | lack | | |
| Print Resolution | Up to 1200 x 2400 dpi | | | |
| Page Description Languages | Adobe® PostScript® 3™ PCL® 5e, 6 PDF XPS TIFF JPEG HP-GL | | | |
| Maximum Print Area | 4 mm from lead edge of paper, 2 mm from Side and Trail edges of paper | | | |
| Print Features | Application Defaults Bi-directional Real-time Status Booklet Creation Draft Mode Job Identification Job Monitoring Personal Print (additional capacity enabled with HDD) Print from USB Sample Set Saved Job (additional capacity enabled with HDD) Scaling | | | |

| | Secure Print (additional capacity enabled with HDD) Skip Blank Pages Store and Recall Driver Settings Two-sided Printing (as default) Xerox® Earth Smart Driver Settings | |
|---|--|--|
| Print from USB | Allows walk-up printing from Type A USB port Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, XPS | |
| Operating Systems | Windows [®] , 7, 8, 10, Server 2000, Server 2003, Server 2008, Server 2008 R2 Server 2012 Mac OS [®] version 10.10, 10.11, & 10.12 Citrix Redhat [®] Enterprise Linux [®] IBM [®] AIX [®] 7.2 HP-UX [®] 11iv3 Oracle [®] Solaris 11.3 Fedora Core 24 SUSE [®] 13.2 | |
| Fonts | PostScript fonts: 136 PCL fonts: 83 | |
| Mobile Solutions and Mobile Devi | ce Apps | |
| Xerox [®] Mobile Express Driver [®] | Makes it easy for mobile users to find, use and manage Xerox [®] and non-Xerox [®] devices in every new location. Plug into a new network, and Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of "favourite" printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT. | |
| Xerox® Global Print Driver® | A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox® devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management. | |
| Apple [®] AirPrint [®] | Print email, photos and important office documents directly from an Apple iPhone® or iPad® with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network. | |
| Google Cloud Print™ | Google Cloud Print connects print devices to the web, enabling users to print the applications they use every day from smartphones, tablets, Chromebook™ notebook computers and any other web- connected device. | |
| Xerox® Print Service Plug-in for Android™ (Free at Google Play™ Store) | The Xerox [®] Print Service Plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, Web pages and documents when your mobile device is connected to printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play [™] store. | |
| Xerox [®] Print Management and Mobility Suite, Xerox [®] Print Management and Mobility Service | Xerox [®] Print Management and Mobility Suite is a modular set of workflows designed to save customers time and money by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version and with a cloud based-version of this solution. | |
| Software Solutions | | |
| Xerox® ConnectKey® Apps (Found at the Xerox® App Gallery) | Increase user productivity by simplifying and shortening everyday tasks. Unlike traditional software, ConnectKey Apps do not require a dedicated server, PC or IT resource. Instead, simply download these lightweight, serverless ConnectKey Apps to the device. | |
| Security | | |
| Standard Security Features | Firmware Verification Security Certificate Management Automatic Self-Signed Certificate Creation Certificate Revocation List (CRL)/Online Certificate Status Protocol (OCSP) Certificate Path Validation Immediate Disk Overwrite (requires optional HDD) AES 256-bit Encryption FIPS 140-2 TLS/SSL SNMPv3 Smart Card Enablement (CAC/PIV/.NET) | |

| Accounting | Detection of external programme falsification (XCP Plug-in) Network Authentication Access Controls Role Based Permissions Domain Filtering IP Address Filtering Port Filtering Audit Log Secure Print |
|---|---|
| Xerox [®] Standard Accounting / Ne | twork Accounting (Standard) |
| Tracking | Print usage |
| Accounting | Xerox® Standard Accounting Up to 1,000 User Accounts Up to 9,999 User Accounts with HDD installed Network Accounting (Job Based Accounting) Up to 1,000 User IDs; Up to 1,000 Account IDs Up to 60,000 User IDs; Up to 60,000 Account IDs with HDD installed Up to 14,000 accounting records (transactions) |
| Features | Administrator can manage the feature via the Embedded Web Server or local user interface on device |
| Accounting Options – Network Ac | counting (Allows central server to manage all accounting) |
| | Enhanced network accounting with up to the minute data on how the system is being used Comprehensive management and enterprise scale tracking and reporting of device print usage Numerous solutions are available through Xerox Alliance Partners. For details visit www.xerox.com Security enhancements includes support for HTTPS protocol Device requests account authentication from third party server enabling larger databases of users and accounts Accept Authentication Login at control panel and pass to third party Networking Account |
| Paper Handling | |
| Bypass Tray | |
| Capacity ⁴ | 100 sheets |
| Sizes | Custom sizes: 88.9 x 98.4 mm to 297 x 431.8 mm |
| Weights | 60 to 216 gsm |
| Types | Bond Plain Paper Cardstock Custom Envelopes Hole Punched Labels Heavyweight Labels Letterhead Lightweight Cardstock Lightweight Glossy Cardstock Lightweight Glossy Cardstock Reload Pre-Printed Recycled |
| Tray 1 | |
| Capacity ⁴ | 520 sheets |
| Sizes | Custom sizes: 139.7 x 182.0 mm to 297.0 x 431.8 mm |
| Weights | 60 to 256 gsm |
| Types | Bond Plain Paper Cardstock Custom |

| Single Tray Module (Optional) | Hole Punched Labels Heavyweight Labels Extra Heavyweight Labels Letterhead Lightweight Cardstock Lightweight Glossy Cardstock Reload Heavyweight Cardstock Pre-Printed Recycled | |
|----------------------------------|---|--|
| Capacity ⁴ | 520 sheets | |
| Sizes | Custom sizes: 139.7 x 182.0 mm to 297.0 x 431.8 mm | |
| Weights | 60 to 256 gsm | |
| Types | Bond Plain Paper Cardstock Custom Hole Punched Labels Heavyweight Labels Extra Heavyweight Labels Letterhead Lightweight Cardstock Lightweight Glossy Cardstock Reload Heavyweight Cardstock Pre-Printed Recycled | |
| Single Tray Module with Stand (O | ptional) | |
| Capacity ⁴ | 520 sheets | |
| Sizes | Custom sizes: 139.7 x 182.0 mm to 297.0 x 431.8 mm | |
| Weights | 60 to 256 gsm | |
| Types | Bond Plain Paper Cardstock Custom Hole Punched Labels Heavyweight Labels Extra Heavyweight Labels Letterhead Lightweight Cardstock Lightweight Glossy Cardstock Reload Heavyweight Cardstock Reload Heavyweight Cardstock Recycled | |
| Three Tray Module (Optional) | | |
| Capacity ⁴ | Tray 2: 520 sheets Tray 3: 520 sheets Tray 4: 520 sheets | |
| Sizes | Custom sizes: 139.7 x 182.0 mm to 297.0 x 431.8 mm | |
| Weights | 60 to 256 gsm | |
| Types | Bond Plain Paper Cardstock Custom Hole Punched Labels | |

| | Heavyweight Labels Extra Heavyweight Labels Letterhead Lightweight Cardstock Lightweight Glossy Cardstock Lightweight Glossy Cardstock Reload Heavyweight Cardstock Pre-Printed Recycled | |
|---|--|--|
| Envelope Tray – Replaces Tray 1 (| Optional) | |
| Capacity ⁴ | Up to 60 envelopes | |
| Sizes | DL, C5 Custom sizes: 98 x 148 mm to 162 x 241 mm | |
| Weights | 75 to 90 gsm | |
| Total Capacity | | |
| Base Unit Capacity ⁴ | 620 sheets | |
| Single Tray Module Capacity ⁴ | 1,140 sheets | |
| Single Tray Module with Stand Capacity ³ | 1,140 sheets | |
| Three Tray Module Capacity ⁴ | 2,180 sheets | |
| Finishing | | |
| Output Trays | | |
| Centre Output Catch Trays | 500 sheets; tray offsets | |
| Integrated Office Finisher (Option | nal) | |
| Stacking Tray | 500 sheets of 80 gsm – A4 or 250 sheets of 80 gsm – A3 | |
| Sizes | 89 x 98 mm to 297 x 432 mm | |
| Weights | 60 to 220 gsm | |
| Stapling | Single Auto stapling: 50 sheets maximum: A4 / B5-size sheets (less than 90 gsm or (2) 220 gsm covers) 30 sheets maximum: A3 / B4-size sheets (less than 90 gsm or (2) 220 gsm covers) | |
| Device Management | | |
| Network Protocols | TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD LDAP Bonjour® / AirPrint™ Most protocols not in use can be disabled | |
| Administrative Protocols | DHCP, SNMP, WINS, HTTP, HTTPS, TLS, SNTP, MDNS | |
| Xerox [®] CentreWare [®] Web | | |
| | A Web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system Works with any SNMP-managed printer from any manufacturer Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management | |
| Xerox [®] Embedded Web Server – I | ntegrated Device Web Page | |
| Device Status | Web server embedded • Tray status/contents • Consumables status | |
| Print Queue Viewing | Job print queue management—view and delete | |
| Job Submission | Print-ready files (PS, PCL, PDF, XPS, JPEG) | |

| Device Administration | Allows simple, remote installation setting of confid | auration options and management of the device | |
|---|--|--|--|
| Browsers | Allows simple, remote installation setting of configuration options and management of the device Microsoft® Internet Explorer® 11 Microsoft Edge™ 38 Mozilla™ Firefox® 48 Apple® Safari® 9.1 Google Chrome™ 52 | | |
| Remote Services | | | |
| Automated Meter Reading (AMR) | Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time. | | |
| Automated Supplies Replenishment (ASR) | Automatically orders supplies for Xerox output devices based on actual usage, eliminating the need to manually manage supplies inventory. | | |
| MaintenanceAssistant | Offers a fast (and free) way to resolve potential issues and receive assistance and automate the troubleshooting/repair process. Diagnostic data is sent to Xerox, allowing for problems to be solved faster with increased uptime. | | |
| Supplies and Accessories | Quantity | Part Number | |
| Supplies | | | |
| Standard Capacity Toner Cartridges | Cyan: 3,300 standard pages ⁵ Magenta: 3,300 standard pages ⁵ Yellow: 3,300 standard pages ⁵ Black: 5,300 standard pages ⁵ | 106R03764 106R03763 106R03762 106R03761 | |
| High Capacity Toner Cartridges | Cyan: 10,100 standard pages ⁵ Magenta: 10,100 standard pages ⁵ Yellow: 10,100 standard pages ⁵ Black: 10,700 standard pages ⁵ | 106R03760 106R03759 106R03758 106R03757 | |
| CMYK Drum Cartridge | 82,200 standard pages ⁶ | 113R00782 | |
| Waste Toner Bottle | 21,200 standard pages ⁶ | 115R00129 | |
| Fuser | 220V Fuser | 115R00138 | |
| Staple Refills for Finishers (3 refills per container) | 15,000 staples (5,000 each refill) | 008R12941 | |
| Staple Cartridge for Finishers (1 cartridge per container) | 5,000 staples (5,000 each cartridge) | 008R12964 | |
| Accessories / Options | | | |
| Single Tray Module (does not include stand) | | 097504910 | |
| Single Tray with Stand Module | | 097504907 | |
| Three Tray Module | | 097504908 | |
| Envelope Tray (This replaces Tray 1) | | 497K17720 | |
| Integrated Office Finisher | | 097504911 | |
| HDD (320 GB hard drive) (Optional) | | 497K17740 | |
| Wireless Network Adapter Kit | | 497K16750 | |
| Internal Card Reader / RFID Kit | | Various | |
| Unicode Printing Kit | | 320500291 | |

¹ Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.
 ² Expected regular monthly throughput.
 ³ Power states defined per ENERGY STAR® Programme requirements for Imaging Equipment.
 ⁴ Paper capacities are based on 75 gsm stock; capacities will vary with different weight stocks.
 ⁵ Average standard pages. Declared Yield in accordance with ISO/IEC19798. Yield will vary based on image, area coverage and print mode.
 ⁶ Approximate pages. Declared yield will vary depending on job run length, media size/orientation and machine speed. For more information visit: http://www.office.xerox.com/latest/SUPGL-01.pdf.

www.xerox.com

Configurations vary by geography.

©2017 Xerox Corporation. All rights reserved. Xerox®, Xerox and Design®, CentreWare®, ConnectKey® Global Print Driver®, Mobile Express Driver®, SuppliesAssistant® and VersaLink® are trademarks of Xerox Corporation in the United States and/or other countries. The information in this brochure is subject to change without notice. 6/17 VCVSS-01EA

