











PRODUCT FEATURES:

- Quick and easy installation,
- Equipped with four vertical mounting rails,

M. Lanberg

- Cable openings in the top and bottom panels and removable rear panel,

» /////////

- Equipped with front lock and side latches,
- Optional mounting of casters or feet.

PRODUCT SPECIFICATION:

Type of cabinet	Wall mount
Size	10",
ICT height	4 U
Assembly type	Self-assembly
Working depth	231 mm
Front door type	Temper glass
Door type	Single-leaf
Maximum front door opening angle	215 °
Maximum static load	30 kg
Slot amount for fans	2
Number of vertical rails	4
Thermostat	No
LCD panel	No
RAL color	RAL7035
Weatherproof rating	IP20
Upper & lower panel thickness	1 mm
Mounting rails thickness	1,5 mm
Frame thickness	1 mm
Depth	300 mm
Width	300 mm
Height	0 mm
Height without casters	281 mm
Weight	6,8 kg
Standard	ANSI/EIA RS-310-D, DIN 41491/PART 1, DIN 41494/PART 7, IEC297-2:1982
Grounding Details	Front door, Bottom panel
Included Accessories	User guide, Grounding cable, M6 screws, Mounting bracket, Front lock

EAN-13: 5901969441604 CAT. NO: WF11-3304-105