

### Overview

### Models

HP USB 3.0 to Gigabit RJ45 Adapter	N7P47AA
HP USB-C™ to USB 3.0	N2Z63AA
HP USB-C™ to 3 mm and 4.5 mm Power Adapter	N2Z65AA
HP USB-C™ to RJ45/USB 3.0/USB-C	N2Z64AA
HP USB-C™ to RJ45	V7W66AA
HP USB-C™ to USB-A Hub	Z6A00AA
HP USB-A to USB-C Dongle	3RV49AA
HP Elite USB-C Hub	4WX89AA
HP USB-C to 4.5mm Adapter	4ST73AA

#### HP USB 3.0 to Gigabit RJ45 Adapter

Convert your notebook's high-speed USB 3.0 connection to a fast 10/100/1000 Ethernet connection with the USB 3.0 to Giga LAN Adapter.

#### HP USB-C™ to USB 3.0

Convert your notebook or tablet's USB-C™ port to USB 3.0 with the HP USB-C™ to USB 3.0 Adapter.

#### HP USB-C™ to 3 mm and 4.5 mm Power Adapter

Travel light with the HP USB-C™ to 3 mm and 4.5 mm Adapter, which lets you use one power adapter to charge your tablet and notebook.

#### HP USB-C™ to RJ45/USB 3.0/USB-C

Easily enable reliable connectivity through wired USB 3.0, Ethernet, and USB-C™ power-in connections with the HP USB-C™ to RJ45/USB3/USB-C™ Adapter.

#### HP USB-C™ to RJ45

Easily connect to your network through your notebook or tablet's USB-C™ power-in port with the HP USB-C™ to RJ45 Adapter

#### HP USB-C to USB-A Hub

Optimize your workspace with easy connectivity to your frequently-used accessories in the office and on the road. Convert your notebook or tablet's USB-C™ port to a portable, lightweight USB hub and enable simultaneous connections to up to three USB accessories with the HP USB-C to USB-A Hub.

#### HP USB-A to USB-C Dongle

Give your HP notebook or mobile device access to the complete desktop experience of your HP USB-C Universal Dock with the HP USB-A to USB-C Dongle.

### Overview

#### HP Elite USB-C Hub

Take your tasks on the road or maximize your notebook's ports in the office with the modern, metallic, and portable HP Elite USB-C Hub. With just one USB-C™ cable, you get pass-through charging<sup>1</sup> and expanded data, video, and device connectivity.

1. Pass-through charging requires a notebook or tablet USB-C™ AC adapter. The hub does not include an AC Adapter.

---

#### HP USB-C to 4.5mm Adapter

Use one power cord for your HP tablets and notebooks with the HP USB-C to 4.5mm Adapter that connects from your device's USB-C™ port to a standard HP Smart AC Adapter.

---

### Technical Specifications

#### HP USB 3.0 to Gigabit RJ45 Adapter

<b>Part number</b>	N7P47AA
<b>Dimensions (L x W x H)</b>	6.1 X 2.0 x 1.4 cm 2.4 x 0.78 x 0.55 in
<b>Weight</b>	19 g .67 ounce
<b>Networking</b>	
<b>Connectivity Technology</b>	Wired
<b>Data Link Protocol</b>	Ethernet, Fast Ethernet, Gigabit Ethernet
<b>Data Transfer Rate</b>	1000
<b>Interfaces</b>	1 x network - Ethernet 10Base-T/100Base-TX/1000Base-T - RJ-45
<b>Connections</b>	1 x Super -Speed USB - 9 pin USB Type A
<b>LED's</b>	Yes
<b>Compatible Operating Systems</b>	Windows 7 (32-bit and 64-bit) Windows 8 (32-bit and 64-bit) Chrome

#### HP USB-C™ to USB 3.0

<b>Part number</b>	N2Z63AA
<b>Dimensions</b>	14.08 X 2.33 X 1.10 cm 5.55 x 0.92 x 0.43 in
<b>Weight</b>	175 g 6.17 ounces
<b>Connectors:</b>	HP USB Type-C to USB 3.0 Adapter
<b>LED's:</b>	NA
<b>Environmental Design</b>	
<b>Operating Temperature</b>	0°C to 40°C
<b>Non-operating (storage)</b>	-20°C to 60°C
<b>Humidity</b>	20%-80%RH
<b>Storage Humidity</b>	20%-90%RH
<b>EMI and Safety Certifications</b>	CE/FCC&IC/BSMI/VCCI/C-tick(RCM)/UL&cUL
<b>Compatibility</b>	TBD

#### HP USB-C™ to 3 mm and 4.5 mm Power Adapter

<b>Part number</b>	N2Z65AA		
<b>Dimensions (L x W x H)</b>	16.06 x 4.75 x 1.90 cm 6.32 x 1.87 x .75		
<b>Weight</b>	50 g 1.76 ounces		
<b>Connectors</b>	<b>I/O Port</b>	<b>Description</b>	<b>Quantity</b>
	<b>Input</b>	3 mm DC jack	1
	<b>Input</b>	4.5 mm DC Jack	1
	<b>Output</b>	Type C PD cable connector	1



### Technical Specifications

<b>LEDS</b>	None
<b>Environmental Design</b>	<p><b>Non-operating mode</b></p> <p><b>Transportation &amp; Storage</b> -40 to +70 °C for 72 hours Test Time of 4 hours Temperature Gradient: 20°C/ hour Min. Humidity 50%</p> <p><b>Operating mode</b></p> <p><b>Operating Temperature</b> +0 to +40 °C Test Time of 4 hours Temperature Gradient: 20°/ hour Humidity 50% Max Wet Bulb Temperature 29°C</p>
<b>EMI and Safety Certifications</b>	USB IF
<b>Compatibility</b>	TBD
<b>HP AC adapter compatibility</b>	Please connect a HP AC Adapter up to 65W.

### HP USB-C™ to RJ45/USB 3.0/USB-C

<b>Part number</b>	N2Z64AA
<b>Dimensions</b>	18.07 x 7.10 x 1.87 cm 7.12 x 2.80 x 0.74 in
<b>Weight</b>	245 g 8.64 ounces
<b>Data Link Protocol</b>	Ethernet, Fast Ethernet, Gigabit Ethernet
<b>Data Transfer Rate</b>	10/100/1000Mbps
<b>Connectors</b>	HP USB-C to RJ45/USB 3/USB-C
<b>LED's</b>	NA
<b>Operating Temperature</b>	0°C to 40°C
<b>Non-operating (storage)</b>	-20°C to 60°C
<b>Humidity</b>	20%-80%RH
<b>Storage Humidity</b>	20%-90%RH
<b>EMI and Safety Certifications</b>	CE/FCC&IC/BSMI/VCCI/C-tick(RCM)/UL&cUL/KCC/EAC/UK/SABS&NRCS/CB
<b>Compatibility</b>	TBD

### HP USB-C™ to RJ45

<b>Part number</b>	V7W66AA
<b>Dimensions (L x W x H)</b>	18.0 X 2.1 x 1.7 cm 7.1 x 0.8 x 0.7 in
<b>Weight</b>	71.4 gm 2.5 ounce
<b>Networking</b>	
<b>Connectivity Technology</b>	Wired
<b>Data Link Protocol</b>	Ethernet, Fast Ethernet, Gigabit Ethernet
<b>Data Transfer Rate</b>	10/100/1000Mbps
<b>Interfaces</b>	1 x network - Ethernet 10Base-T/100Base-TX/1000Base-T - RJ-45
<b>Connections</b>	1 x 22 pin USB Type C
<b>LED's</b>	Yes



### Technical Specifications

#### Environmental Design

<b>Operating Temperature</b>	0°C to 70°C
<b>Non-operating (storage)</b>	-55°C to +125°C
<b>Humidity</b>	Level 3
<b>Storage Humidity</b>	<=90% Rh in Al bag
<b>EMI and Safety Certifications</b>	EMC, CB, VCCI, CE, REACH, FCC, RCM, KCC, EAC, Ukraine

#### Compatible Operating Systems

Windows 7/8/8.1/10  
 Chrome OS  
 MACBOOK OSX

### HP USB-C™ to USB-A Hub

<b>Part number</b>	Z6A00AA
<b>Dimensions</b>	6.68 x 4.14 x 1.05 cm 2.63 x 1.63 x 0.42 in
<b>Weight</b>	36.5 g 1.28 ounces
<b>Connectors:</b>	HP USB-C™ to USB-A Hub
<b>LED's:</b>	NO
<b>Environmental Design</b>	
<b>Operating Temperature</b>	0°C to 35°C
<b>Non-operating (storage)</b>	-10°C to 35°C
<b>Humidity</b>	5%-85%RH
<b>Storage Humidity</b>	85%RH
<b>EMI and Safety Certifications</b>	CE/CB/FCC&IC/BSMI/VCCI/RCM/KCC/EAC/UL&Cul/Ukraine
<b>Compatibility</b>	HP Elite x2 1012 G1-G2, HP Pro x2 612 G2 HP EliteBook x360 1030 G2 HP EliteBook Folio 1040 G3 HP EliteBook Folio G1 HP EliteBook 1030 G1 HP EliteBook 820, 840, 850 G3-G4 HP EliteBook 725, 745, 755 G3-G4 HP ProBook 640, 650, 645, 655 G2-G3 HP ProBook 430, 440, 450, 470, 455 G4 HP Spectre Pro 13 G1 HP Chromebook 13 G1

### HP USB-A to USB-C Dongle

<b>Part number</b>	3RV49AA
<b>Dimensions</b>	36.6 x 23.3 x 11mm
<b>Dimensions</b> (Not including cable and USB-C plug)	
<b>Dimensions</b> (Including cable and USB-C plug)	138 x 23.3 x 11mm
<b>Weight</b>	17g
<b>Upstream port</b>	USB Type-A (USB 3.0) plug to host platform
<b>Downstream port</b>	USB 3.0 Type-C receptacle x1 Standard USB-C CC Logic IC integrated Standard USB-C MUX IC integrated for USB-C Reversible Function
<b>Temperature (operation)</b>	32~104 °F (0~40°C)
<b>Temperature (Non-operation)</b>	-4~140 °F (-20~+60°C)



### Technical Specifications

<b>Relative humidity (operation)</b>	5%~90% RH, non-condensing
<b>Relative humidity (Non-operation)</b>	5%~95% RH, non-condensing
<b>Altitude (operation)</b>	10000ft (3048m)
<b>Altitude (Non-operation)</b>	30000ft (9144m)
<b>Shock (operation)</b>	40G, 2ms, half-sine
<b>Shock (Non-operation)</b>	240G, 2ms, half-sine
<b>Random vibration (operation)</b>	~0.21Grms, 5~500 Hz
<b>Random vibration (Non-operation)</b>	~2.09Grms, 5-500 Hz, Non-Operating
<b>EMI and Safety Certifications</b>	TBA
<b>Compatibility</b>	HP USB-C Universal Dock

### HP Elite USB-C Hub

<b>Part number</b>	4WX89AA
<b>Dimensions</b>	3.8 x 0.98 x 0.28 in (97 x 25 x 7 mm)
<b>Unpackaged product dimensions (H x W x D)</b>	3.94 x 1.11 x 0.35 in (100.3 x 28.4 x 8.9 mm)
<b>Cable length</b>	1.5 in (37 mm)
<b>Unpackaged cable length</b>	1.18 in (30 mm)
<b>Weight</b>	1.3 oz (37g)
<b>Unpackaged product weight</b>	0.096 lb (0.043 kg)
<b>Connectors</b>	<ul style="list-style-type: none"> <li>- 1x Host Port (USB 3.0 - Type C Alt-Mode w/PD 3.0) with cable</li> <li>- 1x USB 3.0 connector</li> <li>- 1x USB 2.0 connector</li> <li>- 1x HDMI 2.0 port</li> <li>- 1x Type C power pass through port</li> </ul>
<b>Operating systems supported</b>	Win 10
<b>ALT mode video support</b>	2 Lanes
<b>Power delivery style</b>	Power pass thru (45W 65W 90W)
<b>Video output</b>	Single HDMI
<b>Max. display resolution</b>	HDMI 4K@60Hz
<b>Compatibility</b>	HP EliteBook 700 series G3, G4, G5; HP EliteBook 800 Series G3, G4, G5; HP EliteBook 1040 G4; HP EliteBook 1050 G1; HP Elite x2 1013 G3 Tablet; HP Elite x2 1012 Tablet G1, G2; HP Elite x2 612 G2 Tablet; HP EliteBook x360 1020 G2; HP EliteBook x360 1030 G2, G3; HP EliteBook x360 1040 G5; HP EliteBook Folio G1; HP ProBook 600 series G4; HP ProBook 400 series G5; HP ZBook 14u G5; HP ZBook 15u G5; HP ZBook 17 G3, G4, G5; HP ZBook 15 G3, G4, G5; HP ZBook Studio G3, G4; HP ZBook Create G4; HP ZBook Studio x360 G5 and HP ZBook Studio NT G5
<b>What is in the box?</b>	HP Elite USB-C Hub; Documentation

### Technical Specifications

#### HP USB-C to 4.5mm Adapter

<b>Part number</b>	4ST73AA
<b>Dimensions</b>	1.38 x 9.65 x 0.26 in (3.5 x 24.51 x 0.66 cm)
<b>Weight</b>	0.26 lb. (0.11 kg)
<b>Operating systems supported</b>	MS Windows 7 and above, Android, Chrome, and Mobile Win
<b>Power support</b>	45W, 65W and 90W barrel power adapters for HP notebooks
<b>Input voltage range</b>	Max. 20.5 Vdc Typical 19.5 Vdc Min. 18.5 Vdc
<b>Operating temperature</b>	+0 to +40°C
<b>Non-operating temperature</b>	-40 to +70°C for 72 hours
<b>Storage temperature</b>	-20°C - 60°C
<b>Operating humidity</b>	5% - 95% relative humidity; 40°C 24 hours
<b>Non-operating humidity</b>	90% relative humidity, (24 hr. soak at 65°C)
<b>Storage humidity</b>	5% - 95% relative humidity
<b>Compatibility</b>	Compatibility with all USB Type C products
<b>Warranty</b>	One-year limited
<b>Country of origin</b>	China

#### Service and Support

One-year limited warranty. Additional support is available 24 hours a day, seven days a week by phone as well as online support forums.

**NOTE:** Certain restrictions and exclusions apply. Consult the [HP Customer Support Center](#) for details.

### Summary

© Copyright 2019 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. Microsoft and Windows are US registered trademarks of Microsoft Corporation. USB Type-C™ and USB-C™ are trademarks of USB Implementers Forum.

<b>Date of change:</b>	<b>Version History:</b>		<b>Description of change:</b>
January 19, 2016	Version 1 to 2	Added	HP USB-C™ to RJ45
February 1, 2015	Version 2 to 3	Added	Environmental Design Specs for HP USB-C™ to RJ45
May 18, 2016	Version 3 to 4	Changed	Name and specs for HP USB-C™ to 3 mm and 4.5 mm Power Adapter
January 30, 2017	Version 4 to 5	Added	HP USB-C™ to USB-A Hub specs added
March 22, 2018	Version 5 to 6	Added	HP USB-A to USB-C Dongle specs
April 3, 2018	Version 6 to 7	Removed	“Multigenerational” removed from HP USB-A to USB-C Dongle overview
December 11, 2018	Version 7 to 8	Added	HP Elite USB-C Hub added
January 24, 2019	Version 8 to 9	Added	HP USB-C to 4.5mm Adapter
May 22, 2019	Version 9 to 10	Corrected	Typo in HP USB-C™ to RJ45/USB 3.0/USB-C
June 28, 2019	Version 10 to 11	Update	Dimensions and weight added to HP USB-C to 4.5mm Adapter specs