





TS-h1683XU-RP-E2136-128G	
CPU	Intel® Xeon® E-2136 6-core 3.3 GHz processor (burst up to 4.5 GHz)
CPU Architecture	64-bit x86
Floating Point Unit	Yes
Encryption Engine	Yes (AES-NI)
System Memory	128 GB UDIMM DDR4 ECC (4 x 32GB)
Maximum Memory	128 GB (4 x 32 GB)
Memory Slot	4 x UDIMM DDR4
Flash Memory	5GB (Dual boot OS protection)
Drive Bay	16 x 3.5-inch SATA 6Gb/s, 3Gb/s
Drive Compatibility	3.5-inch bays: 3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives
Hot-swappable	Yes
SSD Cache Acceleration Support	Yes
GPU pass-through	Yes
Gigabit Ethernet Port (RJ45)	4
10 Gigabit Ethernet Port	2 x 10GbE SFP+ SmartNIC port, 2 x 10GBase-T port
Wake on LAN (WOL)	Yes
Jumbo Frame	Yes
PCIe Slot	4 Slot 1: PCIe Gen 2 x4 (PCH) Slot 2: PCIe Gen 3 x8 (CPU) Slot 3: PCIe Gen 3 x4 (CPU) Slot 4: PCIe Gen 3 x4 (CPU)

USB 3.2 Gen 2 (10Gbps) Port	2 x Type-C USB 3.2 Gen 2 10Gbps 4 x Type-A USB 3.2 Gen 2 10Gbps
Form Factor	3U Rackmount
LED Indicators	HDD 1-16, Status, LAN, storage expansion port status
Buttons	Power, Reset
Dimensions (HxWxD)	130 × 481 × 573.5 mm
Weight (Net)	13.76 kg
Weight (Gross)	21.79 kg
Operating temperature	0 - 40 °C (32°F - 104°F)
Storage Temperature	-20 - 70°C (-4°F - 158°F)
Relative Humidity	5-95% RH non-condensing, wet bulb: 27°C (80.6°F)
Power Supply Unit	500W(x2), 100-240V
Power Consumption: Operating Mode, Typical	149 W
Fan	System fan: 3 x 80mm, 12VDC
System Warning	Buzzer
Max. Number of Concurrent Connections (CIFS) - with Max. Memory	10000

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications.

 $Warning: Using \ unsupported \ modules \ may \ degrade \ performance, \ cause \ errors, \ or \ prevent \ the \ operating \ system \ from \ starting.$

Environment: Refer to ISO 7779; Maximum HDD loaded; Bystander Position; Average data from 1 meter in front of operating NAS. Product images are for illustrative purposes only and may differ from the actual product. Due to differences in monitors, colors of products may also appear different to those shown on the site.

Designs and specifications are subject to change without notice.

^{*} Sound Level Test