

**Data Sheet** 

## Barracuda®

The Power of One

## **Key Advantages**

- Double your capacity and reduce costs with the industry's first 1TBper-disc hard drive technology
- Up to 3TB capacity with 7,200 RPM performance why compromise?
- SATA 6Gb/s interface optimises burst performance
- Seagate AcuTrac<sup>™</sup> servo technology delivers dependable performance, even with hard drive track widths of only 75 nanometres
- Seagate OptiCache<sup>™</sup> technology boosts overall performance by as much as 45% over the previous generation
- Seagate SmartAlign<sup>™</sup> technology provides a simple, transparent migration to Advanced Format 4K sectors
- Free Seagate DiscWizard<sup>™</sup> software allows you to install a 3TB hard drive in Windows, including XP, without UEFI BIOS

## **Best-fit Applications**

- Desktop or all-in-one PCs
- Home servers
- PC-based gaming systems
- Desktop RAID
- Direct attached external storage devices (DAS)
- Network attached storage devices (NAS)



## Barracuda®





Specifications	3TB <sup>1</sup>	2TB <sup>1</sup>	1.5TB <sup>1</sup>	1TB <sup>1</sup>	750GB <sup>1</sup>	500GB <sup>1</sup>	320GB <sup>1</sup>	250GB <sup>1</sup>
Model Number	ST3000DM001	ST2000DM001	ST1500DM003	ST1000DM003	ST750DM003	ST500DM002 <sup>2</sup>	ST320DM000 <sup>2</sup>	ST250DM000 <sup>2</sup>
Interface Options	SATA 6Gb/s NCQ	SATA 6Gb/s NCQ	SATA 6Gb/s NCQ	SATA 6Gb/s NCQ	SATA 6Gb/s NCQ	SATA 6Gb/s NCQ	SATA 6Gb/s NCQ	SATA 6Gb/s NCQ
Performance								
Spindle Speed (RPM)	7,200	7,200	7,200	7,200	7,200	7,200	7,200	7,200
Cache, Multi-segmented (MB)	64	64	64	64	64	16	16	16
SATA Transfer Rates Supported (Gb/s)	6.0/3.0/1.5	6.0/3.0/1.5	6.0/3.0/1.5	6.0/3.0/1.5	6.0/3.0/1.5	6.0/3.0/1.5	6.0/3.0/1.5	6.0/3.0/1.5
Seek Average, Read (ms)	<8.5	<8.5	<8.5	<8.5	<8.5	<11	<11	<11
Seek Average, Write (ms)	<9.5	<9.5	<9.5	<9.5	<9.5	<12	<12	<12
Average Data Rate, Read/Write (MB/s)	156	156	156	156	156	125	125	125
Max Sustained Data Rate, OD Read (MB/s)	210	210	210	210	210	144	144	144
Configuration/Organisation								
Heads/Discs	6/3	6/3	4/2	2/1	2/1	2/1	2/1	1/1
Bytes per Sector	4,096	4,096	4,096	4,096	4,096	4,096 or 512 <sup>2</sup>	4,096 or 512 <sup>2</sup>	4,096 or 512 <sup>2</sup>
Voltage								
Voltage Tolerance, Including Noise (5V)	+10%/-5.0%	+10%/-5.0%	+10%/-5.0%	+10%/-5.0%	+10%/-5.0%	+10%/-5.0%	+10%/-5.0%	+10%/-5.0%
Voltage Tolerance, Including Noise (12V)	+10%/-7.5%	+10%/-7.5%	+10%/-7.5%	+10%/-7.5%	+10%/-7.5%	+10%/-7.5%	+10%/-7.5%	+10%/-7.5%
Reliability/Data Integrity								
Contact Start/Stop Cycles	_	_	_	_	_	50,000	50,000	50,000
Load/Unload Cycles	300,000	300,000	300,000	300,000	300,000	_	_	_
Non-recoverable Read Errors per Bits Read, Max	1 per 10E14	1 per 10E14	1 per 10E14	1 per 10E14	1 per 10E14	1 per 10E14	1 per 10E14	1 per 10E14
Annualised Failure Rate (AFR)	<1%	<1%	<1%	<1%	<1%	<1%	<1%	<1%
Power-on Hours	2,400	2,400	2,400	2,400	2,400	2,400	2,400	2,400
Power Management								
Startup Power (A)	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0
Operating Mode, Typical (W)	8.0	8.0	6.70	5.90	5.90	6.19	6.19	6.19
Idling2 Average (W)	5.40	5.40	4.50	3.36	3.36	_	_	_
Idling Average (W)	_	_	_	_	_	4.60	4.60	4.60
Standby Mode (W)	0.75	0.75	0.75	0.63	0.63	0.79	0.79	0.79
Sleep Mode (W)	0.75	0.75	0.75	0.63	0.63	0.79	0.79	0.79
Environmental								
Temperature								
Operating (ambient min °C)	0	0	0	0	0	0	0	0
Operating (drive case max °C)	60	60	60	60	60	60	60	60
Non-operating (ambient °C)	-40 to 70	-40 to 70	-40 to 70	-40 to 70	-40 to 70	-40 to 70	-40 to 70	-40 to 70
Physical								
Height (mm/in)	26.11/1.028	26.11/1.028	26.11/1.028	20.17/0.7825	20.17/0.7825	19.98/0.787	19.98/0.787	19.98/0.787
Width (mm/in)	101.6/4.0	101.6/4.0	101.6/4.0	101.6/4.0	101.6/4.0	101.6/4.0	101.6/4.0	101.6/4.0
Depth (mm/in)	146.99/5.787	146.99/5.787	146.99/5.787	146.99/5.787	146.99/5.787	146.99/5.787	146.99/5.787	146.99/5.787
Weight (g/lb)	626/1.38	626/1.38	535/1.18	400/0.88	400/0.88	415/0.92	415/0.92	415/0.92
Carton Unit Quantity	20	20	20	25	25	25	25	25
Cartons per Layer	40	40	40	40	40	40	40	40
Cartons per Pallet	8	8	8	8	8	8	8	8
Special Features								
Seagate OptiCache™ Technology	Yes	Yes	Yes	Yes	Yes	No	No	No
Seagate AcuTrac <sup>™</sup> Technology	Yes	Yes	Yes	Yes	Yes	No	No	No
Seagate SmartAlign™ Technology	Yes	Yes	Yes	Yes	Yes	Yes <sup>2</sup>	Yes <sup>2</sup>	Yes <sup>2</sup>

<sup>&</sup>lt;sup>1</sup> One gigabyte, or GB, equals one billion bytes; and one terabyte, or TB, equals one trillion bytes when referring to drive capacity.





www.seagate.com

EUROPE, MIDDLE EAST AND AFRICA

AMERICAS

Seagate Technology LLC 10200 South De Anza Boulevard, Cupertino, California 95014, United States, +1 408 658 1000 Seagate Singapore International Headquarters Pte. Ltd. 7000 Ang Mo Kio Avenue 5, Singapore 569877, +65 6485 3888 Seagate Technology SAS 16-18 rue du Dôme, 92100 Boulogne-Billancourt, France, +33 1 41 86 10 00

<sup>&</sup>lt;sup>2</sup> Seagate ships this drive in both 4K- and 512-byte sectors. SmartAlign technology is included on 4K sector drives. Both drives are functionally and physically equivalent.