



System Specification	Phaser 6510N	Phaser 6510DN	Phaser 6510DNI
One-Sided Speed 8.5 x 11 in. 8.5 x 14 in. / 216 x 356 mm A4 / 210 x 297 mm	Up to 30 ppm Color and Black and White Up to 24 ppm Color and Black and White Up to 28 ppm Color and Black and White		
Two-Sided Speed 8.5 x 11 in. 8.5 x 14 in. / 216 x 356 mm A4 / 210 x 297 mm	NA NA NA	Up to 18 ppm Color and Black and White Up to 17 ppm Color and Black and White Up to 19 ppm Color and Black and White	
Monthly Duty Cycle ¹	Up to 50,000 pages / month		
Recommended Average Monthly Print Volume ²	Up to 3,000 pages		
Processor	733 MHz		
Memory	1 GB		
Connectivity	10/100/1000Base-T Ethernet USB 3.0		10/100/1000Base-T Ethernet USB 3.0 Wi-Fi 802.11n Wi-Fi Direct®
Paper Handling	Phaser 6510N	Phaser 6510DN	Phaser 6510DNI
Bypass Tray			
Capacity ³	50 sheets		
Sizes	Custom Sizes: 3 x 5 in. to 8.5 x 14 in. / 76 x 127	mm to 216 x 356 mm	
Weights	16 lb. bond to 58 lb. cover / 60 to 220 gsm		
Media Types	Bond Plain Card Stock Custom Envelopes Glossy Card Stock Hole punched Labels Letterhead Lightweight Cardstock Lightweight Glossy Card Stock Preprinted Recycled		
Tray 1			
Capacity ³	250 sheets		
Sizes	Custom Sizes 3 x 5.8 in. to 8.5 x 14 in. / 76 x 14	7 mm to 216 x 356 mm	
Weights	16 lb. bond to 65 lb. cover / 60 to 176 gsm		

-					
	Tray 1				
Media Types	Bond Plain Card Stock Custom Envelopes Glossy Card Stock Hole punched Labels Letterhead Lightweight Cardstock Lightweight Glossy Card Stock Preprinted Recycled				
Optional Tray 2					
Capacity ³	550 sheets				
Sizes	Custom Sizes: 3 x 7.5 in. to 8.5 x 14 in. / 76 x 19	91 mm to 216 x 356 mm			
Weights	16 lb. bond to 65 lb. cover / 60 to 176 gsm				
Media Types	Bond Plain Card Stock Custom Glossy Card Stock Hole punched Letterhead Lightweight Cardstock Lightweight Glossy Card Stock Preprinted Recycled				
Total Capacity					
Device Standard Capacity ³	300 sheets				
Device Total Capacity ³	850 sheets				
Paper Output					
Output Capacity ³	150 sheets				
Automatic 2-Sided	NA	Standard			
Device Specification	Phaser 6510N	Phaser 6510DN	Phaser 6510DNI		
Electrical Requirements					
North America	Voltage: 120 VAC +/- 10 % Frequency: 60 Hz +/- 3 Hz, 12A				
Europe	Voltage: 220-240 VAC +/- 10% Frequency: 50 Hz +/- 3 Hz, 6A				
Power Consumption					
Operation ⁴	120V: Maximum 380 watts 220V: Maximum 350 watts				
Standby Mode ⁴	120V: Maximum 41 watts 220V: Maximum 44 watts				
Power Off Mode ⁴	120V: Maximum 0.2 watts 220V: Maximum 0.3 watts				
Sleep Mode [®]	120V: Maximum 0.9 watts 220V: Maximum 1.0 watts				
Warm-up (from Sleep Mode)	As fast as 26 seconds				
Operating Environment					
Required Temperature Range Storage Operating	-4°F to 104°F / -20°C to 40°C 41°F to 90°F / 5°C to 32°C				
Required Reletive Humidity	15% to 85%				

Operating Environment		
Sound Power Levels		
Operating Standby	6.76 B or less 4.00 B or less	
Sound Pressure Levels Operating Standby	51.9 dB(A) or less 24.9 dB(A) or less	
Dimensions and Weight (unpackaged)		
Phaser 6510N, and DN	Width: 16.5 in. / 420 mm Depth: 19 in. / 483 mm Height: 13.7 in. / 347 mm Weight: 52.5 lb. / 23.8 kg	
Phaser 6510 DNI	Width: 16.5 in. / 420 mm Depth: 19.6 in. / 499 mm Height: 13.7 in. / 347 mm Weight: 52.5 lb. / 23.8 kg	
550-sheet Paper Tray	Width: 16.5 in. / 420 mm Depth: 18.3 in. / 465 mm Height: 5.9 in. / 150 mm Weight: 14.8 lb. / 6.7 kg	
Dimensions and Weight (packaged)		
Phaser 6510N, DN, and DNI	Width: 14.3 in. / 634 mm Depth: 22.8 in. / 580 mm Height: 19.9 in. / 505 mm Weight: 64.4 lb. / 29.2 kg	
550-sheet Paper Tray	Width: 21.1 in. / 535 mm Depth: 23 in. / 584 mm Height: 9.8 in. / 248 mm Weight: 18.7 lb. / 8.5 kg	
System Certification/Regulatory Compliance		
Certifications	FCC Part 15 Class A FCC Part 68 CE Mark applicable to Directives 2006/95/EC, 2004/108/EC and 1999/5/EC UL 60950-1/CSA 60950-1-07, 2nd Edition NOM GS Mark EAC Citrix [™] Certified Cerner (undergoing evaluation) Apple® AirPrint [®] Certification Google Cloud Print [®] Certification Mopria® certified Wi-Fi Alliance Certified Blue Angel MEDITECH ENERGY STAR® ECOLOGO® EPEAT (United States) To view the latest list of certifications, go to www.xerox.com/OfficeCertifications.	
Print	Phaser 6510N Phaser 6510DN Phaser	6510DNI
First-Page-Out Time	As fast as 12 seconds Color and Black and White	
Resolution	Up to 1200 x 2400 dpi	
Page Description Languages	Adobe® PostScript® 3 [™] PCL® 5e, 6 PDF TIFF	
Maximum Print Area	4 mm from all edges	

Print	Phaser 6510N	Phaser 6510DN	Phaser 6510DNI
Print Features	Banner Sheets Booklet Print Cover / Separators Draft Mode Fit to Page N-up Overlays PANTONE [®] Color Calibrated Solic Personal Print Poster Printing Proof Print RAM Collation Run Black Saved Print Secure Print Watermarks	d-color Simulations	
Print from USB	Allows walk-up printing from Typ Supports direct printing from cor Supported file formats: PDF, JPE(mputer via Type B USB port	
Operating Systems	Windows [®] , 7, 8, 10, Server 2000, Mac OS [®] version 10.9 and higher Citrix [®] Redhat [®] Enterprise Linux [®] IBM [®] AIX [®] 5 HP-UX [®] 11iv2 Oracle [®] Solaris 9, 10 Fedora Core 12-15 SUSE [®]	Server 2003, Server 2008, Server 2008 R2, Server 20	012
Network Protocols	TCP/IP: HTTP/HTTPS, IPP, LPR/LE SMB SMTP, Secure SMTP LDAP, Secure LDAP Bonjour® / Airprint® FTP Most protocols not in use can be	DP, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD	
Administrative Protocols	DHCP, SNMP v2/3, WINS, DHCP	Autonet, TLS, SNTP, MDNS	
Font Capability	136 PostScript fonts 88 PCL fonts		
Mobile Solutions and Mobile Device Apps	'		
Xerox [®] Mobile Express Driver [®]	Makes it easy for mobile users to find, use and manage Xerox [®] and non Xerox [®] devices in every new location. Plug into a new network, and N Express Driver automatically discovers available printers and provides status and capability information. Save a list of "favorite" printers for location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.		pability information. Save a list of "favorite" printers for each
Xerox [®] Global Print Driver [®]	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox [®] and non Xerox [®] devices from a single driver. It prov a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.		
Apple [®] AirPrint [®]	Print email, photos and important office documents directly from an Apple iPhone® or iPad® with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network.		
Google Cloud Print [™]		t devices to the web, enabling users to print the ap ters and any other web-connected device.	plications they use every day from smartphones, tablets,
Xerox® Print Service Plug-in for Android [™] (Free at Google Play™ Store)	The Xerox [®] Print Service Plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, Web pages and documents when your mobile device is connected to multifunction printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play [™] store.		
$\operatorname{Xerox}^{\otimes}$ Wireless Print Solutions Adapter (Optional)		ns Adapter seamlessly connects your Xerox [®] printer nore information, visit <mark>www.xerox.com/WPSA</mark>	or MFP to modern mobile and desktop workflows, regardless

Security	Phaser 6510N	Phaser 6510DN	Phaser 6510DNI	
Security Features	Secure HTTPS (TLS) IPsec 802.1x Authentication S/MIME IP Filtering Secure Print SNMP v3 LDAP (SASL)			
Device Management				
Xerox [®] CentreWare [®] Web				
	whether running Windows or UWorks with any SNMP-manager	 A Web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system Works with any SNMP-managed printer from any manufacturer Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management. 		
Xerox® Embedded Web Server - Integrated	d Device Web Page			
Device Status	Web server embedded • Tray status/contents • Consumables status			
Print Queue Viewing	Complete job print queue manag	gement—hold, release, promote and delete		
Job Submission	Print-ready files (PS, PCL [®] , PDF, XF Output feature selection	Print-ready files (PS, PCL [®] , PDF, XPS, JPEG) Output feature selection		
Device Administration	Allows simple, remote installation	n setting of configuration options and manage	ement of the device.	
Browsers	Microsoft [®] Internet Explorer 11 Microsoft Edge [™] 38 Mozilla [™] Firefox [®] 48 Apple [®] Safari [®] 9.1 Google Chrome [™] 52 Opera [™] 39			
Remote Print Services				
Xerox [®] MeterAssistant [®] Service		Automates the process of collecting and submitting meter reads for tracking and billing of Xerox $^{\circ}$ device usage. Eliminates the need for time- consumingend-user involvement and ensures that meter reads are submitted to Xerox on time.		
Xerox [®] SuppliesAssistant [®] Service	Automatically orders supplies for	Automatically orders supplies for Xerox [®] output devices based on actual usage, eliminating the need to manually manage supplies inventory.		
Maintenance Assistant		Offers a fast (and free) way to resolve potential issues and receive assistance and automate the troubleshooting/repair process. Diagnostic data is sent to Xerox, allowing for problems to be solved faster with increased uptime.		
What's In The Box				
	 Phaser 6510 Color Printer Standard Capacity Print cartridy Software and Documentation (Warranty Statement) Installation Guide Quick Use Guides Power cord 	 Standard Capacity Print cartridge: One of each (Cyan, Magenta, Yellow: 1,000 print capacity⁵; Black: 1,500 print capacity⁵ Software and Documentation CD (with User Manual, Quick Install Guide, Safety, Regulatory, Recycling and Disposal Guides, Print Drivers, and Warranty Statement) Installation Guide Quick Use Guides 		
Supplies and Accessories	Quantity	Part M	Number	
Supplies				
Extra-High Capacity Print Cartridges	Cyan: 4,300 standard pages ⁵ Magenta: 4,300 standard pages ⁵ Yellow: 4,300 standard pages ⁵	106R0	03690 03691 03692	
High Capacity Print Cartridges	Black: 5,500 standard pages ⁵ Cyan: 2,400 standard pages ⁵ Magenta: 2,400 standard pages ⁵ Yellow: 2,400 standard pages ⁵	106R0 106R0	03480 03477 03478 03479	
Standard Capacity Print Cartridges	Black: 2,500 standard pages ⁵ Cyan: 1,000 standard pages ⁵ Magenta: 1,000 standard pages ⁵ Yellow: 1,000 standard pages ⁵	106R0 106R0	03476 03473 03474 03475	

Supplies and Accessories	Quantity	Part Number	
Supplies			
Drum Cartridge	Black: 48,000 pages ⁶ Cyan: 48,000 pages ⁶ Magenta: 48,000 pages ⁶ Yellow: 48,000 pages ⁶	108R01420 108R01417 108R01418 108R01419	
Waste Cartridge	30,000 pages ⁶	108R01416	
Accessories			
550-sheet Paper Tray		097504765	
Wireless Network Adapter		497K16750	

 1 Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis. 2 Expected regular monthly throughput.

³ Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks.

⁶ Average standard pages. Declared Yield in accordance with ISO/IEC19752. Yield will vary based on image, area coverage and print mode. ⁶ Approximate pages. Declared Yield based on letter-/A4-size 20 lb. (75 gsm) pages. Yield will vary based on media type, size, weight, orientation, and usage patterns.

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling program . For more information, visit www.xerox.com/about-xerox/recycling.



For more information, visit us at www.xerox.com/office

©2016 Xerox Corporation. All rights reserved. Xerox[®], Xerox and Design[®], CentreWare[®], Global Print Driver[®], MeterAssistant[®], Mobile Express Driver[®], Phaser[®], and SuppliesAssistant[®] are trademarks of Xerox Corporation in the United States and/or other countries. As an ENERGY STAR[®] partner, Xerox Corporation has determined that this product meets the ENERGY STAR guidelines for energy efficiency (DN and DNI configurations). ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. The information in this brochure is subject to change without notice. 11/16 BR19948 65XSS-01UA