

With the PROTON Series, CHIEFTEC advances into the new-age DC to DC power supply technology. The series allows for energy conservation, as well as a much higher efficiency and power stability, which in turn ensures a higher longevity of installed components. The efficiency of the PROTON Series is certified at 80 PLUS® BRONZE thereby fulfilling all ENERGY STAR 5.0 and higher requirements as stipulated by the EU.



Technical data					
Model	Proton 850W				
Artikel no.	BDF-850C				
EAN code	4710713231306				
Weight (without/with package)	2.48 kg / 2.98 kg				
Specification	ATX 12V 2.3				
Form factor	PS II				
Efficiency	80 PLUS® Bronze				
PFC	Active PFC (0.9)				
Fan	140mm silent fan				
Dimension (DxWxH)	160mm x 150mm x 87mm				
Security	AFC (Automatic Fanspeed Control) OCP (Overcurrent Protection) OPP (Overload Protection) OTP (Over Temperature Protection) OVP (Overvoltage Protection) SCP (Short-circuit Protection) SIP (Surge & Inrush Protection) UVP (Undervoltage Protection)				
Warranty	24 Months				

Output data								
	AC Input	100-240V 50-60Hz 15A						
Proton 850W	DC Output	+3.3V	+5V	+12V	-12V	+5VSB		
	Max. Current	22A	22A	70.5A	0.5A	3A		
	Max. Combined Power	140W		846W	6W	15W		
		850W						

^{*} The listed specifications may be altered at any point in time without any pre-notice.

^{**} Chieftec® is a registered trademark. All other brands and/or logos are property of the respective owners.



Proton Series | 850W

	Cable	Connectors	Length (mm)	
	24 PIN (20+4)	1	500	
	8 PIN EPS (4+4)	1	550	
	8 PIN EPS	1	550	
	8 PIN PCI-E (6+2)	6	3x 500/150	
	MOLEX	3	450/150/150/150	
	FLOPPY	1		
SATA SATA SATA SATA SATA SATA SATA SATA	SATA	9	3x 450/150/150	
SATA SATA SATA				



^{*} The listed specifications may be altered at any point in time without any pre-notice.

^{**} Chieftec* is a registered trademark. All other brands and/or logos are property of the respective owners.