




MX320/MX420 Series

Reliability. Security. Productivity.



Lexmork













Lexmark MX320/MX420 Series

The MX320/420 Series offers print speeds up to 42 pages per minute*, plus fax, automatic document feeder, and copy functions powered by a standard multi-core processor and a full gigabyte of memory. Connect with standard USB and gigabit ethernet. And up to 350 sheets of standard input can grow to 900 with optional trays.



Get more done

- Fax, print, copy and scan with the power of a multi-core processor and 1 GB of memory.
- Print at up to 42 or 38 pages per minute (depending on model) and scan up to 45 images per minute.
- Intuitive 4.3-inch colour touch screen (MX421ade) offers smooth, tablet-like interaction.
- 2.4-inch colour LCD (MX321adn) lets you configure, interact and monitor vital system information.
- Built-in productivity apps (MX421ade) save time and improve efficiency.

Ready when you are

- ▶ Long-life fuser and imaging components extend uptime.
- Unison[™] Toner replacement cartridges deliver up to 20,000 pages** of high-quality printing.
- Maximum input capacity of 900 pages means fewer interruptions.
- Durable metal frame is designed for longevity.

Robust, built-in security

- Lexmark's full-spectrum security architecture helps keep your information safe—on the document, the device, over the network, and everywhere in between.
- A range of embedded features harden device against attacks.
- Go beyond standard Confidential Print with optional security solutions like Print Release (available on MX421ade).
- Keypoint Intelligence Buyers Lab honored Lexmark with a prestigious BLI PaceSetter award for Document Imaging Security***.



Built for planet earth

- Energy management features reduce power consumption in active use or sleep mode.
- Standard two-sided printing saves paper.
- Use of post-consumer recycled content in manufacturing saves natural resources.
- Device is rated EPEAT® Silver and ENERGY STAR® certified.
- Recycle cartridges through the award-winning Lexmark Cartridge Collection Program (LCCP).

^{**}Average standard page yield value declared in accordance with ISO/IEC 19752. ***Award based on North American data.



^{*}Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds.

Lexmark MX320/MX420 Series



- 2 Lexmork
- Multifunction product with 2.4-inch (6-cm) colour display
 18.4 x 15.7 x 16.9 inches
 467 x 399 x 429.5 mm
- 3 550-sheet tray 5 x 15.7 x 14.7 inches 126 x 389 x 374 mm

- 2 Multifunction product with 4.3-inch (10.9-cm) colour touch screen 18.4 x 15.7 x 16.9 inches 467 x 399 x 429.5 mm
- 4 250-sheet tray 3.7 x 15.7 x 14.7 inches 95 x 389 x 374 mm
- Standard
 Optional

Supports one optional tray.

© 2018 Lexmark. All rights reserved.

Lexmark, the Lexmark logo and Unison are trademarks of Lexmark International, Inc., registered in the United States and/or other countries. AirPrint and the AirPrint Logo are trademarks of Apple, Inc. ENERGY STAR® is a U.S. registered mark. EPEAT® is a trademark of EPEAT, Inc. in the United States and other countries. Google Cloud Print is a trademark of Google, Inc. MOPRIA®, the Mopria® Logo[™] and the Mopria® Alliance logos are trademarks, service marks, and certification marks of Mopria Alliance, Inc. in the United States and other countries. All other trademarks are the property of their respective owners.

This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (http:// ww.openssl.org/).



Product specifications	Lexmark MX321adn	Lexmark MX421ade
Printing		
Display	2.4-inch (60 mm) Color LCD display	Lexmark e-Task 4.3-inch (10.9 cm) color touch screen
Print Speed: Up to ⁶	Black: 38 ppm	Black: 42 ppm
Time to First Page: As fast as	Black: 6.5 seconds	Black: 6.25 seconds
Print Resolution	Black: 600 x 600 dpi, 2400 Image Quality, 1200 x 1200 dpi, 1200 Image Quality	
Memory / Processor	Standard: 1024 MB / Maximum: 1024 MB / Dual Core, 1000 MHz	
Hard Disk	Not Available	
Recommended Monthly Page Volume ⁷	500 - 6000 pages	1000 - 10000 pages
Maximum Monthly Duty Cycle: Up to⁵	50000 pages per month	100000 pages per month
Copying		
Copy Speed: Up to ⁶	Black: 38 cpm	Black: 42 cpm
Time to First Copy: as fast as	Black: 6.5 seconds	Black: 6.25 seconds
Scanning		
Scanner Type / ADF Scan	Flatbed scanner with ADF / Simplex	Flatbed scanner with ADF / RADF (reversing Duplex)
A4/Ltr Duplex Scan Speed: Up to	Black: N/A sides per minute / Colour: N/A sides per minute	Black: 20 / 20 sides per minute / Colour: 10.5 / 10.5 sides per minute
A4/Ltr Simplex Scan Speed: Up to	Black: 42 / 45 sides per minute / Colour: 20 / 22 sides per minute	
ADF Paper Input Capacity: Up to	50 pages 20 lb or 75 gsm bond	
Faxing		
Modem Speed	ITU T.30, V.34 Half-Duplex, 33.6 Kbps	
Supplies ⁴	·	
Laser Cartridge Yields (up to) ¹	6,000-page Cartridge, 15,000-page High Yield Cartridge	6,000-page Cartridge, 20,000-page Extra High Yield Cartridge, 15,000-page High Yield Cartridge
Imaging Unit Estimated Yield: Up to ³	60000 pages, based on 3 average letter/A4-size pages per print job and ~ 5% coverage	
Cartridge(s) Shipping with Product ¹	2,500-page Return Program Toner Cartridge	3,000-page Starter Return Program Toner Cartridge
Paper Handling		
Included Paper Handling	Integrated Duplex, 250-Sheet Input, 150-Sheet Output Bin, 100-Sheet Multipurpose Feeder	
Optional Paper Handling	550-Sheet Lockable Tray, 550-Sheet Tray, 250-Sheet Tray	
Paper Input Capacity: Up to	Standard: 350 pages 20 lb or 75 gsm bond / Maximum: 900 pages 20 lb or 75 gsm bond	
Paper Output Capacity: Up to	Standard: 150 pages 20 lb or 75 gsm bond / Maximum: 150 pages 20 lb or 75 gsm bond	
Media Types Supported	Refer to the Card Stock & Label Guide., Transparencies, Plain Paper, Paper Labels, Envelopes, Card Stock	
Media Sizes Supported	A6, Oficio, Universal, Statement, Letter, Legal, JIS-B5, Folio, Executive, DL Envelope, A5, A4, 9 Envelope, 7 3/4 Envelope, 10 Envelope	
General Information ²		
Standard Ports	USB 2.0 Specification Hi-Speed Certified (Type B), Ethernet 10/100BaseTX (RJ-45), also works with 1000Base-T	Front USB 2.0 Specification Hi-Speed Certified port (Type A), Gigabit Ethernet (10/100/1000), USB 2.0 Specification Hi-Speed Certified (Type B)
Optional Network Ports	N/A	Marknet N8372 WiFi Option
Noise Level: Operating	Print: 54 dBA / Copy: 54 dBA / Scan: 55 dBA	Print: 55 dBA / Copy: 55 dBA / Scan: 55 dBA
Specified Operating Environment	Temperature: 10 to 32°C (50 to 90°F), Humidity: 8 to 80% Relative Humidity, Altitude: 0 - 5000 meters	
Limited Warranty - See Statement of Limited Warranty	1-Year Advanced Exchange Service	
Size (mm - H x W x D) / Weight	467 x 399 x 429.5 mm / 19.4 kg	

All information in this brochure is subject to change without notice. Lexmark is not liable for any errors or omissions.

¹Average standard page yield value declared in accordance with ISO/IEC 19752. ²Printers are sold subject to certain license/agreement conditions. See www.lexmark.com/printerlicense for details. ³Actual Yield may vary based on other factors such as device speed, paper size and feed orientation, toner coverage, tray source, percentage of black-only printing and average print job complexity. ⁴Product functions only with replacement cartridges designed for use in a specific geographical region. See www.lexmark.com/regions for more details. ⁵Maximum Monthly Duty Cycle ¹ is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs. ⁴Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds. ⁵™Recommended Monthly Page Volume¹ is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage.

