Fujitsu recommends Windows 11 Pro.

FUJITSU

Data Sheet Fujitsu Tablet LIFEBOOK U9311X

World's Lightest Convertible With A Pen

Available in red and black, the FUJITSU Tablet LIFEBOOK U9311X is a lightweight 360-degree foldable device. All-day battery runtime and global LTE ensure highest productivity in any place, while security features such as the integrated PalmSecure[™] sensor keep your business data protected. Powerful performance and full connectivity with Intel[®] Thunderbolt[™] 4 offer you best-in-class user experience.

Ultra-slim and lightweight Convertible

The very slim and light housing make it very comfortable to carry the device. Thanks to its 360° foldability, it can be immediately turned from a Notebook to a Tablet – and back.

- Available in red or black
- Weighing from 1 kg with a robust magnesium housing
- Durability is MIL-STD-810H tested
- Intel[®] Iris[®] Xe Graphics

Security at its best

No compromises in security and data protection – the integrated PalmSecure[™] sensor turns your unique palm vein pattern into your personal key.

- PalmSecure[™]
- Fingerprint & Full HD IR Camera supporting Windows Hello
- SmartCard reader
- Kensington Lock support

Excellent connectivity and usability

Newest interfaces and convenient features. All ports are full-sized – even the LAN port. No adapters, that can be lost and cause additional costs, needed.

- Complete set of full-sized interfaces: HDMI, LAN and USB Type-C with Intel® Thunderbolt™ 4
- 13.3 inch FHD anti-glare touch display with pen input
- Pen garage with inductive charging function
- 5 MP rear camera

Convenient mobility supporting usage on the go

- Highest productivity on business trips without empty batteries or waste of time
- All-day battery runtime offers you the exceptional mobility that you need when on the move
- Anytime USB charging functionality for your peripheral devices, even when system is turned off
- Always connected and instantly ready







Components

Base unit	LIFEBOOK U9311X black	LIFEBOOK U9311X red
Operating systems		
Operating system pre-installed	Windows 11 Pro. Fujitsu recommends Windows 11 Home Windows 10 Pro. Fujitsu recommends	
Operating system compatible	FREE Upgrade to Windows 11* *Upgrade timing may vary by device. specific hardware (see aka.ms/windov	Features and app availability may vary by region. Certain features require vs11-spec).
Operating system notes	account) For all Windows 11 editions, internet a some features. A Microsoft account is Windows 10 Support: After the end of Window 10 releases for a period of ma	the product life FUJITSU will continue to test and support all upcoming uximum 5 years – depending on the available extension of hardware services r details please see "FUJITSU Service Statement for Windows 10 Semi-Annual-
Processor	Intel® Core™ i7-1185G7 processor (4 C Intel® Core™ i5-1145G7 processor (4 C Intel® Core™ i5-1135G7 processor (4 C	ores / 8 Threads)
	*Processor only for retail, SMB, educat	ion and government
Hard disk drives (internal)	SSD PCIe, Teton Glacier (32GB Optane	+ 512GB SSD), SED
	SSD PCIe, SSD 512GB Value PCIe G3 M	2 FDE, SED
	SSD PCIe, SSD 512GB MS PCIe G3 M.2	FDE, SED
	SSD PCIe, SSD 256GB Value PCIe G3 M	.2 FDE, SED
	SSD PCIe, SSD 2TB MS PCIe G3 M.2 FD	E, SED
	SSD PCIe, SSD 1TB Value PCIe G3 M.2 F	DE, SED
	SSD PCIe, SSD 1TB MS PCIe G3 M.2 FD	E, SED
Hard disk notes	Accessible capacity may vary, also dep	pending on used software.
Interface add on cards/components (optional)		
4G/ LTE (optional)	LTE Sierra Wireless EM7421 (Cat. 7)	
	LTE module Fibocom L850-GL(Cat.9)	
Display	33.8 cm (13.3-inch), IPS, FHD, 1,920 x 1	,080 pixel, Anti-glare touchscreen, 400 cd/m², 1000:1
Multimedia		
Camera	Front: IR Cam (2 MP) supporting Wind Out camera: 5 MP with autofocus on t	

Base unit

LIFEBOOK U9311X black	LIFEBOOK U9311X red	
Integrated in CPU		
8 GB		
32 GB		
LPDDR4 (4266 MHz)		
	Integrated in CPU 8 GB 32 GB	Integrated in CPU 8 GB 32 GB

General system information				
Memory notes	8 GB / 16 GB / 32 GB onboard			
	LPDDR4 (3,200 MHz)			
	Dual channel support			
LAN	10/100/1,000 MBit/s Intel® I219LM			
LAN notes	Intel vPro support			
Integrated WLAN	Intel WiFi 6 AX201 - WLAN, BT, SRD cat. 1			
BIOS version	UEFI Specification 2.7			
BIOS features	InsydeH2O BIOS			
Audio type	On board			
Audio codec	Realtek ALC255			
Audio features	2x digital array microphones, 2x built-in speakers (stere	20)		
MIL-STD tested				
Color	Black	Red		
Material	Magnesium	Magnesium		
Display				
Diagonal Size	33.8 cm (13.3-inch)			
Display Technology	IPS			
Display type	Anti-glare touchscreen			
Display Resolution type	FHD			
Resolution (native)	1,920 x 1,080 pixel			
Aspect ratio	16:9			
Brightness - typical	400 cd/m ²			
Contrast - typical	1000:1			
Viewing angle (h/v) - typical	178°/178°			
Display notes	Wide-view high-bright LED display (for enhanced outd	oor viewing). With magnesium display lid.		
Sensors	3-axis Accelerometer			
	Gyroscope			
	Magnetic Field Sensor Compass			
Digitizer / Touch Technology	Wacom Digitizer for pen (AES) input plus capacitive 10	finger multi-touch screen		
Pen	AES			
	4k pressure level			
	Pen garage inductive charging			
	inductive charging			
Graphics				
Base unit	LIFEBOOK U9311X black	LIFEBOOK U9311X red		
TFT resolution (HDMI)	up to 4,096 x 2,160 @ 60 Hz	up to 4,096 x 2,160 @ 60 Hz		
Graphics brand name	Intel [®] Iris [®] Xe Graphics (with Dual channel memory)	Intel [®] Iris [®] Xe Graphics (with Dual channel memory)		
Graphics features	4 Display Support (3 external, 1 internal)	4 Display Support (3 external, 1 internal)		
	HDCP support DirectX [®] 12	HDCP support DirectX® 12		
	OpenGL [®] 4.5	OpenGL [®] 4.5		
Graphics notes	Shared memory depending on main memory size and	•		
	3D accelerator			
Interfaces				
DC-in	1			
Audio: line-out / headphone	1 (combo port with Audio line-in)			
Audio: line-in / microphone	1 (combo port with Audio line-out)			
Internal microphones	2x digital array microphones			
USB 3.2 Gen1 (5 Gbps) total	2x Type-A (1 with Anytime USB charge functionality)			

Interfaces		
USB Type-C	2 USB 4 Gen3 Thunderbolt™4, Power Delivery (15W), DP	1.4
HDMI	1 v2.0	
Ethernet (RJ-45)	1	
Memory card slots	I 1 (USH-II) SD 4.0 standard SD/microSD card: 2GB SDHC/microSDHC card: 32GB SDXC/microSDXC card: 2TB Speed Class: up to UHS-II (156MB/s)	
SmartCard slot	1	
SIM card slot	1 (Nano-SIM, only for models with integrated 4G/LTE mod	dule)
Docking connector for Port Replicator	USB Type-C	
Kensington Lock support	1	
Port Replicator interfaces (optional)		
	Thunderbolt™ 4 PR	USB Type-C PR
DC-in	1 (20V/170W required)	1 (19V/90W required)
Power on switch	1	1
Audio: comments	1 Combo jack for headset usage	1 Combo jack for headset usage
DisplayPort	2x V1.4++	1x V1.2
VGA		1
HDMI text	V 2.0b	1
Interface Notes	2x Type-A - 5V/0.9A, 4.5W 1x Type-A - 5V/2.4A, 12W 2x Type-C - 5V, 1.5A/4.5W charging port 1x Type-C - TBT4 up to 60 W (PD v2.0-1.1), 5-20V/3.0A upstream (PC), Intel AMT support (vPRO) 1x Type C - TDT4 up to 15 W (PD v2.0-1.1) 5 V (2.04)	3x Type-A - 5V/0.9A, 4.5W 1x Type-C - 15W 1x Type-C - Up to 60 W (PD v2.0-1.1) power output to client or 4.5W input
	1x Type-C - TBT4 up to 15 W (PD v2.0-1.1), 5V/3.0A downstream, power output to client	
Kensington Lock support		no
	downstream, power output to client	no 1
	downstream, power output to client 1 1 (10/100/1000 Mbit/s, 2,5 Gbps)	1 esolutions and frequencies depend on mobile system and
Ethernet (RJ-45)	downstream, power output to client 1 1 1 (10/100/1000 Mbit/s, 2,5 Gbps) Number of simultaneous used displays and its possible re display interface type.	1 esolutions and frequencies depend on mobile system and
Ethernet (RJ-45) Notes	downstream, power output to client 1 1 1 (10/100/1000 Mbit/s, 2,5 Gbps) Number of simultaneous used displays and its possible re display interface type.	1 esolutions and frequencies depend on mobile system and
Ethernet (RJ-45) Notes	downstream, power output to client 1 1 1 (10/100/1000 Mbit/s, 2,5 Gbps) Number of simultaneous used displays and its possible re display interface type. Please consult always also the manual of the connected of	1 esolutions and frequencies depend on mobile system and client.
Ethernet (RJ-45) Notes	downstream, power output to client 1 1 1 (10/100/1000 Mbit/s, 2,5 Gbps) Number of simultaneous used displays and its possible re display interface type. Please consult always also the manual of the connected of Backlit keyboard w/o touchstick	1 esolutions and frequencies depend on mobile system and client. eyboard stroke: 1.5 mm
Ethernet (RJ-45) Notes	downstream, power output to client 1 1 1 (10/100/1000 Mbit/s, 2,5 Gbps) Number of simultaneous used displays and its possible re display interface type. Please consult always also the manual of the connected o Backlit keyboard w/o touchstick Number of keyboard keys: 85, Keyboard pitch: 19 mm, Ke Multi gesture touchpad with integrated mouse button fu Touchscreen	1 esolutions and frequencies depend on mobile system and client. eyboard stroke: 1.5 mm
Ethernet (RJ-45) Notes Keyboard and pointing devices	downstream, power output to client 1 1 1 (10/100/1000 Mbit/s, 2,5 Gbps) Number of simultaneous used displays and its possible re display interface type. Please consult always also the manual of the connected o Backlit keyboard w/o touchstick Number of keyboard keys: 85, Keyboard pitch: 19 mm, Ke Multi gesture touchpad with integrated mouse button fu Touchscreen	1 esolutions and frequencies depend on mobile system and client. eyboard stroke: 1.5 mm inctionality
Ethernet (RJ-45) Notes Keyboard and pointing devices Wireless technologies	downstream, power output to client 1 1 1 (10/100/1000 Mbit/s, 2,5 Gbps) Number of simultaneous used displays and its possible re display interface type. Please consult always also the manual of the connected of Backlit keyboard w/o touchstick Number of keyboard keys: 85, Keyboard pitch: 19 mm, Ke Multi gesture touchpad with integrated mouse button fu Touchscreen Tablet Pen (AES), stored in pen garage	1 esolutions and frequencies depend on mobile system and client. eyboard stroke: 1.5 mm inctionality
Ethernet (RJ-45) Notes Keyboard and pointing devices Wireless technologies Antennas Bluetooth	downstream, power output to client 1 1 1 (10/100/1000 Mbit/s, 2,5 Gbps) Number of simultaneous used displays and its possible re display interface type. Please consult always also the manual of the connected o Backlit keyboard w/o touchstick Number of keyboard keys: 85, Keyboard pitch: 19 mm, Ke Multi gesture touchpad with integrated mouse button fu Touchscreen Tablet Pen (AES), stored in pen garage 2x dual band for WLAN, 2x for LTE, Bluetooth shared with	1 esolutions and frequencies depend on mobile system and client. eyboard stroke: 1.5 mm inctionality
Ethernet (RJ-45) Notes Keyboard and pointing devices Wireless technologies Antennas Bluetooth Integrated WLAN	downstream, power output to client 1 1 1 (10/100/1000 Mbit/s, 2,5 Gbps) Number of simultaneous used displays and its possible redisplay interface type. Please consult always also the manual of the connected of Backlit keyboard w/o touchstick Number of keyboard keys: 85, Keyboard pitch: 19 mm, Ke Multi gesture touchpad with integrated mouse button fu Touchscreen Tablet Pen (AES), stored in pen garage 2x dual band for WLAN, 2x for LTE, Bluetooth shared with v5.1 Intel WiFi 6 AX201 - WLAN, BT, SRD cat. 1	1 esolutions and frequencies depend on mobile system and client. eyboard stroke: 1.5 mm inctionality
Ethernet (RJ-45) Notes Keyboard and pointing devices Wireless technologies Antennas Bluetooth Integrated WLAN WLAN encryption	downstream, power output to client 1 1 1 (10/100/1000 Mbit/s, 2,5 Gbps) Number of simultaneous used displays and its possible re display interface type. Please consult always also the manual of the connected o Backlit keyboard w/o touchstick Number of keyboard keys: 85, Keyboard pitch: 19 mm, Ke Multi gesture touchpad with integrated mouse button fu Touchscreen Tablet Pen (AES), stored in pen garage 2x dual band for WLAN, 2x for LTE, Bluetooth shared with v5.1 Intel WiFi 6 AX201 - WLAN, BT, SRD cat. 1 WPA/WPA2/WPA3 (Wi-Fi Protected Access)	1 esolutions and frequencies depend on mobile system and client. eyboard stroke: 1.5 mm unctionality
Ethernet (RJ-45) Notes Keyboard and pointing devices Wireless technologies Antennas Bluetooth	downstream, power output to client 1 1 (10/100/1000 Mbit/s, 2,5 Gbps) Number of simultaneous used displays and its possible redisplay interface type. Please consult always also the manual of the connected of Backlit keyboard w/o touchstick Number of keyboard keys: 85, Keyboard pitch: 19 mm, Ke Multi gesture touchpad with integrated mouse button fu Touchscreen Tablet Pen (AES), stored in pen garage 2x dual band for WLAN, 2x for LTE, Bluetooth shared with v5.1 Intel WiFi 6 AX201 - WLAN, BT, SRD cat. 1 WPA/WPA2/WPA3 (Wi-Fi Protected Access) Import and usage according to country-specific regulation LTE Sierra Wireless EM7421 (Cat.7) - UMTS,LTE	1 esolutions and frequencies depend on mobile system and client. eyboard stroke: 1.5 mm unctionality
Ethernet (RJ-45) Notes Keyboard and pointing devices Wireless technologies Antennas Bluetooth Integrated WLAN WLAN encryption WLAN notes	downstream, power output to client 1 1 1 1 (10/100/1000 Mbit/s, 2,5 Gbps) Number of simultaneous used displays and its possible re display interface type. Please consult always also the manual of the connected o Backlit keyboard w/o touchstick Number of keyboard keys: 85, Keyboard pitch: 19 mm, Ke Multi gesture touchpad with integrated mouse button fu Touchscreen Tablet Pen (AES), stored in pen garage 2x dual band for WLAN, 2x for LTE, Bluetooth shared with v5.1 Intel WiFi 6 AX201 - WLAN, BT, SRD cat. 1 WPA/WPA2/WPA3 (Wi-Fi Protected Access) Import and usage according to country-specific regulation	1 esolutions and frequencies depend on mobile system and client. eyboard stroke: 1.5 mm inctionality WLAN ons.
Ethernet (RJ-45) Notes Keyboard and pointing devices Wireless technologies Antennas Bluetooth Integrated WLAN WLAN encryption WLAN notes Integrated WWAN WWAN notes	downstream, power output to client 1 1 1 1 (10/100/1000 Mbit/s, 2,5 Gbps) Number of simultaneous used displays and its possible re display interface type. Please consult always also the manual of the connected o Backlit keyboard w/o touchstick Number of keyboard keys: 85, Keyboard pitch: 19 mm, Ke Multi gesture touchpad with integrated mouse button fu Touchscreen Tablet Pen (AES), stored in pen garage 2x dual band for WLAN, 2x for LTE, Bluetooth shared with v5.1 Intel WiFi 6 AX201 - WLAN, BT, SRD cat. 1 WPA/WPA2/WPA3 (Wi-Fi Protected Access) Import and usage according to country-specific regulation LTE Sierra Wireless EM7421 (Cat.7) - UMTS,LTE Fibocom L850-GL (Cat.9) - UMTS,LTE Including GPS functionality Import and usage according to country-specific regulation	1 esolutions and frequencies depend on mobile system and client. eyboard stroke: 1.5 mm inctionality WLAN ons.
Ethernet (RJ-45) Notes Keyboard and pointing devices Keyboard and pointing devices Wireless technologies Antennas Bluetooth Integrated WLAN WLAN encryption WLAN notes Integrated WWAN WWAN notes GPS	downstream, power output to client 1 1 1 1 (10/100/1000 Mbit/s, 2,5 Gbps) Number of simultaneous used displays and its possible redisplay interface type. Please consult always also the manual of the connected of Backlit keyboard w/o touchstick Number of keyboard keys: 85, Keyboard pitch: 19 mm, Ke Multi gesture touchpad with integrated mouse button fu Touchscreen Tablet Pen (AES), stored in pen garage 2x dual band for WLAN, 2x for LTE, Bluetooth shared with v5.1 Intel WiFi 6 AX201 - WLAN, BT, SRD cat. 1 WPA/WPA2/WPA3 (Wi-Fi Protected Access) Import and usage according to country-specific regulatio LTE Sierra Wireless EM7421 (Cat.7) - UMTS,LTE Fibocom L850-GL (Cat.9) - UMTS,LTE Including GPS functionality Import and usage according to country-specific regulatio LTE Connection Manager (if configured with 4G/LTE)	1 esolutions and frequencies depend on mobile system and client. eyboard stroke: 1.5 mm inctionality WLAN ons.
Ethernet (RJ-45) Notes Keyboard and pointing devices Wireless technologies Antennas Bluetooth Integrated WLAN WLAN encryption WLAN notes Integrated WWAN	downstream, power output to client 1 1 1 (10/100/1000 Mbit/s, 2,5 Gbps) Number of simultaneous used displays and its possible redisplay interface type. Please consult always also the manual of the connected of Backlit keyboard w/o touchstick Number of keyboard keys: 85, Keyboard pitch: 19 mm, Ke Multi gesture touchpad with integrated mouse button fu Touchscreen Tablet Pen (AES), stored in pen garage 2x dual band for WLAN, 2x for LTE, Bluetooth shared with v5.1 Intel WiFi 6 AX201 - WLAN, BT, SRD cat. 1 WPA/WPA2/WPA3 (Wi-Fi Protected Access) Import and usage according to country-specific regulation LTE Sierra Wireless EM7421 (Cat.7) - UMTS,LTE Fibocom L850-GL (Cat.9) - UMTS,LTE Including GPS functionality Import and usage according to country-specific regulation LTE Connection Manager (if configured with 4G/LTE) Embedded in 4G module if configured with WWAN 20 V / 65 W (3.25 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin	1 esolutions and frequencies depend on mobile system and client. eyboard stroke: 1.5 mm unctionality WLAN ons. ons.
Ethernet (RJ-45) Notes Keyboard and pointing devices Wireless technologies Antennas Bluetooth Integrated WLAN WLAN encryption WLAN notes Integrated WWAN WWAN notes GPS Power supply	downstream, power output to client 1 1 1 1 (10/100/1000 Mbit/s, 2,5 Gbps) Number of simultaneous used displays and its possible redisplay interface type. Please consult always also the manual of the connected of Backlit keyboard w/o touchstick Number of keyboard keys: 85, Keyboard pitch: 19 mm, Ke Multi gesture touchpad with integrated mouse button fu Touchscreen Tablet Pen (AES), stored in pen garage 2x dual band for WLAN, 2x for LTE, Bluetooth shared with v5.1 Intel WiFi 6 AX201 - WLAN, BT, SRD cat. 1 WPA/WPA2/WPA3 (Wi-Fi Protected Access) Import and usage according to country-specific regulatio LTE Sierra Wireless EM7421 (Cat.7) - UMTS,LTE Fibocom L850-GL (Cat.9) - UMTS,LTE Including GPS functionality Import and usage according to country-specific regulatio LTE Connection Manager (if configured with 4G/LTE) Embedded in 4G module if configured with WWAN	1 esolutions and frequencies depend on mobile system and client. eyboard stroke: 1.5 mm inctionality WLAN ons. ons.

Power supply			
AC Adapter	20 V / 65 W (3.25 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) Type-C AC-Adapter slim&light	20 V / 65 W (3.25 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) Type-C AC-Adapter slim&light	
AC adapter	19 V / 65 W (3.42 A) 20 V / 65 W (3.25 A) Type C	19 V / 65 W (3.42 A) 20 V / 65 W (3.25 A) Type C	
Notes	65W AC adapter for usage with system/ min. 90W AC Adapter for usage with Port Replicator	65W AC adapter for usage with system/ min. 90W AC Adapter for usage with Port Replicator	
Rated voltage range	100 V - 240 V (AC Input)	100 V - 240 V (AC Input)	
Rated frequency range	50 Hz - 60 Hz	50 Hz - 60 Hz	
1st battery options	Lithium polymer battery 4-cell, 50 Wh	Lithium polymer battery 4-cell, 50 Wh	
1st battery	Lithium polymer battery 4-cell, 50 Wh	Lithium polymer battery 4-cell, 50 Wh	
Battery features	Quick Charge: 80% in 1h	Quick Charge: 80% in 1h	
Runtime 1st battery	11 h	11 h	
Battery notes	•		
	depending on product model, configuration, application and power management settings. The battery capacity decreases slightly with every re-charge and over its lifetime.		
Noise emission			
Noise emission	Please refer to the Eco Declaration		
Dimensions / Weight / Environmental			
Dimensions (W x D x H)	309 x 214.8 x 16.9 mm		
	12.18 x 8.41 x 0.62 inch		
Weight	1,015 kg		
Weight (lbs)	2,23 lbs		
Weight notes	Weight may vary depending on actual configuration		
Operating ambient temperature	5 - 35 °C (41 - 95 °F); Packed -10 - 60 °C (14 - 140 °F)		
Operating relative humidity	Running: 20 - 80% (relative humidity); Packed: 20 - 80%	(relative humidity)	
Compliance			
Product	LIFEBOOK U9311X		
Germany	GS		
Europe	CE CB		
USA/Canada	FCC (depending on configuration)		
Global	TCO Certified 8.0 (depending on configuration) EPEAT® Silver (dedicated regions), depending on configuration WEEE (Waste electrical and electronic equipment) RoHS (Restriction of hazardous substances) MIL-STD-810H tested Microsoft Operating Systems (HCT / HCL entry / WHQL)		
India	BIS		
Russia	EAC		
China	ССС		
Compliance link	https://sp.ts.fujitsu.com/sites/certificates		
Additional Software			
Additional software (preinstalled)	Adobe® Reader® (pdf reader) CyberLink YouCam (webcam software) Fujitsu Display Manager Fujitsu DeskUpdate (driver and utility tool) ShockSensor Utility Power Saving Utility Fujitsu Plugfree Network (network management utility)		

Additional Software	
Additional software (optional)	Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) optional CyberLink PowerDVD BD (playback software for Blu-ray Disc™) CyberLink PowerDVD DVD (playback software for DVD) CyberLink YouCam (webcam software) Nero (backup and burning software)
Additional software (notes)	Use of additional software is subject to proactive acceptance of the respective End User License Agreement as applicable for the relevant software whether preinstalled or optional. This also applies for any available patches thereof.
Manageability	
Manageability technology	DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode) WoL (Wake on LAN) Intel® vPro™ technology iAMT 14.0 (depending on processor)
Manageability software	DeskView Client DeskView Instant BIOS Management
DeskView components	Inventory Management BIOS Management Driver Management Security Management Alarm Management
Supported standards	WMI (Windows Management Instrumentation) PXE (Preboot Execution Environment) DMI (Desktop Management Interface) SMBIOS (System Management BIOS) WBEM (Web Based Enterprise Management) CIM (Common Information Model) BootP (made4you)
Manageability link	http://www.fujitsu.com/fts/manageability
Security	
Physical Security	Kensington Lock support
System and BIOS Security	Absolute Persistence® technology capable BIOS Optional: Trusted Platform Module (TPM 2.0) EraseDisk
User Security	Hard disk password User and supervisor BIOS password Embedded fingerprint sensor (optional) Embedded PalmSecure™ sensor (optional) Smartcard reader (integrated) AuthConductor Client Basic (secure authentication solution)
Security Notes	The security features included in the product alone cannot protect from any and all intrusion attempts and cyberattacks. For an adequate overall level of IT security, further IT security measures (e.g. supplementary virus scanner settings, firewall, access rights management, encryption etc.) must be adopted independently of the available system configuration options. Hence the overall IT security for the product is within the sole responsibil of the respective user/administrator of the product.
De alta ain a information	

Packaging information

Warranty	
Warranty period	2 years (for countries within EMEIA)
Warranty type	Bring-in Service / Collect & Return Service (depending on country)
Warranty Terms & Conditions	http://www.fujitsu.com/warranty
Digital bug fixes	Subject to availability and following their generic release for the product, bug fixes and function-preserving patches for product-related software (firmware) can be downloaded from the technical support at: https://support.ts.fujitsu. com/ free of charge by entering the respective product serial number. For application software supplied together with the product, please directly refer to the support websites of the respective software manufacturer.

Warranty	
Product Support Services - the p	erfect extension
Recommended Service	9x5, Onsite Response Time: Next Business Day
Spare Parts availability	5 years after end of product life
Service Weblink	http://www.fujitsu.com/emeia/products/product-support-services/

Recommended Accessories

Thunderbolt [™] 4 Port Replicator	First Thunderbolt [™] Port Replicator on the market providing enhanced security and full support of Intel® AMT (vPro®). The universal port can easily connect almost everything with a single cable and high speed-data transfer. This smart workspace solution keeps your desk clean and tidy.	
USB Type-C Port Replicator 2	Connect to your peripherals. Adapt to the task on demand. The universal USB Type-C interface supports you to get your peripheral devices connected easily. Multiply your USB ports to connect your peripherals as well as your external display via HDMI, DisplayPort or VGA. You also can charge your external USB devices without the need of any additional charger.	le: 3327-L100
USB Type-C AC Adapter	Recharge your notebook or tablet at work, at home or on the road with this Order Coc USB Type-C power source easily. S26391-F3	de: 3326-L502
AES Pen with replacement stylus tips	Take your creativity to the next level, with the most natural pen experience Order Coc with the AES Pen with replacement stylus tips. With pen nibs that are very S26391-Fi thin, you can experience the writing and signing behavior of an ink pen.	le: 3149-L500
Car Adapter USB-C-QC	One Car Adapter fits all. Independent of your mobile device charging method this car adapter will fulfill all major requirements and standards for fast charging vendorbrand- independent notebooks and all mobile devices. The Car Adapter USB-C- QC supports USB PD with PPS, Quick Charge (QC), Apple- and Samsung charge.	de: 2613-L630

More information

Fujitsu products, solutions & services

In addition to Fujitsu Tablet LIFEBOOK U9311X, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products www.fujitsu.com/global/products/ computing/

Software www.fujitsu.com/software/

More information

Learn more about Fujitsu Tablet LIFEBOOK U9311X, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website. www.fujitsu.com/emeia/products/

computing/pc/tablets

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT.

Please find further information at http://www. fujitsu.com/global/about/environment



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://www.fujitsu.com/ emeia/resources/navigation/terms-of-use. html

Copyright 2022 Fujitsu Technology Solutions GmbH

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

Fujitsu Technology Solutions GmbH Website: www.fujitsu.com 2022-05-01 EM-EN All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html Copyright 2022 Fujitsu Technology Solutions GmbH